

Label, Temporary, FCC ID, AVM-16S1-B, Silver w/Black Text, 1.500" x 0.750", Metallized Polyester, Matte Silver, Perm Acrylic Adh

Specification Control4 P/N 22-0300-51 Rev A

1. Label Type: 8 ½" x 11" laser-printable sheet

2. Manufacturer: Brady (<u>www.bradyid.com</u>) or equivalent

Mfr. P/N: LAT-20-773
 Label Size: 1.500" x 0.750"

5. # per Sheet: 60

6. Material: B-773 Matte Silver Metallized Polyester or equivalent

7. Adhesive: Permanent Acrylic Adhesive

8. Temp Range: -65C to 120C

9. Approvals: UL Recognized / CSA Approved materials

10. Printer/Toner: CSA: Refer to bradyid.com, Support/Knowledge Base,

document # JM173350 (titled CSA Accepted Materials) for approved types.

Or refer to Brady's Acceptance Record (LS41833) with CSA.

UL: Refer to bradyid.com, Support/Knowledge Base, document # JM134823

(titled UL Recognized Components) for approved types.

11. Artwork: Inherent in source file number "22-0300-51 Rev A.lab" provided by Control4

12. File Type: ".lab" (Wasp Barcode Labeler v5)

13. Software: "Wasp Barcode Labeler v5" (www.waspbarcode.com)

14. Barcode: None required on this label 15. # Sequencing: None required on this label

<u>Label Example – Actual Size</u>

Control CAUDIO MATRIX SWITCH - 16
AVM-16S1-B
FCC ID: R33AVM16S11

Enlarged

Control

AUDIO MATRIX SWITCH - 16 AVM-16S1-B FCC ID: R33AVM16S11

22-0300-51 Rev A

| REVISION HISTORY | | | | |
|------------------|-----|--|---------------|--|
| Date | Rev | Description | Person | |
| 5 Mar 2005 | A | Initial design specification and production release. | Roger Johnsen | |



Label, FCC Compliance, Black w/White Text, H=1.000" x W=1.750" x Rmax=0.125", Polyester, Gloss, Perm Adh, UL

Specification Control4 P/N 22-3012 Rev A

1. Size: H=1.000" x W=1.750" label with 0.125" max radius on each corner

Base Material:
 Laminate Overlay:
 Adhesive:
 2.0 mil (0.002") white polyester, 3M 7871 or equivalent (UL)
 2.0 mil (0.002") clear gloss polyester, 3M 7861 or equivalent (UL)
 2.0 mil (0.002") permanent acrylic, 3M #350 or equivalent (UL)

5. Liner: 50# bleached white kraft paper

6. Printing: Flexopress

7. Ink: Reverse print, black, Akzo Nobel 4000 Series or equivalent (UL)

8. Art: See graphic below

9. Font: Arial 6.5 pt.

10. Wording: See paragraph below

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

| REVISION HISTORY | | | | |
|------------------|-----|--|---------------|--|
| Date | Rev | Description | Person | |
| 5 Mar 2005 | A | Initial design specification and production release. | Roger Johnsen | |
| | | | | |
| | | | | |