

RF EXPOSURE Test Report

Product: 27000mAh solar power bank

Trade Mark: DEXNOR

Model Number: DEX-DC001

FCC ID: 2BA3T-DEX-DC001

Prepared for

Shenzhen Houlici Network Technology CO., Ltd
2606, West Tower, Galaxy Twin Towers, Yaxing Road 8, Nankeng
Community, Bantian Street, Longgang District, Shenzhen

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	TEST FACILITIES AND ACCREDITATIONS	7
2.1	TEST LABORATORY	7
2.2	ENVIRONMENTAL CONDITIONS	7
2.3	MEASUREMENT UNCERTAINTY	7
2.4	TEST SOFTWARE	7
3	LIST OF TEST EQUIPMENT	8
4	RF EXPOSURE.....	9
4.1	MAXIMUM PERMISSIBLE EXPOSURE	9
4.1.1.	<i>Limit</i>	9
4.1.2.	<i>Test Procedures</i>	9
4.1.3.	<i>Test Setup</i>	9
4.1.4.	<i>Test Result</i>	10
5	PHOTOGRAPHS OF THE TEST SETUP.....	11

TEST RESULT CERTIFICATION

Applicant's Name : Shenzhen Houlici Network Technology CO., Ltd
2606, West Tower, Galaxy Twin Towers, Yaxing Road 8,
Address : Nankeng Community, Bantian Street, Longgang District,
Shenzhen
Manufacturer's Name : Shenzhen Houlici Network Technology CO., Ltd
2606, West Tower, Galaxy Twin Towers, Yaxing Road 8,
Address : Nankeng Community, Bantian Street, Longgang District,
Shenzhen

Product description

Product name : 27000mAh solar power bank

Model Number : DEX-DC001

Standards : FCC CFR 47 PART 1 , 1.1310

Test procedure : KDB 680106 D01 Wireless Power Transfer v04

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test :

Date (s) of performance of tests : Mar. 17, 2025~ Mar. 26, 2025

Test Result..... : **Pass**

Testing Engineer :

Zoe Su

(Z o e S u)

Technical Manager :

Gary Lu

(G a r y L u)

Authorized Signatory :

Leo Su

(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	27000mAh solar power bank
Model name:	DEX-DC001
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	115kHz-205kHz
Operational mode:	Wireless charging
Modulation type:	ASK
Antenna type:	Coil Antenna
Battery:	Capacity: 22.2V 4500mAh/ 99.9Wh Li-ion Battery Cells Inside: 4500mAh*6pcs 3.7V Rated Capacity: 16200mAh (5V/1A)
Power supply:	Capacity: 22.2V 4500mAh/ 99.9Wh Li-ion Battery Cells Inside: 4500mAh*6pcs 3.7V Rated Capacity: 16200mAh (5V/1A) Type-C1 Input: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (45W Max) Micro-B Input: 5V=2A (10W Max) Solar Panel Input: 5V=0.42A (2.1W Max) Type C1 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.25A (65W Max) PPS: 3.3-11V=3A, 3.3-21V=3A Type-C2 Output: 5V=3A, 9V=2.22A (20W Max) PPS: 3.3-11V=2A (22W Max) USB-A Output: 5V=3A, 9V=2A, 12V=1.5A (18W Max) Wireless Output: 5W/7.5W/10W/15W A1+C2 Output: 15W C1+A1/C2 Output:45W+18W/20W A1/C2+Wireless Charging Output: 18W/20W+15W C1+Wireless Charging Output: 45W+15W (A1+C2)+Wireless Charging Output: 15W+15W C1+(A1+C2)+Wireless Charging Output: 30W+15W+15W
Adapter information:	N/A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	AC/DC Adapter + Wireless Output: 5W
2	AC/DC Adapter + Wireless Output: 7.5W

3	AC/DC Adapter + Wireless Output: 10W
4	AC/DC Adapter + Wireless Output: 15W
5	Battery + Wireless Output: 5W
6	Battery + Wireless Output: 7.5W
7	Battery + Wireless Output: 10W
8	Battery + Wireless Output: 15W

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	CD289	35810	Ugreen Group Limited
Phone	LE2120	8602840564 41073	Shenzhen Oneplus Technology Co., Ltd

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
E-field	± 2.5 dB	
H-field	± 4.2 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
MAGPy V2.6	Schmid & Partner Engineering AG	MAGPy V2.6	V2.6

3 List of Test Equipment

Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E077	Magnetic Amplitude and Gradient Probe System	Schmid & Partner Engineering AG	MAGPy -8H3D+E3D	3107	2024-03-15	2026-03-14
2	HB-E078	Magnetic Amplitude and Gradient Probe System	Schmid & Partner Engineering AG	MAGPy-DAS	3097	2024-03-15	2026-03-14

Note: the calibration interval of the above test instruments is 24 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Maximum Permissible Exposure

4.1.1. Limit


Frequency range(MHz)	Electric field strength(V/m)	Magnetic field strength(A/m)	Power density(mW/cm ²)	Averaging time(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0 6	6
300-1500	/	/	f/300	6
1500-100000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100000	/	/	1	30

f = frequency in MHz * = Plane-wave equivalent power density

4.1.2. Test Procedures

- The RF exposure test was performed in anechoic chamber.
- Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm.
- The highest emission level was recorded and compared with limit.

4.1.3. Test Setup



4.1.4. Test Result

For portable exposure condition:

Operating modes with client device (1 %, 50%, 99% battery status of client device) have been test, only show the data of worst case of 1% battery status of client device.

H-field measurements taken every 2 cm (starting as close to 20 cm as possible) on each edge/top surface of the host/client pair were also evaluated for portable use conditions. The report reflects data for the worst 0 cm test distance mode only.

Test condition 1: Mode 8 operating mode with client device (1 % battery status of client device).


Measurement results directly tested using MAGPy.

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	0	140	0.55
<1%	Left	0	14.2	0.62
<1%	Right	0	14.3	0.59
<1%	Front	0	32.5	0.66
<1%	Back	0	22.2	0.10
<1%	Bottom	0	72.6	0.57
Limit			614	1.63
Margin Limit (%)			22.8%	40.49%

When setting MAGPy to select compliance location as probe tip, the measured value is extrapolated to 0mm as the result.

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	0	136	0.59
<1%	Left	0	15.3	0.67
<1%	Right	0	14.9	0.64
<1%	Front	0	30.4	0.75
<1%	Back	0	21.7	0.25
<1%	Bottom	0	73	0.65
Limit			614	1.63
Margin Limit (%)			22.15 %	46.01%

5 Photographs of the Test Setup



******* END OF REPORT *******