

## FCC RF Exposure

EUT Description: Smart Projector

ModelNo.:HY320mini,HY320,H320,X1,X2,X3,X4,X5,X6,X7

FCC ID: 2BF3V-HY320MINI

Equipment type: mobile device

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where :

Pd = power density in mW/cm<sup>2</sup>,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.62

## 3. Test Result of RF Exposure Evaluation

## WIFI

	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
U-NII 1 802.11a	5.63/3.66	4.18	0.00191	1.0	Pass
U-NII 1 802.11n(HT20)	6.92/4.92	4.18	0.00257	1.0	Pass
U-NII 1 802.11n(HT40)	6.54/4.51	4.18	0.00235	1.0	Pass
U-NII 1 802.11ac(HT20)	6.16/4.13	4.18	0.00215	1.0	Pass
U-NII 1 802.11ac(HT40)	6.49/4.46	4.18	0.00233	1.0	Pass
U-NII 1 802.11ac(HT80)	6.12/4.09	4.18	0.00213	1.0	Pass
U-NII 3 802.11a	4.16/2.61	4.18	0.00136	1.0	Pass
U-NII 3 802.11n(HT20)	4.09/2.56	4.18	0.00134	1.0	Pass
U-NII 3 802.11n(HT40)	3.24/2.11	4.18	0.00110	1.0	Pass
U-NII 3 802.11ac(HT20)	4.06/2.55	4.18	0.00133	1.0	Pass
U-NII 3 802.11ac(HT40)	3.30/2.14	4.18	0.00112	1.0	Pass
U-NII 3 802.11ac(HT80)	4.51/2.82	4.18	0.00235	1.0	Pass
802.11b	19.69/93.11	1.73	0.02761	1.0	Pass
802.11g	14.58/28.71	1.73	0.00851	1.0	Pass
802.11n20	15.58/36.14	1.73	0.01072	1.0	Pass

Note:2.4G / 5G cannot work at the same time and do not support the same development.

Conclusion: No SAR is required