

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Wifi 2.4G

Frequency	Max output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2462MHz (802.11g)	21.67	146.89	0.045	1.0	PASS

Antenna gain: 1.88dBi

Propriety 2.4G

Frequency	Field strength (dBuV/m@3m)	EIRP (dBm)	P _{conducted} (dBm)	P _{conducted} (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2480MHz	91.05	-4.11	-5.99	0.25	0.00008	1.0	PASS

Antenna gain: 1.88dBi

Simultaneous Transmission

Mode	WIFI	Propriety 2.4G
Output power (dBm)	21.67	-5.99
Output power (mW)	146.89	0.25
Antenna gain (dBi)	1.88	1.88
ERP (mW)	138.04	0.24
P _{th} / ERP _{th}	3060	3060
$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	0.048	
$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	0.045	
$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$	0.045	
$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$	0.138	
Limit	1	

The max power density is less than MPE exempt limit, so it is compliance.