



FCC RF Test Report

APPLICANT : Espressif Systems (Shanghai) Co.,Ltd.
EQUIPMENT : 2.4GHz Wi-Fi & BT IoT Module
BRAND NAME : ESPRESSIF
MODEL NAME : ESP32-S3-MINI-1
FCC ID : 2AC7Z-ESPS3MINI1
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Dec. 19, 2021 ~ Jan. 18, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	31
3.6 AC Conducted Emission Measurement.....	35
3.7 Antenna Requirements.....	37
4 LIST OF MEASURING EQUIPMENT	38
5 UNCERTAINTY OF EVALUATION	39
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR1N0918B	Rev. 01	Initial issue of report	Feb. 14, 2022

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.01 dB at 2389.95 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.23 dB at 0.153 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.2 Manufacturer

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	2.4GHz Wi-Fi & BT IoT Module
Brand Name	ESPRESSIF
Model Name	ESP32-S3-MINI-1
FCC ID	2AC7Z-ESPS3MINI1
HW Version	V1.1
SW Version	v1.1.3.4
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 22.48 dBm (0.1770 W) 802.11g : 25.27 dBm (0.3365 W) 802.11n HT20 : 25.08 dBm (0.3221 W) 802.11n HT40 : 24.81 dBm (0.3027 W)
99% Occupied Bandwidth	802.11b : 13.19MHz 802.11g : 19.03MHz 802.11n HT20 : 19.18MHz 802.11n HT40 : 34.77MHz
Antenna Type / Gain	PCB Antenna type with gain 4.54 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		




2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	WLAN(2.4G) Link + Test Jig Powered by Notebook

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	V130-15IKB005	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss

Following shows an offset computation example with cable loss 5.5dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Engineer :	kid shi	Temperature :	21~25°C
		Relative Humidity :	51~54%

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	10
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 7 JAN 2022 09:26:19

Channel Plot




Date: 7 JAN 2022 09:26:33

Spurious Emission 30MHz~3GHz



Date: 7 JAN 2022 09:27:18

Spurious Emission 2GHz~25GHz




Date: 7 JAN 2022 09:27:58




Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Test Channel :	01
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----


100kHz PSD reference Level




Channel Plot

N/A

Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Test Channel :	10
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----







Test Mode : 802.11n HT40

Test Channel : 03


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----







Test Mode : 802.11n HT40

Test Channel : 09


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 14, 2021	Dec. 19, 2021~Jan. 07, 2022	Oct. 13, 2022	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 07, 2021	Dec. 19, 2021~Jan. 07, 2022	Jan. 06, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 07, 2021	Dec. 19, 2021~Jan. 07, 2022	Jan. 06, 2023	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 16, 2021	Jan. 03, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44G,MAX 30dB	Oct. 16, 2021	Jan. 03, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Jan. 03, 2022	Oct. 29, 2022	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Jan. 26, 2021	Jan. 03, 2022	Jan. 25, 2022	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 30, 2021	Jan. 03, 2022	Oct. 29, 2022	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 05, 2021	Jan. 03, 2022	Nov. 04, 2022	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Jan. 06, 2021	Jan. 03, 2022	Jan. 05, 2022	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	100MHz~18GHz	Jan. 06, 2021	Jan. 03, 2022	Jan. 05, 2022	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 16, 2021	Jan. 03, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GG A	060728	18~40GHz	Jan. 06, 2021	Jan. 03, 2022	Jan. 05, 2022	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Jan. 03, 2022	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 03, 2022	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 03, 2022	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 21, 2021	Jan. 18, 2022	Apr. 20, 2022	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 14, 2021	Jan. 18, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Apr. 13, 2021	Jan. 18, 2022	Apr. 12, 2022	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 14, 2021	Jan. 18, 2022	Oct. 13, 2022	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

----- THE END -----



Appendix A. Conducted Test Results

A1. Conducted Test Results

Test Engineer:	kid shi	Temperature:	21~25	°C
Test Date:	2021/12/19~2022/1/07	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant1	Ant2	Ant1	Ant2		
11b	1Mbps	1	1	2412	13.14	-	9.04	-	0.50	Pass
11b	1Mbps	1	6	2437	13.19	-	8.62	-	0.50	Pass
11b	1Mbps	1	11	2462	13.14	-	10.04	-	0.50	Pass
11g	6Mbps	1	1	2412	18.68	-	16.34	-	0.50	Pass
11g	6Mbps	1	6	2437	18.83	-	16.34	-	0.50	Pass
11g	6Mbps	1	10	2457	18.63	-	16.32	-	0.50	Pass
11g	6Mbps	1	11	2462	19.03	-	16.32	-	0.50	Pass
HT20	MCS0	1	1	2412	19.13	-	17.58	-	0.50	Pass
HT20	MCS0	1	6	2437	19.13	-	17.56	-	0.50	Pass
HT20	MCS0	1	10	2457	19.13	-	17.55	-	0.50	Pass
HT20	MCS0	1	11	2462	19.18	-	17.62	-	0.50	Pass
HT40	MCS0	1	3	2422	34.67	-	31.96	-	0.50	Pass
HT40	MCS0	1	6	2437	34.77	-	31.40	-	0.50	Pass
HT40	MCS0	1	9	2452	34.57	-	32.64	-	0.50	Pass

TEST RESULTS DATA
Peak Output Power

2.4GHz Band Single Antenna																
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	21.57	-		30.00	-	4.54	-	26.11	-	36.00	-	Pass
11b	1Mbps	1	6	2437	21.59	-		30.00	-	4.54	-	26.13	-	36.00	-	Pass
11b	1Mbps	1	11	2462	22.48	-		30.00	-	4.54	-	27.02	-	36.00	-	Pass
11g	6Mbps	1	1	2412	24.52	-		30.00	-	4.54	-	29.06	-	36.00	-	Pass
11g	6Mbps	1	6	2437	25.26	-		30.00	-	4.54	-	29.80	-	36.00	-	Pass
11g	6Mbps	1	10	2457	25.27	-		30.00	-	4.54	-	29.81	-	36.00	-	Pass
11g	6Mbps	1	11	2462	23.89	-		30.00	-	4.54	-	28.43	-	36.00	-	Pass
HT20	MCS0	1	1	2412	23.84	-		30.00	-	4.54	-	28.38	-	36.00	-	Pass
HT20	MCS0	1	6	2437	24.93	-		30.00	-	4.54	-	29.47	-	36.00	-	Pass
HT20	MCS0	1	10	2457	25.08	-		30.00	-	4.54	-	29.62	-	36.00	-	Pass
HT20	MCS0	1	11	2462	22.51	-		30.00	-	4.54	-	27.05	-	36.00	-	Pass
HT40	MCS0	1	3	2422	24.37	-		30.00	-	4.54	-	28.91	-	36.00	-	Pass
HT40	MCS0	1	6	2437	24.81	-		30.00	-	4.54	-	29.35	-	36.00	-	Pass
HT40	MCS0	1	9	2452	23.85	-		30.00	-	4.54	-	28.39	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density


2.4GHz Band Single Antenna												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant1	Ant2	Worse + 3.01	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	-3.70	-		4.54	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-2.44	-		4.54	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-2.08	-		4.54	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-8.12	-		4.54	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-6.47	-		4.54	-	8.00	-	Pass
11g	6Mbps	1	10	2457	-7.03	-		4.54	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-10.33	-		4.54	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-9.19	-		4.54	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-6.74	-		4.54	-	8.00	-	Pass
HT20	MCS0	1	10	2457	-7.02	-		4.54	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-11.52	-		4.54	-	8.00	-	Pass
HT40	MCS0	1	3	2422	-10.55	-		4.54	-	8.00	-	Pass
HT40	MCS0	1	6	2437	-9.86	-		4.54	-	8.00	-	Pass
HT40	MCS0	1	9	2452	-12.35	-		4.54	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.



Appendix B. AC Conducted Emission Test Results





Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Test Engineer :	Henry LI	Temperature :	22~23°C
		Relative Humidity :	41~42%

Band		Power setting
11b Tx	CH01	0
11b Tx	CH06	0
11b Tx	CH11	0
11g Tx	CH01	4
11g Tx	CH06	0
11g Tx	CH10	0
11g Tx	CH11	16
11n(20M) Tx	CH01	6
11n(20M) Tx	CH06	0
11n(20M) Tx	CH10	0
11n(20M) Tx	CH11	20
11n(40M) Tx	CH03	2
11n(40M) Tx	CH06	0
11n(40M) Tx	CH09	12



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2387.48	57.79	-16.21	74	57.05	30.5	7.1	36.86	354	0	P	H
		2385.92	46.6	-7.4	54	45.86	30.5	7.1	36.86	354	0	A	H
	*	2412	112.56	-	-	111.71	30.57	7.13	36.85	354	0	P	H
	*	2412	105.28	-	-	104.43	30.57	7.13	36.85	354	0	A	H
		2385.66	59.86	-14.14	74	59.12	30.5	7.1	36.86	103	312	P	V
		2385.92	48.76	-5.24	54	48.02	30.5	7.1	36.86	103	312	A	V
	*	2412	113.33	-	-	112.48	30.57	7.13	36.85	103	312	P	V
	*	2410	106.22	-	-	105.37	30.57	7.13	36.85	103	312	A	V
802.11b CH 11 2462MHz		2483.56	58.7	-15.3	74	57.41	30.86	7.25	36.82	378	354	P	H
		2488.48	48.26	-5.74	54	46.89	30.93	7.25	36.81	378	354	A	H
	*	2462	114.81	-	-	113.63	30.79	7.22	36.83	378	354	P	H
	*	2462	107.6	-	-	106.42	30.79	7.22	36.83	378	354	A	H
		2488.84	59.06	-14.94	74	57.69	30.93	7.25	36.81	138	314	P	V
		2488.6	49.02	-4.98	54	47.65	30.93	7.25	36.81	138	314	A	V
	*	2462	114.73	-	-	113.55	30.79	7.22	36.83	138	314	P	V
	*	2462	107.79	-	-	106.61	30.79	7.22	36.83	138	314	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz	*	4830	54.01	-19.99	74	74.53	34.61	10.25	65.38	104	212	P	H
		4830	47.85	-6.15	54	68.37	34.61	10.25	65.38	104	212	A	H
		7230	50.55	-34.97	85.52	66.78	36.71	12.71	65.65	300	0	P	H
		9645	49.62	-35.9	85.52	63.86	37.79	14.94	66.97	300	0	P	H
	*	4830	53.19	-20.81	74	73.71	34.61	10.25	65.38	296	138	P	V
		4830	46.77	-7.23	54	67.29	34.61	10.25	65.38	296	138	A	V
		7230	50.12	-36	86.12	66.35	36.71	12.71	65.65	100	0	P	V
		9645	52.82	-33.3	86.12	67.06	37.79	14.94	66.97	100	0	P	V
802.11b CH 06 2437MHz	*	4875	53.36	-20.64	74	73.8	34.69	10.29	65.42	100	215	P	H
		4875	47.89	-6.11	54	68.33	34.69	10.29	65.42	100	215	A	H
		7311	53.62	-20.38	74	70.13	36.68	12.72	65.91	107	236	P	H
		7311	44.67	-9.33	54	61.18	36.68	12.72	65.91	107	236	A	H
		9750	51.3	-32.64	83.94	65.45	37.91	14.99	67.05	300	0	P	H
		4875	52.87	-21.13	74	73.31	34.69	10.29	65.42	347	137	P	V
	*	4875	46.77	-7.23	54	67.21	34.69	10.29	65.42	347	137	A	V
		7305	54.42	-19.58	74	70.93	36.68	12.72	65.91	100	295	P	V
		7305	46.18	-7.82	54	62.69	36.68	12.72	65.91	100	295	A	V
		9750	53.47	-33.47	86.94	67.62	37.91	14.99	67.05	100	0	P	V
802.11b CH 11 2462MHz	*	4920	54.83	-19.17	74	75.17	34.77	10.34	65.45	106	216	P	H
		4920	48.5	-5.5	54	68.84	34.77	10.34	65.45	106	216	A	H
		7380	54.51	-19.49	74	71.24	36.65	12.73	66.11	238	311	P	H
		7380	46.51	-7.49	54	63.24	36.65	12.73	66.11	238	311	A	H
		9840	53.43	-32.98	86.41	67.5	38.01	15.03	67.11	300	0	P	H
		4920	54.47	-19.53	74	74.81	34.77	10.34	65.45	100	145	P	V
	*	4920	47.57	-6.43	54	67.91	34.77	10.34	65.45	100	145	A	V
		7380	54.72	-19.28	74	71.45	36.65	12.73	66.11	100	294	P	V
		7380	46.65	-7.35	54	63.38	36.65	12.73	66.11	100	294	A	V
		9840	54.99	-32.81	87.80	69.06	38.01	15.03	67.11	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.95	70.64	-3.36	74	69.9	30.5	7.1	36.86	354	356	P	H
		2389.95	52.82	-1.18	54	52.08	30.5	7.1	36.86	354	356	A	H
	*	2412	109.77	-	-	108.92	30.57	7.13	36.85	354	356	P	H
	*	2410	101.24	-	-	100.39	30.57	7.13	36.85	354	356	A	H
		2389.82	71.12	-2.88	74	70.38	30.5	7.1	36.86	130	214	P	V
		2389.95	52.71	-1.29	54	51.97	30.5	7.1	36.86	130	214	A	V
	*	2412	109.28	-	-	108.43	30.57	7.13	36.85	130	214	P	V
	*	2410	101.57	-	-	100.72	30.57	7.13	36.85	130	214	A	V
802.11g CH 10 2457MHz		2483.5	61.77	-12.23	74	60.48	30.86	7.25	36.82	384	223	P	H
		2483.5	48.29	-5.71	54	47	30.86	7.25	36.82	384	223	A	H
	*	2452	108.96	-	-	107.9	30.71	7.19	36.84	384	223	P	H
	*	2452	101.16	-	-	100.1	30.71	7.19	36.84	384	223	A	H
		2483.56	66.28	-7.72	74	64.99	30.86	7.25	36.82	112	222	P	V
		2483.5	52.09	-1.91	54	50.8	30.86	7.25	36.82	112	222	A	V
	*	2458	112.11	-	-	110.93	30.79	7.22	36.83	112	222	P	V
	*	2456	103.83	-	-	102.65	30.79	7.22	36.83	112	222	A	V
802.11g CH 11 2462MHz		2483.5	69.39	-4.61	74	68.1	30.86	7.25	36.82	377	9	P	H
		2483.5	50.97	-3.03	54	49.68	30.86	7.25	36.82	377	9	A	H
		2456	108.31	-	-	107.13	30.79	7.22	36.83	377	9	P	H
		2456	100.4	-	-	99.22	30.79	7.22	36.83	377	9	A	H
		2483.56	71.65	-2.35	74	70.36	30.86	7.25	36.82	124	313	P	V
		2483.5	52.77	-1.23	54	51.48	30.86	7.25	36.82	124	313	A	V
		2468	108.73	-	-	107.55	30.79	7.22	36.83	124	313	P	V
		2468	101.03	-	-	99.85	30.79	7.22	36.83	124	313	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4830	48.07	-25.93	74	63.25	34.61	10.25	60.04	300	0	P	H
		4830	47.21	-26.79	74	62.39	34.61	10.25	60.04	100	0	P	V
802.11g CH 06 2437MHz		4875	47.38	-26.62	74	62.43	34.69	10.29	60.03	300	0	P	H
		7320	56.32	-17.68	74	67.45	36.67	12.72	60.52	241	310	P	H
		7320	46.37	-7.63	54	57.5	36.67	12.72	60.52	241	310	A	H
		4875	47.39	-26.61	74	62.44	34.69	10.29	60.03	100	0	P	V
		7305	56.82	-17.18	74	67.93	36.68	12.72	60.51	100	283	P	V
		7305	45.18	-8.82	54	56.29	36.68	12.72	60.51	100	283	A	V
802.11g CH 10 2457MHz		4914	49.93	-24.07	74	70.29	34.74	10.34	65.44	300	0	P	H
		7365	54.95	-19.05	74	71.62	36.66	12.73	66.06	269	235	P	H
		7365	43.27	-10.73	54	59.94	36.66	12.73	66.06	269	235	A	H
		4914	48.3	-25.7	74	68.66	34.74	10.34	65.44	100	0	P	V
		7365	54.94	-19.06	74	71.61	36.66	12.73	66.06	100	277	P	V
		7365	43.98	-10.02	54	60.65	36.66	12.73	66.06	100	277	A	V
802.11g CH 11 2462MHz		4920	47.87	-26.13	74	62.78	34.77	10.34	60.02	300	0	P	H
		7380	48.52	-25.48	74	59.67	36.65	12.73	60.53	300	0	P	H
		4920	46.5	-27.5	74	61.41	34.77	10.34	60.02	100	0	P	V
		7380	47.87	-26.13	74	59.02	36.65	12.73	60.53	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.82	68.27	-5.73	74	67.53	30.5	7.1	36.86	354	0	P	H
		2389.95	51.31	-2.69	54	50.57	30.5	7.1	36.86	354	0	A	H
	*	2414	108.05	-	-	107.2	30.57	7.13	36.85	354	0	P	H
	*	2410	99.96	-	-	99.11	30.57	7.13	36.85	354	0	A	H
		2389.95	69.68	-4.32	74	68.94	30.5	7.1	36.86	102	210	P	V
		2389.95	52.76	-1.24	54	52.02	30.5	7.1	36.86	102	210	A	V
	*	2410	108.6	-	-	107.75	30.57	7.13	36.85	102	210	P	V
	*	2410	100.54	-	-	99.69	30.57	7.13	36.85	102	210	A	V
802.11n HT20 CH 10 2457MHz		2483.74	63.42	-10.58	74	62.13	30.86	7.25	36.82	342	221	P	H
		2483.5	49.18	-4.82	54	47.89	30.86	7.25	36.82	342	221	A	H
		2464	108.31	-	-	107.13	30.79	7.22	36.83	342	221	P	H
		2464	100.23	-	-	99.05	30.79	7.22	36.83	342	221	A	H
		2483.5	65.35	-8.65	74	64.06	30.86	7.25	36.82	110	222	P	V
		2483.5	51.11	-2.89	54	49.82	30.86	7.25	36.82	110	222	A	V
		2454	111.11	-	-	109.93	30.79	7.22	36.83	110	222	P	V
		2456	102.65	-	-	101.47	30.79	7.22	36.83	110	222	A	V
802.11n HT20 CH 11 2462MHz		2483.62	66.06	-7.94	74	64.77	30.86	7.25	36.82	379	360	P	H
		2483.5	50.83	-3.17	54	49.54	30.86	7.25	36.82	379	360	A	H
	*	2460	107.77	-	-	106.59	30.79	7.22	36.83	379	360	P	H
	*	2456	98.9	-	-	97.72	30.79	7.22	36.83	379	360	A	H
		2483.62	68.25	-5.75	74	66.96	30.86	7.25	36.82	111	314	P	V
		2483.5	52.96	-1.04	54	51.67	30.86	7.25	36.82	111	314	A	V
	*	2458	107.04	-	-	105.86	30.79	7.22	36.83	111	314	P	V
	*	2456	99.38	-	-	98.2	30.79	7.22	36.83	111	314	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4830	46.67	-27.33	74	61.85	34.61	10.25	60.04	300	0	P	H
		4830	45.31	-28.69	74	60.49	34.61	10.25	60.04	100	0	P	V
802.11n HT20 CH 06 2437MHz		4875	48.79	-25.21	74	63.84	34.69	10.29	60.03	300	0	P	H
		7320	53.18	-20.82	74	64.31	36.67	12.72	60.52	273	239	P	H
		7320	41.85	-12.15	54	52.98	36.67	12.72	60.52	273	239	A	H
		4875	46.3	-27.7	74	61.35	34.69	10.29	60.03	100	0	P	V
		7305	53.36	-20.64	74	64.47	36.68	12.72	60.51	100	282	P	V
		7305	42.82	-11.18	54	53.93	36.68	12.72	60.51	100	282	A	V
802.11n HT20 CH 10 2457MHz		4914	46.92	-27.08	74	67.28	34.74	10.34	65.44	300	0	P	H
		7365	52.49	-21.51	74	69.16	36.66	12.73	66.06	100	229	P	H
		7365	40.51	-13.49	54	57.18	36.66	12.73	66.06	100	229	A	H
		4914	47.15	-26.85	74	67.51	34.74	10.34	65.44	100	0	P	V
		7365	53.43	-20.57	74	70.1	36.66	12.73	66.06	100	277	P	V
		7365	42.03	-11.97	54	58.7	36.66	12.73	66.06	100	277	A	V
802.11n HT20 CH 11 2462MHz		4920	48.2	-25.8	74	63.11	34.77	10.34	60.02	300	0	P	H
		7386	45.77	-28.23	74	56.93	36.64	12.73	60.53	300	0	P	H
		4920	44.5	-29.5	74	59.41	34.77	10.34	60.02	100	0	P	V
		7386	46.45	-27.55	74	57.61	36.64	12.73	60.53	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.95	65.33	-8.67	74	64.59	30.5	7.1	36.86	350	360	P	H
		2389.95	49.25	-4.75	54	48.51	30.5	7.1	36.86	350	360	A	H
		2485.06	53.75	-20.25	74	52.46	30.86	7.25	36.82	350	360	P	H
		2483.5	43.04	-10.96	54	41.75	30.86	7.25	36.82	350	360	A	H
	*	2430	105.27	-	-	104.32	30.64	7.16	36.85	350	360	P	H
	*	2424	96.73	-	-	95.78	30.64	7.16	36.85	350	360	A	H
		2389.56	69.62	-4.38	74	68.88	30.5	7.1	36.86	137	313	P	V
		2389.95	52.99	-1.01	54	52.25	30.5	7.1	36.86	137	313	A	V
		2499.52	55.86	-18.14	74	54.46	30.93	7.28	36.81	137	313	P	V
		2496.1	44.97	-9.03	54	43.57	30.93	7.28	36.81	137	313	A	V
	*	2430	106.72	-	-	105.77	30.64	7.16	36.85	137	313	P	V
	*	2424	98.41	-	-	97.46	30.64	7.16	36.85	137	313	A	V
802.11n HT40 CH 06 2437MHz		2389.69	56.84	-17.16	74	56.1	30.5	7.1	36.86	302	357	P	H
		2389.95	43.35	-10.65	54	42.61	30.5	7.1	36.86	302	357	A	H
		2483.68	61.66	-12.34	74	60.37	30.86	7.25	36.82	302	357	P	H
		2483.5	48.23	-5.77	54	46.94	30.86	7.25	36.82	302	357	A	H
	*	2446	106.68	-	-	105.62	30.71	7.19	36.84	302	357	P	H
	*	2446	98.2	-	-	97.14	30.71	7.19	36.84	302	357	A	H
		2389.95	63.8	-10.2	74	63.06	30.5	7.1	36.86	100	310	P	V
		2389.95	49.22	-4.78	54	48.48	30.5	7.1	36.86	100	310	A	V
		2483.56	64.13	-9.87	74	62.84	30.86	7.25	36.82	100	310	P	V
		2483.5	49.71	-4.29	54	48.42	30.86	7.25	36.82	100	310	A	V
	*	2436	108.18	-	-	107.2	30.64	7.19	36.85	100	310	P	V
	*	2434	100.28	-	-	99.33	30.64	7.16	36.85	100	310	A	V



802.11n HT40 CH 09 2452MHz		2383.19	50.11	-23.89	74	49.4	30.48	7.1	36.87	390	360	P	H
		2389.95	39.97	-14.03	54	39.23	30.5	7.1	36.86	390	360	A	H
		2483.62	64.6	-9.4	74	63.31	30.86	7.25	36.82	390	360	P	H
		2483.5	49.15	-4.85	54	47.86	30.86	7.25	36.82	390	360	A	H
	*	2450	103.78	-	-	102.72	30.71	7.19	36.84	390	360	P	H
	*	2450	96.1	-	-	95.04	30.71	7.19	36.84	390	360	A	H
		2389.69	52.74	-21.26	74	52	30.5	7.1	36.86	104	311	P	V
		2389.95	41.51	-12.49	54	40.77	30.5	7.1	36.86	104	311	A	V
		2483.5	67.96	-6.04	74	66.67	30.86	7.25	36.82	104	311	P	V
		2483.5	52.45	-1.55	54	51.16	30.86	7.25	36.82	104	311	A	V
	*	2454	104.39	-	-	103.21	30.79	7.22	36.83	104	311	P	V
	*	2454	96.57	-	-	95.39	30.79	7.22	36.83	104	311	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4845	43.78	-30.22	74	64.29	34.63	10.25	65.39	300	0	P	H
		7260	45.2	-28.8	74	61.54	36.7	12.72	65.76	300	0	P	H
		4845	43.35	-30.65	74	63.86	34.63	10.25	65.39	100	0	P	V
		7260	46.01	-27.99	74	62.35	36.7	12.72	65.76	100	0	P	V
802.11n HT40 CH 06 2437MHz		4890	45.35	-28.65	74	60.34	34.71	10.32	60.02	300	0	P	H
		7320	48.61	-25.39	74	59.74	36.67	12.72	60.52	300	0	P	H
		4875	44.29	-29.71	74	59.34	34.69	10.29	60.03	100	0	P	V
		7305	49.18	-24.82	74	60.29	36.68	12.72	60.51	100	0	P	V
802.11n HT40 CH 09 2452MHz		4905	42.77	-31.23	74	63.13	34.74	10.34	65.44	300	0	P	H
		7350	44.33	-29.67	74	61.01	36.66	12.72	66.06	300	0	P	H
		4905	42.41	-31.59	74	62.77	34.74	10.34	65.44	100	0	P	V
		7350	43.75	-30.25	74	60.43	36.66	12.72	66.06	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		34.85	19.52	-20.48	40	28.66	22.3	0.76	32.2	-	-	P	H
		166.77	27.91	-15.59	43.5	42.53	15.6	1.88	32.1	-	-	P	H
		216.24	30.87	-15.13	46	46.03	14.88	2.09	32.13	-	-	P	H
		359.8	27.7	-18.3	46	36.62	20.5	2.8	32.22	-	-	P	H
		498.51	33.1	-12.9	46	38.58	23.77	3.14	32.39	-	-	P	H
		640.13	27.92	-18.08	46	30.13	26.3	3.71	32.22	-	-	P	H
		60.07	19.11	-20.89	40	38.34	11.8	1.07	32.1	-	-	P	V
		167.74	23.5	-20	43.5	38.22	15.5	1.88	32.1	-	-	P	V
		408.3	25.5	-20.5	46	32.7	22.06	3.02	32.28	-	-	P	V
		498.51	35.49	-10.51	46	40.97	23.77	3.14	32.39	-	-	P	V
		640.13	35.54	-10.46	46	37.75	26.3	3.71	32.22	-	-	P	V
		880.69	29.32	-16.68	46	28.14	29.06	4.4	32.28	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots





Note symbol

-L	Low channel location
-R	High channel location
Only the worst case Radiated Spurious Emission Plots are shown.	







2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																									
ANT	802.11g CH01 2412MHz																																																									
1	Horizontal	Fundamental																																																								
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 3000 000000 SRT Auto Mode : (FR) 1N0918 Plane : 13 Polar : Full-directivity Polarization : #2 Power setting : 4 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th>on</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>70.64</td><td>-3.36</td><td>74.00</td><td>69.90</td><td>30.50</td><td>7.10</td><td>36.86</td><td>354</td><td>356 Peak</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor		on	deg	1	2389.95	70.64	-3.36	74.00	69.90	30.50	7.10	36.86	354	356 Peak	HORIZONTAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 3000 000000 SRT Auto Mode : (FR) 1N0918 Plane : 13 Polar : Full-directivity Polarization : #2 Power setting : 4 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th>on</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>109.77</td><td>35.77</td><td>74.00</td><td>108.92</td><td>30.57</td><td>7.13</td><td>36.85</td><td>354</td><td>356 Peak</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor		on	deg	1	2412.00	109.77	35.77	74.00	108.92	30.57	7.13	36.85	354	356 Peak	HORIZONTAL
Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																			
Freq	Level	Line	Level Factor	Loss Factor		on	deg																																																			
1	2389.95	70.64	-3.36	74.00	69.90	30.50	7.10	36.86	354	356 Peak	HORIZONTAL																																															
Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																			
Freq	Level	Line	Level Factor	Loss Factor		on	deg																																																			
1	2412.00	109.77	35.77	74.00	108.92	30.57	7.13	36.85	354	356 Peak	HORIZONTAL																																															
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 0.018000 SRT Auto Mode : (FR) 1N0918 Plane : 13 Polar : Full-directivity Polarization : #2 Power setting : 4 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th>on</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>52.82</td><td>-1.18</td><td>54.00</td><td>52.08</td><td>30.50</td><td>7.10</td><td>36.86</td><td>354</td><td>356 Average</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor		on	deg	1	2389.95	52.82	-1.18	54.00	52.08	30.50	7.10	36.86	354	356 Average	HORIZONTAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 0.018000 SRT Auto Mode : (FR) 1N0918 Plane : 13 Polar : Full-directivity Polarization : #2 Power setting : 4 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th>on</th><th>deg</th></tr><tr><td>1</td><td>2410.00</td><td>101.24</td><td>47.24</td><td>54.00</td><td>100.39</td><td>30.57</td><td>7.13</td><td>36.85</td><td>354</td><td>356 Average</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor		on	deg	1	2410.00	101.24	47.24	54.00	100.39	30.57	7.13	36.85	354	356 Average	HORIZONTAL
Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																			
Freq	Level	Line	Level Factor	Loss Factor		on	deg																																																			
1	2389.95	52.82	-1.18	54.00	52.08	30.50	7.10	36.86	354	356 Average	HORIZONTAL																																															
Over	Limit	ReadAntenna	Cable Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																			
Freq	Level	Line	Level Factor	Loss Factor		on	deg																																																			
1	2410.00	101.24	47.24	54.00	100.39	30.57	7.13	36.85	354	356 Average	HORIZONTAL																																															







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																										
ANT	802.11g CH10 2457MHz - L																																																																																																																																										
1	Horizontal	Fundamental																																																																																																																																									
Peak	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Site : 03C805-E5 Condition : FCC PART 15C 3m 3117 00218052 HORIZONTAL Project : RSW 1000.000MHz YMW 3000.000MHz SPT Auto Mode : CPUL180918 Plane : 22 Polarization : Pull-directivity IME1 : #2 Power setting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2483.58</td><td>61.77</td><td>-12.23</td><td>74.00</td><td>68.48</td><td>38.86</td><td>7.25</td><td>36.82</td><td>384</td><td>223 Peak</td><td>HORIZONTAL</td></tr></table>  No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Site : 03C805-E5 Condition : FCC PART 15C 3m 3117 00218052 HORIZONTAL Project : RSW 1000.000MHz YMW 3000.000MHz SPT Auto Mode : CPUL180918 Plane : 22 Polarization : Pull-directivity IME1 : #2 Power setting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2452.88</td><td>188.96</td><td>34.96</td><td>74.00</td><td>187.98</td><td>38.71</td><td>7.19</td><td>36.84</td><td>384</td><td>223 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1	2483.58	61.77	-12.23	74.00	68.48	38.86	7.25	36.82	384	223 Peak	HORIZONTAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1	2452.88	188.96	34.96	74.00	187.98	38.71	7.19	36.84	384	223 Peak	HORIZONTAL	Avg.	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Site : 03C805-E5 Condition : FCC PART 15C (AVG) 3m 3117 00218052 HORIZONTAL Project : RSW 1000.000MHz YMW 3000.000MHz SPT Auto Mode : CPUL180918 Plane : 22 Polarization : Pull-directivity IME1 : #2 Power setting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2483.58</td><td>48.29</td><td>-5.71</td><td>54.00</td><td>47.88</td><td>38.86</td><td>7.25</td><td>36.82</td><td>384</td><td>223 Average</td><td>HORIZONTAL</td></tr></table>  No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Site : 03C805-E5 Condition : FCC PART 15C (AVG) 3m 3117 00218052 HORIZONTAL Project : RSW 1000.000MHz YMW 3000.000MHz SPT Auto Mode : CPUL180918 Plane : 22 Polarization : Pull-directivity IME1 : #2 Power setting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2452.88</td><td>181.16</td><td>47.16</td><td>54.00</td><td>180.18</td><td>38.71</td><td>7.19</td><td>36.84</td><td>384</td><td>223 Average</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1	2483.58	48.29	-5.71	54.00	47.88	38.86	7.25	36.82	384	223 Average	HORIZONTAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1	2452.88	181.16	47.16	54.00	180.18	38.71	7.19	36.84	384	223 Average	HORIZONTAL
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																			
1	2483.58	61.77	-12.23	74.00	68.48	38.86	7.25	36.82	384	223 Peak	HORIZONTAL																																																																																																																																
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																			
1	2452.88	188.96	34.96	74.00	187.98	38.71	7.19	36.84	384	223 Peak	HORIZONTAL																																																																																																																																
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																			
1	2483.58	48.29	-5.71	54.00	47.88	38.86	7.25	36.82	384	223 Average	HORIZONTAL																																																																																																																																
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																			
1	2452.88	181.16	47.16	54.00	180.18	38.71	7.19	36.84	384	223 Average	HORIZONTAL																																																																																																																																







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																									
ANT	802.11g CH10 2457MHz - L																																																									
1	Vertical	Fundamental																																																								
Peak	 Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.56</td><td>66.28</td><td>-7.72</td><td>74.00</td><td>64.99</td><td>30.86</td><td>7.25 36.82</td><td>112 222 Peak</td><td>VERTICAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg		1	2483.56	66.28	-7.72	74.00	64.99	30.86	7.25 36.82	112 222 Peak	VERTICAL	 Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2458.00</td><td>112.11</td><td>38.11</td><td>74.00</td><td>110.93</td><td>38.79</td><td>7.22 36.83</td><td>112 222 Peak</td><td>VERTICAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg		1	2458.00	112.11	38.11	74.00	110.93	38.79	7.22 36.83	112 222 Peak	VERTICAL
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																		
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																			
1	2483.56	66.28	-7.72	74.00	64.99	30.86	7.25 36.82	112 222 Peak	VERTICAL																																																	
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																		
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																			
1	2458.00	112.11	38.11	74.00	110.93	38.79	7.22 36.83	112 222 Peak	VERTICAL																																																	
Avg.	 Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.58</td><td>52.89</td><td>-1.91</td><td>54.80</td><td>58.88</td><td>30.86</td><td>7.25 36.82</td><td>112 222 Average</td><td>VERTICAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg		1	2483.58	52.89	-1.91	54.80	58.88	30.86	7.25 36.82	112 222 Average	VERTICAL	 Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2456.00</td><td>183.83</td><td>49.83</td><td>54.80</td><td>182.65</td><td>38.79</td><td>7.22 36.83</td><td>112 222 Average</td><td>VERTICAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg		1	2456.00	183.83	49.83	54.80	182.65	38.79	7.22 36.83	112 222 Average	VERTICAL
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																		
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																			
1	2483.58	52.89	-1.91	54.80	58.88	30.86	7.25 36.82	112 222 Average	VERTICAL																																																	
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																		
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																			
1	2456.00	183.83	49.83	54.80	182.65	38.79	7.22 36.83	112 222 Average	VERTICAL																																																	







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																			
ANT	802.11g CH11 2462MHz																																																																			
1	Horizontal	Fundamental																																																																		
Peak	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RSR 1000 000KHz VBR 3000 000KHz SRT Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dBm</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 1 2483.50</td><td>69.39</td><td>-4.61</td><td>74.00</td><td>68.10</td><td>30.86</td><td>7.25</td><td>36.82</td><td>377</td><td>9 Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg		1 1 2483.50	69.39	-4.61	74.00	68.10	30.86	7.25	36.82	377	9 Peak	HORIZONTAL	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RSR 1000 000KHz VBR 3000 000KHz SRT Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dBm</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 * 2462.00</td><td>108.31</td><td>34.31</td><td>74.00</td><td>107.13</td><td>30.79</td><td>7.22</td><td>36.83</td><td>377</td><td>9 Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg		1 * 2462.00	108.31	34.31	74.00	107.13	30.79	7.22	36.83	377	9 Peak	HORIZONTAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																									
MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg																																																											
1 1 2483.50	69.39	-4.61	74.00	68.10	30.86	7.25	36.82	377	9 Peak	HORIZONTAL																																																										
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg																																																											
1 * 2462.00	108.31	34.31	74.00	107.13	30.79	7.22	36.83	377	9 Peak	HORIZONTAL																																																										
Avg.	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RSR 1000 000KHz VBR 0 01000K SRT Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dBm</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 1 2483.50</td><td>50.97</td><td>-3.03</td><td>54.00</td><td>49.68</td><td>30.86</td><td>7.25</td><td>36.82</td><td>377</td><td>9 Average</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg		1 1 2483.50	50.97	-3.03	54.00	49.68	30.86	7.25	36.82	377	9 Average	HORIZONTAL	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RSR 1000 000KHz VBR 0 01000K SRT Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dBm</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 * 2462.00</td><td>100.40</td><td>46.40</td><td>54.00</td><td>99.22</td><td>30.79</td><td>7.22</td><td>36.83</td><td>377</td><td>9 Average</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg		1 * 2462.00	100.40	46.40	54.00	99.22	30.79	7.22	36.83	377	9 Average	HORIZONTAL
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg																																																											
1 1 2483.50	50.97	-3.03	54.00	49.68	30.86	7.25	36.82	377	9 Average	HORIZONTAL																																																										
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dB	dBm	dBm	dB	dB	dB	dB	deg																																																											
1 * 2462.00	100.40	46.40	54.00	99.22	30.79	7.22	36.83	377	9 Average	HORIZONTAL																																																										







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																			
ANT	802.11g CH11 2462MHz																																																																			
1	Vertical	Fundamental																																																																		
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : RSR 1000.000kHz VBR 3000.000kHz SRT Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><tr><th>IMEI</th><th>Power setting</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>deg</th><th></th></tr><tr><td>1 1</td><td>2483.56</td><td>71.65</td><td>-2.35</td><td>74.00</td><td>70.36</td><td>30.86</td><td>7.25</td><td>36.82</td><td>124</td><td>313 Peak VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : RSR 1000.000kHz VBR 3000.000kHz SRT Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><tr><th>IMEI</th><th>Power setting</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>deg</th><th></th></tr><tr><td>1 *</td><td>2468.00</td><td>108.73</td><td>34.73</td><td>74.00</td><td>107.55</td><td>30.79</td><td>7.22</td><td>36.83</td><td>124</td><td>313 Peak VERTICAL</td></tr></table>	IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg		1 1	2483.56	71.65	-2.35	74.00	70.36	30.86	7.25	36.82	124	313 Peak VERTICAL	IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg		1 *	2468.00	108.73	34.73	74.00	107.55	30.79	7.22	36.83	124	313 Peak VERTICAL	
IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg																																																											
1 1	2483.56	71.65	-2.35	74.00	70.36	30.86	7.25	36.82	124	313 Peak VERTICAL																																																										
IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg																																																											
1 *	2468.00	108.73	34.73	74.00	107.55	30.79	7.22	36.83	124	313 Peak VERTICAL																																																										
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : RSR 1000.000kHz VBR 0.01000kHz SRT Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><tr><th>IMEI</th><th>Power setting</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>deg</th><th></th></tr><tr><td>1 1</td><td>2483.50</td><td>52.77</td><td>-1.23</td><td>54.00</td><td>51.48</td><td>30.86</td><td>7.25</td><td>36.82</td><td>124</td><td>313 Average VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : RSR 1000.000kHz VBR 0.01000kHz SRT Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 16 IMEI : 82 <table><tr><th>IMEI</th><th>Power setting</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>dBm</th><th>deg</th><th></th></tr><tr><td>1 *</td><td>2468.00</td><td>101.03</td><td>47.03</td><td>54.00</td><td>99.85</td><td>30.79</td><td>7.22</td><td>36.83</td><td>124</td><td>313 Average VERTICAL</td></tr></table>	IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg		1 1	2483.50	52.77	-1.23	54.00	51.48	30.86	7.25	36.82	124	313 Average VERTICAL	IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg		1 *	2468.00	101.03	47.03	54.00	99.85	30.79	7.22	36.83	124	313 Average VERTICAL	
IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg																																																											
1 1	2483.50	52.77	-1.23	54.00	51.48	30.86	7.25	36.82	124	313 Average VERTICAL																																																										
IMEI	Power setting	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																										
MHz	dBm	dBm	dBm	dBm	dBm	dBm	dBm	dBm	deg																																																											
1 *	2468.00	101.03	47.03	54.00	99.85	30.79	7.22	36.83	124	313 Average VERTICAL																																																										







2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 3000 000000 SRT Auto Mode : (F) 1N0918 Plane : 1a Z : 2 Full-directivity : 0 Power setting : 0 Over Limit : 0 ReadAntenna : 0 Cable Preamp : 0 A/Pos : 354 T/Pos : 354 Remark : 0 Peak Pol/Phas : HORIZONTAL	 Site : 030905-KS Condition : FCC PART 15C 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 3000 000000 SRT Auto Mode : (F) 1N0918 Plane : 1a Z : 2 Full-directivity : 0 Power setting : 0 Over Limit : 0 ReadAntenna : 0 Cable Preamp : 0 A/Pos : 354 T/Pos : 354 Remark : 0 Peak Pol/Phas : HORIZONTAL
Avg.	 Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 0.010000 SRT Auto Mode : (F) 1N0918 Plane : 1a Z : 2 Full-directivity : 0 Power setting : 0 Over Limit : 0 ReadAntenna : 0 Cable Preamp : 0 A/Pos : 354 T/Pos : 354 Remark : 0 Average Pol/Phas : HORIZONTAL	 Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Project : RRM 1000 000000 VSW 0.010000 SRT Auto Mode : (F) 1N0918 Plane : 1a Z : 2 Full-directivity : 0 Power setting : 0 Over Limit : 0 ReadAntenna : 0 Cable Preamp : 0 A/Pos : 354 T/Pos : 354 Remark : 0 Average Pol/Phas : HORIZONTAL







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																										
ANT	802.11n HT20 CH01 2412MHz																																																																																																																										
1	Vertical	Fundamental																																																																																																																									
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : 16 Plane : 2 Full-directivity : 2 Power setting : 0 IME1 : 82 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>deg</th><th></th></tr><tr><td>1 1 2389.95</td><td>69.68</td><td>-4.32</td><td>74.00</td><td>68.94</td><td>30.50</td><td>7.10</td><td>36.86</td><td>102</td><td>210 Peak VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : 16 Plane : 2 Full-directivity : 2 Power setting : 0 IME1 : 82 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>deg</th><th></th></tr><tr><td>1 * 2410.00</td><td>108.60</td><td>34.60</td><td>74.00</td><td>107.75</td><td>30.57</td><td>7.13</td><td>36.85</td><td>102</td><td>210 Peak VERTICAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg		1 1 2389.95	69.68	-4.32	74.00	68.94	30.50	7.10	36.86	102	210 Peak VERTICAL	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg		1 * 2410.00	108.60	34.60	74.00	107.75	30.57	7.13	36.85	102	210 Peak VERTICAL	Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117.00218652 VERTICAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : 16 Plane : 2 Full-directivity : 2 Power setting : 0 IME1 : 82 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>deg</th><th></th></tr><tr><td>1 1 2389.95</td><td>52.76</td><td>-1.24</td><td>54.00</td><td>52.02</td><td>30.50</td><td>7.10</td><td>36.86</td><td>102</td><td>210 Average VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030905-KS Condition : FCC PART 15C (AVG) 3m 3117.00218652 VERTICAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : 16 Plane : 2 Full-directivity : 2 Power setting : 0 IME1 : 82 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>deg</th><th></th></tr><tr><td>1 * 2410.00</td><td>100.54</td><td>46.54</td><td>54.00</td><td>99.69</td><td>30.57</td><td>7.13</td><td>36.85</td><td>102</td><td>210 Average VERTICAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg		1 1 2389.95	52.76	-1.24	54.00	52.02	30.50	7.10	36.86	102	210 Average VERTICAL	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg		1 * 2410.00	100.54	46.54	54.00	99.69	30.57	7.13	36.85	102	210 Average VERTICAL
	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																	
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg																																																																																																																			
1 1 2389.95	69.68	-4.32	74.00	68.94	30.50	7.10	36.86	102	210 Peak VERTICAL																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg																																																																																																																			
1 * 2410.00	108.60	34.60	74.00	107.75	30.57	7.13	36.85	102	210 Peak VERTICAL																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg																																																																																																																			
1 1 2389.95	52.76	-1.24	54.00	52.02	30.50	7.10	36.86	102	210 Average VERTICAL																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	deg																																																																																																																			
1 * 2410.00	100.54	46.54	54.00	99.69	30.57	7.13	36.85	102	210 Average VERTICAL																																																																																																																		









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																											
ANT	802.11n HT20 CH10 2457MHz - L																																																											
1	Horizontal	Fundamental																																																										
Peak	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China Tel:+86-512-57900158 Fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Pull-directivity : 2 PowerSetting : 0 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.74</td><td>63.42</td><td>-18.58</td><td>74.00</td><td>62.13</td><td>30.86</td><td>7.25</td><td>36.82</td><td>342</td><td>221</td><td>Peak</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg	1	2483.74	63.42	-18.58	74.00	62.13	30.86	7.25	36.82	342	221	Peak	HORIZONTAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China Tel:+86-512-57900158 Fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Pull-directivity : 2 PowerSetting : 0 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2464.00</td><td>188.31</td><td>34.31</td><td>74.00</td><td>187.13</td><td>38.79</td><td>7.22</td><td>36.83</td><td>342</td><td>221</td><td>Peak</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg	1	2464.00	188.31	34.31	74.00	187.13	38.79	7.22	36.83	342	221	Peak	HORIZONTAL
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg																																																					
1	2483.74	63.42	-18.58	74.00	62.13	30.86	7.25	36.82	342	221	Peak	HORIZONTAL																																																
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg																																																					
1	2464.00	188.31	34.31	74.00	187.13	38.79	7.22	36.83	342	221	Peak	HORIZONTAL																																																
Avg.	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China Tel:+86-512-57900158 Fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Pull-directivity : 2 PowerSetting : 0 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.58</td><td>49.18</td><td>-4.82</td><td>54.00</td><td>47.89</td><td>30.86</td><td>7.25</td><td>36.82</td><td>342</td><td>221</td><td>Average</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg	1	2483.58	49.18	-4.82	54.00	47.89	30.86	7.25	36.82	342	221	Average	HORIZONTAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China Tel:+86-512-57900158 Fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : 2 Pull-directivity : 2 PowerSetting : 0 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2464.00</td><td>188.23</td><td>46.23</td><td>54.00</td><td>99.95</td><td>38.79</td><td>7.22</td><td>36.83</td><td>342</td><td>221</td><td>Average</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg	1	2464.00	188.23	46.23	54.00	99.95	38.79	7.22	36.83	342	221	Average	HORIZONTAL
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg																																																					
1	2483.58	49.18	-4.82	54.00	47.89	30.86	7.25	36.82	342	221	Average	HORIZONTAL																																																
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
Freq	Level	dB	dBuV/m	dBuV	dB	cm	deg																																																					
1	2464.00	188.23	46.23	54.00	99.95	38.79	7.22	36.83	342	221	Average	HORIZONTAL																																																







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																		
ANT	802.11n HT20 CH10 2457MHz - L																																																																																																																																		
1	Vertical	Fundamental																																																																																																																																	
Peak	 No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.50</td><td>65.35</td><td>-8.65</td><td>74.00</td><td>64.86</td><td>30.86</td><td>7.25</td><td>36.82</td><td>110</td><td>222 Peak</td><td>VERTICAL</td></tr></table>  No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2454.00</td><td>111.11</td><td>37.11</td><td>74.00</td><td>109.93</td><td>30.79</td><td>7.22</td><td>36.83</td><td>110</td><td>222 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2483.50	65.35	-8.65	74.00	64.86	30.86	7.25	36.82	110	222 Peak	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2454.00	111.11	37.11	74.00	109.93	30.79	7.22	36.83	110	222 Peak	VERTICAL	Avg.	 No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.50</td><td>51.11</td><td>-2.89</td><td>54.00</td><td>49.82</td><td>30.86</td><td>7.25</td><td>36.82</td><td>110</td><td>222 Average</td><td>VERTICAL</td></tr></table>  No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Site : 03C005-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Model : CPU180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2456.00</td><td>102.65</td><td>48.65</td><td>54.00</td><td>101.47</td><td>30.79</td><td>7.22</td><td>36.83</td><td>110</td><td>222 Average</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2483.50	51.11	-2.89	54.00	49.82	30.86	7.25	36.82	110	222 Average	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2456.00	102.65	48.65	54.00	101.47	30.79	7.22	36.83	110	222 Average	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																											
1	2483.50	65.35	-8.65	74.00	64.86	30.86	7.25	36.82	110	222 Peak	VERTICAL																																																																																																																								
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																										
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																											
1	2454.00	111.11	37.11	74.00	109.93	30.79	7.22	36.83	110	222 Peak	VERTICAL																																																																																																																								
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																										
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																											
1	2483.50	51.11	-2.89	54.00	49.82	30.86	7.25	36.82	110	222 Average	VERTICAL																																																																																																																								
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																										
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																											
1	2456.00	102.65	48.65	54.00	101.47	30.79	7.22	36.83	110	222 Average	VERTICAL																																																																																																																								







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 18 117 Level (dBV/m)  FCC PART 15C dBm Site Condition : 030905-KS Project : FCC PART 15C 3m 3117 00218652 HORIZONTAL Mode : R88-1000 000KHz VBR-3000 000KHz SRT-Auto Plane : (FR) 1N0918 Full-directivity : 18 Power : Full-directivity Power setting : 82 IMEI : 82 Power setting : 20 Over Limit ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phase Freq Level Limit Line Level Factor Loss Factor dB dB cm deg 1 2483.62 66.06 -7.94 74.00 64.77 30.86 7.25 36.82 379 360 Peak HORIZONTAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 20 117 Level (dBV/m)  FCC PART 15C dBm Site Condition : 030905-KS Project : FCC PART 15C 3m 3117 00218652 HORIZONTAL Mode : R88-1000 000KHz VBR-3000 000KHz SRT-Auto Plane : (FR) 1N0918 Full-directivity : 18 Power : Full-directivity Power setting : 82 IMEI : 82 Power setting : 20 Over Limit ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phase Freq Level Limit Line Level Factor Loss Factor dB dB cm deg 1 * 2460.00 107.77 33.77 74.00 106.59 30.79 7.22 36.83 379 360 Peak HORIZONTAL
	Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 19 117 Level (dBV/m)  FCC PART 15C (AVG) dBm Site Condition : 030905-KS Project : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL Mode : R88-1000 000KHz VBR-3000 000KHz SRT-Auto Plane : (FR) 1N0918 Full-directivity : 18 Power : Full-directivity Power setting : 82 IMEI : 82 Power setting : 20 Over Limit ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phase Freq Level Limit Line Level Factor Loss Factor dB dB cm deg 1 2483.50 50.83 -3.17 54.00 49.54 30.86 7.25 36.82 379 360 Average HORIZONTAL



WIFI		2.4GHz 2400~2483.5MHz Fundamental @ 3m																																																										
ANT		802.11n HT20 CH11 2462MHz																																																										
1	Vertical	Fundamental																																																										
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 22 Site : 030H05-KS Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 20 IMEI : 82 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1 1</td><td>2483.62</td><td>68.25</td><td>-5.75</td><td>74.00</td><td>66.96</td><td>30.86</td><td>7.25</td><td>36.82</td><td>111</td><td>314</td><td>Peak</td><td>VERTICAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1 1	2483.62	68.25	-5.75	74.00	66.96	30.86	7.25	36.82	111	314	Peak	VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 24 Site : 030H05-KS Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 20 IMEI : 82 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1 *</td><td>2468.00</td><td>107.04</td><td>33.04</td><td>74.00</td><td>105.86</td><td>30.79</td><td>7.22</td><td>36.83</td><td>111</td><td>314</td><td>Peak</td><td>VERTICAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1 *	2468.00	107.04	33.04	74.00	105.86	30.79	7.22	36.83	111	314	Peak	VERTICAL
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																				
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																						
1 1	2483.62	68.25	-5.75	74.00	66.96	30.86	7.25	36.82	111	314	Peak	VERTICAL																																																
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																					
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																						
1 *	2468.00	107.04	33.04	74.00	105.86	30.79	7.22	36.83	111	314	Peak	VERTICAL																																																
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 23 Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 20 IMEI : 82 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1 1</td><td>2483.50</td><td>52.96</td><td>-1.04</td><td>54.00</td><td>51.67</td><td>30.86</td><td>7.25</td><td>36.82</td><td>111</td><td>314</td><td>Average</td><td>VERTICAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1 1	2483.50	52.96	-1.04	54.00	51.67	30.86	7.25	36.82	111	314	Average	VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 25 Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SRT-Auto Bode : (FIR) 1N0918 Plane : 2 Full-directivity : 2 Power setting : 20 IMEI : 82 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1 *</td><td>2460.00</td><td>99.38</td><td>45.38</td><td>54.00</td><td>98.20</td><td>30.79</td><td>7.22</td><td>36.83</td><td>111</td><td>314</td><td>Average</td><td>VERTICAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1 *	2460.00	99.38	45.38	54.00	98.20	30.79	7.22	36.83	111	314	Average	VERTICAL
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																					
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																						
1 1	2483.50	52.96	-1.04	54.00	51.67	30.86	7.25	36.82	111	314	Average	VERTICAL																																																
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																					
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																						
1 *	2460.00	99.38	45.38	54.00	98.20	30.79	7.22	36.83	111	314	Average	VERTICAL																																																







WIFI		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																					
ANT		802.11n HT40 CH03 2422MHz - R																																																																																																																																					
1	Horizontal	Fundamental																																																																																																																																					
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3e 3117.00218652 HORIZONTAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1 2485.04</td><td>53.75</td><td>-20.25</td><td>74.00</td><td>52.46</td><td>30.86</td><td>7.25</td><td>36.82</td><td>350</td><td>360 Peak</td><td>HORIZONTAL</td></tr></tbody></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3e 3117.00218652 HORIZONTAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1 * 2430.00</td><td>105.27</td><td>31.27</td><td>74.00</td><td>104.32</td><td>30.64</td><td>7.16</td><td>36.85</td><td>350</td><td>360 Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1 2485.04	53.75	-20.25	74.00	52.46	30.86	7.25	36.82	350	360 Peak	HORIZONTAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1 * 2430.00	105.27	31.27	74.00	104.32	30.64	7.16	36.85	350	360 Peak	HORIZONTAL	Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3e 3117.00218652 HORIZONTAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1 2483.50</td><td>43.04</td><td>-10.96</td><td>54.00</td><td>41.75</td><td>30.86</td><td>7.25</td><td>36.82</td><td>350</td><td>360 Average</td><td>HORIZONTAL</td></tr></tbody></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3e 3117.00218652 HORIZONTAL Project : RSR-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1 * 2424.00</td><td>94.73</td><td>42.73</td><td>54.00</td><td>95.78</td><td>30.64</td><td>7.16</td><td>36.85</td><td>350</td><td>360 Average</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1 2483.50	43.04	-10.96	54.00	41.75	30.86	7.25	36.82	350	360 Average	HORIZONTAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg			1 * 2424.00	94.73	42.73	54.00	95.78	30.64	7.16	36.85	350	360 Average	HORIZONTAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																												
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																															
1 2485.04	53.75	-20.25	74.00	52.46	30.86	7.25	36.82	350	360 Peak	HORIZONTAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																													
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																															
1 * 2430.00	105.27	31.27	74.00	104.32	30.64	7.16	36.85	350	360 Peak	HORIZONTAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																													
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																															
1 2483.50	43.04	-10.96	54.00	41.75	30.86	7.25	36.82	350	360 Average	HORIZONTAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																													
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																															
1 * 2424.00	94.73	42.73	54.00	95.78	30.64	7.16	36.85	350	360 Average	HORIZONTAL																																																																																																																													



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																						
ANT	802.11n HT40 CH03 2422MHz - L																																																																																																																																						
1	Vertical	Fundamental																																																																																																																																					
Peak	No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : RSM 1000.000kHz VBR 3000.000kHz SRT Auto Bode : (F) 1N0918 Plane : 19 Z : 2 Full-directivity : 2 Power setting : 2 IME1 : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 1 2389.56</td><td>69.62</td><td>-4.38</td><td>74.00</td><td>68.88</td><td>30.50</td><td>7.10</td><td>36.86</td><td>137</td><td>313 Peak</td><td>VERTICAL</td></tr></table> No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : RSM 1000.000kHz VBR 3000.000kHz SRT Auto Bode : (F) 1N0918 Plane : 19 Z : 2 Full-directivity : 2 Power setting : 2 IME1 : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2430.00</td><td>106.72</td><td>32.72</td><td>74.00</td><td>105.77</td><td>30.64</td><td>7.16</td><td>36.85</td><td>137</td><td>313 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 1 2389.56	69.62	-4.38	74.00	68.88	30.50	7.10	36.86	137	313 Peak	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 * 2430.00	106.72	32.72	74.00	105.77	30.64	7.16	36.85	137	313 Peak	VERTICAL	Avg.	No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : RSM 1000.000kHz VBR 0.01000kHz SRT Auto Bode : (F) 1N0918 Plane : 19 Z : 2 Full-directivity : 2 Power setting : 2 IME1 : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 1 2389.95</td><td>52.99</td><td>-1.01</td><td>54.00</td><td>52.25</td><td>30.50</td><td>7.10</td><td>36.86</td><td>137</td><td>313 Average</td><td>VERTICAL</td></tr></table> No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : RSM 1000.000kHz VBR 0.01000kHz SRT Auto Bode : (F) 1N0918 Plane : 19 Z : 2 Full-directivity : 2 Power setting : 2 IME1 : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2424.00</td><td>98.41</td><td>44.41</td><td>54.00</td><td>97.46</td><td>30.64</td><td>7.16</td><td>36.85</td><td>137</td><td>313 Average</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 1 2389.95	52.99	-1.01	54.00	52.25	30.50	7.10	36.86	137	313 Average	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 * 2424.00	98.41	44.41	54.00	97.46	30.64	7.16	36.85	137	313 Average	VERTICAL
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 1 2389.56	69.62	-4.38	74.00	68.88	30.50	7.10	36.86	137	313 Peak	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 * 2430.00	106.72	32.72	74.00	105.77	30.64	7.16	36.85	137	313 Peak	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 1 2389.95	52.99	-1.01	54.00	52.25	30.50	7.10	36.86	137	313 Average	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 * 2424.00	98.41	44.41	54.00	97.46	30.64	7.16	36.85	137	313 Average	VERTICAL																																																																																																																													



WIFI		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																														
ANT		802.11n HT40 CH03 2422MHz - R																																																														
1	Vertical	Fundamental																																																														
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218602 VERTICAL Project : RSR 1000.000MHz VBR 3000.000MHz SRT-Auto Bode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><tr><th>MEI</th><th>Power setting</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dB</th><th>dBm/100m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr><tr><td>1</td><td>2499.92</td><td>55.86</td><td>-18.14</td><td>74.00</td><td>54.46</td><td>30.93</td><td>7.28</td><td>36.81</td><td>137</td><td>313</td><td>Peak</td><td>VERTICAL</td></tr></table>	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg		1	2499.92	55.86	-18.14	74.00	54.46	30.93	7.28	36.81	137	313	Peak	VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218602 VERTICAL Project : RSR 1000.000MHz VBR 3000.000MHz SRT-Auto Bode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><tr><th>MEI</th><th>Power setting</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dB</th><th>dBm/100m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr><tr><td>1</td><td>2430.00</td><td>106.72</td><td>32.72</td><td>74.00</td><td>105.77</td><td>30.64</td><td>7.16</td><td>36.85</td><td>137</td><td>313</td><td>Peak</td><td>VERTICAL</td></tr></table>	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg		1	2430.00	106.72	32.72	74.00	105.77	30.64	7.16	36.85	137	313	Peak	VERTICAL
	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																							
MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg																																																									
1	2499.92	55.86	-18.14	74.00	54.46	30.93	7.28	36.81	137	313	Peak	VERTICAL																																																				
MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																								
MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg																																																									
1	2430.00	106.72	32.72	74.00	105.77	30.64	7.16	36.85	137	313	Peak	VERTICAL																																																				
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218602 VERTICAL Project : RSR 1000.000MHz VBR 3000.000MHz SRT-Auto Bode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><tr><th>MEI</th><th>Power setting</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dB</th><th>dBm/100m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr><tr><td>1</td><td>2496.10</td><td>44.97</td><td>-9.03</td><td>54.00</td><td>43.57</td><td>30.93</td><td>7.28</td><td>36.81</td><td>137</td><td>313</td><td>Average</td><td>VERTICAL</td></tr></table>	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg		1	2496.10	44.97	-9.03	54.00	43.57	30.93	7.28	36.81	137	313	Average	VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218602 VERTICAL Project : RSR 1000.000MHz VBR 3000.000MHz SRT-Auto Bode : (FR) 1N0918 Plane : 19 Full-directivity : 2 Power setting : 2 <table><tr><th>MEI</th><th>Power setting</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dB</th><th>dBm/100m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr><tr><td>1</td><td>2424.00</td><td>98.41</td><td>44.41</td><td>54.00</td><td>97.46</td><td>30.64</td><td>7.16</td><td>36.85</td><td>137</td><td>313</td><td>Average</td><td>VERTICAL</td></tr></table>	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg		1	2424.00	98.41	44.41	54.00	97.46	30.64	7.16	36.85	137	313	Average	VERTICAL
	MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																							
MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg																																																									
1	2496.10	44.97	-9.03	54.00	43.57	30.93	7.28	36.81	137	313	Average	VERTICAL																																																				
MEI	Power setting	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																								
MHz	dBm/100m	dB	dBm/100m	dB	dB	dB	deg																																																									
1	2424.00	98.41	44.41	54.00	97.46	30.64	7.16	36.85	137	313	Average	VERTICAL																																																				







FCC RF Test Report





Report No. : FR1N0918B

WIFI		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																
ANT		802.11n HT40 CH06 2437MHz - L																																																																
1	Horizontal	Fundamental																																																																
Peak	 Site : 03C805-E5 Condition : FCC PART 15C 3m 2117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Mode : GPS 180918 Plane : Z Full-directivity : E IMEI : PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2389.69</td><td>56.84</td><td>-17.16</td><td>74.80</td><td>56.18</td><td>38.58</td><td>7.18</td><td>36.86</td><td>382</td><td>357</td><td>Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg		1	2389.69	56.84	-17.16	74.80	56.18	38.58	7.18	36.86	382	357	Peak	HORIZONTAL	 Site : 03C805-E5 Condition : FCC PART 15C 3m 2117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Mode : GPS 180918 Plane : Z Full-directivity : E IMEI : PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2446.88</td><td>186.68</td><td>32.68</td><td>74.80</td><td>185.62</td><td>38.71</td><td>7.19</td><td>36.84</td><td>382</td><td>357</td><td>Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg		1	2446.88	186.68	32.68	74.80	185.62	38.71	7.19	36.84	382	357	Peak	HORIZONTAL	
	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																											
1	2389.69	56.84	-17.16	74.80	56.18	38.58	7.18	36.86	382	357	Peak	HORIZONTAL																																																						
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																										
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																										
1	2446.88	186.68	32.68	74.80	185.62	38.71	7.19	36.84	382	357	Peak	HORIZONTAL																																																						
Avg.	 Site : 03C805-E5 Condition : FCC PART 15C (AVG) 3m 2117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Mode : GPS 180918 Plane : Z Full-directivity : E IMEI : PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2389.95</td><td>43.35</td><td>-18.65</td><td>54.80</td><td>42.61</td><td>38.58</td><td>7.18</td><td>36.86</td><td>382</td><td>357</td><td>Average</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg		1	2389.95	43.35	-18.65	54.80	42.61	38.58	7.18	36.86	382	357	Average	HORIZONTAL	 Site : 03C805-E5 Condition : FCC PART 15C (AVG) 3m 2117 00218052 HORIZONTAL Project : RSH 1000.000MHz YEW 3000.000MHz SPT Auto Mode : GPS 180918 Plane : Z Full-directivity : E IMEI : PowerSetting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2446.88</td><td>98.28</td><td>44.28</td><td>54.80</td><td>97.34</td><td>38.71</td><td>7.19</td><td>36.84</td><td>382</td><td>357</td><td>Average</td><td>HORIZONTAL</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg		1	2446.88	98.28	44.28	54.80	97.34	38.71	7.19	36.84	382	357	Average	HORIZONTAL
	Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																										
1	2389.95	43.35	-18.65	54.80	42.61	38.58	7.18	36.86	382	357	Average	HORIZONTAL																																																						
Freq	Level	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																										
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																										
1	2446.88	98.28	44.28	54.80	97.34	38.71	7.19	36.84	382	357	Average	HORIZONTAL																																																						







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sportson.com.cn Date: 3 Level (dBuV/m) Freq Level Limit Line ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phas 1 2483.68 61.66 -12.34 74.00 69.37 30.86 7.25 36.82 382 357 Peak HORIZONTAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sportson.com.cn Date: 5 Level (dBuV/m) Freq Level Limit Line ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phas 1 * 2446.00 106.68 32.68 74.00 105.62 30.71 7.19 36.84 382 357 Peak HORIZONTAL
	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sportson.com.cn Date: 4 Level (dBuV/m) Freq Level Limit Line ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phas 1 2483.58 48.23 -5.77 54.00 46.94 30.86 7.25 36.82 382 357 Average HORIZONTAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sportson.com.cn Date: 6 Level (dBuV/m) Freq Level Limit Line ReadAntenna Cable Preamp A/Pos T/Pos Remark Pol/Phas 1 * 2446.00 98.28 44.28 54.00 97.34 30.71 7.19 36.84 382 357 Average HORIZONTAL









WIFI		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																
ANT		802.11n HT40 CH06 2437MHz - L																																																																
1	Vertical	Fundamental																																																																
Peak	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Date: 7 Site : 03CB05-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : QPU 180918 Plane : 20 Polarization : Full-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.95</td><td>63.88</td><td>-18.28</td><td>74.00</td><td>63.86</td><td>38.50</td><td>7.18</td><td>36.86</td><td>180</td><td>318 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2389.95	63.88	-18.28	74.00	63.86	38.50	7.18	36.86	180	318 Peak	VERTICAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Date: 11 Site : 03CB05-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : QPU 180918 Plane : 20 Polarization : Full-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2436.80</td><td>188.18</td><td>34.18</td><td>74.00</td><td>187.20</td><td>38.64</td><td>7.19</td><td>36.85</td><td>100</td><td>318 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2436.80	188.18	34.18	74.00	187.20	38.64	7.19	36.85	100	318 Peak	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																								
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2389.95	63.88	-18.28	74.00	63.86	38.50	7.18	36.86	180	318 Peak	VERTICAL																																																							
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2436.80	188.18	34.18	74.00	187.20	38.64	7.19	36.85	100	318 Peak	VERTICAL																																																							
Avg.	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Date: 8 Site : 03CB05-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : QPU 180918 Plane : 20 Polarization : Full-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.95</td><td>49.22</td><td>-4.78</td><td>54.00</td><td>48.48</td><td>38.50</td><td>7.18</td><td>36.86</td><td>180</td><td>318 Average</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2389.95	49.22	-4.78	54.00	48.48	38.50	7.18	36.86	180	318 Average	VERTICAL	 No. 1008, Pengxi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.sporton.com.cn Date: 12 Site : 03CB05-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : QPU 180918 Plane : 20 Polarization : Full-directivity PowerSetting : 0 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2434.80</td><td>188.28</td><td>46.28</td><td>54.00</td><td>99.33</td><td>38.64</td><td>7.16</td><td>36.85</td><td>100</td><td>318 Average</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2434.80	188.28	46.28	54.00	99.33	38.64	7.16	36.85	100	318 Average	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																								
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2389.95	49.22	-4.78	54.00	48.48	38.50	7.18	36.86	180	318 Average	VERTICAL																																																							
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2434.80	188.28	46.28	54.00	99.33	38.64	7.16	36.85	100	318 Average	VERTICAL																																																							







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																				
ANT	802.11n HT40 CH06 2437MHz - R																																																																																																																				
1	Vertical	Fundamental																																																																																																																			
Peak	 No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.spectrum.com.cn Date: 9  Site : 03CB05-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : GPS 180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.56</td><td>64.13</td><td>-9.87</td><td>74.00</td><td>62.64</td><td>30.86</td><td>7.25</td><td>36.82</td><td>100</td><td>310</td><td>Peak</td><td>VERTICAL</td></tr></tbody></table>  No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.spectrum.com.cn Date: 11  Site : 03CB05-ES Condition : FCC PART 15C 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : GPS 180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2436.00</td><td>34.18</td><td>74.00</td><td>187.20</td><td>38.64</td><td>7.19</td><td>36.85</td><td>100</td><td>310</td><td>Peak</td><td>VERTICAL</td></tr></tbody></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg	1	2437.56	64.13	-9.87	74.00	62.64	30.86	7.25	36.82	100	310	Peak	VERTICAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg	1	2436.00	34.18	74.00	187.20	38.64	7.19	36.85	100	310	Peak	VERTICAL	Avg.	 No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.spectrum.com.cn Date: 10  Site : 03CB05-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : GPS 180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.50</td><td>49.71</td><td>-4.29</td><td>54.00</td><td>48.42</td><td>30.86</td><td>7.25</td><td>36.82</td><td>100</td><td>310</td><td>Average</td><td>VERTICAL</td></tr></tbody></table>  No. 1098, Pengzi North Road,Kunshan Economic & Technical Development Zone,Jiangsu,China tel:+86-512-57900158 fax:+86-512-57900958 http://www.spectrum.com.cn Date: 12  Site : 03CB05-ES Condition : FCC PART 15C (AVG) 3m 3117 00218052 VERTICAL Project : RSH 1000.000MHz YFW 3000.000MHz SPT Auto Model : GPS 180918 Plane : Z Polarization : Pull-directivity PowerSetting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2434.00</td><td>46.28</td><td>54.00</td><td>99.33</td><td>38.64</td><td>7.16</td><td>36.85</td><td>100</td><td>310</td><td>Average</td><td>VERTICAL</td></tr></tbody></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg	1	2437.50	49.71	-4.29	54.00	48.42	30.86	7.25	36.82	100	310	Average	VERTICAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg	1	2434.00	46.28	54.00	99.33	38.64	7.16	36.85	100	310	Average	VERTICAL
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																													
Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg																																																																																																														
1	2437.56	64.13	-9.87	74.00	62.64	30.86	7.25	36.82	100	310	Peak	VERTICAL																																																																																																									
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																														
Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg																																																																																																														
1	2436.00	34.18	74.00	187.20	38.64	7.19	36.85	100	310	Peak	VERTICAL																																																																																																										
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																														
Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg																																																																																																														
1	2437.50	49.71	-4.29	54.00	48.42	30.86	7.25	36.82	100	310	Average	VERTICAL																																																																																																									
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																														
Freq	Level	Limit	Level Factor	Loss Factor	dB	cm	deg																																																																																																														
1	2434.00	46.28	54.00	99.33	38.64	7.16	36.85	100	310	Average	VERTICAL																																																																																																										



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																										
ANT	802.11n HT40 CH09 2452MHz - R																																																										
1	Horizontal	Fundamental																																																									
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 33   Site Condition Project Bode Plane IME1 Power setting : 030H05-KS : FCC PART 15C 3m 3117 00218652 HORIZONTAL : RSR 1000 000KHz VBR 3000 000KHz SRT Auto : (FR) 1N0918 : 21 : Full-directivity : 42 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.62</td><td>64.60</td><td>-9.40</td><td>74.00</td><td>63.31</td><td>30.86</td><td>7.25</td><td>36.82</td><td>390</td><td>360</td><td>Peak</td><td>HORIZONTAL</td></tr></table>  Site Condition Project Bode Plane IME1 Power setting No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 35   Site Condition Project Bode Plane IME1 Power setting : 030H05-KS : FCC PART 15C 3m 3117 00218652 HORIZONTAL : RSR 1000 000KHz VBR 3000 000KHz SRT Auto : (FR) 1N0918 : 21 : Full-directivity : 42 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1</td><td>2450.00</td><td>103.78</td><td>29.78</td><td>74.00</td><td>102.72</td><td>30.71</td><td>7.19</td><td>36.84</td><td>390</td><td>360</td><td>Peak</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1	2483.62	64.60	-9.40	74.00	63.31	30.86	7.25	36.82	390	360	Peak	HORIZONTAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1	2450.00	103.78	29.78	74.00	102.72	30.71	7.19	36.84	390	360	Peak	HORIZONTAL
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																			
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																					
1	2483.62	64.60	-9.40	74.00	63.31	30.86	7.25	36.82	390	360	Peak	HORIZONTAL																																															
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																				
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																					
1	2450.00	103.78	29.78	74.00	102.72	30.71	7.19	36.84	390	360	Peak	HORIZONTAL																																															
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 34   Site Condition Project Bode Plane IME1 Power setting : 030H05-KS : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL : RSR 1000 000KHz VBR 0 01000K SRT Auto : (FR) 1N0918 : 21 : Full-directivity : 42 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.50</td><td>49.15</td><td>-4.85</td><td>54.00</td><td>47.86</td><td>30.86</td><td>7.25</td><td>36.82</td><td>390</td><td>360</td><td>Average</td><td>HORIZONTAL</td></tr></table>  Site Condition Project Bode Plane IME1 Power setting No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 36   Site Condition Project Bode Plane IME1 Power setting : 030H05-KS : FCC PART 15C (AVG) 3m 3117 00218652 HORIZONTAL : RSR 1000 000KHz VBR 0 01000K SRT Auto : (FR) 1N0918 : 21 : Full-directivity : 42 <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>cn</th><th>deg</th><th></th></tr><tr><td>1</td><td>2450.00</td><td>96.10</td><td>42.10</td><td>54.00</td><td>95.04</td><td>30.71</td><td>7.19</td><td>36.84</td><td>390</td><td>360</td><td>Average</td><td>HORIZONTAL</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1	2483.50	49.15	-4.85	54.00	47.86	30.86	7.25	36.82	390	360	Average	HORIZONTAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase	Freq	Level	Line	Level Factor	Loss Factor	cn	deg		1	2450.00	96.10	42.10	54.00	95.04	30.71	7.19	36.84	390	360	Average	HORIZONTAL
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																				
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																					
1	2483.50	49.15	-4.85	54.00	47.86	30.86	7.25	36.82	390	360	Average	HORIZONTAL																																															
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																				
Freq	Level	Line	Level Factor	Loss Factor	cn	deg																																																					
1	2450.00	96.10	42.10	54.00	95.04	30.71	7.19	36.84	390	360	Average	HORIZONTAL																																															







WIFI		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																					
ANT		802.11n HT40 CH09 2452MHz - R																																																																																																																																					
1	Vertical	Fundamental																																																																																																																																					
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : R88-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity Powersetting : 12 IMEI : 42 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 2483.50</td><td>67.96</td><td>-6.04</td><td>74.00</td><td>66.67</td><td>30.86</td><td>7.25</td><td>36.82</td><td>104</td><td>311 Peak</td><td>VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C 3m 3117 00218652 VERTICAL Project : R88-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity Powersetting : 12 IMEI : 42 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2454.00</td><td>104.39</td><td>30.39</td><td>74.00</td><td>103.21</td><td>30.79</td><td>7.22</td><td>36.83</td><td>104</td><td>311 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 2483.50	67.96	-6.04	74.00	66.67	30.86	7.25	36.82	104	311 Peak	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 * 2454.00	104.39	30.39	74.00	103.21	30.79	7.22	36.83	104	311 Peak	VERTICAL	Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : R88-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity Powersetting : 12 IMEI : 42 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 2483.50</td><td>52.45</td><td>-1.55</td><td>54.00</td><td>51.16</td><td>30.86</td><td>7.25</td><td>36.82</td><td>104</td><td>311 Average</td><td>VERTICAL</td></tr></table>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030H05-KS Condition : FCC PART 15C (AVG) 3m 3117 00218652 VERTICAL Project : R88-1000.000KHz VBR-3000.000KHz SRT-Auto Mode : (FR) 1N0918 Plane : 2 Full-directivity Powersetting : 12 IMEI : 42 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2454.00</td><td>96.57</td><td>42.57</td><td>54.00</td><td>95.39</td><td>30.79</td><td>7.22</td><td>36.83</td><td>104</td><td>311 Average</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 2483.50	52.45	-1.55	54.00	51.16	30.86	7.25	36.82	104	311 Average	VERTICAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg			1 * 2454.00	96.57	42.57	54.00	95.39	30.79	7.22	36.83	104	311 Average	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																												
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 2483.50	67.96	-6.04	74.00	66.67	30.86	7.25	36.82	104	311 Peak	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 * 2454.00	104.39	30.39	74.00	103.21	30.79	7.22	36.83	104	311 Peak	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 2483.50	52.45	-1.55	54.00	51.16	30.86	7.25	36.82	104	311 Average	VERTICAL																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	cm	deg																																																																																																																															
1 * 2454.00	96.57	42.57	54.00	95.39	30.79	7.22	36.83	104	311 Average	VERTICAL																																																																																																																													






2.4GHz 2400~2483.5MHz



WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																																																																																																																																																																																																																	
ANT	802.11b CH01 2412MHz																																																																																																																																																																																																																																																																																	
1	Horizontal	Vertical																																																																																																																																																																																																																																																																																
Peak Avg.	 Site : 03D05-KS Condition : FCC PART 15C 3m 3117.00218653 HORIZONTAL Project : RSM 1000.000KHz VSW.3000.000KHz SMT.Auto Mode : FR1N0918B Plane : Z Full-directivity : 0 Power setting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4830.00</td><td>54.01</td><td>-19.99</td><td>74.00</td><td>74.53</td><td>34.61</td><td>10.25</td><td>65.38</td><td>104</td><td>212</td><td>Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>4830.00</td><td>47.85</td><td>-6.15</td><td>54.00</td><td>48.37</td><td>34.01</td><td>10.25</td><td>65.38</td><td>104</td><td>212</td><td>Average</td><td>HORIZONTAL</td></tr><tr><td>3</td><td>7230.00</td><td>50.55</td><td></td><td></td><td>66.78</td><td>50.71</td><td>12.71</td><td>65.65</td><td></td><td></td><td>0 Peak</td><td>HORIZONTAL</td></tr><tr><td>4</td><td>9045.00</td><td>49.62</td><td></td><td></td><td>63.86</td><td>37.79</td><td>14.94</td><td>66.97</td><td></td><td></td><td>0 Peak</td><td>HORIZONTAL</td></tr></tbody></table>  Site : 03D05-KS Condition : FCC PART 15C 3m 3117.00218653 HORIZONTAL Project : RSM 1000.000KHz VSW.3000.000KHz SMT.Auto Mode : FR1N0918B Plane : Z Full-directivity : 0 Power setting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4830.00</td><td>54.01</td><td>-19.99</td><td>74.00</td><td>74.53</td><td>34.61</td><td>10.25</td><td>65.38</td><td>104</td><td>212</td><td>Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>4830.00</td><td>47.85</td><td>-6.15</td><td>54.00</td><td>48.37</td><td>34.01</td><td>10.25</td><td>65.38</td><td>104</td><td>212</td><td>Average</td><td>HORIZONTAL</td></tr><tr><td>3</td><td>7230.00</td><td>50.55</td><td></td><td></td><td>66.78</td><td>50.71</td><td>12.71</td><td>65.65</td><td></td><td></td><td>0 Peak</td><td>HORIZONTAL</td></tr><tr><td>4</td><td>9045.00</td><td>49.62</td><td></td><td></td><td>63.86</td><td>37.79</td><td>14.94</td><td>66.97</td><td></td><td></td><td>0 Peak</td><td>HORIZONTAL</td></tr></tbody></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg	1	4830.00	54.01	-19.99	74.00	74.53	34.61	10.25	65.38	104	212	Peak	HORIZONTAL	2	4830.00	47.85	-6.15	54.00	48.37	34.01	10.25	65.38	104	212	Average	HORIZONTAL	3	7230.00	50.55			66.78	50.71	12.71	65.65			0 Peak	HORIZONTAL	4	9045.00	49.62			63.86	37.79	14.94	66.97			0 Peak	HORIZONTAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg	1	4830.00	54.01	-19.99	74.00	74.53	34.61	10.25	65.38	104	212	Peak	HORIZONTAL	2	4830.00	47.85	-6.15	54.00	48.37	34.01	10.25	65.38	104	212	Average	HORIZONTAL	3	7230.00	50.55			66.78	50.71	12.71	65.65			0 Peak	HORIZONTAL	4	9045.00	49.62			63.86	37.79	14.94	66.97			0 Peak	HORIZONTAL	 Site : 03D05-KS Condition : FCC PART 15C 3m 3117.00218653 VERTICAL Project : RSM 1000.000KHz VSW.3000.000KHz SMT.Auto Mode : FR1N0918B Plane : Z Full-directivity : 0 Power setting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4830.00</td><td>53.19</td><td>-20.81</td><td>74.00</td><td>73.71</td><td>34.61</td><td>10.25</td><td>65.38</td><td>296</td><td>138</td><td>Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>4830.00</td><td>46.77</td><td>-7.23</td><td>54.00</td><td>67.29</td><td>34.61</td><td>10.25</td><td>65.38</td><td>296</td><td>138</td><td>Average</td><td>VERTICAL</td></tr><tr><td>3</td><td>7230.00</td><td>50.12</td><td></td><td></td><td>66.35</td><td>36.71</td><td>12.71</td><td>65.65</td><td></td><td></td><td>0 Peak</td><td>VERTICAL</td></tr><tr><td>4</td><td>9045.00</td><td>52.82</td><td></td><td></td><td>67.06</td><td>37.79</td><td>14.94</td><td>66.97</td><td></td><td></td><td>0 Peak</td><td>VERTICAL</td></tr></tbody></table>  Site : 03D05-KS Condition : FCC PART 15C 3m 3117.00218653 VERTICAL Project : RSM 1000.000KHz VSW.3000.000KHz SMT.Auto Mode : FR1N0918B Plane : Z Full-directivity : 0 Power setting : 0 <table><thead><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4830.00</td><td>53.19</td><td>-20.81</td><td>74.00</td><td>73.71</td><td>34.61</td><td>10.25</td><td>65.38</td><td>296</td><td>138</td><td>Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>4830.00</td><td>46.77</td><td>-7.23</td><td>54.00</td><td>67.29</td><td>34.61</td><td>10.25</td><td>65.38</td><td>296</td><td>138</td><td>Average</td><td>VERTICAL</td></tr><tr><td>3</td><td>7230.00</td><td>50.12</td><td></td><td></td><td>66.35</td><td>36.71</td><td>12.71</td><td>65.65</td><td></td><td></td><td>0 Peak</td><td>VERTICAL</td></tr><tr><td>4</td><td>9045.00</td><td>52.82</td><td></td><td></td><td>67.06</td><td>37.79</td><td>14.94</td><td>66.97</td><td></td><td></td><td>0 Peak</td><td>VERTICAL</td></tr></tbody></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg	1	4830.00	53.19	-20.81	74.00	73.71	34.61	10.25	65.38	296	138	Peak	VERTICAL	2	4830.00	46.77	-7.23	54.00	67.29	34.61	10.25	65.38	296	138	Average	VERTICAL	3	7230.00	50.12			66.35	36.71	12.71	65.65			0 Peak	VERTICAL	4	9045.00	52.82			67.06	37.79	14.94	66.97			0 Peak	VERTICAL	Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas	Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg	1	4830.00	53.19	-20.81	74.00	73.71	34.61	10.25	65.38	296	138	Peak	VERTICAL	2	4830.00	46.77	-7.23	54.00	67.29	34.61	10.25	65.38	296	138	Average	VERTICAL	3	7230.00	50.12			66.35	36.71	12.71	65.65			0 Peak	VERTICAL	4	9045.00	52.82			67.06	37.79	14.94	66.97			0 Peak	VERTICAL
	Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																																																																																																																																																																																																																										
Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg																																																																																																																																																																																																																																																																											
1	4830.00	54.01	-19.99	74.00	74.53	34.61	10.25	65.38	104	212	Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
2	4830.00	47.85	-6.15	54.00	48.37	34.01	10.25	65.38	104	212	Average	HORIZONTAL																																																																																																																																																																																																																																																																						
3	7230.00	50.55			66.78	50.71	12.71	65.65			0 Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
4	9045.00	49.62			63.86	37.79	14.94	66.97			0 Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																																																																																																																																																																																																																											
Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg																																																																																																																																																																																																																																																																											
1	4830.00	54.01	-19.99	74.00	74.53	34.61	10.25	65.38	104	212	Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
2	4830.00	47.85	-6.15	54.00	48.37	34.01	10.25	65.38	104	212	Average	HORIZONTAL																																																																																																																																																																																																																																																																						
3	7230.00	50.55			66.78	50.71	12.71	65.65			0 Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
4	9045.00	49.62			63.86	37.79	14.94	66.97			0 Peak	HORIZONTAL																																																																																																																																																																																																																																																																						
Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																																																																																																																																																																																																																											
Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg																																																																																																																																																																																																																																																																											
1	4830.00	53.19	-20.81	74.00	73.71	34.61	10.25	65.38	296	138	Peak	VERTICAL																																																																																																																																																																																																																																																																						
2	4830.00	46.77	-7.23	54.00	67.29	34.61	10.25	65.38	296	138	Average	VERTICAL																																																																																																																																																																																																																																																																						
3	7230.00	50.12			66.35	36.71	12.71	65.65			0 Peak	VERTICAL																																																																																																																																																																																																																																																																						
4	9045.00	52.82			67.06	37.79	14.94	66.97			0 Peak	VERTICAL																																																																																																																																																																																																																																																																						
Over	Limit	ReadAntenna	Cable Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																																																																																																																																																																																																																											
Freq	Level	Line	Level Factor	Loss Factor	dB	dB	deg																																																																																																																																																																																																																																																																											
1	4830.00	53.19	-20.81	74.00	73.71	34.61	10.25	65.38	296	138	Peak	VERTICAL																																																																																																																																																																																																																																																																						
2	4830.00	46.77	-7.23	54.00	67.29	34.61	10.25	65.38	296	138	Average	VERTICAL																																																																																																																																																																																																																																																																						
3	7230.00	50.12			66.35	36.71	12.71	65.65			0 Peak	VERTICAL																																																																																																																																																																																																																																																																						
4	9045.00	52.82			67.06	37.79	14.94	66.97			0 Peak	VERTICAL																																																																																																																																																																																																																																																																						



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																																																																																																					
ANT	802.11b CH06 2437MHz																																																																																																																																																																					
1	Horizontal	Vertical																																																																																																																																																																				
Peak	 Site : 030905-K5 Condition : FCC PART 15C 3m 3117.00218652 HORIZONTAL Project : RSM-1000.000KHz VBR-3000.000KHz SMT-Auto Bode : (F) 100dB Plane : 11 Polar : 2 Full-directivity : 2 IMEI : 87 Power setting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100K</th><th>dB</th><th>dBm/100K</th><th>dBm</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>4875.00</td><td>53.36</td><td>-20.44</td><td>74.00</td><td>73.80</td><td>34.69</td><td>10.29</td><td>65.42</td><td>100</td><td>210 Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>4875.00</td><td>47.89</td><td>-6.11</td><td>54.00</td><td>68.33</td><td>34.69</td><td>10.29</td><td>65.42</td><td>100</td><td>210 Average</td><td>HORIZONTAL</td></tr><tr><td>3</td><td>7311.00</td><td>53.42</td><td>-20.38</td><td>74.00</td><td>70.12</td><td>35.68</td><td>12.72</td><td>65.91</td><td>107</td><td>230 Peak</td><td>HORIZONTAL</td></tr><tr><td>4</td><td>7311.00</td><td>44.67</td><td>-9.33</td><td>54.00</td><td>61.18</td><td>35.68</td><td>12.72</td><td>65.91</td><td>107</td><td>230 Average</td><td>HORIZONTAL</td></tr><tr><td>5</td><td>9750.00</td><td>51.30</td><td></td><td></td><td>65.45</td><td>37.91</td><td>14.99</td><td>67.05</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr></tbody></table> <td>  Site : 030905-K5 Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SMT-Auto Bode : (F) 100dB Plane : 11 Polar : 2 Full-directivity : 2 IMEI : 87 Power setting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100K</th><th>dB</th><th>dBm/100K</th><th>dBm</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>4875.00</td><td>52.87</td><td>-21.13</td><td>74.00</td><td>73.31</td><td>34.69</td><td>10.29</td><td>65.42</td><td>347</td><td>137 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>4875.00</td><td>46.77</td><td>-7.23</td><td>54.00</td><td>67.21</td><td>34.69</td><td>10.29</td><td>65.42</td><td>347</td><td>137 Average</td><td>VERTICAL</td></tr><tr><td>3</td><td>7305.00</td><td>54.42</td><td>-19.58</td><td>74.00</td><td>70.92</td><td>36.68</td><td>12.72</td><td>65.91</td><td>100</td><td>295 Peak</td><td>VERTICAL</td></tr><tr><td>4</td><td>7305.00</td><td>46.15</td><td>-7.82</td><td>54.00</td><td>62.69</td><td>36.68</td><td>12.72</td><td>65.91</td><td>100</td><td>295 Average</td><td>VERTICAL</td></tr><tr><td>5</td><td>9750.00</td><td>53.47</td><td></td><td></td><td>67.42</td><td>37.91</td><td>14.99</td><td>67.05</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr></tbody></table> </td>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg			1	4875.00	53.36	-20.44	74.00	73.80	34.69	10.29	65.42	100	210 Peak	HORIZONTAL	2	4875.00	47.89	-6.11	54.00	68.33	34.69	10.29	65.42	100	210 Average	HORIZONTAL	3	7311.00	53.42	-20.38	74.00	70.12	35.68	12.72	65.91	107	230 Peak	HORIZONTAL	4	7311.00	44.67	-9.33	54.00	61.18	35.68	12.72	65.91	107	230 Average	HORIZONTAL	5	9750.00	51.30			65.45	37.91	14.99	67.05	300	0 Peak	HORIZONTAL	 Site : 030905-K5 Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RSM-1000.000KHz VBR-3000.000KHz SMT-Auto Bode : (F) 100dB Plane : 11 Polar : 2 Full-directivity : 2 IMEI : 87 Power setting : 0 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100K</th><th>dB</th><th>dBm/100K</th><th>dBm</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>4875.00</td><td>52.87</td><td>-21.13</td><td>74.00</td><td>73.31</td><td>34.69</td><td>10.29</td><td>65.42</td><td>347</td><td>137 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>4875.00</td><td>46.77</td><td>-7.23</td><td>54.00</td><td>67.21</td><td>34.69</td><td>10.29</td><td>65.42</td><td>347</td><td>137 Average</td><td>VERTICAL</td></tr><tr><td>3</td><td>7305.00</td><td>54.42</td><td>-19.58</td><td>74.00</td><td>70.92</td><td>36.68</td><td>12.72</td><td>65.91</td><td>100</td><td>295 Peak</td><td>VERTICAL</td></tr><tr><td>4</td><td>7305.00</td><td>46.15</td><td>-7.82</td><td>54.00</td><td>62.69</td><td>36.68</td><td>12.72</td><td>65.91</td><td>100</td><td>295 Average</td><td>VERTICAL</td></tr><tr><td>5</td><td>9750.00</td><td>53.47</td><td></td><td></td><td>67.42</td><td>37.91</td><td>14.99</td><td>67.05</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg			1	4875.00	52.87	-21.13	74.00	73.31	34.69	10.29	65.42	347	137 Peak	VERTICAL	2	4875.00	46.77	-7.23	54.00	67.21	34.69	10.29	65.42	347	137 Average	VERTICAL	3	7305.00	54.42	-19.58	74.00	70.92	36.68	12.72	65.91	100	295 Peak	VERTICAL	4	7305.00	46.15	-7.82	54.00	62.69	36.68	12.72	65.91	100	295 Average	VERTICAL	5	9750.00	53.47			67.42	37.91	14.99	67.05	100	0 Peak	VERTICAL
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																												
MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg																																																																																																																																																														
1	4875.00	53.36	-20.44	74.00	73.80	34.69	10.29	65.42	100	210 Peak	HORIZONTAL																																																																																																																																																											
2	4875.00	47.89	-6.11	54.00	68.33	34.69	10.29	65.42	100	210 Average	HORIZONTAL																																																																																																																																																											
3	7311.00	53.42	-20.38	74.00	70.12	35.68	12.72	65.91	107	230 Peak	HORIZONTAL																																																																																																																																																											
4	7311.00	44.67	-9.33	54.00	61.18	35.68	12.72	65.91	107	230 Average	HORIZONTAL																																																																																																																																																											
5	9750.00	51.30			65.45	37.91	14.99	67.05	300	0 Peak	HORIZONTAL																																																																																																																																																											
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																												
MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg																																																																																																																																																														
1	4875.00	52.87	-21.13	74.00	73.31	34.69	10.29	65.42	347	137 Peak	VERTICAL																																																																																																																																																											
2	4875.00	46.77	-7.23	54.00	67.21	34.69	10.29	65.42	347	137 Average	VERTICAL																																																																																																																																																											
3	7305.00	54.42	-19.58	74.00	70.92	36.68	12.72	65.91	100	295 Peak	VERTICAL																																																																																																																																																											
4	7305.00	46.15	-7.82	54.00	62.69	36.68	12.72	65.91	100	295 Average	VERTICAL																																																																																																																																																											
5	9750.00	53.47			67.42	37.91	14.99	67.05	100	0 Peak	VERTICAL																																																																																																																																																											



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																																																																																																					
ANT	802.11b CH11 2462MHz																																																																																																																																																																					
1	Horizontal	Vertical																																																																																																																																																																				
Peak Avg.	 No. 1098 Pengzi North Road Kunshan Economic & Technical Development Zone Jiangsu China Tel: +86-512-57900158 Fax: +86-512-57900158 http://www.sporton.com.cn Site : 030905-K5 Condition : FCC PART 15C 3m 3117.00218652 HORIZONTAL Project : RRM-1000.000KHz VBR-3000.000KHz SMT-Auto Bode : FFS1100F15 Plane : 12 Full-directivity : 2 IME1 : Full-directivity Power setting : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100K</th><th>dB</th><th>dBm/100K</th><th>dBm</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4920.00</td><td>54.83</td><td>-19.17</td><td>74.00</td><td>75.17</td><td>34.77</td><td>10.34</td><td>65.45</td><td>106</td><td>216 Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>4920.00</td><td>48.50</td><td>-5.50</td><td>54.00</td><td>68.84</td><td>34.77</td><td>10.34</td><td>65.45</td><td>106</td><td>216 Average</td><td>HORIZONTAL</td></tr><tr><td>3</td><td>7380.00</td><td>54.51</td><td>-15.49</td><td>74.00</td><td>71.24</td><td>36.60</td><td>12.73</td><td>66.11</td><td>238</td><td>311 Peak</td><td>HORIZONTAL</td></tr><tr><td>4</td><td>7380.00</td><td>46.01</td><td>-7.49</td><td>54.00</td><td>63.24</td><td>36.60</td><td>12.73</td><td>66.11</td><td>238</td><td>311 Average</td><td>HORIZONTAL</td></tr><tr><td>5</td><td>19840.00</td><td>53.43</td><td></td><td></td><td>67.50</td><td>38.01</td><td>15.03</td><td>67.11</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg			1	4920.00	54.83	-19.17	74.00	75.17	34.77	10.34	65.45	106	216 Peak	HORIZONTAL	2	4920.00	48.50	-5.50	54.00	68.84	34.77	10.34	65.45	106	216 Average	HORIZONTAL	3	7380.00	54.51	-15.49	74.00	71.24	36.60	12.73	66.11	238	311 Peak	HORIZONTAL	4	7380.00	46.01	-7.49	54.00	63.24	36.60	12.73	66.11	238	311 Average	HORIZONTAL	5	19840.00	53.43			67.50	38.01	15.03	67.11	300	0 Peak	HORIZONTAL	 No. 1098 Pengzi North Road Kunshan Economic & Technical Development Zone Jiangsu China Tel: +86-512-57900158 Fax: +86-512-57900158 http://www.sporton.com.cn Site : 030905-K5 Condition : FCC PART 15C 3m 3117.00218652 VERTICAL Project : RRM-1000.000KHz VBR-3000.000KHz SMT-Auto Bode : FFS1100F15 Plane : 12 Full-directivity : 2 IME1 : Full-directivity Power setting : 47 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100K</th><th>dB</th><th>dBm/100K</th><th>dBm</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4920.00</td><td>54.47</td><td>-19.53</td><td>74.00</td><td>74.81</td><td>34.77</td><td>10.34</td><td>65.45</td><td>100</td><td>145 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>4920.00</td><td>47.57</td><td>-6.43</td><td>54.00</td><td>67.91</td><td>34.77</td><td>10.34</td><td>65.45</td><td>100</td><td>145 Average</td><td>VERTICAL</td></tr><tr><td>3</td><td>7380.00</td><td>54.72</td><td>-15.28</td><td>74.00</td><td>71.45</td><td>36.60</td><td>12.73</td><td>66.11</td><td>100</td><td>294 Peak</td><td>VERTICAL</td></tr><tr><td>4</td><td>7380.00</td><td>46.60</td><td>-7.35</td><td>54.00</td><td>63.38</td><td>36.60</td><td>12.73</td><td>66.11</td><td>100</td><td>294 Average</td><td>VERTICAL</td></tr><tr><td>5</td><td>19840.00</td><td>54.99</td><td></td><td></td><td>69.56</td><td>38.01</td><td>15.03</td><td>67.11</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg			1	4920.00	54.47	-19.53	74.00	74.81	34.77	10.34	65.45	100	145 Peak	VERTICAL	2	4920.00	47.57	-6.43	54.00	67.91	34.77	10.34	65.45	100	145 Average	VERTICAL	3	7380.00	54.72	-15.28	74.00	71.45	36.60	12.73	66.11	100	294 Peak	VERTICAL	4	7380.00	46.60	-7.35	54.00	63.38	36.60	12.73	66.11	100	294 Average	VERTICAL	5	19840.00	54.99			69.56	38.01	15.03	67.11	100	0 Peak	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																											
MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg																																																																																																																																																														
1	4920.00	54.83	-19.17	74.00	75.17	34.77	10.34	65.45	106	216 Peak	HORIZONTAL																																																																																																																																																											
2	4920.00	48.50	-5.50	54.00	68.84	34.77	10.34	65.45	106	216 Average	HORIZONTAL																																																																																																																																																											
3	7380.00	54.51	-15.49	74.00	71.24	36.60	12.73	66.11	238	311 Peak	HORIZONTAL																																																																																																																																																											
4	7380.00	46.01	-7.49	54.00	63.24	36.60	12.73	66.11	238	311 Average	HORIZONTAL																																																																																																																																																											
5	19840.00	53.43			67.50	38.01	15.03	67.11	300	0 Peak	HORIZONTAL																																																																																																																																																											
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																												
MHz	dBm/100K	dB	dBm/100K	dBm	dB	dB	cm	deg																																																																																																																																																														
1	4920.00	54.47	-19.53	74.00	74.81	34.77	10.34	65.45	100	145 Peak	VERTICAL																																																																																																																																																											
2	4920.00	47.57	-6.43	54.00	67.91	34.77	10.34	65.45	100	145 Average	VERTICAL																																																																																																																																																											
3	7380.00	54.72	-15.28	74.00	71.45	36.60	12.73	66.11	100	294 Peak	VERTICAL																																																																																																																																																											
4	7380.00	46.60	-7.35	54.00	63.38	36.60	12.73	66.11	100	294 Average	VERTICAL																																																																																																																																																											
5	19840.00	54.99			69.56	38.01	15.03	67.11	100	0 Peak	VERTICAL																																																																																																																																																											



Emission below 1GHz
2.4GHz WIFI 802.11n HT40 (LF)

WIFI	2.4GHz 2400~2483.5MHz																																																																																																																																																																																	
ANT	802.11n HT40 LF																																																																																																																																																																																	
1	Horizontal	Vertical																																																																																																																																																																																
QP / Peak	No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900158 http://www.sporton.com.cn Site : 030602-KS Condition : FCC PART 15C 3m CBL 01110 59913 HORIZONTAL Project : RSM 100.000000 VSW 300.000000 SRT Auto Mode : 19 Plane : 2 Full-directivity : 2 IMEI : 82 <table><tr><th>Line</th><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th></th><th>MHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>34.85</td><td>19.52</td><td>-20.48</td><td>40.00</td><td>28.66</td><td>22.30</td><td>0.76</td><td>32.20</td><td>---</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>160.77</td><td>27.81</td><td>-15.99</td><td>43.00</td><td>42.03</td><td>15.60</td><td>1.88</td><td>32.10</td><td>---</td><td>HORIZONTAL</td></tr><tr><td>3</td><td>276.24</td><td>30.87</td><td>-15.13</td><td>46.00</td><td>46.03</td><td>14.88</td><td>2.09</td><td>32.13</td><td>---</td><td>HORIZONTAL</td></tr><tr><td>4</td><td>399.80</td><td>27.70</td><td>-18.30</td><td>46.00</td><td>36.62</td><td>20.50</td><td>2.80</td><td>32.22</td><td>---</td><td>HORIZONTAL</td></tr><tr><td>5</td><td>498.51</td><td>33.10</td><td>-17.90</td><td>46.00</td><td>38.58</td><td>23.77</td><td>3.14</td><td>32.39</td><td>---</td><td>HORIZONTAL</td></tr><tr><td>6</td><td>640.13</td><td>27.92</td><td>-18.08</td><td>46.00</td><td>30.13</td><td>26.30</td><td>3.71</td><td>32.22</td><td>---</td><td>HORIZONTAL</td></tr></table>	Line	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas		MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dB	dB	dB	dB	dB		1	34.85	19.52	-20.48	40.00	28.66	22.30	0.76	32.20	---	HORIZONTAL	2	160.77	27.81	-15.99	43.00	42.03	15.60	1.88	32.10	---	HORIZONTAL	3	276.24	30.87	-15.13	46.00	46.03	14.88	2.09	32.13	---	HORIZONTAL	4	399.80	27.70	-18.30	46.00	36.62	20.50	2.80	32.22	---	HORIZONTAL	5	498.51	33.10	-17.90	46.00	38.58	23.77	3.14	32.39	---	HORIZONTAL	6	640.13	27.92	-18.08	46.00	30.13	26.30	3.71	32.22	---	HORIZONTAL	No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900158 http://www.sporton.com.cn Site : 030602-KS Condition : FCC PART 15C 3m CBL 01110 59913 VERTICAL Project : RSM 100.000000 VSW 300.000000 SRT Auto Mode : 19 Plane : 2 Full-directivity : 2 IMEI : 82 <table><tr><th>Line</th><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th></th><th>MHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>60.07</td><td>19.11</td><td>-20.89</td><td>40.00</td><td>38.34</td><td>11.80</td><td>1.07</td><td>32.10</td><td>---</td><td>VERTICAL</td></tr><tr><td>2</td><td>167.74</td><td>23.50</td><td>-20.00</td><td>43.00</td><td>38.22</td><td>15.90</td><td>1.88</td><td>32.10</td><td>---</td><td>VERTICAL</td></tr><tr><td>3</td><td>408.20</td><td>25.56</td><td>-20.50</td><td>46.00</td><td>32.70</td><td>22.50</td><td>3.02</td><td>32.28</td><td>---</td><td>VERTICAL</td></tr><tr><td>4</td><td>498.51</td><td>35.49</td><td>-10.51</td><td>46.00</td><td>40.97</td><td>23.77</td><td>3.14</td><td>32.39</td><td>---</td><td>VERTICAL</td></tr><tr><td>5</td><td>640.13</td><td>30.54</td><td>-15.46</td><td>46.00</td><td>27.79</td><td>26.30</td><td>3.71</td><td>32.22</td><td>---</td><td>VERTICAL</td></tr><tr><td>6</td><td>880.69</td><td>29.32</td><td>-16.68</td><td>46.00</td><td>28.14</td><td>29.06</td><td>4.40</td><td>32.28</td><td>---</td><td>VERTICAL</td></tr></table>	Line	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas		MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dB	dB	dB	dB	dB		1	60.07	19.11	-20.89	40.00	38.34	11.80	1.07	32.10	---	VERTICAL	2	167.74	23.50	-20.00	43.00	38.22	15.90	1.88	32.10	---	VERTICAL	3	408.20	25.56	-20.50	46.00	32.70	22.50	3.02	32.28	---	VERTICAL	4	498.51	35.49	-10.51	46.00	40.97	23.77	3.14	32.39	---	VERTICAL	5	640.13	30.54	-15.46	46.00	27.79	26.30	3.71	32.22	---	VERTICAL	6	880.69	29.32	-16.68	46.00	28.14	29.06	4.40	32.28	---	VERTICAL
	Line	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																							
	MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dB	dB	dB	dB	dB																																																																																																																																																																									
1	34.85	19.52	-20.48	40.00	28.66	22.30	0.76	32.20	---	HORIZONTAL																																																																																																																																																																								
2	160.77	27.81	-15.99	43.00	42.03	15.60	1.88	32.10	---	HORIZONTAL																																																																																																																																																																								
3	276.24	30.87	-15.13	46.00	46.03	14.88	2.09	32.13	---	HORIZONTAL																																																																																																																																																																								
4	399.80	27.70	-18.30	46.00	36.62	20.50	2.80	32.22	---	HORIZONTAL																																																																																																																																																																								
5	498.51	33.10	-17.90	46.00	38.58	23.77	3.14	32.39	---	HORIZONTAL																																																																																																																																																																								
6	640.13	27.92	-18.08	46.00	30.13	26.30	3.71	32.22	---	HORIZONTAL																																																																																																																																																																								
Line	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																								
	MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dB	dB	dB	dB	dB																																																																																																																																																																									
1	60.07	19.11	-20.89	40.00	38.34	11.80	1.07	32.10	---	VERTICAL																																																																																																																																																																								
2	167.74	23.50	-20.00	43.00	38.22	15.90	1.88	32.10	---	VERTICAL																																																																																																																																																																								
3	408.20	25.56	-20.50	46.00	32.70	22.50	3.02	32.28	---	VERTICAL																																																																																																																																																																								
4	498.51	35.49	-10.51	46.00	40.97	23.77	3.14	32.39	---	VERTICAL																																																																																																																																																																								
5	640.13	30.54	-15.46	46.00	27.79	26.30	3.71	32.22	---	VERTICAL																																																																																																																																																																								
6	880.69	29.32	-16.68	46.00	28.14	29.06	4.40	32.28	---	VERTICAL																																																																																																																																																																								

Appendix E. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	100	-	-	10Hz
802.11n HT20	100	-	-	10Hz
802.11n HT40	98.7179	-	-	10Hz

802.11b





802.11g



802.11n HT20





802.11n HT40

