

S

T

S

L

A

B



Certificate #4338.01

## RADIO TEST REPORT

Report No: STS2106120H02

Issued for

Owlet Baby Care, Inc

2500 Executive Parkway, Suite 500, Lehi, Utah 84043, United States

Product Name:	OC1B
Brand Name:	Owlet
Model Name:	OC1B
Series Model:	N/A
FCC ID:	2AIEP-OC1B
Test Standard:	FCC 47CFR §2.1091

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,  
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail: sts@stsapp.com





## Test Report Certification

**Applicant's Name**..... : Owlet Baby Care, Inc  
**Address** ..... : 2500 Executive Parkway, Suite 500, Lehi, Utah 84043, United States  
**Manufacturer's Name** ..... : SHENZHEN AONI ELECTRONIC CO,LTD  
**Address** ..... : No.5,Bldg.,Honghui Industrial Park,2nd Liuxian Road,Baoan District,Shenzhen,China

### Product Description

**Product Name**..... : OC1B  
**Brand Name** ..... : Owlet  
**Model Name** ..... : OC1B  
**Series Model**..... : N/A

**Standards**..... : FCC 47CFR §2.1091

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

**Date of Test**..... :

**Date of receipt of test item** ..... : 18 June 2021

**Date (s) of performance of tests**..... : 18 June 2021 ~ 29 June 2021

**Date of Issue**..... : 29 June 2021

**Test Result**..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>5</b>
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
<b>2. FCC 47CFR §2.1091 REQUIREMENT</b>	<b>6</b>
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	6
2.4 CLASSIFICATION	6
2.5 TEST RESULT	7



**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	29 June 2021	STS2106120H02	ALL	Initial Issue





## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	OC1B	
Brand Name	Owlet	
Model Name	OC1B	
Series Model	N/A	
Model Difference	OC1B has two types of CPUs, one is SSC333, the other is SSC337, internal circuit design is the same.	
Product Description	The EUT is OC1B	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM
	Antenna gain:	3 dBi
	Antenna Designation:	PIFA Antenna
Adapter	Input: 100~240V 0.2A MAX Output:5V 1A, 5W	
Hardware version number	V1.4	
Software versionnumber	V2.1.3	

### 1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



## 2. FCC 47CFR §2.1091 REQUIREMENT

### 2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

### 2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

### 2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

### 2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



## 2.5 TEST RESULT

### Turn up

Mode	Detector	Turn up power(dBm)
802.11b	AV	14.8±1dBm
802.11g	AV	15.96±1dBm
802.11n(HT20)	AV	14.37±1dBm
802.11n(HT40)	AV	13.88±1dBm

### ANT Gain (G)

2402-2483.5MHz: 3dBi (gain of antenna in linear scale=1.995)

Protocol	Max Turn up power (dBm)	Max Turn up power (mW)	ANT Gain( gain of antenna in linear scale)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	15.8	38.02	1.995	0.015	1	Pass
802.11g	16.96	49.66	1.995	0.020	1	Pass
802.11n(HT20)	15.37	34.43	1.995	0.014	1	Pass
802.11n(HT40)	14.88	30.76	1.995	0.012	1	Pass

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*