



element

Athena GTX, Inc.

HMAPS

FCC 2.1093:2020

802.11bgn

Report: AGTX0045



NVLAP Lab Code: 200630-0



This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. This Report shall not be reproduced, except in full without written approval of the laboratory.

EAR-Controlled Data - This document contains technical data whose export and reexport/retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or re-export/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

More: <https://www.bis.doc.gov/index.php/forms-documents/regulations-docs/14-commerce-country-chart/fileT>

CERTIFICATE OF EVALUATION

Last Date of Evaluation: Wednesday, November 25, 2020

Athena GTX, Inc.

EUT: HMAPS

RF Exposure Evaluation

Standards

| Specification | Method |
|-----------------|---|
| FCC 2.1093:2020 | FCC 447498 D01 General RF Exposure Guidance v06 |

Results

| Method Clause | Description | Applied | Results | Comments |
|---------------|--------------------|---------|---------|----------|
| 4.3.1 | SAR Test Exclusion | Yes | Pass | None |

Deviations From Evaluation Standards

None

Approved By:



Donald Facteau, Process Architect

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information. As indicated in the Statement of Work sent with the quotation, Element's standard process is to always use the latest published version of the test methods even when earlier versions are cited in the test specification. Issuance of a purchase order was de facto acceptance of this approach. Otherwise, the client would have advised Element in writing of the specific version of the test methods they wanted applied to the subject testing

REVISION HISTORY



| Revision Number | Description | Date (yyyy-mm-dd) | Page Number |
|-----------------|-------------|----------------------|-------------|
| 00 | None | | |

ACCREDITATIONS AND AUTHORIZATIONS



United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Accredited by A2LA to ISO / IEC 17065 as a product certifier. This allows Element to certify transmitters to FCC and IC specifications.

NVLAP - Each laboratory is accredited by NVLAP to ISO 17025

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB) and as a CAB for the acceptance of test data.

European Union

European Commission – Within Element, we have a EU Notified Body validated for the EMCD and RED Directives.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:

<https://www.nwemc.com/emc-testing-accreditations>

FACILITIES



| | | | | |
|---|---|---|--|---|
| California Labs OC01-17 41 Tesla Irvine, CA 92618 (949) 861-8918 | Minnesota Labs MN01-10 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612)-638-5136 | Oregon Labs EV01-12 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066 | Texas Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255 | Washington Labs NC01-05 19201 120 th Ave NE Bothell, WA 98011 (425)984-6600 |
| NVLAP | | | | |
| NVLAP Lab Code: 200676-0 | NVLAP Lab Code: 200881-0 | NVLAP Lab Code: 200630-0 | NVLAP Lab Code:201049-0 | NVLAP Lab Code: 200629-0 |
| Innovation, Science and Economic Development Canada | | | | |
| 2834B-1, 2834B-3 | 2834E-1, 2834E-3 | 2834D-1 | 2834G-1 | 2834F-1 |
| BSMI | | | | |
| SL2-IN-E-1154R | SL2-IN-E-1152R | SL2-IN-E-1017 | SL2-IN-E-1158R | SL2-IN-E-1153R |
| VCCI | | | | |
| A-0029 | A-0109 | A-0108 | A-0201 | A-0110 |
| Recognized Phase I CAB for ISED, ACMA, BSMI, IDA, KCC/RRR, MIC, MOC, NCC, OFCA | | | | |
| US0158 | US0175 | US0017 | US0191 | US0157 |



PRODUCT DESCRIPTION

Client and Equipment Under Evaluation Information

| | |
|---------------------------------|-------------------------------|
| Company Name: | Athena GTX, Inc. |
| Address: | 5900 NW 86th Street Suite 300 |
| City, State, Zip: | Johnston, IA 50131 |
| Evaluation Requested By: | Sean Mahoney |
| EUT: | HMAPS |
| Date of Evaluation: | Wednesday, November 25, 2020 |

Information Provided by the Party Requesting the Evaluation

Functional Description of the Equipment:

The HMAPS is a vital sign monitoring device. The HMAPS includes a 802.11bgn radio (FCC ID: 2AVRK-XBS6BTH) and a Bluetooth Low Energy radio (FCC ID: 2AA9B04, certified under 15.249 and exempt from RF exposure evaluation). The 802.11bgn radio operates at a duty cycle of <1%. The following information was provided by Eric Joyce, Principal Electrical Engineer at Athena GTX, Inc.: "The device only transmits 1500 bytes per 5 seconds which is ~0.24% at 1Mb/s 802.11b. The radio sends no beacon signals."

Objective:

To demonstrate compliance with FCC RF exposure requirements for 2.1093 portable devices.

RF Exposure Condition



| The following RF Exposure conditions were used for the assessment documented in this report: | |
|--|--|
| Intended Use | Portable |
| Location on Body (if applicable) | Head/Torso |
| How is the Device Used | The HMAPS is used at a distance of less than 20 cm from the user. |
| Radios Contained in the Same Host Device | 802.11bgn |
| | Bluetooth Low Energy radio (FCC ID: 2AA9B04, certified under 15.249 and exempt from RF exposure evaluation). |
| Simultaneous Transmitting Radios | None |
| Body Worn Accessories | None |
| Environment | General Population/Uncontrolled Exposure |

SAR TEST EXCLUSION



OVERVIEW

Human exposure to RF emissions from portable devices (47 CFR §2.1093) used with the radiating antenna closer than 20 cm to the user requires Specific Absorption Rate (SAR) to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation.

COMPLIANCE WITH FCC 2.1093

“Portable devices that operate in the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Service (PCS) pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, the 4.9 GHz Band Service, and the 3650 MHz Wireless Broadband Service pursuant to part 90 of this chapter; the Wireless Medical Telemetry Service (WMTS) and the Medical Device Radiocommunication Service (MedRadio), pursuant to subparts H and I of part 95 of this chapter, respectively, unlicensed personal communication service, unlicensed NII devices and millimeter wave devices authorized under §§15.253(f), 15.255(g), 15.257(g), 15.319(i), and 15.407(f) of this chapter; and the Citizens Broadband Radio Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use. All other portable transmitting devices are categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in §§1.1307(c) and 1.1307(d) of this chapter. Applications for equipment authorization of portable transmitting devices subject to routine environmental evaluation must contain a statement confirming compliance with the limits specified in paragraph (d) of this section. Technical information showing the basis for this statement must be submitted to the Commission upon request.”

The EUT will be used with a separation distance of less than 20 centimeters between the radiating antenna and the body of the user or nearby persons and must therefore be considered a portable transmitter per 47 CFR 2.1093(b).

COMPLIANCE WITH FCC KDB 447498 D01 General RF Exposure Guidance v06

“KDB 447498 D01 General RF Exposure Guidance v06” provides the procedures, requirements, and authorization policies for mobile and portable devices.

Standalone radio SAR test exclusion is covered under section 4.3.1. Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Thresholds are met as shown in the Limits section below.

Simultaneous transmission SAR test exclusion is covered under section 4.3.2. SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneously transmitting antenna. When the sum of 1-g or 10-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

SAR TEST EXCLUSION

LIMITS

Limits for General Population /Uncontrolled Exposure: 47 CFR 1.1310 (c)

The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the SAR test exclusion thresholds are 1-g for head and body SAR and 10-g SAR for extremity SAR.

ASSESSMENT

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] = \begin{matrix} 3.0 \text{ for 1-g SAR} \\ 7.5 \text{ for 10-g extremity SAR} \end{matrix}$$

Where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1f) is applied to determine SAR test exclusion.

The SAR Test Exclusion Threshold is summarized in the following table(s):

| Radio | Transmit Frequency (MHz) | Measured Conducted Output Power | Duty Cycle | Minimum Separation Distance (mm) | Exclusion Threshold | Limit | Compliant |
|-----------|--------------------------|---------------------------------|------------|----------------------------------|---------------------|-------|-----------|
| 802.11bgn | 2412 | 28.8 dBm | 1% | 5 | 2.3 | 3.0 | Yes |

The information in the table above was obtained from:

Client supplied information and UltraTech test report # DIGI-064F15C247 for FCC ID: MCQ-S6BSB. The client completed a change in ID on this module under FCC ID: 2AVRK-XBS6BTH.