



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2163-4, XT2163DL
FCC ID : IHDT56ZX2
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Jun. 02, 2021 ~ Jul. 13, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	8
1.9 Specification of Accessory.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 26dB & 99% Occupied Bandwidth Measurement	14
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	18
3.4 Unwanted Emissions Measurement	20
3.5 AC Conducted Emission Measurement.....	25
3.6 Antenna Requirements	27
4 LIST OF MEASURING EQUIPMENT	28
5 UNCERTAINTY OF EVALUATION	29
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR151921D	Rev. 01	Initial issue of report	Jul. 22, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	2.1049 & 15.403(i)	26dB & 99% Bandwidth	-	N/A	Report only
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	Pass	Under limit 3.07 dB at 5459.920 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.66 dB at 0.620 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	N/A	N/A	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2163-4, XT2163DL
FCC ID	IHDT56ZX2
IMEI Code	Conducted: 352304800016305 Conduction: 352304800007379 Radiation: 352304800014847
HW Version	DVT2
SW Version	RRH31.Q3-36
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5700 MHz
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> 802.11a : 18.45 dBm / 0.0700 W 802.11n HT20 : 18.20 dBm / 0.0661 W 802.11n HT40 : 17.03 dBm / 0.0505 W 802.11ac VHT20 : 18.20 dBm / 0.0661 W 802.11ac VHT40 : 17.00 dBm / 0.0501 W 802.11ac VHT80 : 17.38 dBm / 0.0547 W <5260 MHz ~ 5320 MHz> 802.11a : 18.91 dBm / 0.0778 W 802.11n HT20 : 18.82 dBm / 0.0762 W 802.11n HT40 : 17.88 dBm / 0.0614 W 802.11ac VHT20 : 18.80 dBm / 0.0759 W 802.11ac VHT40 : 17.86 dBm / 0.0611 W 802.11ac VHT80 : 15.97 dBm / 0.0395 W <5500 MHz ~ 5700 MHz > 802.11a : 18.66 dBm / 0.0735 W 802.11n HT20 : 18.58 dBm / 0.0721 W 802.11n HT40 : 17.59 dBm / 0.0574 W 802.11ac VHT20 : 18.56 dBm / 0.0718 W 802.11ac VHT40 : 17.56 dBm / 0.0570 W 802.11ac VHT80 : 17.25 dBm / 0.0531 W
99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz> 802.11a : 18.63 MHz 802.11n HT20 : 18.88 MHz 802.11n HT40 : 36.46 MHz 802.11ac VHT80 : 75.28 MHz <5260 MHz ~ 5320 MHz> 802.11a : 18.48 MHz 802.11n HT20 : 19.53 MHz 802.11n HT40 : 36.56 MHz 802.11ac VHT80 : 75.40 MHz <5500 MHz ~ 5700 MHz > 802.11a : 18.23 MHz 802.11n HT20 : 18.73 MHz 802.11n HT40 : 36.56 MHz 802.11ac VHT80 : 75.28 MHz
Antenna Type / Gain	<5180 MHz ~ 5240 MHz > FPC Antenna with gain -2.92 dBi <5260 MHz ~ 5320 MHz > FPC Antenna with gain -2.57 dBi <5500 MHz ~ 5700 MHz > FPC Antenna with gain -2.47 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note:

1. WLAN operation in 5600 MHz ~ 5650 MHz is notched.
2. Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing have assessed only 802.11n HT20/HT40 by referring to their maximum conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola(Aohai)	Model Name	MC-101
AC Adapter 2	Brand Name	Motorola(Salcomp)	Model Name	MC-101
AC Adapter 3	Brand Name	Motorola(Chenyang)	Model Name	MC-101
Battery	Brand Name	Motorola(ATL)	Model Name	NT40
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18C24367
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18C49697
USB Cable 3	Brand Name	Motorola(Luxshare)	Model Name	SC18C24368

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5700 MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM 850 Idle + BT Link + WLAN Link (5G) + Battery + Earphone + USB Cable 3(Charging from Adapter 3)
Remark: For Radiated Test Cases, The tests were performed with Adapter 1, Battery, Earphone and USB Cable 1.	



Ch. #		U-NII-1 : 5180-5240 MHz	U-NII-2A : 5260-5320 MHz	U-NII-2C : 5500-5700MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140


Ch. #		U-NII-1 : 5180-5240 MHz	U-NII-2A : 5260-5320 MHz	U-NII-2C : 5500-5700MHz
		802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140

Ch. #		U-NII-1 : 5180-5240 MHz	U-NII-2A : 5260-5320 MHz	U-NII-2C : 5500-5700MHz
		802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102
M	Middle	-	-	110
H	High	46	62	134


Ch. #		U-NII-1 : 5180-5240 MHz	U-NII-2A : 5260-5320 MHz	U-NII-2C : 5500-5700MHz
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	-
M	Middle	42	58	106
H	High	-	-	-

2.3 Connection Diagram of Test System

For Conducted Emission:



For Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
3.	NOTE BOOK	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Earphone	MOTO	S88731AA1	N/A	Unshielded,1.2m	N/A
5.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.8 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.8 + 20 = 22.8 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
-
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 08, 2021	Jun. 29, 2021	Apr. 07, 2022	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 25, 2020	Jun. 29, 2021	Dec. 24, 2021	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 25, 2020	Jun. 29, 2021	Dec. 24, 2021	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Jul. 21, 2020	Jul. 13, 2021	Jul. 20, 2021	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 21, 2020	Jul. 13, 2021	Jul. 20, 2021	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 22, 2020	Jul. 13, 2021	Jul. 21, 2021	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 15, 2020	Jul. 13, 2021	Jul. 14, 2021	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 25, 2020	Jul. 13, 2021	Jul. 24, 2021	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 23, 2021	Jul. 13, 2021	Apr. 22, 2022	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 17, 2021	Jul. 13, 2021	Apr. 16, 2022	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 17, 2020	Jul. 13, 2021	Oct. 16, 2021	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 16, 2020	Jul. 13, 2021	Oct. 15, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 21, 2020	Jul. 13, 2021	Jul. 20, 2021	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jul. 13, 2021	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 13, 2021	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 13, 2021	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Mar. 07, 2021	Jun. 02, 2021	Mar. 06, 2022	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2 LISN	00103912	9kHz~30MHz	Dec. 25, 2020	Jun. 02, 2021	Dec. 24, 2021	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 15, 2020	Jun. 02, 2021	Oct. 14, 2021	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 21, 2020	Jun. 02, 2021	Jul. 20, 2021	Conduction (CO01-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Test Engineer:	Zhang Xue Yi	Temperature:	21~25	°C
Test Date:	2021/6/29	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)		
11a	6Mbps	1	36	5180	18.03	31.30	-	22.56		
11a	6Mbps	1	44	5220	18.13	32.40	-	22.58		
11a	6Mbps	1	48	5240	18.63	36.75	-	22.70		
HT20	MCS0	1	36	5180	18.78	33.85	-	22.74		
HT20	MCS0	1	44	5220	18.78	34.50	-	22.74		
HT20	MCS0	1	48	5240	18.88	31.40	-	22.76		
HT40	MCS0	1	38	5190	36.46	45.63	-	23.01		
HT40	MCS0	1	46	5230	36.36	42.75	-	23.01		
VHT80	MCS0	1	42	5210	75.28	89.28	-	23.01		

TEST RESULTS DATA
Average Power Table

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.00	18.22	24.00	-2.92		Pass
11a	6Mbps	1	44	5220	0.00	18.36	24.00	-2.92		Pass
11a	6Mbps	1	48	5240	0.00	18.45	24.00	-2.92		Pass
HT20	MCS0	1	36	5180	0.00	18.20	24.00	-2.92		Pass
HT20	MCS0	1	44	5220	0.00	18.16	24.00	-2.92		Pass
HT20	MCS0	1	48	5240	0.00	18.20	24.00	-2.92		Pass
HT40	MCS0	1	38	5190	0.00	16.31	24.00	-2.92		Pass
HT40	MCS0	1	46	5230	0.00	17.03	24.00	-2.92		Pass
VHT20	MCS0	1	36	5180	0.00	18.20	24.00	-2.92		Pass
VHT20	MCS0	1	44	5220	0.00	18.14	24.00	-2.92		Pass
VHT20	MCS0	1	48	5240	0.00	17.93	24.00	-2.92		Pass
VHT40	MCS0	1	38	5190	0.00	16.28	24.00	-2.92		Pass
VHT40	MCS0	1	46	5230	0.00	17.00	24.00	-2.92		Pass
VHT80	MCS0	1	42	5210	0.00	17.38	24.00	-2.92		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.00	7.11	11.00	-2.92		Pass
11a	6Mbps	1	44	5220	0.00	6.92	11.00	-2.92		Pass
11a	6Mbps	1	48	5240	0.00	6.90	11.00	-2.92		Pass
HT20	MCS0	1	36	5180	0.00	6.58	11.00	-2.92		Pass
HT20	MCS0	1	44	5220	0.00	6.43	11.00	-2.92		Pass
HT20	MCS0	1	48	5240	0.00	6.47	11.00	-2.92		Pass
HT40	MCS0	1	38	5190	0.00	2.36	11.00	-2.92		Pass
HT40	MCS0	1	46	5230	0.00	2.26	11.00	-2.92		Pass
VHT80	MCS0	1	42	5210	0.00	-0.59	11.00	-2.92		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	52	5260	18.48	37.75	23.67	29.67	23.98	
11a	6M bps	1	60	5300	18.33	35.60	23.63	29.63	23.98	
11a	6M bps	1	64	5320	18.48	27.70	23.67	29.67	23.98	
HT20	MCS 0	1	52	5260	18.98	33.65	23.78	29.78	23.98	
HT20	MCS 0	1	60	5300	19.53	34.45	23.91	29.91	23.98	
HT20	MCS 0	1	64	5320	18.73	33.00	23.73	29.73	23.98	
HT40	MCS 0	1	54	5270	36.46	49.50	23.98	30.00	23.98	
HT40	MCS 0	1	62	5310	36.56	43.74	23.98	30.00	23.98	
VHT80	MCS 0	1	58	5290	75.40	95.20	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table

FCC Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	52	5260	0.00	18.84	23.98	-2.57	26.99	Pass
11a	6M bps	1	60	5300	0.00	18.82	23.98	-2.57	26.99	Pass
11a	6M bps	1	64	5320	0.00	18.91	23.98	-2.57	26.99	Pass
HT20	MCS 0	1	52	5260	0.00	18.81	23.98	-2.57	26.99	Pass
HT20	MCS 0	1	60	5300	0.00	18.80	23.98	-2.57	26.99	Pass
HT20	MCS 0	1	64	5320	0.00	18.82	23.98	-2.57	26.99	Pass
HT40	MCS 0	1	54	5270	0.00	17.88	23.98	-2.57	26.99	Pass
HT40	MCS 0	1	62	5310	0.00	16.90	23.98	-2.57	26.99	Pass
VHT20	MCS 0	1	52	5260	0.00	18.80	23.98	-2.57	26.99	Pass
VHT20	MCS 0	1	60	5300	0.00	18.78	23.98	-2.57	26.99	Pass
VHT20	MCS 0	1	64	5320	0.00	18.79	23.98	-2.57	26.99	Pass
VHT40	MCS 0	1	54	5270	0.00	17.86	23.98	-2.57	26.99	Pass
VHT40	MCS 0	1	62	5310	0.00	16.75	23.98	-2.57	26.99	Pass
VHT80	MCS 0	1	58	5290	0.00	15.97	23.98	-2.57	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	52	5260	0.00	7.55	11.00	-2.57		Pass
11a	6M bps	1	60	5300	0.00	7.17	11.00	-2.57		Pass
11a	6M bps	1	64	5320	0.00	6.83	11.00	-2.57		Pass
HT20	MCS 0	1	52	5260	0.00	7.15	11.00	-2.57		Pass
HT20	MCS 0	1	60	5300	0.00	7.18	11.00	-2.57		Pass
HT20	MCS 0	1	64	5320	0.00	6.94	11.00	-2.57		Pass
HT40	MCS 0	1	54	5270	0.00	2.91	11.00	-2.57		Pass
HT40	MCS 0	1	62	5310	0.00	2.99	11.00	-2.57		Pass
VHT80	MCS 0	1	58	5290	0.00	-0.13	11.00	-2.57		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	100	5500	17.98	26.85	23.55	29.55	23.98	
11a	6M bps	1	116	5580	18.23	26.55	23.61	29.61	23.98	
11a	6M bps	1	140	5700	18.13	28.15	23.58	29.58	23.98	
HT20	MCS 0	1	100	5500	18.63	30.35	23.70	29.70	23.98	
HT20	MCS 0	1	116	5580	18.73	30.60	23.73	29.73	23.98	
HT20	MCS 0	1	140	5700	18.53	27.55	23.68	29.68	23.98	
HT40	MCS 0	1	102	5510	36.56	44.46	23.98	30.00	23.98	
HT40	MCS 0	1	110	5550	36.36	41.85	23.98	30.00	23.98	
HT40	MCS 0	1	134	5670	36.46	44.64	23.98	30.00	23.98	
VHT80	MCS 0	1	106	5530	75.28	80.96	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table


FCC Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	100	5500	0.00	18.59	23.98	-2.47	26.99	Pass
11a	6M bps	1	116	5580	0.00	18.49	23.98	-2.47	26.99	Pass
11a	6M bps	1	140	5700	0.00	18.66	23.98	-2.47	26.99	Pass
HT20	MCS 0	1	100	5500	0.00	18.58	23.98	-2.47	26.99	Pass
HT20	MCS 0	1	116	5580	0.00	18.48	23.98	-2.47	26.99	Pass
HT20	MCS 0	1	140	5700	0.00	18.45	23.98	-2.47	26.99	Pass
HT40	MCS 0	1	102	5510	0.00	17.59	23.98	-2.47	26.99	Pass
HT40	MCS 0	1	110	5550	0.00	17.48	23.98	-2.47	26.99	Pass
HT40	MCS 0	1	134	5670	0.00	17.28	23.98	-2.47	26.99	Pass
VHT20	MCS 0	1	100	5500	0.00	18.56	23.98	-2.47	26.99	Pass
VHT20	MCS 0	1	116	5580	0.00	18.45	23.98	-2.47	26.99	Pass
VHT20	MCS 0	1	140	5700	0.00	18.42	23.98	-2.47	26.99	Pass
VHT40	MCS 0	1	102	5510	0.00	17.56	23.98	-2.47	26.99	Pass
VHT40	MCS 0	1	110	5550	0.00	17.22	23.98	-2.47	26.99	Pass
VHT40	MCS 0	1	134	5670	0.00	17.12	23.98	-2.47	26.99	Pass
VHT80	MCS 0	1	106	5530	0.00	17.25	23.98	-2.47	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	100	5500	0.00	6.73	11.00	-2.47		Pass
11a	6M bps	1	116	5580	0.00	7.59	11.00	-2.47		Pass
11a	6M bps	1	140	5700	0.00	7.37	11.00	-2.47		Pass
HT20	MCS 0	1	100	5500	0.00	7.36	11.00	-2.47		Pass
HT20	MCS 0	1	116	5580	0.00	7.05	11.00	-2.47		Pass
HT20	MCS 0	1	140	5700	0.00	6.42	11.00	-2.47		Pass
HT40	MCS 0	1	102	5510	0.00	2.66	11.00	-2.47		Pass
HT40	MCS 0	1	110	5550	0.00	2.76	11.00	-2.47		Pass
HT40	MCS 0	1	134	5670	0.00	2.29	11.00	-2.47		Pass
VHT80	MCS 0	1	106	5530	0.00	-0.31	11.00	-2.47		Pass




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Xie YuQiang	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15E_QP LISN_20201030_N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.48	25.95	-20.32	46.27	15.80	0.10	10.05	Average
2	0.48	38.45	-17.82	56.27	28.30	0.10	10.05	QP
3	0.53	25.55	-20.45	46.00	15.40	0.10	10.05	Average
4	0.53	38.25	-17.75	56.00	28.10	0.10	10.05	QP
5	0.62	30.54	-15.46	46.00	20.40	0.10	10.04	Average
6 *	0.62	45.34	-10.66	56.00	35.20	0.10	10.04	QP
7	0.69	27.34	-18.66	46.00	17.20	0.10	10.04	Average
8	0.69	42.24	-13.76	56.00	32.10	0.10	10.04	QP
9	1.63	26.76	-19.24	46.00	16.60	0.09	10.07	Average
10	1.63	39.36	-16.64	56.00	29.20	0.09	10.07	QP
11	3.51	23.47	-22.53	46.00	13.20	0.05	10.22	Average
12	3.51	36.37	-19.63	56.00	26.10	0.05	10.22	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Band U-NII-1 - 5150~5250MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5149.24	56.01	-17.99	74	45.03	31.36	12.15	32.53	220	296	P	H
		5150	46.13	-7.87	54	35.15	31.36	12.15	32.53	220	296	A	H
		5180	107.66	-	-	96.66	31.38	12.16	32.54	220	296	P	H
		5180	100.87	-	-	89.87	31.38	12.16	32.54	220	296	A	H
		5048.1	51.02	-22.98	74	40.09	31.32	12.12	32.51	196	32	P	V
		5150	41.16	-12.84	54	30.18	31.36	12.15	32.53	196	32	A	V
		5180	100.75	-	-	89.75	31.38	12.16	32.54	196	32	P	V
		5180	93.24	-	-	82.24	31.38	12.16	32.54	196	32	A	V
802.11a CH 44 5220MHz		5071.5	53.02	-20.98	74	42.08	31.33	12.13	32.52	213	288	P	H
		5150	43.49	-10.51	54	32.51	31.36	12.15	32.53	213	288	A	H
		5220	107.94	-	-	96.92	31.4	12.17	32.55	213	288	P	H
		5220	101.36	-	-	90.34	31.4	12.17	32.55	213	288	A	H
		5372.4	52.58	-21.42	74	41.47	31.47	12.21	32.57	213	288	P	H
		5386.08	42.29	-11.71	54	31.17	31.48	12.22	32.58	213	288	A	H
		5077.22	51.16	-22.84	74	40.22	31.33	12.13	32.52	341	211	P	V
		5123.24	40.41	-13.59	54	29.44	31.36	12.14	32.53	341	211	A	V
		5220	104.41	-	-	93.39	31.4	12.17	32.55	341	211	P	V
		5220	97.59	-	-	86.57	31.4	12.17	32.55	341	211	A	V
		5407.2	49.57	-24.43	74	38.44	31.49	12.22	32.58	341	211	P	V
		5382.24	39.64	-14.36	54	28.52	31.48	12.22	32.58	341	211	A	V



802.11a CH 48 5240MHz		5149.24	52.97	-21.03	74	41.99	31.36	12.15	32.53	217	292	P	H
		5148.2	42.43	-11.57	54	31.45	31.36	12.15	32.53	217	292	A	H
		5240	107.1	-	-	96.06	31.41	12.18	32.55	217	292	P	H
		5240	100.1	-	-	89.06	31.41	12.18	32.55	217	292	A	H
		5353.44	51.48	-22.52	74	40.38	31.46	12.21	32.57	217	292	P	H
		5350.8	41.71	-12.29	54	30.61	31.46	12.21	32.57	217	292	A	H
		5122.72	51.07	-22.93	74	40.1	31.36	12.14	32.53	336	231	P	V
		5126.36	40.98	-13.02	54	30	31.36	12.15	32.53	336	231	A	V
		5240	105.91	-	-	94.87	31.41	12.18	32.55	336	231	P	V
		5240	99	-	-	87.96	31.41	12.18	32.55	336	231	A	V
		5351.76	50.99	-23.01	74	39.89	31.46	12.21	32.57	336	231	P	V
		5356.32	40.34	-13.66	54	29.24	31.46	12.21	32.57	336	231	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		10360	49.81	-18.49	68.3	45.71	39.84	15.31	51.05	152	260	P	H
		15540	47.65	-26.35	74	43.7	38.85	17.76	52.66	189	238	P	H
		10360	48.96	-19.34	68.3	44.86	39.84	15.31	51.05	152	260	P	V
		15540	48.82	-25.18	74	44.87	38.85	17.76	52.66	189	238	P	V
802.11a CH 44 5220MHz		10440	50.49	-17.81	68.3	46.31	39.93	15.32	51.07	150	230	P	H
		15660	47.42	-26.58	74	44.15	38.32	17.83	52.88	160	225	P	H
		10440	50.71	-17.59	68.3	46.53	39.93	15.32	51.07	150	230	P	V
		15660	45.87	-28.13	74	42.6	38.32	17.83	52.88	160	225	P	V
802.11a CH 48 5240MHz		10480	51.07	-17.23	68.3	46.85	39.99	15.32	51.09	150	289	P	H
		15720	46.04	-27.96	74	43.16	38.01	17.87	53	150	291	P	H
		10480	49.64	-18.66	68.3	45.42	39.99	15.32	51.09	150	289	P	V
		15720	45.03	-28.97	74	42.15	38.01	17.87	53	150	291	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		5145.34	56.77	-17.23	74	45.79	31.36	12.15	32.53	223	288	P	H
		5150	46.49	-7.51	54	35.51	31.36	12.15	32.53	223	288	A	H
		5180	107.58	-	-	96.58	31.38	12.16	32.54	223	288	P	H
		5180	100.62	-	-	89.62	31.38	12.16	32.54	223	288	A	H
		5145.86	53.17	-20.83	74	42.19	31.36	12.15	32.53	327	232	P	V
		5150	43.98	-10.02	54	33	31.36	12.15	32.53	327	232	A	V
		5180	104.95	-	-	93.95	31.38	12.16	32.54	327	232	P	V
		5180	97.68	-	-	86.68	31.38	12.16	32.54	327	232	A	V
802.11n HT20 CH 44 5220MHz		5110.76	53.26	-20.74	74	42.29	31.35	12.14	32.52	218	295	P	H
		5149.76	42.44	-11.56	54	31.46	31.36	12.15	32.53	218	295	A	H
		5220	107.48	-	-	96.46	31.4	12.17	32.55	218	295	P	H
		5220	99.6	-	-	88.58	31.4	12.17	32.55	218	295	A	H
		5395.68	51.13	-22.87	74	40	31.49	12.22	32.58	218	295	P	H
		5388.96	40.13	-13.87	54	29.01	31.48	12.22	32.58	218	295	A	H
		5120.12	51.8	-22.2	74	40.84	31.35	12.14	32.53	362	234	P	V
		5149.76	40.9	-13.1	54	29.92	31.36	12.15	32.53	362	234	A	V
		5220	104.64	-	-	93.62	31.4	12.17	32.55	362	234	P	V
		5220	97.81	-	-	86.79	31.4	12.17	32.55	362	234	A	V
		5354.64	49.75	-24.25	74	38.65	31.46	12.21	32.57	362	234	P	V
		5356.08	40.22	-13.78	54	29.12	31.46	12.21	32.57	362	234	A	V



802.11n HT20 CH 48 5240MHz		5136.76	54.2	-19.8	74	43.22	31.36	12.15	32.53	216	289	P	H
		5147.94	42.8	-11.2	54	31.82	31.36	12.15	32.53	216	289	A	H
		5240	107.35	-	-	96.31	31.41	12.18	32.55	216	289	P	H
		5240	100.71	-	-	89.67	31.41	12.18	32.55	216	289	A	H
		5376.48	52.3	-21.7	74	41.19	31.47	12.22	32.58	216	289	P	H
		5350.08	42.22	-11.78	54	31.12	31.46	12.21	32.57	216	289	A	H
		5101.14	51	-23	74	40.04	31.34	12.14	32.52	339	212	P	V
		5125.58	40.1	-13.9	54	29.12	31.36	12.15	32.53	339	212	A	V
		5240	103.32	-	-	92.28	31.41	12.18	32.55	339	212	P	V
		5240	97.14	-	-	86.1	31.41	12.18	32.55	339	212	A	V
		5360.4	49.54	-24.46	74	38.44	31.46	12.21	32.57	339	212	P	V
		5359.92	39.68	-14.32	54	28.58	31.46	12.21	32.57	339	212	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		10360	47.99	-20.31	68.3	43.89	39.84	15.31	51.05	152	260	P	H
HT20		15540	47.11	-26.89	74	43.16	38.85	17.76	52.66	189	238	P	H
CH 36		10360	48.5	-19.8	68.3	44.4	39.84	15.31	51.05	152	260	P	V
5180MHz		15540	46.28	-27.72	74	42.33	38.85	17.76	52.66	189	238	P	V
802.11n		10440	48.67	-19.63	68.3	44.49	39.93	15.32	51.07	150	230	P	H
HT20		15660	45.88	-28.12	74	42.61	38.32	17.83	52.88	160	225	P	H
CH 44		10440	48.69	-19.61	68.3	44.51	39.93	15.32	51.07	150	230	P	V
5220MHz		15660	46.7	-27.3	74	43.43	38.32	17.83	52.88	160	225	P	V
802.11n		10480	48.81	-19.49	68.3	44.59	39.99	15.32	51.09	150	289	P	H
HT20		15720	45.27	-28.73	74	42.39	38.01	17.87	53	150	291	P	H
CH 48		10480	48.62	-19.68	68.3	44.4	39.99	15.32	51.09	150	289	P	V
5240MHz		15720	45.68	-28.32	74	42.8	38.01	17.87	53	150	291	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5143.78	57.01	-16.99	74	46.03	31.36	12.15	32.53	106	270	P	H
		5149.24	47.93	-6.07	54	36.95	31.36	12.15	32.53	106	270	A	H
		5190	101.18	-	-	90.18	31.38	12.16	32.54	106	270	P	H
		5190	94.69	-	-	83.69	31.38	12.16	32.54	106	270	A	H
		5388.04	48.94	-25.06	74	37.82	31.48	12.22	32.58	106	270	P	H
		5353.88	40.68	-13.32	54	29.58	31.46	12.21	32.57	106	270	A	H
		5149.24	52.99	-21.01	74	42.01	31.36	12.15	32.53	103	146	P	V
		5150	45.27	-8.73	54	34.29	31.36	12.15	32.53	103	146	A	V
		5190	100.57	-	-	89.57	31.38	12.16	32.54	103	146	P	V
		5190	93.67	-	-	82.67	31.38	12.16	32.54	103	146	A	V
		5440.68	49.09	-24.91	74	37.95	31.5	12.23	32.59	103	146	P	V
		5354.72	40.01	-13.99	54	28.91	31.46	12.21	32.57	103	146	A	V
802.11n HT40 CH 46 5230MHz		5091.52	50.53	-23.47	74	39.57	31.34	12.14	32.52	102	1	P	H
		5131.3	41.08	-12.92	54	30.1	31.36	12.15	32.53	102	1	A	H
		5230	100.25	-	-	89.22	31.41	12.17	32.55	102	1	P	H
		5230	93.55	-	-	82.52	31.41	12.17	32.55	102	1	A	H
		5361.12	48.96	-25.04	74	37.85	31.47	12.21	32.57	102	1	P	H
		5381.28	39.8	-14.2	54	28.68	31.48	12.22	32.58	102	1	A	H
		5145.08	51.52	-22.48	74	40.54	31.36	12.15	32.53	101	120	P	V
		5149.5	41.42	-12.58	54	30.44	31.36	12.15	32.53	101	120	A	V
		5230	101.04	-	-	90.01	31.41	12.17	32.55	101	120	P	V
		5230	93.6	-	-	82.57	31.41	12.17	32.55	101	120	A	V
		5437.92	50.86	-23.14	74	39.72	31.5	12.23	32.59	101	120	P	V
		5352.96	40.43	-13.57	54	29.33	31.46	12.21	32.57	101	120	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		10380	49.67	-18.63	68.3	45.53	39.87	15.32	51.05	150	360	P	H
HT40		15570	48.71	-25.29	74	44.95	38.7	17.78	52.72	155	360	P	H
CH 38		10380	49.08	-19.22	68.3	44.94	39.87	15.32	51.05	150	360	P	V
5190MHz		15570	48.2	-25.8	74	44.44	38.7	17.78	52.72	155	360	P	V
802.11n		10460	48.66	-19.64	68.3	44.47	39.95	15.32	51.08	150	360	P	H
HT40		15690	46.8	-27.2	74	43.72	38.17	17.85	52.94	150	225	P	H
CH 46		10460	49.71	-18.59	68.3	45.52	39.95	15.32	51.08	150	360	P	V
5230MHz		15690	47.53	-26.47	74	44.45	38.17	17.85	52.94	150	225	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-1 5150~5250MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 42 5210MHz		5130.78	59.8	-14.2	74	48.82	31.36	12.15	32.53	211	301	P	H
		5150	50.54	-3.46	54	39.56	31.36	12.15	32.53	211	301	A	H
		5210	100.73	-	-	89.7	31.4	12.17	32.54	211	301	P	H
		5210	92.91	-	-	81.88	31.4	12.17	32.54	211	301	A	H
		5355.84	52.76	-21.24	74	41.66	31.46	12.21	32.57	211	301	P	H
		5356.08	42.92	-11.08	54	31.82	31.46	12.21	32.57	211	301	A	H
		5143.78	57.34	-16.66	74	46.36	31.36	12.15	32.53	363	211	P	V
		5150	46.7	-7.3	54	35.72	31.36	12.15	32.53	363	211	A	V
		5210	98.14	-	-	87.11	31.4	12.17	32.54	363	211	P	V
		5210	92.08	-	-	81.05	31.4	12.17	32.54	363	211	A	V
		5367.12	50.44	-23.56	74	39.33	31.47	12.21	32.57	363	211	P	V
		5350.8	40.99	-13.01	54	29.89	31.46	12.21	32.57	363	211	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band U-NII-1 5150~5250MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		10420	49.85	-18.45	68.3	45.69	39.91	15.32	51.07	150	230	P	H
VHT80		15630	46.07	-27.93	74	42.71	38.39	17.82	52.85	160	225	P	H
CH 42		10420	48.81	-19.49	68.3	44.65	39.91	15.32	51.07	150	230	P	V
5210MHz		15630	47.84	-26.16	74	44.48	38.39	17.82	52.85	160	225	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A - 5250~5350MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 52 5260MHz		5140.4	52.56	-21.44	74	41.58	31.36	12.15	32.53	218	287	P	H
		5092.3	42.21	-11.79	54	31.25	31.34	12.14	32.52	218	287	A	H
		5260	108.89	-	-	97.84	31.42	12.18	32.55	218	287	P	H
		5260	102.1	-	-	91.05	31.42	12.18	32.55	218	287	A	H
		5376	52.61	-21.39	74	41.5	31.47	12.22	32.58	218	287	P	H
		5350.08	42.98	-11.02	54	31.88	31.46	12.21	32.57	218	287	A	H
		5092.56	50.92	-23.08	74	39.96	31.34	12.14	32.52	318	228	P	V
		5096.72	40.63	-13.37	54	29.67	31.34	12.14	32.52	318	228	A	V
		5260	105.34	-	-	94.29	31.42	12.18	32.55	318	228	P	V
		5260	98.36	-	-	87.31	31.42	12.18	32.55	318	228	A	V
		5379.84	49.9	-24.1	74	38.78	31.48	12.22	32.58	318	228	P	V
		5351.04	40.48	-13.52	54	29.38	31.46	12.21	32.57	318	228	A	V
802.11a CH 60 5300MHz		5097.3	51.16	-22.84	74	40.2	31.34	12.14	32.52	275	284	P	H
		5129.5	41.2	-12.8	54	30.22	31.36	12.15	32.53	275	284	A	H
		5300	109.3	-	-	98.23	31.44	12.19	32.56	275	284	P	H
		5300	102.86	-	-	91.79	31.44	12.19	32.56	275	284	A	H
		5352.96	55.51	-18.49	74	44.41	31.46	12.21	32.57	275	284	P	H
		5350.08	45.01	-8.99	54	33.91	31.46	12.21	32.57	275	284	A	H
		5036.4	51.18	-22.82	74	40.26	31.31	12.12	32.51	333	230	P	V
		5129.85	41.06	-12.94	54	30.08	31.36	12.15	32.53	333	230	A	V
		5300	106.7	-	-	95.63	31.44	12.19	32.56	333	230	P	V
		5300	100.12	-	-	89.05	31.44	12.19	32.56	333	230	A	V
		5351.76	52.44	-21.56	74	41.34	31.46	12.21	32.57	333	230	P	V
		5355.6	42.23	-11.77	54	31.13	31.46	12.21	32.57	333	230	A	V



802.11a CH 64 5320MHz		5320	110.8	-	-	99.71	31.45	12.2	32.56	277	285	P	H
		5320	104.47	-	-	93.38	31.45	12.2	32.56	277	285	A	H
		5352.64	58.93	-15.07	74	47.83	31.46	12.21	32.57	277	285	P	H
		5350.08	48.2	-5.8	54	37.1	31.46	12.21	32.57	277	285	A	H
		5320	107.07	-	-	95.98	31.45	12.2	32.56	279	209	P	V
		5320	100.79	-	-	89.7	31.45	12.2	32.56	279	209	A	V
		5365.28	53.13	-20.87	74	42.02	31.47	12.21	32.57	279	209	P	V
		5350.08	43.75	-10.25	54	32.65	31.46	12.21	32.57	279	209	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 52 5260MHz		10520	49.86	-18.44	68.3	45.57	40.03	15.37	51.11	150	220	P	H
		15780	46.62	-27.38	74	44.03	37.79	17.9	53.1	159	345	P	H
		10520	50.48	-17.82	68.3	46.19	40.03	15.37	51.11	150	220	P	V
		15780	46.5	-27.5	74	43.91	37.79	17.9	53.1	159	345	P	V
802.11a CH 60 5300MHz		10600	50.16	-23.84	74	45.64	40.13	15.55	51.16	185	215	P	H
		15900	44.32	-29.68	74	42.4	37.26	17.97	53.31	196	190	P	H
		10600	50.21	-23.79	74	45.69	40.13	15.55	51.16	185	215	P	V
		15900	44.03	-29.97	74	42.11	37.26	17.97	53.31	196	190	P	V
802.11a CH 64 5320MHz		10640	48.01	-25.99	74	24.26	40.17	15.65	32.07	161	360	P	H
		15960	46.07	-27.93	74	44.55	36.95	18.01	53.44	173	245	P	H
		10640	48.83	-25.17	74	44.19	40.17	15.65	51.18	152	135	P	V
		15960	45.16	-28.84	74	43.64	36.95	18.01	53.44	173	245	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 52 5260MHz		5144.04	52.03	-21.97	74	41.05	31.36	12.15	32.53	217	296	P	H
		5099.32	41.04	-12.96	54	30.08	31.34	12.14	32.52	217	296	A	H
		5260	106.83	-	-	95.78	31.42	12.18	32.55	217	296	P	H
		5260	99.27	-	-	88.22	31.42	12.18	32.55	217	296	A	H
		5388	50.86	-23.14	74	39.74	31.48	12.22	32.58	217	296	P	H
		5350.32	40.71	-13.29	54	29.61	31.46	12.21	32.57	217	296	A	H
		5099.32	50.15	-23.85	74	39.19	31.34	12.14	32.52	356	210	P	V
		5146.64	40.1	-13.9	54	29.12	31.36	12.15	32.53	356	210	A	V
		5260	106.12	-	-	95.07	31.42	12.18	32.55	356	210	P	V
		5260	99.22	-	-	88.17	31.42	12.18	32.55	356	210	A	V
		5351.28	50	-24	74	38.9	31.46	12.21	32.57	356	210	P	V
		5350.08	39.96	-14.04	54	28.86	31.46	12.21	32.57	356	210	A	V
802.11n HT20 CH 60 5300MHz		5051.1	51.98	-22.02	74	41.05	31.32	12.12	32.51	217	289	P	H
		5131.25	42.18	-11.82	54	31.2	31.36	12.15	32.53	217	289	A	H
		5300	110.08	-	-	99.01	31.44	12.19	32.56	217	289	P	H
		5300	103.38	-	-	92.31	31.44	12.19	32.56	217	289	A	H
		5360.4	55.85	-18.15	74	44.75	31.46	12.21	32.57	217	289	P	H
		5358.72	44.73	-9.27	54	33.63	31.46	12.21	32.57	217	289	A	H
		5064.4	50.61	-23.39	74	39.68	31.32	12.13	32.52	372	208	P	V
		5129.15	40.24	-13.76	54	29.26	31.36	12.15	32.53	372	208	A	V
		5300	106.27	-	-	95.2	31.44	12.19	32.56	372	208	P	V
		5300	99.43	-	-	88.36	31.44	12.19	32.56	372	208	A	V
		5377.2	50.91	-23.09	74	39.8	31.47	12.22	32.58	372	208	P	V
		5350.8	41.09	-12.91	54	29.99	31.46	12.21	32.57	372	208	A	V



802.11n HT20 CH 64 5320MHz		5320	109.49	-	-	98.4	31.45	12.2	32.56	274	283	P	H
		5320	102.18	-	-	91.09	31.45	12.2	32.56	274	283	A	H
		5350.08	60.19	-13.81	74	49.09	31.46	12.21	32.57	274	283	P	H
		5350.08	46.33	-7.67	54	35.23	31.46	12.21	32.57	274	283	A	H
		5320	107.27	-	-	96.18	31.45	12.2	32.56	330	235	P	V
		5320	100.77	-	-	89.68	31.45	12.2	32.56	330	235	A	V
		5350.88	54.52	-19.48	74	43.42	31.46	12.21	32.57	330	235	P	V
		5350.08	43.87	-10.13	54	32.77	31.46	12.21	32.57	330	235	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		10520	49.53	-18.77	68.3	45.24	40.03	15.37	51.11	150	220	P	H
HT20		15780	45.57	-28.43	74	42.98	37.79	17.9	53.1	159	345	P	H
CH 52		10520	49.54	-18.76	68.3	45.25	40.03	15.37	51.11	150	220	P	V
5260MHz		15780	45.9	-28.1	74	43.31	37.79	17.9	53.1	159	345	P	V
802.11n		10600	49.23	-24.77	74	44.71	40.13	15.55	51.16	185	215	P	H
HT20		15900	44.47	-29.53	74	42.55	37.26	17.97	53.31	196	190	P	H
CH 60		10600	50.66	-23.34	74	46.14	40.13	15.55	51.16	185	215	P	V
5300MHz		15900	44.89	-29.11	74	42.97	37.26	17.97	53.31	196	190	P	V
802.11n		10640	49.1	-24.9	74	44.46	40.17	15.65	51.18	152	135	P	H
HT20		15960	43.78	-30.22	74	42.26	36.95	18.01	53.44	173	245	P	H
CH 64		10640	49.38	-24.62	74	44.74	40.17	15.65	51.18	152	135	P	V
5320MHz		15960	43.94	-30.06	74	42.42	36.95	18.01	53.44	173	245	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 54 5270MHz		5107.45	51.76	-22.24	74	40.79	31.35	12.14	32.52	100	298	P	H
		5112	42.82	-11.18	54	31.85	31.35	12.14	32.52	100	298	A	H
		5270	103.57	-	-	92.51	31.42	12.19	32.55	100	298	P	H
		5270	96.91	-	-	85.85	31.42	12.19	32.55	100	298	A	H
		5357.28	54.24	-19.76	74	43.14	31.46	12.21	32.57	100	298	P	H
		5350.32	44.47	-9.53	54	33.37	31.46	12.21	32.57	100	298	A	H
		5035.7	50.94	-23.06	74	40.02	31.31	12.12	32.51	100	119	P	V
		5148.4	41.41	-12.59	54	30.43	31.36	12.15	32.53	100	119	A	V
		5270	102.39	-	-	91.33	31.42	12.19	32.55	100	119	P	V
		5270	95.8	-	-	84.74	31.42	12.19	32.55	100	119	A	V
		5371.68	50.03	-23.97	74	38.92	31.47	12.21	32.57	100	119	P	V
		5350.32	40.92	-13.08	54	29.82	31.46	12.21	32.57	100	119	A	V
802.11n HT40 CH 62 5310MHz		5051.1	50.42	-23.58	74	39.49	31.32	12.12	32.51	100	258	P	H
		5124.6	41.3	-12.7	54	30.33	31.36	12.14	32.53	100	258	A	H
		5310	101.15	-	-	90.06	31.45	12.2	32.56	100	258	P	H
		5310	94.67	-	-	83.58	31.45	12.2	32.56	100	258	A	H
		5356.8	55.46	-18.54	74	44.36	31.46	12.21	32.57	100	258	P	H
		5350.08	47.4	-6.6	54	36.3	31.46	12.21	32.57	100	258	A	H
		5137.55	50.27	-23.73	74	39.29	31.36	12.15	32.53	100	177	P	V
		5149.8	41.38	-12.62	54	30.4	31.36	12.15	32.53	100	177	A	V
		5310	101.85	-	-	90.76	31.45	12.2	32.56	100	177	P	V
		5310	95.36	-	-	84.27	31.45	12.2	32.56	100	177	A	V
		5352.96	56.14	-17.86	74	45.04	31.46	12.21	32.57	100	177	P	V
		5350.08	47.03	-6.97	54	35.93	31.46	12.21	32.57	100	177	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		10540	48.14	-20.16	68.3	43.8	40.05	15.41	51.12	150	220	P	H
HT40		15810	45.34	-28.66	74	42.95	37.63	17.92	53.16	168	345	P	H
CH 54		10540	47.25	-21.05	68.3	42.91	40.05	15.41	51.12	150	220	P	V
5270MHz		15810	44.24	-29.76	74	41.85	37.63	17.92	53.16	168	345	P	V
802.11n		10620	49.34	-24.66	74	44.76	40.15	15.6	51.17	150	220	P	H
HT40		15930	45.01	-28.99	74	43.3	37.1	17.99	53.38	160	100	P	H
CH 62		10620	49.65	-24.35	74	45.07	40.15	15.6	51.17	150	220	P	V
5310MHz		15930	45.38	-28.62	74	43.67	37.1	17.99	53.38	160	100	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2A 5250~5350MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 58 5290MHz		5074.55	50.89	-23.11	74	39.95	31.33	12.13	32.52	312	286	P	H
		5124.25	41.62	-12.38	54	30.65	31.36	12.14	32.53	312	286	A	H
		5290	99.46	-	-	88.4	31.43	12.19	32.56	312	286	P	H
		5290	92.18	-	-	81.12	31.43	12.19	32.56	312	286	A	H
		5352.24	58.92	-15.08	74	47.82	31.46	12.21	32.57	312	286	P	H
		5350.08	49.88	-4.12	54	38.78	31.46	12.21	32.57	312	286	A	H
		5120.05	50.72	-23.28	74	39.76	31.35	12.14	32.53	350	178	P	V
		5127.05	41.03	-12.97	54	30.05	31.36	12.15	32.53	350	178	A	V
		5290	98.57	-	-	87.51	31.43	12.19	32.56	350	178	P	V
		5290	92.08	-	-	81.02	31.43	12.19	32.56	350	178	A	V
		5359.44	56.48	-17.52	74	45.38	31.46	12.21	32.57	350	178	P	V
		5350.32	45.15	-8.85	54	34.05	31.46	12.21	32.57	350	178	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band U-NII-2A 5250~5350MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		10580	50.49	-17.81	68.3	46.02	40.11	15.51	51.15	150	220	P	H
VHT80		15870	46.97	-27.03	74	44.97	37.33	17.95	53.28	168	345	P	H
CH 58		10580	48.59	-19.71	68.3	44.12	40.11	15.51	51.15	150	220	P	V
5290MHz		15870	46.19	-27.81	74	44.19	37.33	17.95	53.28	168	345	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 100 5500MHz		5424.72	54.29	-19.71	74	43.15	31.49	12.23	32.58	270	283	P	H
		5469.2	59.75	-8.55	68.3	48.58	31.52	12.24	32.59	270	283	P	H
		5460	44.75	-9.25	54	33.59	31.51	12.24	32.59	270	283	A	H
		5500	109.51	-	-	98.32	31.54	12.25	32.6	270	283	P	H
		5500	103.89	-	-	92.7	31.54	12.25	32.6	270	283	A	H
		5459.12	53.54	-20.46	74	42.38	31.51	12.24	32.59	295	207	P	V
		5468.72	57.49	-10.81	68.3	46.32	31.52	12.24	32.59	295	207	P	V
		5460	42.62	-11.38	54	31.46	31.51	12.24	32.59	295	207	A	V
		5500	107.56	-	-	96.37	31.54	12.25	32.6	295	207	P	V
		5500	100.19	-	-	89	31.54	12.25	32.6	295	207	A	V
802.11a CH 116 5580MHz		5443.84	52.2	-21.8	74	41.06	31.5	12.23	32.59	263	286	P	H
		5466.16	52.23	-16.07	68.3	41.06	31.52	12.24	32.59	263	286	P	H
		5459.92	42.35	-11.65	54	31.19	31.51	12.24	32.59	263	286	A	H
		5580	109.71	-	-	98.47	31.57	12.27	32.6	263	286	P	H
		5580	104.69	-	-	93.45	31.57	12.27	32.6	263	286	A	H
		5730.665	52.34	-15.96	68.3	40.73	31.91	12.3	32.6	263	286	P	H
		5448.88	50.35	-23.65	74	39.19	31.51	12.24	32.59	258	209	P	V
		5462.08	50.13	-18.17	68.3	38.97	31.51	12.24	32.59	258	209	P	V
		5459.92	39.82	-14.18	54	28.66	31.51	12.24	32.59	258	209	A	V
		5580	106.12	-	-	94.88	31.57	12.27	32.6	258	209	P	V
		5580	100.09	-	-	88.85	31.57	12.27	32.6	258	209	A	V
		5726.57	49.82	-18.48	68.3	38.21	31.91	12.3	32.6	258	209	P	V



802.11a CH 140 5700MHz		5700	109.59	-	-	98.12	31.78	12.29	32.6	261	283	P	H
		5700	104.72	-	-	93.25	31.78	12.29	32.6	261	283	A	H
		5725.72	61.48	-6.82	68.3	49.87	31.91	12.3	32.6	261	283	P	H
		5700	107.78	-	-	96.31	31.78	12.29	32.6	321	205	P	V
		5700	100.81	-	-	89.34	31.78	12.29	32.6	321	205	A	V
		5725	60.44	-7.86	68.3	48.83	31.91	12.3	32.6	321	205	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 100 5500MHz		11000	50.43	-23.57	74	44.75	40.59	16.49	51.4	163	230	P	H
		16500	46.73	-21.57	68.3	42.29	38.94	18.2	52.7	178	296	P	H
		11000	49.85	-24.15	74	44.17	40.59	16.49	51.4	163	230	P	V
		16500	45.6	-22.7	68.3	41.16	38.94	18.2	52.7	178	296	P	V
802.11a CH 116 5580MHz		11160	50.35	-23.65	74	44.32	40.8	16.5	51.27	170	200	P	H
		16740	46.25	-22.05	68.3	41.17	39.93	18.28	53.13	156	350	P	H
		11160	49.05	-24.95	74	43.02	40.8	16.5	51.27	170	200	P	V
		16740	43.91	-24.39	68.3	38.83	39.93	18.28	53.13	156	350	P	V
802.11a CH 140 5700MHz		11400	49.12	-24.88	74	42.6	41.08	16.52	51.08	157	285	P	H
		17100	48.3	-20	68.3	41.81	41.6	18.41	53.52	165	246	P	H
		11400	50.6	-23.4	74	44.08	41.08	16.52	51.08	157	285	P	V
		17100	48.05	-20.25	68.3	41.56	41.6	18.41	53.52	165	246	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		5459.92	54.11	-19.89	74	42.95	31.51	12.24	32.59	253	288	P	H
		5466.16	60.75	-7.55	68.3	49.58	31.52	12.24	32.59	253	288	P	H
		5460	44.65	-9.35	54	33.49	31.51	12.24	32.59	253	288	A	H
		5500	109.37	-	-	98.18	31.54	12.25	32.6	253	288	P	H
		5500	102.76	-	-	91.57	31.54	12.25	32.6	253	288	A	H
		5450.16	51.32	-22.68	74	40.16	31.51	12.24	32.59	324	208	P	V
		5467.92	56.57	-11.73	68.3	45.4	31.52	12.24	32.59	324	208	P	V
		5460	41.64	-12.36	54	30.48	31.51	12.24	32.59	324	208	A	V
		5500	106.47	-	-	95.28	31.54	12.25	32.6	324	208	P	V
		5500	99.25	-	-	88.06	31.54	12.25	32.6	324	208	A	V
802.11n HT20 CH 116 5580MHz		5432.32	50.29	-23.71	74	39.15	31.5	12.23	32.59	333	314	P	H
		5462.56	49.49	-18.81	68.3	38.32	31.52	12.24	32.59	333	314	P	H
		5459.68	40.54	-13.46	54	29.38	31.51	12.24	32.59	333	314	A	H
		5580	108.79	-	-	97.55	31.57	12.27	32.6	333	314	P	H
		5580	101.49	-	-	90.25	31.57	12.27	32.6	333	314	A	H
		5729.405	50.22	-18.08	68.3	38.61	31.91	12.3	32.6	333	314	P	H
		5440.48	50.62	-23.38	74	39.48	31.5	12.23	32.59	332	271	P	V
		5462.32	49.08	-19.22	68.3	37.92	31.51	12.24	32.59	332	271	P	V
		5459.92	40.59	-13.41	54	29.43	31.51	12.24	32.59	332	271	A	V
		5580	108.68	-	-	97.44	31.57	12.27	32.6	332	271	P	V
		5580	102.31	-	-	91.07	31.57	12.27	32.6	332	271	A	V
		5735.075	50.77	-17.53	68.3	39.1	31.97	12.3	32.6	332	271	P	V



802.11n HT20 CH 140 5700MHz		5700	108.08	-	-	96.61	31.78	12.29	32.6	321	315	P	H
		5700	101.82	-	-	90.35	31.78	12.29	32.6	321	315	A	H
		5725.48	62.17	-6.13	68.3	50.56	31.91	12.3	32.6	321	315	P	H
		5700	108.14	-	-	96.67	31.78	12.29	32.6	337	275	P	V
		5700	102.33	-	-	90.86	31.78	12.29	32.6	337	275	A	V
		5725.64	59.45	-8.85	68.3	47.84	31.91	12.3	32.6	337	275	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		11000	50.74	-23.26	74	45.06	40.59	16.49	51.4	163	230	P	H
HT20		16500	47.14	-21.16	68.3	42.7	38.94	18.2	52.7	178	296	P	H
CH 100		11000	50.8	-23.2	74	45.12	40.59	16.49	51.4	163	230	P	V
5500MHz		16500	46.09	-22.21	68.3	41.65	38.94	18.2	52.7	178	296	P	V
802.11n		11160	50.72	-23.28	74	44.69	40.8	16.5	51.27	170	200	P	H
HT20		16740	44.75	-23.55	68.3	39.67	39.93	18.28	53.13	156	350	P	H
CH 116		11160	50.39	-23.61	74	44.36	40.8	16.5	51.27	170	200	P	V
5580MHz		16740	46.2	-22.1	68.3	41.12	39.93	18.28	53.13	156	350	P	V
802.11n		11400	50.35	-23.65	74	43.83	41.08	16.52	51.08	157	285	P	H
HT20		17100	47.2	-21.1	68.3	40.71	41.6	18.41	53.52	165	246	P	H
CH 140		11400	51.11	-22.89	74	44.59	41.08	16.52	51.08	157	285	P	V
5700MHz		17100	48.28	-20.02	68.3	41.79	41.6	18.41	53.52	165	246	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 102 5510MHz		5437.12	48.9	-25.1	74	37.76	31.5	12.23	32.59	312	209	P	H
		5469.28	51.92	-16.38	68.3	40.75	31.52	12.24	32.59	312	209	P	H
		5459.92	41.24	-12.76	54	30.08	31.51	12.24	32.59	312	209	A	H
		5510	101.16	-	-	89.97	31.54	12.25	32.6	312	209	P	H
		5510	94.43	-	-	83.24	31.54	12.25	32.6	312	209	A	H
		5732.24	49.27	-19.03	68.3	37.66	31.91	12.3	32.6	312	209	P	H
		5459.68	58.5	-15.5	74	47.34	31.51	12.24	32.59	328	210	P	V
		5467.36	62.31	-5.99	68.3	51.14	31.52	12.24	32.59	328	210	P	V
		5459.92	48.14	-5.86	54	36.98	31.51	12.24	32.59	328	210	A	V
		5510	103.07	-	-	91.88	31.54	12.25	32.6	328	210	P	V
		5510	96.53	-	-	85.34	31.54	12.25	32.6	328	210	A	V
		5748.305	49.86	-18.44	68.3	38.19	31.97	12.3	32.6	328	210	P	V
802.11n HT40 CH 110 5550MHz		5429.44	51.37	-22.63	74	40.23	31.5	12.23	32.59	333	297	P	H
		5465.2	51.23	-17.07	68.3	40.06	31.52	12.24	32.59	333	297	P	H
		5459.68	42.83	-11.17	54	31.67	31.51	12.24	32.59	333	297	A	H
		5550	105.7	-	-	94.48	31.56	12.26	32.6	333	297	P	H
		5550	98.75	-	-	87.53	31.56	12.26	32.6	333	297	A	H
		5730.035	50.61	-17.69	68.3	39	31.91	12.3	32.6	333	297	P	H
		5449.12	49.78	-24.22	74	38.62	31.51	12.24	32.59	355	200	P	V
		5469.52	49.65	-18.65	68.3	38.48	31.52	12.24	32.59	355	200	P	V
		5459.92	41.36	-12.64	54	30.2	31.51	12.24	32.59	355	200	A	V
		5550	103.23	-	-	92.01	31.56	12.26	32.6	355	200	P	V
		5550	96.91	-	-	85.69	31.56	12.26	32.6	355	200	A	V
		5736.965	50.58	-17.72	68.3	38.91	31.97	12.3	32.6	355	200	P	V



802.11n HT40 CH 134 5670MHz		5455.7	51.05	-22.95	74	39.89	31.51	12.24	32.59	260	292	P	H
		5466.2	49.59	-18.71	68.3	38.42	31.52	12.24	32.59	260	292	P	H
		5459.9	41.51	-12.49	54	30.35	31.51	12.24	32.59	260	292	A	H
		5670	107.93	-	-	96.53	31.72	12.28	32.6	260	292	P	H
		5670	100.5	-	-	89.1	31.72	12.28	32.6	260	292	A	H
		5741.725	54.41	-13.89	68.3	42.74	31.97	12.3	32.6	260	292	P	H
		5450.8	48.98	-25.02	74	37.82	31.51	12.24	32.59	361	199	P	V
		5464.1	51.56	-16.74	68.3	40.39	31.52	12.24	32.59	361	199	P	V
		5459.9	40.26	-13.74	54	29.1	31.51	12.24	32.59	361	199	A	V
		5670	105.43	-	-	94.03	31.72	12.28	32.6	361	199	P	V
		5670	98.84	-	-	87.44	31.72	12.28	32.6	361	199	A	V
		5725.45	53.04	-15.26	68.3	41.43	31.91	12.3	32.6	361	199	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		11020	49.3	-24.7	74	43.59	40.61	16.49	51.39	170	230	P	H
HT40		16530	46.79	-21.51	68.3	42.26	39.08	18.21	52.76	160	300	P	H
CH 102		11020	50.88	-23.12	74	45.17	40.61	16.49	51.39	170	230	P	V
5510MHz		16530	46.97	-21.33	68.3	42.44	39.08	18.21	52.76	160	300	P	V
802.11n		11100	50.19	-23.81	74	44.3	40.71	16.5	51.32	150	200	P	H
HT40		16650	46.39	-21.91	68.3	41.54	39.58	18.25	52.98	180	350	P	H
CH 110		11100	50.34	-23.66	74	44.45	40.71	16.5	51.32	150	200	P	V
5550MHz		16650	47.68	-20.62	68.3	42.83	39.58	18.25	52.98	180	350	P	V
802.11n		11340	50.64	-23.36	74	44.25	41	16.52	51.13	200	360	P	H
HT40		17010	46.56	-21.74	68.3	40.68	41.1	18.37	53.59	200	360	P	H
CH 134		11340	49.49	-24.51	74	43.1	41	16.52	51.13	200	360	P	V
5670MHz		17010	49.44	-18.86	68.3	43.56	41.1	18.37	53.59	200	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band U-NII-2C - 5470~5725MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 106 5530MHz		5453.68	59.44	-14.56	74	48.28	31.51	12.24	32.59	109	295	P	H
		5467.36	60.77	-7.53	68.3	49.6	31.52	12.24	32.59	109	295	P	H
		5459.92	50.93	-3.07	54	39.77	31.51	12.24	32.59	109	295	A	H
		5530	102.57	-	-	91.37	31.54	12.26	32.6	109	295	P	H
		5530	95.31	-	-	84.11	31.54	12.26	32.6	109	295	A	H
		5746.73	52.09	-16.21	68.3	40.42	31.97	12.3	32.6	109	295	P	H
		5459.2	53.92	-20.08	74	42.76	31.51	12.24	32.59	326	196	P	V
		5470	56.73	-11.57	68.3	45.56	31.52	12.24	32.59	326	196	P	V
		5458.24	46.84	-7.16	54	35.68	31.51	12.24	32.59	326	196	A	V
		5530	96.23	-	-	85.03	31.54	12.26	32.6	326	196	P	V
		5530	89.71	-	-	78.51	31.54	12.26	32.6	326	196	A	V
		5755.55	49.84	-18.46	68.3	38.11	32.03	12.3	32.6	326	196	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band U-NII-2C 5470~5725MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		11060	50.44	-23.56	74	44.63	40.67	16.49	51.35	170	230	P	H
VHT80		16590	46.85	-21.45	68.3	42.19	39.29	18.23	52.86	160	300	P	H
CH 106		11060	49.35	-24.65	74	43.54	40.67	16.49	51.35	170	230	P	V
5530MHz		16590	47.08	-21.22	68.3	42.42	39.29	18.23	52.86	160	300	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 LF		30.97	25.58	-14.42	40	31.35	24.5	1.03	31.3	100	198	P	H
		152.22	20.08	-23.42	43.5	32.73	16.5	2.24	31.39	-	-	P	H
		205.57	24.19	-19.31	43.5	37.14	15.8	2.6	31.35	-	-	P	H
		252.13	29.67	-16.33	46	39.62	18.86	2.87	31.68	-	-	P	H
		625.58	27.51	-18.49	46	29.15	25.34	4.51	31.49	-	-	P	H
		865.17	30.24	-15.76	46	29.73	26.66	5.28	31.43	-	-	P	H
		30	22.38	-17.62	40	27.83	24.84	1.01	31.3	-	-	P	V
		99.84	24.37	-19.13	43.5	37.29	16.85	1.83	31.6	-	-	P	V
		297.72	24.6	-21.4	46	33.57	19.34	3.11	31.42	-	-	P	V
		443.22	26.56	-19.44	46	31.48	22.78	3.79	31.49	-	-	P	V
		718.7	29.7	-16.3	46	30.72	25.65	4.81	31.48	100	36	P	V
		960.23	32.28	-21.72	54	30.66	27.31	5.59	31.28	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	100	-	-	10Hz
802.11n HT20	100	-	-	10Hz
802.11n HT40	100	-	-	10Hz
802.11ac VHT80	100	-	-	10Hz

802.11a






802.11n HT20



802.11n HT40





802.11ac VHT80

