

NOKIA MOBILE PHONES 6000 Connection Drive Irving, TX 75039 972-894-5000 972-894-4988

August 07, 2003

Federal Communications Commission, Authorization & Evaluation Division, 7435 Oakland Mills Road Columbia, MD. 21046

Attention: Equipment Authorization Branch

We hereby certify that the transceiver FCC ID: GMLRH-42 complies with ANSI/IEEE C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

Compliance was determined by testing appropriate parameters according to standard.

NOKIA MOBILE PHONES

Mike Al-Mefleh Product Program Manager, Dallas

Certification Information (SAR)

THIS MODEL PHONE MEETS THE GOVERNMENT'S REQUIREMENTS FOR EXPOSURE TO RADIO WAVES.

Your wireless phone is a radio transmitter and receiver. It is designed and manufactured not to exceed the emission limits for exposure to radio frequency (RF) energy set by the Federal Communications Commission of the U.S. Government. These limits are part of comprehensive guidelines and establish permitted levels of RF energy for the general population. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons, regardless of age and health.

The exposure standard for wireless mobile phones employs a unit of measurement known as the Specific Absorption Rate, or SAR. The SAR limit set by the FCC is 1.6W/kg.* Tests for SAR are conducted using standard operating positions accepted by the FCC with the phone transmitting at its highest certified power level in all tested frequency bands. Although the SAR is determined at the highest certified power level, the actual SAR level of the phone while operating can be well below the maximum value. This is because the phone is designed to operate at multiple power levels so as to use only the power required to reach the network. In general, the closer you are to a wireless base station antenna, the lower the power output. Before a phone model is available for sale to the public, it must be tested and certified to the FCC that it does not exceed the limit established by the government-adopted requirement for safe exposure. The tests are performed in positions and locations (for example, at the ear and worn on the body) as required by the FCC for each model. The following values are the highest SAR values for this model phone as reported to the FCC.

When tested for use at the ear:

FCCID # GMLRH40 is 1.2 W/kg

FCCID # GMLRH42 is 1.19 W/Kg

When worn on the body as described in this user guide:

FCCID # GMLRH40 is 1.2 W/kg

FCCID # GMLRH42 is 1.21 W/kg

(Body-worn measurements differ among phone models, depending upon available accessories and FCC requirements).

While there may be differences between the SAR levels of various phones and at various positions, they all meet the government requirement.

The FCC has granted an Equipment Authorization for this model phone with all reported SAR levels evaluated as in compliance with the FCC RF exposure guidelines. SAR information on this model phone is on file with the FCC and can be found under the Display Grant section of http://www.fcc.gov/oet/fccid after searching on FCC ID GMLRH-40 and FCC ID GMLRH-42.

For body worn operation, this phone has been tested and meets the FCC RF exposure guidelines for use with an accessory that contains no metal and that positions the handset a minimum of 5/8 inch (1.5 cm) from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines. If you do not use a body-worn accessory and are not holding the phone at the ear, position the handset a minimum of 5/8 inch (1.5 cm) from your body when the phone is switched on.

*In the United States and Canada, the SAR limit for mobile phones used by the public is 1.6 watts/kilogram (W/kg) averaged over one gram of tissue. The standard incorporates a substantial margin of safety to give additional protection for the public and to account for any variations in measurements. SAR values may vary depending on national reporting requirements and the network band. For SAR information in other regions please look under product information at www.nokia.com/us.

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



SAR Compliance Test Report

Test report no.:	02-RF-0263	Date of report:	11 August, 2003			
Number of pages:	65	Contact person:	Nerina Walton			
		Responsible test engineer:	Nerina Walton			
Testing laboratory:	Test & Certification Center (TCC) Dallas Nokia Mobile Phones, Inc 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988	Client:	Nokia Mobile Phones, Inc 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988			
Tested devices:	GMLRH-42, Model 2220 BMC-3, BLC-2, HDE-2					
Testing has been carried out in accordance with:	IEEE Std 1528-200X, Draft CBD 1.0 – April Draft Recommended Practice for Determini (SAR) in the Human Body Due to Wireless (FCC Supplement C Edition, 01-01 Evaluating Compliance with FCC Guidelines Electromagnetic Fields	<u>4, 2002</u> ing the Peak Spatia Communications De s for Human Exposi	I-Average Specific Absorption Rate evices: Experimental Techniques ure to Radiofrequency			
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at Test & Certification Center (TCC) Dallas					
Test results:	The tested device complies with the requised the test. The test results and statements relate only reproduced except in full, without written	uirements in respe- to the items tested approval of the lab	ct of all parameters subject to d. The test report shall not be oratory.			
Date and signatures: For the contents:	11 Alan C. Ewing	August, 2003	Nerina Walton			
	TCC Line Manager 💚		Test Engineer			

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

CONTENTS

1.	QUA	LITY SYSTEM	3
2.	SUN	IMARY FOR SAR TEST REPORT	4
	2.1	MAXIMUM RESULTS FOUND DURING SAR EVALUATION	4
3.	DES	CRIPTION OF TESTED DEVICE	5
	3.1 3.2 3.3 3.4	Picture of Phone Description of the Antenna Battery Options Body Worn Operation	5 5 5
4.	TEST	CONDITIONS	6
	4.1 4.2 4.3	Ambient Conditions RF characteristics of the test site Test Signal, Frequencies, and Output Power	6 6 6
5.	DES	CRIPTION OF THE TEST EQUIPMENT	7
	5.1 5.2 5.3 5.4	System Accuracy Verification Tissue Simulants Phantoms Isotropic E-Field Probe ET3DV6	
6.	DES	CRIPTION OF THE TEST PROCEDURE	11
	6.1 6.2 6.3	Test Positions Scan Procedures SAR Averaging Methods	11 13 13
7.	MEA	SUREMENT UNCERTAINTY	14
	7.1	DESCRIPTION OF INDIVIDUAL MEASUREMENT UNCERTAINTY	14
8.	RESI	ULTS	16
	8.1 8.2	Head Configuration Body Worn Configuration	16 17

APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA APPENDIX B: VALIDATION TEST PRINTOUTS APPENDIX C: SAR DISTRIBUTION PRINTOUTS APPENDIX D: CALIBRATION CERTIFICATE (S) Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



1. QUALITY SYSTEM

The quality system in place for TCC-Dallas conforms to ISO/IEC 17025 and has been audited to the standard by A2LA (American Association of Laboratory Accreditation). Appendix D of this report contains the scope of accreditation for A2LA. TCC – Dallas has also been audited using the ISO 9000 Quality System, as part of Nokia Mobile Phones, Inc., by ABS (American Bureau of Shipping) Quality Evaluations Inc.

TCC-Dallas is a recognized laboratory with the Federal Communications Commission in filing applications for Certification under Parts 15 and 18, Registration Number 100060, and Industry Canada, Registration Number IC 661.

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

Test & Certification Center (TCC) - Dallas

2. SUMMARY FOR SAR TEST REPORT

Date of test	9 June – 16 June 2003
Contact person	Nerina Walton
Test plan referred to	-
FCC ID	GMLRH-42
Type, SN, HW and SW numbers of tested device	Type: RH-42
	ESN: 07201969691, HW: 1130f
	ESN: 07201969678, HW: 1132f
	SW: 3.02
Accessories used in testing	BMC-3 Battery, BLC-2 Battery, HDE-2 Headset
Notes	-
Document code	02-RF-0263
Responsible test engineer	N. Walton
Measurement performed by	E.Parish / J. Love

2.1 Maximum Results Found during SAR Evaluation

The equipment is deemed to fulfill the requirements if the measured values are less than or equal to the limit.

2.1.1 Head Configuration

Mode	Ch / <i>f</i> (MHz)	Power (dBm)	Position	Limit (mW/g)	Measured (mW/g)	Result
AMPS	991 / 848.97	24.1	Right Touch Position	1.6	1.19	PASSED
TDMA 800	991 / 848.97	26.8	Right Touch Position	1.6	0.73	PASSED

2.1.2 Body Worn Configuration

Mode	Ch / <i>f</i> (MHz)	Power (dBm)	Position	Limit (mW/g)	Measured (mW/g)	Result
AMPS	384 / 836.52	24.1	Flat - Back of Phone with 15mm Measurement Distance	1.6	1.21	PASSED
TDMA 800	384 / 836.52	26.9	Flat - Back of Phone with 15mm Measurement Distance	1.6	0.59	PASSED

2.1.3 Measurement Uncertainty

Combined Standard Uncertainty	± 14.5%
Expanded Standard Uncertainty (k=2)	± 29.1%

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

3. DESCRIPTION OF TESTED DEVICE

Device category	Portable device			
Exposure environment	Uncontrolled exposure			
Unit type	Prototype unit			
Case type	Fixed case			
Mode of Operation	AMPS	TDMA 800		
Maximum Device Rating	Power Class III	Power Class III		
Modulation Mode	Frequency Modulation Quadrature Phase Shift Keving			
Duty Cycle	1	1/3		
Transmitter Frequency Range (MHz)	824.04 - 848.97	824.04 - 848.97		

3.1 Picture of Phone

The tested device, GMLRH-42 is shown below: -



3.2 Description of the Antenna

Туре	Internal integrated antenna
Location	Inside the back cover, near the top of the device

3.3 Battery Options

There are three battery options available for the tested device, a BMC-3 and a BLC-2. The BMC-3 battery is a rechargeable Ni-MH and the BLC-2 battery is a rechargeable Li-ion.

3.4 Body Worn Operation

Body SAR was evaluated with a separation distance of 15mm and with the HDE-2 headset connected.

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

Test & Certification Center (TCC) - Dallas

4. TEST CONDITIONS

4.1 Ambient Conditions

Ambient temperature (°C)	22±2
Tissue simulating liquid temperature (°C)	20±2
Humidity (%)	43

4.2 RF characteristics of the test site

Tests were performed in a fully enclosed RF shielded environment.

4.3 Test Signal, Frequencies, and Output Power

The device was controlled by using a radio tester. Communication between the device and the tester was established by air link.

Measurements were performed on the lowest, middle and highest channels of the operating band.

The phone was set to maximum power level during all tests and at the beginning of each test the battery was fully charged.

The DASY3 system measures power drift during SAR testing by comparing e-field in the same location at the beginning and at the end of measurement. These records were used to monitor stability of power output.

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Test & Certification Center (TCC) - Dallas

5. DESCRIPTION OF THE TEST EQUIPMENT

The measurements were performed with an automated near-field scanning system, DASY3, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland.

Test Equipment	Model	NMP #	Serial Number	Due Date
DASY3, Data Acquisition	DAE V1	2292	389	07/03
E-field Probe	ET3DV6	2954	1504	07/03
Dipole Validation Kit	D900V2	3670	025	10/04
Dipole Validation Kit	D835V2	3453	455	07/04

E-field probe and dipole validation kit calibration records are presented in Appendix D.

Additional equipment (required for validation).

Test Equipment	Model	NMP #	Serial Number	Due Date
Signal Generator	HP 8648C	2667	3847U02985	11/03
Amplifier	AR 5S1G4	0188	25583	-
Coupler	AR DC7144	2057	25304	-
Power Meter	Boonton 4232A	0147	26001	07/03
Power Sensor	Boonton 51015	0163	31143	07/03
Power Sensor	Boonton 51015	0164	31144	07/03
Thermometer	Omega CL27	3392	T-228448	07/03
Network Analyzer	Agilent 8753ES	2605	US39174932	01/04
Dielectric Probe Kit	Agilent 85070C	3089	US99360172	-

The calibration interval on all items listed above can be obtained from the Engineering Services Group within NMP, Product Creation – Dallas. Where relevant, measuring equipment is subjected to in-service checks between testing. TCC – Dallas shall notify clients promptly, in writing, of identification of defective measuring equipment that casts doubt on the validity of results given in this report. Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



5.1 System Accuracy Verification

The manufacturer calibrates the probes annually. Dielectric parameters of the simulating liquids are measured using an Agilent 85070C dielectric probe kit and an HP 8720D network analyzer.

SAR measurements of the tested device were performed within 24 hours of system accuracy verification, which was done using the dipole validation kit.

The dipole antenna's, which are manufactured by Schmid & Partner Engineering AG, are matched to be used near a flat phantom filled with tissue simulating solution. Length of the 835 MHz dipole is 161mm with an overall height of 330mm; length of the 900MHz dipole is 149mm with an overall height of 300mm. A specific distance holder is used in the positioning to ensure correct spacing between the phantom and the dipole.

A power level of 250 mW was supplied to the dipole antenna placed under the flat section of the SAM phantom. Validation results are in the table below and a print out of the validation tests are presented in Appendix B. All the measured parameters were within specification.

5.1.1 Head Tissue

	f (MHz)	Description (Date Measured)	SAR (W/kg), 1g	Dielectric I	Temp	
Tissue				ε _r	σ (S/m)	(°C)
	900	09-June-03	10.8	40.1	0.96	20.1
		10-June-03	11.5	40.2	0.96	20.6
Head		11-June-03	10.6	39.8	0.95	20.5
пеай		12-June-03	11.6	40.0	0.96	20.3
		13-June-03	10.8	40.3	0.95	21.0
		Reference Result	11.4	41.5	0.97	N/A

5.1.2 Muscle Tissue

	f	Description	SAR	Dielectric	Parameters	ers Temp	
Tissue	sue (MHz) (Date Measured)		(W/kg), 1g	٤r	σ (S/m)	(°C)	
		13-June-03	9.9	56.1	0.96	21.5	
Muscle	835	16-June-03	10.2	55.4	0.96	21.3	
		Reference Result	10.1	55.3	0.95	N/A	

FCC ID: GMLRH-42Test & Certification Center (TCC) - DallasTest Report #: 02-RF-0263



5.2 Tissue Simulants

All dielectric parameters of tissue simulants were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the ear reference point of the phantom was $15 \text{ cm} \pm 5 \text{ mm}$ during all tests. Volume for each tissue simulant was 27 litres.

5.2.1 Head Tissue Simulant

The composition of the brain tissue simulating liquid for 835 MHz is: -51.07%De-Ionized Water47.31%Sugar

1.15%	Salt
0.23%	HEC
0.24%	Bactericide

f	Description	Dielectric P	Temp (°C)	
(MHz)	(Date Measured)	ε _r	σ (S/m)	
	09-June-03	40.9	0.90	20.1
836.52	10-June-03	40.9	0.90	20.6
	11-June-03	40.6	0.90	20.5
	12-June-03	40.9	0.90	20.3
	13-June-03	41.1	0.90	21.0
	Recommended Values	41.5	0.90	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

5.2.2 Muscle Tissue Simulant

The composition of the muscle tissue simulating liquid for 835 MHz is: -

65.45%	De-Ionized Water
34.31%	Sugar
0.62%	Salt
0.10%	Bactericide

f	Description	Dielectric P	Temp (°C)	
(MHz)	(Date Measured)	ε _r	σ (S/m)	
	13-June-03	56.0	0.97	21.5
836.52	16-June-03	55.3	0.96	21.3
	Recommended Values	55.2	0.97	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



5.3 Phantoms

"SAM v4.0" phantom", manufactured by SPEAG, was used during the measurement. It has a fiberglass shell integrated into a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. Reference markings



on the phantom allow the complete set-up of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

The thickness of phantom shell is 2 mm except for the ear, where an integrated ear spacer provides a 6 mm spacing from the tissue boundary. Manufacturer reports tolerance in shell thickness to be ± 0.1 mm.

5.4 Isotropic E-Field Probe ET3DV6

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycol ether)
Calibration	Calibration certificate in Appendix D
Frequency Optical Surface Detection	10 MHz to 3 GHz (dosimetry); Linearity: \pm 0.2 dB (30 MHz to 3 GHz) \pm 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μW/g to > 100 mW/g; Linearity: <u>+</u> 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Test & Certification Center (TCC) - Dallas

6. DESCRIPTION OF THE TEST PROCEDURE

6.1 Test Positions

The device was placed into a holder using a special positioning tool, which aligns the bottom of the device with the holder and ensures that holder contacts only to the sides of the device.

After positioning is done, the tool is removed. This method provides standard positioning and separation, and also ensures free space for antenna.

Device holder was provided by SPEAG together with the DASY3.



6.1.1 Against Phantom Head

Measurements were made on both the "left hand" and "right hand" side of the phantom.

The device was positioned against phantom according to OET Bulletin 65 (97-01) Supplement C (01-01). Definitions of terms used in aligning the device to a head phantom are available in IEEE Std 1528-200X "Draft Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

6.1.1.1 Initial Ear Position

The device was initially positioned with the earpiece region pressed against the ear spacer of a head phantom parallel to the "Neck-Front" line defined along the base of the ear spacer that contains the "ear reference point". The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane".

6.1.1.2 Touch Position

"Initial ear position" alignments are maintained and the device is brought toward the mouth of the head phantom by pivoting along the "Neck-Front" line until any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom or when any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



The following picture shows the tested device in the right touch position:



6.1.1.3 Tilt Position

In the "Touch Position", if the earpiece of the device is not in full contact with the phantom's ear spacer and the peak SAR location for the "touch position" is located at the ear spacer region or corresponds to the earpiece region of the handset, the device is returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer. Otherwise, the device is moved away from the cheek perpendicular to the line passes through both "ear reference points" for approximate 2–3 cm. While it is in this position, the device is tilted away from the mouth with respect to the "test device reference point" by 15°. After the tilt, it is then moved back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process is repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously.

The following picture shows the tested device in the right tilt position:



FCC ID: GMLRH-42 Test Report #: 02-RF-0263



6.1.2 Body Worn Configuration

Test & Certification Center (TCC) - Dallas

Body SAR measurements were performed with the antenna facing towards the flat part of the phantom with a separation distance of 15mm and with the HDE-2 headset connected.

I5mm Spacer HDE-2 Headset

The following picture shows the tested device in the body test position: -

Note: the 15mm spacer was removed before the SAR measurement.

6.2 Scan Procedures

First coarse scans are used for quick determination of the field distribution. Next a cube scan, 5x5x7 points; spacing between each point 8x8x5 mm, is performed around the highest E-field value to determine the averaged SAR-distribution over 1g.

6.3 SAR Averaging Methods

The maximum SAR value is averaged over its volume using interpolation and extrapolation.

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot" -condition [W. Gander, Computermathematik, p. 141-150] (x, y and z -directions) [Numerical Recipes in C, Second Edition, p 123].

The extrapolation is based on least square algorithm [W. Gander, Computermathematik, p.168–180]. Through the points in the first 30 mm in all z-axis, polynomials of order four are calculated. This polynomial is then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1mm from one another.

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

Test & Certification Center (TCC) - Dallas

7. MEASUREMENT UNCERTAINTY

7.1 Description of Individual Measurement Uncertainty

7.1.1 Assessment Uncertainty

а	b	с	d	e = f(d,k)	F	h = c x f/e	k
Uncertainty	Section	Tol.	Prob.	D .	C _i	u i	Vi
Component	in P1528.	(%)	Dist.	DIV.		(%)	
Measurement System							
Probe Calibration	E2.1	±4.8	Ν	1	1	±4.8	×
Axial Isotropy	E2.2	±4.7	R	√3	(1-cp) ^{1/2}	±1.9	×
Hemispherical Isotropy	E2.2	±9.6	R	√3	$\sqrt{c_p}$	±3.9	×
Boundary Effect	E2.3	±8.3	R	√3	1	±4.8	×
Linearity	E2.4	±4.7	R	√3	1	±2.7	×
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	×
Readout Electronics	E2.6	±1.0	Ν	1	1	±1.0	×
Response Time	E2.7	±0.8	R	√3	1	±0.5	×
Integration Time	E2.8	±2.6	R	√3	1	±1.5	×
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	×
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	×
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	×
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	×
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5.2	±3.9	R	√3	1	±2.3	×
Test sample Related							
Test Sample Positioning	E4.2.1	±6.0	Ν	1	1	±6.0	11
Device Holder Uncertainty	E4.1.1	±5.0	Ν	1	1	±5.0	7
Output Power Variation – SAR drift measurement	6.6.3	±10.0	R	√3	1	±5.8	x
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	×
Liquid Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	×
Liquid Conductivity - measurement uncertainty	E3.3	±5.5	Ν	1	0.64	±3.5	5

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

а	Ь	с	d	e = f(d,k)	F	h = c x f/e	k
Uncertainty Component	Section in P1528.	Tol. (%)	Prob. Dist.	Div.	c _i	u _i (%)	Vi
Measurement System							
Liquid Permittivity Target tolerance	E3.2	±5.0	R	√3	0.6	±1.7	×
Liquid Permittivity - measurement uncertainty	E3.3	±2.9	Ν	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±14.5	208
Expanded Uncertainty (95% CONFIDENCE INTERVAL)						±29.1	

Test & Certification Center (TCC) - Dallas

Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



8. RESULTS

Corresponding SAR distribution print outs of maximum results in every operating mode and position are shown in Appendix C; z-axis plots of the maximum measurement results in head and body worn configurations are also included. The SAR distributions are substantially similar or equivalent to the plots submitted, regardless of used channel in each mode and position unless otherwise presented.

Note: the results recorded in the following tables for head and body are the highest values measured from the two HWID's that were tested.

8.1 Head Configuration

Mode	Channal	Dowor	SAR, averaged over 1g (mW/g)					
	f(MH ₂)	(dBm)	Left-hand		Right-hand			
	7 (10112)	(ubiii)	Touch	Tilt	Touch	Tilt		
	991 / 824.04	24.1	1.16	0.88	1.17	0.87		
AMPS	384 / 836.52	24.1	0.93	0.71	0.99	0.68		
	799 / 848.97	23.9	0.98	0.80	1.01	0.75		

BMC-3 Battery

	Channel/	Dower	SAR, averaged over 1g (mW/g)				
Mode		(dBm)	Left-hand		Right-hand		
	7 (10112)		Touch	Tilt	Touch	Tilt	
TDMA 800	991 / 824.04	26.8	0.68	0.51	0.69	0.50	
	384 / 836.52	26.9	0.58	0.43	0.63	0.41	
	799 / 848.97	26.5	0.64	0.50	0.63	0.45	

Battery Check with BLC-2

	Channel	Dower	SAR, averaged over 1g (mW/g)				
Mode		(dBm)	Left-hand		Right-hand		
	7 (101112)	(ubm)	Touch	Tilt	Touch	Tilt	
AMPS	991 / 824.04	24.1	1.16	0.88	1.19	0.82	
	384 / 836.52	24.1	0.90	-	0.96	-	
	799 / 848.97	23.9	1.06	-	1.03	-	

	Channel	Dower	SAR, averaged over 1g (mW/g)				
Mode	f(MHz)	(dBm)	Left-hand		Right-hand		
			Touch	Tilt	Touch	Tilt	
TDMA 800	991 / 824.04	26.8	0.68	0.52	0.71	0.50	

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



8.2 Body Worn Configuration

Test & Certification Center (TCC) - Dallas

Body SAR measurements were performed with the HDE-2 headset connected.

Mode	Channel/	Power	SAR, averaged over 1g (mW/g)
woue	<i>f</i> (MHz)	(dBm)	HDE-2
	991 / 824.04	24.1	1.01
AMPS	384 / 836.52	24.1	1.21
	799 / 848.97	23.9	0.72

Mode	Channel/ Power		SAR, averaged over 1g (mW/g)	
WOUL	<i>f</i> (MHz)	(dBm)	HDE-2	
	991 / 824.04	26.8	0.51	
TDMA 800	384 / 836.52	26.9	0.59	
	799 / 848.97	26.5	0.40	

Battery Check with BLC-2

Mode	Channel/	Power	SAR, averaged over 1g (mW/g)	
Wouc	f (MHz)	(dBm)	HDE-2	
	991 / 824.04	24.1	0.99	
	384 / 836.52	24.1	0.76	

Mode	Channel/	Power	SAR, averaged over 1g (mW/g)
WOUL	<i>f</i> (MHz)	(dBm)	HDE-2
TDMA 800	384 / 836.52	26.9	0.54

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Test & Certification Center (TCC) - Dallas

APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA

TCC-Dallas is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below:



Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-42 Test Report #: 02-RF-0263



Accredited Laboratory Certificate Number: 1819-01

Amorican A	esociation for Laboratory Accreditation	Tests	Test Method
American A	ssociation for Laboratory Accreditation	Winders	A MALANNING
SCOPE OF /	ACCREDITATION TO ISO/IEC 17025-1999	GSM (850/900/1800/1900 MHz)	3GPP TS 51.010-1, -2, -3 3GPP TS 11.10-4
TEST &	NOKIA MOBILE PHONES CERTIFICATION CENTER DALLAS 6021 Comection Drive Tring: TX 75039 an Iving: Phone: 752.994.4744	TDMA	PTCRB NAPRD.03 CTIA TDMA/AMPS Test Plan (excluding Sections 7.3.3 & 7.3.4) TIA/EIA-136-270
	ELECTRICAL.		
Valid to: November 30, 2003	Certificate Number: 1819-01		
In recognition of the successful comple laboratory to perform the following Els and tests on wireless communications of	rtion of the A2LA evaluation process, accreditation is granted to this extromagnetic Compatibility (EMC), Specific Absorption Rate (SAR), devices:		
Tests	Test Method		
Emissions			
Conducted and Radiated	CFR 47 Part 2, 15, 22, 24 CISPR 22; EX 5502 ICES 500; RSS-128, 112 and 133 3GPP TS 51:016-1 Section 12.2 ETTS EFN 301 489-1; EN 301 489-7 (using ANSI C63.4 and RSS-212)		
Specific Absorption Rate	IEEE 1528 EN 30360; EX 50361 CFR 47 Parts 2 and 24 OET Bulletin 65 and Supplement C RSS-102		
Immunity			
Vehicular Immunity Electrostatic Discharge (ESD) RF Radiated Electrical Fast Transient/Burst Surge Conducted Voltage Dips, Short Interruptions and Voltage Variations	ISO 7637-1; ETSI EN 301 489-1; EN 301 489-7 EN 61000-4-2; ETSI EN 301 489-1; EN 301 489-7 EN 61000-4-2; ETSI EN 301 489-1; EN 301 489-7 EN 61000-4; ETSI EN 301 489-1; EN 301 489-7 EN 61000-4-6; ETSI EN 301 489-1; EN 301 489-7 EN 61000-4-1; ETSI EN 301 489-1; EN 301 489-7		
	0, 0		

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined to be in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, such data would not be covered by this laboratory's A2LA accreditation

APPENDIX B: VALIDATION TEST PRINTOUTS

SAM 1 (Cellular - Brain Tissue) Frequency: 900 MHz; Crest factor: 1.0 Validation 900MHz - Brain Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 40.1 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 4.34 mW/g ± 0.01 dB, SAR (1g): 2.69 mW/g ± 0.01 dB, SAR (10g): 1.69 mW/g ± 0.02 dB, (Worst-case extrapolation) Penetration depth: 11.3 (10.2, 12.9) [mm] Powerdrift: -0.16 dB Liquid Temperature (°C): 20.1



SAM 1 (Cellular - Brain Tissue) Frequency: 900 MHz; Crest factor: 1.0 Validation 900MHz - Brain Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 40.2 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 4.64 mW/g ± 0.01 dB, SAR (1g): 2.87 mW/g ± 0.01 dB, SAR (10g): 1.80 mW/g ± 0.01 dB, (Worst-case extrapolation) Penetration depth: 11.3 (10.2, 12.9) [mm] Powerdrift: -0.22 dB Liquid Temperature (°C): 20.6



SAM 1 (Cellular - Brain Tissue) Frequency: 900 MHz; Crest factor: 1.0 Validation 900MHz - Brain Tissue: $\sigma = 0.95$ mho/m $\varepsilon_r = 39.8 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 4.25 mW/g ± 0.01 dB, SAR (1g): 2.64 mW/g ± 0.00 dB, SAR (10g): 1.66 mW/g ± 0.01 dB, (Worst-case extrapolation) Penetration depth: 11.4 (10.3, 12.8) [mm] Powerdrift: -0.33 dB Liquid Temperature (°C): 20.5



SAM 1 (Cellular - Brain Tissue) Frequency: 900 MHz; Crest factor: 1.0 Validation 900MHz - Brain Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 40.0 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 4.67 mW/g ± 0.02 dB, SAR (1g): 2.90 mW/g ± 0.01 dB, SAR (10g): 1.82 mW/g ± 0.01 dB, (Worst-case extrapolation) Penetration depth: 11.3 (10.2, 12.8) [mm] Powerdrift: -0.27 dB Liquid Temperature (°C): 20.3



SAM 1 (Cellular - Brain Tissue) Frequency: 900 MHz; Crest factor: 1.0 Validation 900MHz - Brain Tissue: $\sigma = 0.95$ mho/m $\varepsilon_r = 40.3 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 4.36 mW/g ± 0.01 dB, SAR (1g): 2.71 mW/g ± 0.01 dB, SAR (10g): 1.70 mW/g ± 0.01 dB, (Worst-case extrapolation) Penetration depth: 11.4 (10.3, 12.9) [mm] Powerdrift: -0.18 dB Liquid Temperature (°C): 21.0



Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue) Frequency: 835 MHz; Crest factor: 1.0 Validation 835MHz - Muscle Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 56.1 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 3.86 mW/g ± 0.01 dB, SAR (1g): 2.48 mW/g ± 0.00 dB, SAR (10g): 1.60 mW/g ± 0.02 dB, (Worst-case extrapolation) Penetration depth: 12.6 (11.2, 14.4) [mm] Powerdrift: -0.09 dB Liquid Temperature (°C): 21.5



Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue) Frequency: 835 MHz; Crest factor: 1.0 Validation 835MHz - Muscle Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 55.4 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cubes (2): Peak: 3.97 mW/g \pm 0.01 dB, SAR (1g): 2.54 mW/g \pm 0.01 dB, SAR (10g): 1.65 mW/g \pm 0.01 dB, (Worst-case extrapolation) Penetration depth: 12.6 (11.2, 14.4) [mm] Powerdrift: -0.30 dB Liquid Temperature (°C): 21.3



APPENDIX C: SAR DISTRIBUTION PRINTOUTS

GMLRH-42, AMPS, Channel 991, Left Touch Position with BMC-3 Battery

SAM 1 (Cellular - Brain Tissue) Phantom Frequency: 824 MHz; Crest factor: 1.0 Cellular Band - Brain Tissue: $\sigma = 0.90$ mho/m $\varepsilon_r = 40.6 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 1.16 mW/g, SAR (10g): 0.797 mW/g, (Worst-case extrapolation) Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0 Powerdrift: 0.06 dB Liquid Temperature (°C): 20.5



GMLRH-42, AMPS, Channel 991, Left Tilt Position with BLC-2 (1000 mAh) Battery

SAM 1 (Cellular - Brain Tissue) Phantom Frequency: 824 MHz; Crest factor: 1.0 Cellular Band - Brain Tissue: $\sigma = 0.90$ mho/m $\varepsilon_r = 40.6 \ \rho = 1.00$ g/cm³ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 0.880 mW/g, SAR (10g): 0.586 mW/g, (Worst-case extrapolation) Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0 Powerdrift: 0.02 dB Liquid Temperature (°C): 20.5



GMLRH-42, AMPS, Channel 991, Right Touch Position with BLC-2 (1000 mAh) Battery

SAM 1 (Cellular - Brain Tissue) Phantom Frequency: 824 MHz; Crest factor: 1.0 Cellular Band - Brain Tissue: $\sigma = 0.90$ mho/m $\varepsilon_r = 40.6 \ \rho = 1.00$ g/cm³ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 1.19 mW/g, SAR (10g): 0.847 mW/g, (Worst-case extrapolation) Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0 Powerdrift: 0.07 dB Liquid Temperature (°C): 20.5



06/12/03

GMLRH-42, AMPS, Channel 991, Right Tilt Position with BMC-3 Battery

SAM 1 (Cellular - Brain Tissue) Phantom Frequency: 824 MHz; Crest factor: 1.0 Cellular Band - Brain Tissue: $\sigma = 0.90$ mho/m $\varepsilon_r = 40.9 \ \rho = 1.00$ g/cm³ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 0.870 mW/g, SAR (10g): 0.599 mW/g, (Worst-case extrapolation) Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0 Powerdrift: 0.18 dB Liquid Temperature (°C): 20.3



GMLRH-42, AMPS, Channel 384, Flat Position - Back of Phone with 15mm Spacer, BMC-3 Battery and HDE-2 Headset

SAM 2 (Cellular - Muscle Tissue) Phantom Frequency: 837 MHz; Crest factor: 1.0 Cellular Band - Muscle Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 55.3 \ \rho = 1.00$ g/cm³ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 1.21 mW/g, SAR (10g): 0.836 mW/g, (Worst-case extrapolation) Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0 Powerdrift: 0.05 dB Liquid Temperature (°C): 21.3



SAR_{Tot} [mW/g]

GMLRH-42, AMPS, Channel 991, Right Touch Position with BLC-2 (1000 mAh) Battery

SAM 1 (Cellular - Brain Tissue) Phantom Frequency: 824 MHz; Crest factor: 1.0 Cellular Band - Brain Tissue: $\sigma = 0.90$ mho/m $\varepsilon_r = 40.6 \ \rho = 1.00 \ g/cm^3$ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 1.19 mW/g, SAR (10g): 0.847 mW/g, (Worst-case extrapolation) Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0 Liquid Temperature (°C): 20.5



06/16/03

GMLRH-42, AMPS, Channel 384, Flat Position - Back of Phone with 15mm Spacer, BMC-3 Battery and HDE-2 Headset

SAM 2 (Cellular - Muscle Tissue) Phantom Frequency: 837 MHz; Crest factor: 1.0 Cellular Band - Muscle Tissue: $\sigma = 0.96$ mho/m $\varepsilon_r = 55.3 \ \rho = 1.00$ g/cm³ Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50) Cube 5x5x7: SAR (1g): 1.21 mW/g, SAR (10g): 0.836 mW/g, (Worst-case extrapolation) Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0 Liquid Temperature (°C): 21.3



APPENDIX D: CALIBRATION CERTIFICATE (S)

APPENDIX D: CALIBRATION CERTIFICATE (S)

Schmid & Partner **Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Calibration Certificate

Dosimetric E-Field Probe

Туре:	ET3DV6
Serial Number:	1504
Place of Calibration:	Zurich
Date of Calibration:	July 26, 2002
Calibration Interval:	12 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:





Approved by:

Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Telephone +41 1 245 97 00, Fax +41 1 245 97 79

Probe ET3DV6

SN:1504

Manufactured: Last calibration: Recalibrated: October 24, 1999 January 10, 2002 July 26, 2002

Calibrated for System DASY3

DASY3 - Parameters of Probe: ET3DV6 SN:1504

Sensitivity in Free Space			Diode Compression	
	NormX NormY NormZ	2.02 μV/(V/m) ² 1.78 μV/(V/m) ² 1.73 μV/(V/m) ²	DCP X DCP Y DCP Z	95 mV 95 mV 95 mV
Sensi	tivity in Tissue :	Simulating Liquid		
Head Head	835 MHz 900 MHz	ε _r = 41.5 ± 5% ε _r = 41.5 ± 5%	$\sigma = 0.90 \pm 5\%$ mh $\sigma = 0.97 \pm 5\%$ mh	o/m o/m
	ConvF X	6.5 ± 9.5% (k=2)	Boundary effe	ct:
	ConvF Y	6.5 ± 9.5% (k=2)	Alpha	0.39
	ConvF Z	6.5 ± 9.5% (k=2)	Depth	2.42
Head Head	1880 MHz 1800 MHz	ε _r = 40.0 ± 5% ε _r = 40.0 ± 5%	σ = 1.40 ± 5% mh σ = 1.40 ± 5% mh	o/m o/m
	ConvF X	5.4 ± 9.5% (k=2)	Boundary effe	ct:
	ConvF Y	5.4 ± 9.5% (k=2)	Alpha	0.53
	ConvF Z	5.4 ± 9.5% (k=2)	Depth	2.44

Boundary Effect

Head	835	5 MHz	Typical SAR gradient: 5	% per mm	
	Probe Tip to	o Bounda	ary	1 mm	2 mm
	SAR _{be} [%]	Without	t Correction Algorithm	9.6	5.3
	SAR _{be} [%]	With Co	orrection Algorithm	0.3	0.5
Head	1880) MHz	Typical SAR gradient: 10) % per mm	
	Probe Tip to	o Bounda	ary	1 mm	2 mm
	SAR _{be} [%]	Without	t Correction Algorithm	13.0	8.5
	SAR _{be} [%]	With Co	prrection Algorithm	0.2	0.2
Senso	r Offset				

Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	1.4 ± 0.2	mm



Receiving Pattern (ϕ), θ = 0°



Isotropy Error (ϕ), $\theta = 0^{\circ}$



Frequency Response of E-Field

(TEM-Cell:ifi110, Waveguide R22)









Conversion Factor Assessment

Head	835 MHz	ε _r = 41.5 ± 5%	σ = 0.90 ± 5% mł	ıo/m
Head	900 MHz	ε _r = 41.5 ± 5%	σ = 0.97 ± 5% mł	10/m
	ConvF X	6.5 ± 9.5% (k=2)	Boundary effe	ect:
	ConvF Y	6.5 ± 9.5% (k=2)	Alpha	0.39
	ConvF Z	6.5 ± 9.5% (k=2)	Depth	2.42

Head	1880 MHz	$\varepsilon_r = 40.0 \pm 5\%$	σ = 1.40 ± 5% mho/m
Head	1800 MHz	ε _r = 40.0 ± 5%	σ = 1.40 ± 5% mho/m
	ConvF X	5.4 ± 9.5% (k=2)	Boundary effect:
	ConvF Y	5.4 ± 9.5% (k=2)	Alpha 0.53
	ConvF Z	5.4 ± 9.5% (k=2)	Depth 2.44



Conversion Factor Assessment

Body	835 MHz	$\varepsilon_r = 55.2 \pm 5\%$	σ = 0.97 ± 5% mho/m	
Body	900 MHz	ε _r = 55.0 ± 5%	σ = 1.05 ± 5% mho/m	
	ConvF X	6.5 ± 9.5% (k=2)	Boundary effect:	
	ConvF Y	6.5 ± 9.5% (k=2)	Alpha 0.42	
	ConvF Z	6.5 ± 9.5% (k=2)	Depth 2.38	

Body	1880 MHz		ε _r = 53.3 ± 5%	σ = 1.52 ± 5% mho/r	n
Body	1800 MHz		$\varepsilon_r = 53.3 \pm 5\%$	σ = <mark>1.52 ± 5% mho</mark> /r	n
	ConvF X	5.0	± 9.5% (k=2)	Boundary effect:	
	ConvF Y	5.0	± 9.5% (k=2)	Alpha	0.74
	ConvF Z	5.0	± 9.5% (k=2)	Depth	2.06

Deviation from Isotropy in HSL Error (θ, ϕ) , f = 900 MHz





Schmid & Partner **Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Calibration Certificate

835 MHz System Validation Dipole

Type: D835V2 Serial Number: 455 Place of Calibration: Zurich Date of Calibration: July 16, 2002 Calibration Interval: 24 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:





Approved by:

Schmid & Partner **Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

DASY

Dipole Validation Kit

Type: D835V2

Serial: 455

Manufactured: January 31, 2002 Calibrated:

July 16, 2002

1. Measurement Conditions

The measurements were performed in the flat section of the new generic twin phantom filled with head simulating solution of the following electrical parameters at 835 MHz:

Relative Dielectricity	42.5	± 5%
Conductivity	0.90 mho/m	± 5%

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, Conversion factor 6.6 at 835 MHz) was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feedpoint was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was <u>15mm</u> from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging. The dipole input power (forward power) was $250\text{mW} \pm 3\%$. The results are normalized to 1W input power.

2.1. SAR Measurement with DASY3 System

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the <u>worst-case extrapolation</u> are:

averaged over 1 cm^3 (1 g) of tissue:9.84 mW/gaveraged over 10 cm^3 (10 g) of tissue:6.32 mW/g

2.2 SAR Measurement with DASY4 System

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the <u>advanced extrapolation</u> are:

averaged over 1 cm^3 (1 g) of tissue: 9.20 mW/g averaged over 10 cm^3 (10 g) of tissue: 6.08 mW/g

3. Dipole Impedance and Return Loss

The impedance was measured at the SMA-connector with a network analyzer and numerically transformed to the dipole feedpoint. The transformation parameters from the SMA-connector to the dipole feedpoint are:

Electrical delay:	1.375 ns	(one direction)
Transmission factor:	0.992	(voltage transmission, one direction)

The dipole was positioned at the flat phantom sections according to section 1 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 835 MHz:	$Re{Z} = 49.6 Ω$
	$\operatorname{Im} \{Z\} = -1.8 \Omega$
Return Loss at 835 MHz	-34.7 dB

4. Measurement Conditions

The measurements were performed in the flat section of the new generic twin phantom filled with body simulating solution of the following electrical parameters at 835 MHz:

Relative Dielectricity	55.3	± 5%
Conductivity	0.95 mho/m	± 5%

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, Conversion factor 6.2 at 835 MHz) was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feedpoint was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was <u>15mm</u> from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was $250\text{mW} \pm 3\%$. The results are normalized to 1W input power.

5.1. SAR Measurement with DASY3 System

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the <u>worst-case extrapolation</u> are:

averaged over 1 cm^3 (1 g) of tissue:10.1 mW/gaveraged over 10 cm^3 (10 g) of tissue:6.60 mW/g

5.2 SAR Measurement with DASY4 System

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the <u>advanced extrapolation</u> are:

averaged over 1 cm^3 (1 g) of tissue:	9.24 mW/g
averaged over 10 cm^3 (10 g) of tissue:	6.20 mW/g

6. Dipole Impedance and Return Loss

The dipole was positioned at the flat phantom sections according to section 4 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 835 MHz:	Re{Z} = 45.6 Ω
	Im $\{Z\} = -4.3 \Omega$
Return Loss at 835 MHz	-23.7 dB

4. Handling

Do not apply excessive force to the dipole arms, because they might bend. Bending of the dipole arms stresses the soldered connections near the feedpoint leading to a damage of the dipole.

5. Design

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

6. Power Test

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

07/15/02

Validation Dipole D835V2 SN455, d = 15 mm Frequency: 835 MHz; Antenna Input Power: 250 [mW]

Cubes (2): Peak: 3.84 mW/g \pm 0.02 dB, SAR (1g): 2.46 mW/g \pm 0.02 dB, SAR (10g): 1.58 mW/g \pm 0.01 dB, (Worst-case extrapolation) Penetration depth: 12.1 (11.1, 13.5) [mm] Powerdrift: 0.00 dB Probe: ET3DV6 - SN1507; ConvF(6.60, 6.60) at 835 MHz; IEEE1528 835 MHz; σ = 0.90 mho/m ε_r = 42.5 ρ = 1.00 g/cm³ Frequency: 835 MHz; Antenna Input Power: 250 [mW] SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0





07/15/02

Validation Dipole D835V2 SN455, d = 15 mm

Cubes (2): Peak: 3.40 mW/g \pm 0.02 dB, SAR (1g): 2.30 mW/g \pm 0.02 dB, SAR (10g): 1.52 mW/g \pm 0.01 dB, (Advanced extrapolation) Penetration depth: 13.1 (12.8, 13.6) [mm] Probe: ET3DV6 - SN1507; ConvF(6.60,6.60) at 835 MHz; IEEE1528 835 MHz: $\sigma = 0.90$ mho/m $s_r = 42.5$ $\rho = 1.00$ g/cm³ Frequency: 835 MHz, Antenna Input Power: 250 [mW] SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0









Validation Dipole D835V2 SN455, d = 15 mm

Cubes (2): Peak: 3.91 mW/g \pm 0.01 dB, SAR (1g): 2.53 mW/g \pm 0.01 dB, SAR (10g): 1.65 mW/g \pm 0.01 dB, (Worst-case extrapolation) Penetration depth: 12.7 (11.6, 14.2) [mm] Powerdrift: 0.01 dB Probe: ET3DV6 - SN1507; ConvF(6.20,6.20) at 835 MHz; IEEE1528 835 MHz: σ = 0.95 mho/m ε, = 55.3 ρ = 1.00 g/cm³ Frequency: 835 MHz; Antenna Input Power: 250 [mW] SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0





Schmid & Partner Engineering, Zurich, Switzerland

07/16/02

Validation Dipole D835V2 SN455, d = 15 mm

Cubes (2): Peak: 3.30 mW/g \pm 0.01 dB, SAR (1g): 2.31 mW/g \pm 0.01 dB, SAR (10g): 1.55 mW/g \pm 0.01 dB, (Advanced extrapolation) Penetration depth: 14.3 (14.2, 14.5) [mm] Powerdrift: 0.01 dB SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0Probe: ET3DV6 - SN1507; ConvF(6.20,6.20) at 835 MHz; IEEE1528 835 MHz: $\sigma = 0.95$ mho/m $\varepsilon_r = 55.3$ $\rho = 1.00$ g/cm³ Frequency: 835 MHz; Antenna Input Power: 250 [mW]









STOP 1 035.000 000 MHz

Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Calibration Certificate

900 MHz System Validation Dipole

Туре:	D900V2
Serial Number:	025
Place of Calibration:	Zurich
Date of Calibration:	October 23, 2001
Calibration Interval:	24 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

flear the

Approved by:

Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

DASY

Dipole Validation Kit

Type: D900V2

Serial: 025

Manufactured: Calibrated: November 12, 1997 October 23, 2001

<u>1. Measurement Conditions</u>

The measurements were performed in the flat section of the new generic twin phantom filled with head simulating solution of the following electrical parameters at 900 MHz:

Relative Dielectricity	41.5	±5%
Conductivity	0.97 mho/m	± 5%

The DASY3 System (Software version 3.1c) with a dosimetric E-field probe ET3DV6 (SN:1507, Conversion factor 6.27 at 900 MHz) was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feedpoint was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was <u>15mm</u> from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 15mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was $250 \text{mW} \pm 3$ %. The results are normalized to 1W input power.

2. SAR Measurement

Standard SAR-measurements were performed with the phantom according to the measurement conditions described in section 1. The results have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values are:

averaged over 1 cm^3 (1 g) of tissue: 11.36 mW/g averaged over 10 cm^3 (10 g) of tissue: 7.20 mW/g

Note: If the liquid parameters for validation are slightly different from the ones used for initial calibration, the SAR-values will be different as well.

3. Dipole Impedance and Return Loss

The impedance was measured at the SMA-connector with a network analyzer and numerically transformed to the dipole feedpoint. The transformation parameters from the SMA-connector to the dipole feedpoint are:

Electrical delay:	1.401 ns	(one direction)
Transmission factor:	0.993	(voltage transmission, one direction)

The dipole was positioned at the flat phantom sections according to section 1 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 900 MHz:	$\operatorname{Re}\{Z\} = 49.2 \Omega$
	Im $\{Z\} = -3.6 \Omega$
Return Loss at 900 MHz	-28.7 dB

4. Handling

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

Do not apply excessive force to the dipole arms, because they might bend. If the dipole arms have to be bent back, take care to release stress to the soldered connections near the feedpoint; they might come off.

After prolonged use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

10/23/01

requency: 900 MHz; Antenna Input Power: 250 [mW] AM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0 'robe: ET3DV6 - SN1507; ConvF(6.27,6.27) at 900 MHz; IEEE1528 900 MHz; σ = 0.97 mho/m ε_r = 41.5 ρ = 1.00 g/cm³ ubes (2): Peak: 4.59 mW/g ± 0.00 dB, SAR (1g): 2.84 mW/g ± 0.00 dB, SAR (10g): 1.80 mW/g ± 0.00 dB, (Worst-case extrapolation) enetration depth: 11.5 (10.3, 13.2) [mm] /alidation Dipole D900V2 SN:025, d = 15 mm



mid & Partner Engineering AG, Zurich, Switzerland

