



REPORT NO.: 4790809762-1-RF-1

Page 456 of 458

11.7. APPENDIX G: DUTY CYCLE 11.7.1. Test Result

| Test Mode | On Time (msec) | Period (msec) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/T Minimum VBW (kHz) | Final setting For VBW (kHz) |
|------------|-------------------|------------------|--------------------------------|----------------------|--|--------------------------------|--------------------------------------|
| 11B-CDD | 8.36 | 8.43 | 0.9917 | 99.17 | 0.04 | 0.12 | 0.01 |
| 11G-CDD | 1.39 | 1.45 | 0.9586 | 95.86 | 0.18 | 0.72 | 1 |
| 11AX20-CDD | 0.31 | 0.37 | 0.8378 | 83.78 | 0.77 | 3.23 | 4 |
| 11AX40-CDD | 0.19 | 0.25 | 0.7600 | 76.00 | 1.19 | 5.26 | 6 |
| 11BE20-CDD | 0.56 | 0.62 | 0.9032 | 90.32 | 0.44 | 1.79 | 2 |
| 11BE40-CDD | 0.54 | 0.61 | 0.8852 | 88.52 | 0.53 | 1.85 | 2 |

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)


Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used. If the EUT is configured to transmit with duty cycle \geq 98%, set VBW \leq RBW/100 (i.e., 10 kHz)


but not less than 10 Hz.



11.7.2. Test Graphs







END OF REPORT