

11B Ant1 2412



11B Ant1 2437




11B Ant1 2462




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO Ant1 2412



11N20SISO Ant1 2437




11N20SISO Ant1 2462




11N40SISO Ant1 2422



11N40SISO Ant1 2437



11N40SISO Ant1 2452



8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Reference level measurement

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
11B	Ant1	2412	2414.02	4.45
		2437	2435.47	4.64
		2462	2461.50	5.65



11B_Ant1_2412



11B_Ant1_2437




11B_Ant1_2462



Band edge measurements

TestMode	Antenna	ChName	Frequency [MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	4.45	-32.35	≤-25.55	PASS
		High	2462	5.65	-39.98	≤-24.35	PASS




Conducted Spurious Emission


TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	30~1000	4.45	-71.53	≤-25.55	PASS
			1000~26500	4.45	-47.13	≤-25.55	PASS
		2437	30~1000	4.64	-71.57	≤-25.36	PASS
			1000~26500	4.64	-46.69	≤-25.36	PASS
		2462	30~1000	5.65	-70.58	≤-24.35	PASS
			1000~26500	5.65	-42.62	≤-24.35	PASS




11B Ant1 2412 30~1000



11B Ant1 2412 1000~26500




11B Ant1 2437 30~1000




11B_Ant1_2437_1000~26500



11B_Ant1_2462_30~1000



11B_Ant1_2462_1000~26500



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11 b Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9298.12	V	56.85	39.29	74	54	17.15	14.71
11510.6	V	60.18	38.77	74	54	13.82	15.23
17613.7	V	67.16	45.84	74	54	6.84	8.16
9305.62	H	56.50	39.10	74	54	17.50	14.90
11520	H	60.33	38.59	74	54	13.67	15.41
17008.1	H	66.01	44.24	74	54	7.99	9.76

Test mode: 802.11 b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9226.87	V	56.98	38.81	74	54	17.02	15.19
11501.2	V	59.72	38.94	74	54	14.28	15.06
17535	V	65.40	44.26	74	54	8.60	9.74
8270.62	H	55.26	36.26	74	54	18.74	17.74
11512.5	H	59.77	38.75	74	54	14.23	15.25
17625	H	67.22	45.44	74	54	6.78	8.56

Test mode: 802.11 b Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8743.12	V	56.58	36.64	74	54	17.42	17.36
11523.7	V	59.58	38.51	74	54	14.42	15.49
17611.8	V	67.49	45.90	74	54	6.51	8.10
8598.75	H	55.76	36.70	74	54	18.24	17.30
11461.8	H	59.85	38.42	74	54	14.15	15.58
17602.5	H	67.59	46.27	74	54	6.41	7.73

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4)The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11 n20 Frequency: Channel 1: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.78	H	44.93	74.00	36.94	54.00
2385.59	V	45.94	74.00	37.05	54.00

Test mode: 802.11 n20 Frequency: Channel 11: 2462MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.25	H	45.45	74.00	37.21	54.00
2483.75	V	45.20	74.00	37.28	54.00


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor +Cable Loss.


(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Spurious Emission in Restricted Band 2310-2390MHz				
Test Model	☐ 802.11b	☐ 802.11g	☒ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 1: 2412MHz	☐ Channel 3: 2422MHz	Polarity: H	
	VBW=3MHz			



Spurious Emission in Restricted Band 2310-2390MHz				
Test Model	☐ 802.11b	☐ 802.11g	☒ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 1: 2412MHz	☐ Channel 3: 2422MHz	Polarity:V	
	VBW=3MHz			




Spurious Emission in Restricted Band 2483.5-2500MHz

Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

☒ Channel 11: 2462MHz ☐ Channel 9: 2452MHz ☐ Polarity: H

VBW=3MHz




Spurious Emission in Restricted Band 2483.5-2500MHz

Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)


☒ Channel 11: 2462MHz ☐ Channel 9: 2452MHz ☐ Polarity: V

VBW=3MHz




- Spurious Emission below 1GHz (30MHz to 1GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

2412



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	43.14	-18.23	24.91	PK	40.00	15.09	Vertical
2	41.6517	49.69	-17.80	31.89	PK	40.00	8.11	Vertical
3	43.5936	48.42	-17.66	30.76	PK	40.00	9.24	Vertical
4	52.3323	43.12	-17.52	25.60	PK	40.00	14.40	Vertical
5	339.739	45.98	-13.46	32.52	PK	46.00	13.48	Vertical
6	486.356	42.91	-9.79	33.12	PK	46.00	12.88	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	34.8549	-18.23	23.75	40.00	16.25
2	41.6517	-17.80	30.09	40.00	9.91
3	43.5936	-17.66	28.96	40.00	11.04
4	52.3323	-17.52	23.63	40.00	16.37
5	339.7397	-13.46	30.55	46.00	15.45
6	486.3564	-9.79	31.15	46.00	14.85




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	297.017	46.38	-14.15	32.23	PK	46.00	13.77	Horizontal
2	315.465	45.69	-14.14	31.55	PK	46.00	14.45	Horizontal
3	431.982	46.97	-11.40	35.57	PK	46.00	10.43	Horizontal
4	440.720	50.96	-11.18	39.78	PK	46.00	6.22	Horizontal
5	823.283	36.04	-4.23	31.81	PK	46.00	14.19	Horizontal
6	960.190	41.87	-2.28	39.59	PK	54.00	14.41	Horizontal

Final Data List


NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	297.017	-14.15	30.35	46.00	15.65
2	315.4655	-14.14	30.03	46.00	15.97
3	431.982	-11.40	33.89	46.00	12.11
4	440.7207	-11.18	38.46	46.00	7.54
5	823.2833	-4.23	30.49	46.00	15.51
6	960.1902	-2.28	37.63	54.00	16.37

2437



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	43.08	-18.47	24.61	PK	40.00	15.39	Vertical
2	41.6517	49.08	-17.80	31.28	PK	40.00	8.72	Vertical
3	43.5936	46.95	-17.66	29.29	PK	40.00	10.71	Vertical
4	51.3614	42.46	-17.39	25.07	PK	40.00	14.93	Vertical
5	320.320	46.82	-14.12	32.70	PK	46.00	13.30	Vertical
6	486.356	42.75	-9.79	32.96	PK	46.00	13.04	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.47	23.46	40.00	16.54
2	41.6517	-17.80	29.49	40.00	10.51
3	43.5936	-17.66	27.50	40.00	12.50
4	51.3614	-17.39	23.28	40.00	16.72
5	320.3203	-14.12	31.10	46.00	14.90
6	486.3564	-9.79	31.36	46.00	14.64




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	43.29	-18.47	24.82	PK	40.00	15.18	Horizontal
2	299.929	45.80	-14.14	31.66	PK	46.00	14.34	Horizontal
3	431.982	46.56	-11.40	35.16	PK	46.00	10.84	Horizontal
4	440.720	48.57	-11.18	37.39	PK	46.00	8.61	Horizontal
5	823.283	36.75	-4.23	32.52	PK	46.00	13.48	Horizontal
6	960.190	40.73	-2.28	38.45	PK	54.00	15.55	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.47	23.09	40.00	16.91
2	299.9299	-14.14	29.77	46.00	16.23
3	431.982	-11.40	33.27	46.00	12.73
4	440.7207	-11.18	35.86	46.00	10.14
5	823.2833	-4.23	30.82	46.00	15.18
6	960.1902	-2.28	36.75	54.00	17.25

2462




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30	44.35	-18.53	25.82	PK	40.00	14.18	Vertical
2	40.6807	49.35	-17.86	31.49	PK	40.00	8.51	Vertical
3	43.5936	48.08	-17.66	30.42	PK	40.00	9.58	Vertical
4	51.3614	41.95	-17.39	24.56	PK	40.00	15.44	Vertical
5	395.085	42.82	-11.81	31.01	PK	46.00	14.99	Vertical
6	486.356	42.56	-9.79	32.77	PK	46.00	13.23	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30	-18.53	23.91	40.00	16.09
2	40.6807	-17.86	29.94	40.00	10.06
3	43.5936	-17.66	28.87	40.00	11.13
4	51.3614	-17.39	23.37	40.00	16.63
5	395.0851	-11.81	29.66	46.00	16.34
6	486.3564	-9.79	31.42	46.00	14.58



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30	45.74	-18.53	27.21	PK	40.00	12.79	Horizontal
2	297.017	48.01	-14.15	33.86	PK	46.00	12.14	Horizontal
3	320.320	47.23	-14.12	33.11	PK	46.00	12.89	Horizontal
4	427.127	47.19	-11.53	35.66	PK	46.00	10.34	Horizontal
5	440.720	48.98	-11.18	37.80	PK	46.00	8.20	Horizontal
6	960.190	41.09	-2.28	38.81	PK	54.00	15.19	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30	-18.53	25.44	40.00	14.56
2	297.017	-14.15	31.93	46.00	14.07
3	320.3203	-14.12	31.53	46.00	14.47
4	427.1271	-11.53	34.08	46.00	11.92
5	440.7207	-11.18	36.58	46.00	9.42
6	960.1902	-2.28	37.43	54.00	16.57

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3conducted emission test setup


8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

Pass

The 120V &240V voltagehave been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: L1

Temperature: 20.8

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 61 %

Mode: WIFI 2.4G

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1540	35.96	9.56	45.52	65.78	-20.26	QP	
2		0.1540	19.19	9.56	28.75	55.78	-27.03	AVG	
3		0.3220	28.20	9.98	38.18	59.66	-21.48	QP	
4		0.3220	23.76	9.98	33.74	49.66	-15.92	AVG	
5		3.7500	22.44	9.81	32.25	56.00	-23.75	QP	
6		3.7500	10.29	9.81	20.10	46.00	-25.90	AVG	
7		9.0740	35.19	10.03	45.22	60.00	-14.78	QP	
8		9.0740	24.89	10.03	34.92	50.00	-15.08	AVG	
9		18.2460	32.15	10.22	42.37	60.00	-17.63	QP	
10		18.2460	24.35	10.22	34.57	50.00	-15.43	AVG	
11		23.1300	35.65	9.96	45.61	60.00	-14.39	QP	
12	*	23.1300	32.09	9.96	42.05	50.00	-7.95	AVG	



Site Conduction #1

Phase: N

Temperature: 20.8

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 61 %

Mode: WIFI 2.4G

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1540	35.95	9.56	45.51	65.78	-20.27	QP	
2		0.1540	16.09	9.56	25.65	55.78	-30.13	AVG	
3		0.3220	27.57	9.98	37.55	59.66	-22.11	QP	
4		0.3220	21.31	9.98	31.29	49.66	-18.37	AVG	
5		3.5260	24.73	9.80	34.53	56.00	-21.47	QP	
6		3.5260	9.40	9.80	19.20	46.00	-26.80	AVG	
7		9.0740	34.43	10.03	44.46	60.00	-15.54	QP	
8		9.0740	24.35	10.03	34.38	50.00	-15.62	AVG	
9		23.1300	36.05	9.96	46.01	60.00	-13.99	QP	
10	*	23.1300	32.56	9.96	42.52	50.00	-7.48	AVG	
11		27.1620	33.06	9.89	42.95	60.00	-17.05	QP	
12		27.1620	30.54	9.89	40.43	50.00	-9.57	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

- The EUT has a PCB Antenna for WIFI 2.4G, the antenna gain is 0.54 dBi.

Note: ☒ Antenna uses a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

*** End of Report ***