



### 7.6.5. Test Result

| Test Mode | Channel No. | Frequency (MHz) | Time of Occupancy (ms) | Limit (ms) | Result |
|-----------|-------------|-----------------|------------------------|------------|--------|
| DH1       | 39          | 2441            | 131.20                 | < 400      | Pass   |
| DH3       | 39          | 2441            | 265.60                 | < 400      | Pass   |
| DH5       | 39          | 2441            | 302.64                 | < 400      | Pass   |




Note: Test Time Period:  $0.4 \times 79 = 31.6$  sec, Hopping Times Within 1sec:  $40/50$  msec = 800 hops/sec.

The Maximum Occupancy Time within 31.6sec:  $[(0.41 \text{ ms} \times 800)/79] \times 31.6 = 131.20$  msec.



Note: Test Time Period:  $0.4 \times 79 = 31.6$  sec, Hopping Times Within 1sec:  $20/50$  msec = 400 hops/sec.

The Maximum Occupancy Time within 31.6sec:  $[(1.66 \text{ ms} \times 400)/79] \times 31.6 = 265.60$  msec.



Note: Test Time Period:  $0.4 \times 79 = 31.6$  sec, Hopping Times Within 1sec:  $13/50 \text{ msec} = 260$  hops/sec.

The Maximum Occupancy Time within 31.6sec:  $[(2.91 \text{ ms} \times 260)/79] \times 31.6 = 302.64$  msec.

## **7.7. Band-edge Compliance Measurement**

### **7.7.1. Test Limit**

The maximum permissible emission level is 20dBc. Any emissions were lying outside of the emission bandwidth and in authorized band edges to a field strength limit specified in Section 15.209 of the Title 47 CFR.

### **7.7.2. Test Procedure Used**


ANSI C63.10-2013 - Section 6.10.4

### **7.7.3. Test Setting**

1. Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
2. RBW  $\geq$  1% of spectrum analyzer display span
3. VBW  $\geq$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

#### 7.7.4. Test Setup



### 7.7.5. Test Result

| Test Mode | Channel No. | Frequency (MHz) | Limit | Result |
|-----------|-------------|-----------------|-------|--------|
| DH5       | 00          | 2402            | 20dBc | Pass   |
| DH5       | 78          | 2480            | 20dBc | Pass   |
| 2DH5      | 00          | 2402            | 20dBc | Pass   |
| 2DH5      | 78          | 2480            | 20dBc | Pass   |
| 3DH5      | 00          | 2402            | 20dBc | Pass   |
| 3DH5      | 78          | 2480            | 20dBc | Pass   |

### DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### 2DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### 3DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### DH5 Band-edge for Hopping Mode

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### 2DH5 Band-edge for Hopping Mode

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### 3DH5 Band-edge for Hopping Mode

#### Channel 00 (2402MHz)



#### Channel 78 (2480MHz)



## **7.8. Conducted Spurious Emissions Measurement**

### **7.8.1. Test Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### **7.8.2. Test Procedure Used**


ANSI C63.10-2013 - Section 7.8.8

### **7.8.3. Test Setting**

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.
2. RBW = 100 KHz
3. VBW  $\geq$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

#### 7.8.4. Test Setup




### 7.8.5. Test Result

| Test Mode | Channel No. | Frequency (MHz) | Limit (MHz) | Result |
|-----------|-------------|-----------------|-------------|--------|
| DH5       | 00          | 2402            | 20dBc       | Pass   |
| DH5       | 39          | 2441            | 20dBc       | Pass   |
| DH5       | 78          | 2480            | 20dBc       | Pass   |
| 2DH5      | 00          | 2402            | 20dBc       | Pass   |
| 2DH5      | 39          | 2441            | 20dBc       | Pass   |
| 2DH5      | 78          | 2480            | 20dBc       | Pass   |
| 3DH5      | 00          | 2402            | 20dBc       | Pass   |
| 3DH5      | 39          | 2441            | 20dBc       | Pass   |
| 3DH5      | 78          | 2480            | 20dBc       | Pass   |




## 2DH5 Conducted Spurious Emissions


### Channel 00 (2402MHz)



### Channel 39 (2441MHz)




### Channel 78 (2480MHz)




### 3DH5 Conducted Spurious Emissions


#### Channel 00 (2402MHz)



#### Channel 39 (2441MHz)



#### Channel 78 (2480MHz)



## 7.9. Radiated Spurious Emission Measurement

### 7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

| FCC Part 15 Subpart C Paragraph 15.209 |                      |                            |
|----------------------------------------|----------------------|----------------------------|
| Frequency [MHz]                        | Field Strength [V/m] | Measured Distance [Meters] |
| 0.009 - 0.490                          | 2400/F (kHz)         | 300                        |
| 0.490 - 1.705                          | 24000/F (kHz)        | 30                         |
| 1.705 – 30                             | 30                   | 30                         |
| 30 – 88                                | 100                  | 3                          |
| 88 – 216                               | 150                  | 3                          |
| 216 – 960                              | 200                  | 3                          |
| Above 960                              | 500                  | 3                          |

### 7.9.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

### 7.9.3. Test Setting

#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 \* RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Table 1 - RBW as a function of frequency**


| Frequency     | RBW           |
|---------------|---------------|
| 9 ~ 150 kHz   | 200 ~ 300 Hz  |
| 0.15 ~ 30 MHz | 9 ~ 10 kHz    |
| 30 ~ 1000 MHz | 100 ~ 120 kHz |
| > 1000 MHz    | 1 MHz         |

### **Average Field Strength Measurements**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW  $\geq 1/T$
4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

#### 7.9.4. Test Setup


##### 9kHz ~ 30MHz Test Setup:




##### 30MHz ~ 1GHz Test Setup:



### 1GHz ~ 18GHz Test Setup:



### 18GHz ~ 25GHz Test Setup:



### 7.9.5. Test Result

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | DH5                                                                                                                                                                               | Test Site:     | AC2      |
| Test Channel: | 00                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3779.5          | 39.4                 | -0.7        | 38.7                   | 74.0           | -35.3       | Peak     | Horizontal   |
|      | 4808.0          | 46.2                 | 2.7         | 48.9                   | 74.0           | -25.1       | Peak     | Horizontal   |
| *    | 6550.5          | 35.6                 | 7.4         | 43.0                   | 77.8           | -34.8       | Peak     | Horizontal   |
| *    | 9840.0          | 35.2                 | 13.5        | 48.7                   | 77.8           | -29.1       | Peak     | Horizontal   |
|      | 3924.0          | 39.5                 | -0.7        | 38.8                   | 74.0           | -35.2       | Peak     | Vertical     |
|      | 4799.5          | 46.0                 | 2.8         | 48.8                   | 74.0           | -25.2       | Peak     | Vertical     |
| *    | 6627.0          | 35.9                 | 7.6         | 43.5                   | 77.8           | -34.3       | Peak     | Vertical     |
| *    | 9840.0          | 35.2                 | 13.5        | 48.7                   | 77.8           | -29.1       | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (97.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | DH5                                                                                                                                                                               | Test Site:     | AC2      |
| Test channel: | 39                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3779.5          | 39.0                 | -0.7        | 38.3                   | 74.0           | -35.7       | Peak     | Horizontal   |
|      | 4884.5          | 42.4                 | 2.7         | 45.1                   | 74.0           | -28.9       | Peak     | Horizontal   |
| *    | 6695.0          | 35.6                 | 7.5         | 43.1                   | 79.4           | -36.3       | Peak     | Horizontal   |
| *    | 9755.0          | 34.4                 | 13.0        | 47.4                   | 79.4           | -32.0       | Peak     | Horizontal   |
|      | 3805.0          | 39.6                 | -0.6        | 39.0                   | 74.0           | -35.0       | Peak     | Vertical     |
|      | 4884.5          | 42.8                 | 2.7         | 45.5                   | 74.0           | -28.5       | Peak     | Vertical     |
| *    | 6380.5          | 36.7                 | 6.3         | 43.0                   | 79.4           | -36.4       | Peak     | Vertical     |
| *    | 9780.5          | 35.0                 | 12.7        | 47.7                   | 79.4           | -31.7       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (99.4dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | DH5                                                                                                                                                                               | Test Site:     | AC2      |
| Test channel: | 78                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3847.5          | 39.2                 | -0.6        | 38.6                   | 74.0           | -35.4       | Peak     | Horizontal   |
|      | 4961.0          | 45.0                 | 2.7         | 47.7                   | 74.0           | -26.3       | Peak     | Horizontal   |
| *    | 6491.0          | 35.5                 | 7.3         | 42.8                   | 75.6           | -32.8       | Peak     | Horizontal   |
| *    | 9831.5          | 34.1                 | 13.2        | 47.3                   | 75.6           | -28.3       | Peak     | Horizontal   |
|      | 3788.0          | 38.3                 | -0.6        | 37.7                   | 74.0           | -36.3       | Peak     | Vertical     |
|      | 4961.0          | 45.0                 | 2.7         | 47.7                   | 74.0           | -26.3       | Peak     | Vertical     |
| *    | 6431.5          | 35.6                 | 6.7         | 42.3                   | 75.6           | -33.3       | Peak     | Vertical     |
| *    | 9763.5          | 34.8                 | 12.8        | 47.6                   | 75.6           | -28.0       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (95.6dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 2DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 00                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3941.0          | 38.6                 | -0.5        | 38.1                   | 74.0           | -35.9       | Peak     | Horizontal   |
|      | 4808.0          | 40.2                 | 2.7         | 42.9                   | 74.0           | -31.1       | Peak     | Horizontal   |
| *    | 6491.0          | 34.9                 | 7.3         | 42.2                   | 76.1           | -33.9       | Peak     | Horizontal   |
| *    | 9755.0          | 34.6                 | 13.0        | 47.6                   | 76.1           | -28.5       | Peak     | Horizontal   |
|      | 3839.0          | 39.3                 | -0.6        | 38.7                   | 74.0           | -35.3       | Peak     | Vertical     |
|      | 4808.0          | 40.5                 | 2.7         | 43.2                   | 74.0           | -30.8       | Peak     | Vertical     |
| *    | 6431.5          | 36.0                 | 6.7         | 42.7                   | 76.1           | -33.4       | Peak     | Vertical     |
| *    | 9840.0          | 34.4                 | 13.5        | 47.9                   | 76.1           | -28.2       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.1dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 2DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 39                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3720.0          | 39.7                 | -0.8        | 38.9                   | 74.0           | -35.1       | Peak     | Horizontal   |
|      | 4884.5          | 39.2                 | 2.7         | 41.9                   | 74.0           | -32.1       | Peak     | Horizontal   |
| *    | 6508.0          | 35.2                 | 7.3         | 42.5                   | 78.6           | -36.1       | Peak     | Horizontal   |
| *    | 9746.5          | 35.1                 | 12.7        | 47.8                   | 78.6           | -30.8       | Peak     | Horizontal   |
|      | 3728.5          | 39.4                 | -0.8        | 38.6                   | 74.0           | -35.4       | Peak     | Vertical     |
|      | 4884.5          | 37.8                 | 2.7         | 40.5                   | 74.0           | -33.5       | Peak     | Vertical     |
| *    | 6406.0          | 35.9                 | 6.6         | 42.5                   | 78.6           | -36.1       | Peak     | Vertical     |
| *    | 9704.0          | 34.6                 | 12.3        | 46.9                   | 78.6           | -31.7       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (98.6dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 2DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 78                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3779.5          | 38.8                 | -0.7        | 38.1                   | 74.0           | -35.9       | Peak     | Horizontal   |
|      | 4961.0          | 40.3                 | 2.7         | 43.0                   | 74.0           | -31.0       | Peak     | Horizontal   |
| *    | 6550.5          | 36.0                 | 7.4         | 43.4                   | 73.5           | -30.1       | Peak     | Horizontal   |
| *    | 9772.0          | 35.0                 | 12.6        | 47.6                   | 73.5           | -25.9       | Peak     | Horizontal   |
|      | 3779.5          | 39.4                 | -0.7        | 38.7                   | 74.0           | -35.3       | Peak     | Vertical     |
|      | 4961.0          | 43.0                 | 2.7         | 45.7                   | 74.0           | -28.3       | Peak     | Vertical     |
| *    | 6499.5          | 35.6                 | 7.2         | 42.8                   | 73.5           | -30.7       | Peak     | Vertical     |
| *    | 9831.5          | 33.8                 | 13.2        | 47.0                   | 73.5           | -26.5       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (93.5dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 3DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 00                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3941.0          | 39.8                 | -0.5        | 39.3                   | 74.0           | -34.7       | Peak     | Horizontal   |
|      | 4808.0          | 40.6                 | 2.7         | 43.3                   | 74.0           | -30.7       | Peak     | Horizontal   |
| *    | 6482.5          | 35.4                 | 7.2         | 42.6                   | 76.0           | -33.4       | Peak     | Horizontal   |
| *    | 9763.5          | 34.9                 | 12.8        | 47.7                   | 76.0           | -28.3       | Peak     | Horizontal   |
|      | 3728.5          | 39.9                 | -0.8        | 39.1                   | 74.0           | -34.9       | Peak     | Vertical     |
|      | 4799.5          | 38.7                 | 2.8         | 41.5                   | 74.0           | -32.5       | Peak     | Vertical     |
| *    | 6465.5          | 36.2                 | 7.0         | 43.2                   | 76.0           | -32.8       | Peak     | Vertical     |
| *    | 9763.5          | 34.2                 | 12.8        | 47.0                   | 76.0           | -29.0       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.0dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 3DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 39                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3796.5          | 38.8                 | -0.6        | 38.2                   | 74.0           | -35.8       | Peak     | Horizontal   |
|      | 4884.5          | 38.1                 | 2.7         | 40.8                   | 74.0           | -33.2       | Peak     | Horizontal   |
| *    | 6491.0          | 35.4                 | 7.3         | 42.7                   | 79.9           | -37.2       | Peak     | Horizontal   |
| *    | 9780.5          | 35.0                 | 12.7        | 47.7                   | 79.9           | -32.2       | Peak     | Horizontal   |
|      | 3771.0          | 39.1                 | -0.8        | 38.3                   | 74.0           | -35.7       | Peak     | Vertical     |
|      | 4884.5          | 37.6                 | 2.7         | 40.3                   | 74.0           | -33.7       | Peak     | Vertical     |
| *    | 6491.0          | 35.4                 | 7.3         | 42.7                   | 79.9           | -37.2       | Peak     | Vertical     |
| *    | 9763.5          | 35.1                 | 12.8        | 47.9                   | 79.9           | -32.0       | Peak     | Vertical     |

Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (99.9dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

|               |                                                                                                                                                                                   |                |          |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Test Mode:    | 3DH5                                                                                                                                                                              | Test Site:     | AC2      |
| Test channel: | 78                                                                                                                                                                                | Test Engineer: | Will Yan |
| Remark:       | 1. Average measurement was not performed if peak level lower than average limit.<br>2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report. |                |          |

| Mark | Frequency (MHz) | Reading Level (dBμV) | Factor (dB) | Measure Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Polarization |
|------|-----------------|----------------------|-------------|------------------------|----------------|-------------|----------|--------------|
|      | 3856.0          | 38.9                 | -0.6        | 38.3                   | 74.0           | -35.7       | Peak     | Horizontal   |
|      | 4961.0          | 41.7                 | 2.7         | 44.4                   | 74.0           | -29.6       | Peak     | Horizontal   |
| *    | 6423.0          | 36.8                 | 6.7         | 43.5                   | 73.9           | -30.4       | Peak     | Horizontal   |
| *    | 9755.0          | 34.6                 | 13.0        | 47.6                   | 73.9           | -26.3       | Peak     | Horizontal   |
|      | 3728.5          | 40.2                 | -0.8        | 39.4                   | 74.0           | -34.6       | Peak     | Vertical     |
|      | 4961.0          | 42.7                 | 2.7         | 45.4                   | 74.0           | -28.6       | Peak     | Vertical     |
| *    | 6584.5          | 35.0                 | 7.5         | 42.5                   | 73.9           | -31.4       | Peak     | Vertical     |
| *    | 9772.0          | 35.2                 | 12.6        | 47.8                   | 73.9           | -26.1       | Peak     | Vertical     |


Note 1: “\*” is not in restricted band, its limit is 20dBc of the fundamental emission level (93.9dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

### The worst case of Radiated Emission 9KHz ~ 1GHz and 18GHz ~ 25GHz:

|                                           |                          |
|-------------------------------------------|--------------------------|
| Site: AC2                                 | Time: 2016/08/16 - 16:31 |
| Limit: FCC_Part15.209_RE(3m)              | Engineer: Jone Zhang     |
| Probe: VULB9162_0.03-8GHz                 | Polarity: Horizontal     |
| EUT: Solo Pro                             | Power: AC 120V/60Hz      |
| Mode: Transmit at Channel 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 46.975          | 19.347                 | 4.367                | -20.653         | 40.000         | 14.980      | QP   |
| 2  | *    | 206.055         | 23.384                 | 11.003               | -20.116         | 43.500         | 12.382      | QP   |
| 3  |      | 294.810         | 24.462                 | 10.002               | -21.538         | 46.000         | 14.461      | QP   |
| 4  |      | 319.545         | 23.535                 | 8.458                | -22.465         | 46.000         | 15.077      | QP   |
| 5  |      | 430.220         | 23.164                 | 6.024                | -22.836         | 46.000         | 17.140      | QP   |
| 6  |      | 515.970         | 23.402                 | 4.841                | -22.598         | 46.000         | 18.561      | QP   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                           |                          |
|-------------------------------------------|--------------------------|
| Site: AC2                                 | Time: 2016/08/16 - 16:36 |
| Limit: FCC_Part15.209_RE(3m)              | Engineer: Jone Zhang     |
| Probe: VULB9162_0.03-8GHz                 | Polarity: Vertical       |
| EUT: Solo Pro                             | Power: AC 120V/60Hz      |
| Mode: Transmit at Channel 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 30.000          | 28.167                 | 16.100               | -11.833         | 40.000         | 12.067      | QP   |
| 2  | *    | 38.410          | 31.141                 | 17.600               | -8.859          | 40.000         | 13.542      | QP   |
| 3  |      | 47.395          | 30.471                 | 15.500               | -9.529          | 40.000         | 14.971      | QP   |
| 4  |      | 67.825          | 26.407                 | 14.800               | -13.593         | 40.000         | 11.607      | QP   |
| 5  |      | 119.725         | 21.372                 | 10.046               | -22.128         | 43.500         | 11.326      | QP   |
| 6  |      | 204.900         | 22.366                 | 10.003               | -21.134         | 43.500         | 12.363      | QP   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                                            |                          |
|----------------------------------------------------------------------------|--------------------------|
| Site: AC2                                                                  | Time: 2016/08/22 - 18:06 |
| Limit: FCC_Part15.209_RE(3m)                                               | Engineer: Jone Zhang     |
| Probe: FMZB1519_0.009-30MHz                                                | Polarity: Face On        |
| EUT: Solo Pro                                                              | Power: AC 120V/60Hz      |
| <b>Note: There is the ambient noise within frequency range 9kHz~30MHz.</b> |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 0.049           | 50.112                 | 29.552               | -63.677         | 113.789        | 20.560      | AV   |
| 2  |      | *    | 0.105           | 44.043                 | 23.845               | -63.130         | 107.173        | 20.198      | QP   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Limit@3m =  $20 \cdot \log((2400/49) \mu\text{V/m}) + 40 \cdot \log(300\text{m}/3\text{m}) = 113.800 \text{ dBuV/m}$  (Average detector)

|                                                                            |                          |
|----------------------------------------------------------------------------|--------------------------|
| Site: AC2                                                                  | Time: 2016/08/22 - 18:07 |
| Limit: FCC_Part15.209_RE(3m)                                               | Engineer: Jone Zhang     |
| Probe: FMZB1519_0.009-30MHz                                                | Polarity: Face On        |
| EUT: Solo Pro                                                              | Power: AC 120V/60Hz      |
| <b>Note: There is the ambient noise within frequency range 9kHz~30MHz.</b> |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2.175           | 27.371                 | 6.960                | -42.129         | 69.500         | 20.412      | QP   |
| 2  |      |      | 6.216           | 24.786                 | 4.701                | -44.714         | 69.500         | 20.085      | QP   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                                             |                          |
|-----------------------------------------------------------------------------|--------------------------|
| Site: AC2                                                                   | Time: 2016/08/22 - 20:25 |
| Limit: FCC_Part15.209_RE(1m)                                                | Engineer: Roy Cheng      |
| Probe: BBHA9170_18-40GHz                                                    | Polarity: Horizontal     |
| EUT: Solo Pro                                                               | Power: AC 120V/60Hz      |
| <b>Note: There is the ambient noise within frequency range 18GHz~25GHz.</b> |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 23943.000       | 49.776                 | 35.866               | -33.724         | 83.500         | 13.910      | PK   |
| 2  |      | *    | 24741.000       | 52.375                 | 37.681               | -31.125         | 83.500         | 14.694      | PK   |

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre\_Amplifier Gain (dB)

|                                                                             |                          |
|-----------------------------------------------------------------------------|--------------------------|
| Site: AC2                                                                   | Time: 2016/08/22 - 20:31 |
| Limit: FCC_Part15.209_RE(1m)                                                | Engineer: Roy Cheng      |
| Probe: BBHA9170_18-40GHz                                                    | Polarity: Vertical       |
| EUT: Solo Pro                                                               | Power: AC 120V/60Hz      |
| <b>Note: There is the ambient noise within frequency range 18GHz~25GHz.</b> |                          |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 23999.000       | 50.379                 | 36.435               | -33.121         | 83.500         | 13.944      | PK   |
| 2  |      | *    | 24846.000       | 52.503                 | 37.735               | -30.997         | 83.500         | 14.768      | PK   |


Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre\_Amplifier Gain (dB)

## 7.10. Radiated Restricted Band Edge Measurement

### 7.10.1. Test Result

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:13 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Horizontal     |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2389.135        | 59.159                 | 26.886               | -14.841         | 74.000         | 32.273      | PK   |
| 2  |      |      | 2390.000        | 58.600                 | 26.322               | -15.400         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.292        | 97.835                 | 65.562               | N/A             | N/A            | 32.273      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:16 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Horizontal     |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 45.615                 | 13.337               | -8.385          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.008        | 95.117                 | 62.843               | N/A             | N/A            | 32.274      | AV   |

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:26 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Vertical       |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2388.992        | 59.825                 | 27.553               | -14.175         | 74.000         | 32.272      | PK   |
| 2  |      |      | 2390.000        | 58.943                 | 26.665               | -15.057         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.055        | 95.004                 | 62.730               | N/A             | N/A            | 32.273      | PK   |

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:30 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Vertical       |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 45.634                 | 13.356               | -8.366          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.150        | 91.356                 | 59.083               | N/A             | N/A            | 32.273      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:32 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Horizontal     |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2479.837        | 95.554                 | 63.285               | N/A             | N/A            | 32.269      | PK   |
| 2  |      |      | 2483.500        | 57.467                 | 25.186               | -16.533         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2483.698        | 58.963                 | 26.681               | -15.037         | 74.000         | 32.282      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:49 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Horizontal     |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2479.969        | 92.629                 | 60.360               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.325                 | 13.044               | -8.675          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:51 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Vertical       |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2479.837        | 91.908                 | 59.639               | N/A             | N/A            | 32.269      | PK   |
| 2  |      |      | 2483.500        | 57.616                 | 25.335               | -16.384         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2483.709        | 59.077                 | 26.795               | -14.923         | 74.000         | 32.282      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                               |                          |
|-----------------------------------------------|--------------------------|
| Site: AC2                                     | Time: 2016/08/16 - 19:55 |
| Limit: FCC_Part15.209_RE(3m)                  | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                      | Polarity: Vertical       |
| EUT: Solo Pro                                 | Power: AC 120V/60Hz      |
| Test Mode: Transmit by DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.046        | 89.113                 | 56.844               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.212                 | 12.931               | -8.788          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 19:56 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2389.420        | 59.022                 | 26.747               | -14.978         | 74.000         | 32.275      | PK   |
| 2  |      |      | 2390.000        | 57.342                 | 25.064               | -16.658         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.008        | 96.100                 | 63.826               | N/A             | N/A            | 32.274      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:02 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 44.594                 | 12.316               | -9.406          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.150        | 83.298                 | 51.025               | N/A             | N/A            | 32.273      | AV   |

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:03 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2388.613        | 58.691                 | 26.421               | -15.309         | 74.000         | 32.270      | PK   |
| 2  |      |      | 2390.000        | 57.479                 | 25.201               | -16.521         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.103        | 93.458                 | 61.185               | N/A             | N/A            | 32.273      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:08 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 44.508                 | 12.230               | -9.492          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.008        | 80.814                 | 48.540               | N/A             | N/A            | 32.274      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:09 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.002        | 93.504                 | 61.235               | N/A             | N/A            | 32.269      | PK   |
| 2  |      |      | 2483.500        | 57.623                 | 25.342               | -16.377         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2483.610        | 58.769                 | 26.487               | -15.231         | 74.000         | 32.282      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:11 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.090        | 81.186                 | 48.917               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.128                 | 12.847               | -8.872          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:12 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2479.903        | 90.462                 | 58.193               | 16.462          | 74.000         | 32.269      | PK   |
| 2  |      |      | 2483.500        | 58.380                 | 26.099               | -15.620         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2484.776        | 59.749                 | 27.463               | -14.251         | 74.000         | 32.286      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:15 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 2DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.013        | 78.578                 | 46.309               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.071                 | 12.790               | -8.929          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:16 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2389.847        | 58.764                 | 26.487               | -15.236         | 74.000         | 32.277      | PK   |
| 2  |      |      | 2390.000        | 57.423                 | 25.145               | -16.577         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.008        | 96.039                 | 63.765               | N/A             | N/A            | 32.274      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:20 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 44.576                 | 12.298               | -9.424          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.150        | 83.020                 | 50.747               | 29.020          | 54.000         | 32.273      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:21 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2388.992        | 58.740                 | 26.468               | -15.260         | 74.000         | 32.272      | PK   |
| 2  |      |      | 2390.000        | 57.458                 | 25.180               | -16.542         | 74.000         | 32.278      | PK   |
| 3  |      | *    | 2402.150        | 93.476                 | 61.203               | N/A             | N/A            | 32.273      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:24 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2402MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      |      | 2390.000        | 44.554                 | 12.276               | -9.446          | 54.000         | 32.278      | AV   |
| 2  |      | *    | 2402.008        | 81.081                 | 48.807               | N/A             | N/A            | 32.274      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:25 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.046        | 93.906                 | 61.637               | N/A             | N/A            | 32.269      | PK   |
| 2  |      |      | 2483.500        | 57.706                 | 25.425               | -16.294         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2483.610        | 59.101                 | 26.819               | -14.899         | 74.000         | 32.282      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:28 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Horizontal     |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.046        | 81.111                 | 48.842               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.150                 | 12.869               | -8.850          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:29 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2480MHz |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.002        | 90.767                 | 58.498               | N/A             | N/A            | 32.269      | PK   |
| 2  |      |      | 2483.500        | 57.864                 | 25.583               | -16.136         | 74.000         | 32.282      | PK   |
| 3  |      |      | 2483.599        | 59.208                 | 26.926               | -14.792         | 74.000         | 32.282      | PK   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

|                                                |                          |
|------------------------------------------------|--------------------------|
| Site: AC2                                      | Time: 2016/08/16 - 20:31 |
| Limit: FCC_Part15.209_RE(3m)                   | Engineer: Will Yan       |
| Probe: BBHA9120D_1-18GHz                       | Polarity: Vertical       |
| EUT: Solo Pro                                  | Power: AC 120V/60Hz      |
| Test Mode: Transmit by 3DH5 at Channel 2480MHz |                          |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | *    | 2480.002        | 78.642                 | 46.373               | N/A             | N/A            | 32.269      | AV   |
| 2  |      |      | 2483.500        | 45.092                 | 12.811               | -8.908          | 54.000         | 32.282      | AV   |

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

## 7.11. AC Conducted Emissions Measurement


### 7.11.1. Test Limit

| FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits |                 |                      |
|---------------------------------------------------------|-----------------|----------------------|
| Frequency (MHz)                                         | QP (dB $\mu$ V) | Average (dB $\mu$ V) |
| 0.15 - 0.50                                             | 66 - 56         | 56 - 46              |
| 0.50 - 5.0                                              | 56              | 46                   |
| 5.0 - 30                                                | 60              | 50                   |

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 7.11.2. Test Setup



### 7.11.3. Test Result

|                                   |                          |
|-----------------------------------|--------------------------|
| Site: SR2                         | Time: 2016/08/20 - 18:45 |
| Limit: FCC_Part15.207_CE_AC Power | Engineer: Vince Yu       |
| Probe: ENV216_101683_Filter On    | Polarity: Line           |
| EUT: Solo Pro                     | Power: AC 120V/60Hz      |
| Test Mode 1                       |                          |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV) | Factor (dB) | Type |
|----|------|------|-----------------|----------------------|----------------------|-----------------|--------------|-------------|------|
| 1  |      | *    | 0.198           | 54.490               | 44.485               | -9.204          | 63.694       | 10.005      | QP   |
| 2  |      |      | 0.198           | 40.257               | 30.253               | -13.437         | 53.694       | 10.005      | AV   |
| 3  |      |      | 0.298           | 47.107               | 37.104               | -13.192         | 60.298       | 10.002      | QP   |
| 4  |      |      | 0.298           | 32.063               | 22.061               | -18.235         | 50.298       | 10.002      | AV   |
| 5  |      |      | 0.954           | 43.106               | 33.174               | -12.894         | 56.000       | 9.932       | QP   |
| 6  |      |      | 0.954           | 25.639               | 15.707               | -20.361         | 46.000       | 9.932       | AV   |
| 7  |      |      | 1.930           | 42.664               | 32.790               | -13.336         | 56.000       | 9.874       | QP   |
| 8  |      |      | 1.930           | 27.674               | 17.800               | -18.326         | 46.000       | 9.874       | AV   |
| 9  |      |      | 3.602           | 46.567               | 36.649               | -9.433          | 56.000       | 9.917       | QP   |
| 10 |      |      | 3.602           | 34.110               | 24.192               | -11.890         | 46.000       | 9.917       | AV   |
| 11 |      |      | 6.002           | 42.254               | 32.132               | -17.746         | 60.000       | 10.122      | QP   |
| 12 |      |      | 6.002           | 31.368               | 21.246               | -18.632         | 50.000       | 10.122      | AV   |

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

|                                   |                          |
|-----------------------------------|--------------------------|
| Site: SR2                         | Time: 2016/08/20 - 18:50 |
| Limit: FCC_Part15.207_CE_AC Power | Engineer: Vince Yu       |
| Probe: ENV216_101683_Filter On    | Polarity: Neutral        |
| EUT: Solo Pro                     | Power: AC 120V/60Hz      |
| Test Mode 1                       |                          |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV) | Factor (dB) | Type |
|----|------|------|-----------------|----------------------|----------------------|-----------------|--------------|-------------|------|
| 1  |      | *    | 0.206           | 54.086               | 44.084               | -9.279          | 63.365       | 10.001      | QP   |
| 2  |      |      | 0.206           | 43.357               | 33.356               | -10.008         | 53.365       | 10.001      | AV   |
| 3  |      |      | 0.302           | 46.771               | 36.731               | -13.417         | 60.188       | 10.039      | QP   |
| 4  |      |      | 0.302           | 34.458               | 24.419               | -15.729         | 50.188       | 10.039      | AV   |
| 5  |      |      | 0.534           | 43.132               | 32.965               | -12.868         | 56.000       | 10.168      | QP   |
| 6  |      |      | 0.534           | 28.189               | 18.021               | -17.811         | 46.000       | 10.168      | AV   |
| 7  |      |      | 0.934           | 43.187               | 33.241               | -12.813         | 56.000       | 9.945       | QP   |
| 8  |      |      | 0.934           | 26.465               | 16.519               | -19.535         | 46.000       | 9.945       | AV   |
| 9  |      |      | 3.710           | 44.999               | 35.047               | -11.001         | 56.000       | 9.953       | QP   |
| 10 |      |      | 3.710           | 32.472               | 22.519               | -13.528         | 46.000       | 9.953       | AV   |
| 11 |      |      | 7.218           | 38.048               | 27.872               | -21.952         | 60.000       | 10.176      | QP   |
| 12 |      |      | 7.218           | 28.009               | 17.833               | -21.991         | 50.000       | 10.176      | AV   |

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

## 8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Solo Pro FCC ID:**

**2AGN8-P22N14** is in compliance with Part 15C of the FCC Rules.

---

The End