

FCC SAR Test Report

Report No. : ES190731026W09
Applicant : MobileDemand, L.C.
Address : 1501 Boyson Sq Dr, Ste 101 Hiawatha, Iowa, United States
Product : Tablet PC
FCC ID : O86T1180
Trade Mark : MobileDemand
Model No. : xTablet T1180
Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02
KDB 248227 D01 v02r02/ KDB 447498 D01 v06 / KDB 616217 D04 v01r02
KDB 941225 D01 v03r01/ KDB 941225 D05 v02r05
Sample Received Date : August 02, 2019
Date of Testing : August 14, 2019 ~ September 02, 2019

CERTIFICATION: The above equipment have been tested by **EMTEK (SHENZHEN) CO., LTD.** Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared by :



Lance Li/Editor

Reviewer :



Joe Xia/Supervisor

Approve & Authorized Signer :



Lisa Wang/Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
Summary of Maximum SAR Value	4
Description of Equipment Under Test.....	5
Description of Support Device	6
SAR Measurement System	7
3.1 Definition of Specific Absorption Rate (SAR)	7
3.2 SPEAG DASY System	7
3.2.1 Robot.....	8
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	10
3.2.5 Device Holder.....	11
3.2.6 System Validation Dipoles.....	11
3.2.7 Tissue Simulating Liquids.....	12
3.3 SAR System Verification	15
3.4 SAR Measurement Procedure	16
3.4.1 Area & Zoom Scan Procedure	16
3.4.2 Volume Scan Procedure.....	16
3.4.3 Power Drift Monitoring.....	17
3.4.4 Spatial Peak SAR Evaluation	17
3.4.5 SAR Averaged Methods	17
SAR Measurement Evaluation	18
4.1 EUT Configuration and Setting.....	18
4.2 EUT Testing Position	26
4.2.1 Body Exposure Conditions	26
4.2.2 SAR Test Exclusion Evaluations.....	27
4.2.3 Simultaneous Transmission Possibilities	29
4.3 Tissue Verification	30
4.4 System Validation.....	30
4.5 System Verification.....	31
4.6 Maximum Output Power.....	32
4.6.1 Maximum Conducted Power	32
4.6.2 Measured Conducted Power Result.....	35
4.7 SAR Testing Results	66
4.7.1 SAR Test Reduction Considerations	66
4.7.2 SAR Results for Body Exposure Condition	68
4.7.3 2.4GHz 802.11g/n OFDM SAR Test Exclusion Consideration:.....	69
4.7.4 SAR Measurement Variability.....	70
4.7.5 Simultaneous Multi-band Transmission Evaluation	71
Calibration of Test Equipment.....	73
Measurement Uncertainty	74
Information on the Testing Laboratories	78
Appendix A.SAR Plots of System Verification	
Appendix B.SAR Plots of SAR Measurement	
Appendix C.Calibration Certificate for Probe and Dipole	
Appendix D.Photographs of EUT and Setup	

Release Control Record

Report No.	Reason for Change	Date Issued
ES190731026W09	Initial release	September 10, 2019

Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Body SAR _{1g} (W/kg)
PCB	WCDMA II	0.99
	WCDMA IV	0.87
	WCDMA V	0.91
	LTE 2	0.57
	LTE 7	0.64
	LTE 12	0.63
	LTE 13	0.39
	LTE 26	0.76
	LTE 41	0.41
	LTE 66	0.63
DTS	2.4G WLAN	0.55
NII	5.2G WLAN	0.56
	5.6G WLAN	0.57
	5.8G WLAN	0.55
DSS	Bluetooth	N/A
DXX	NFC	N/A
Highest Simultaneous Transmission SAR		Body (W/kg)
PCB +WLAN(DTS)		1.54
PCB +WLAN(NII)		1.56
PCB +BT		1.10

Note:

- The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg) for general population/uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

Description of Equipment Under Test

EUT Type	Tablet PC
FCC ID	O86T1180
Trade Mark	MobileDemand
Model Name	xTablet T1180
Tx Frequency Bands (Unit: MHz)	WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850 ~ 1910 LTE Band 4 : 1710 ~ 1755 LTE Band 5 : 824 ~ 849 LTE Band 7 : 2500 ~ 2570 LTE Band 12 : 699 ~ 716 LTE Band 13 : 777 ~ 787 LTE Band 26 : 814 ~ 849 LTE Band 41 : 2496 ~ 2690 LTE Band 66 : 1710 ~ 1780 WLAN(2.4G) : 2412 ~ 2462 WLAN(5G) : 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 NFC : 13.56
Uplink Modulations	WCDMA : QPSK LTE : QPSK, 16QAM, 64QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK, BLE NFC : ASK
Maximum Tune-up Conducted Power (Unit: dBm)	WCDMA Band II : 23.0 WCDMA Band IV : 23.5 WCDMA Band V : 23.0 LTE Band 2 : 23.0 LTE Band 4 : 23.5 LTE Band 5 : 23.5 LTE Band 7 : 22.0 LTE Band 12 : 23.5 LTE Band 13 : 23.5 LTE Band 26 : 23.5 LTE Band 41 : 23.0 LTE Band 66 : 23.5 WLAN 2.4G : 18.0 WLAN 5.2G : 16.5 WLAN 5.3G : 17.0 WLAN 5.6G : 19.5 WLAN 5.8G : 18.0 Bluetooth : 8.5
Antenna Type	Fixed Internal Antenna
EUT Stage	Identical Prototype

Description of Support Device

ITEM	SKU1	SKU2	SKU3
CPU	M3-8100Y	I5-8200Y	I7-8500Y
eMMC	64G	64G	128G
DRAM 178pin DDR3L	8G(on board)	8G(on board)	16G(on board)
Display	10.1 inch,WUXGA,1200x1920, -,K&D/KD101N80-40NA-A004		
Touch Panel	AV-DISPLAY/T101727-05A-GTN		
PCIE M.2 SSD	M.2 PCIE 128G/1TB		
Front Camera	HRX Front Camera(2M)		
Rear Camera	Bison_BNGT8BNTS-200(8M)		
Finger Printer	FANGTEC/FCU115-1, Crossmatch TCETC1/TCETD1		
WLAN 802.11	INTEL-AC 9260		
4G/3G Bands	EM06		
RFID/NFC	NP05(MSI-002)		
Speaker	V		
Barcode Scanner	Honeywell N3680/N6683		
Battery (V & mAh)	7.2V 6298mAh, 45.3Wh		7.2V 9447mAh, 68Wh
Backup Battery	V		V

Feature of Equipment under Test

ITEM	EUT1	EUT2
CPU	I5-8200Y	I7-8500Y
eMMC	64G	128G
DRAM 178pin DDR3L	8G	16G
PCIE M.2 SSD	M.2 PCIE 1TB	M.2 PCIE 1TB
Finger Printer	Crossmatch TCETC1/TCETD1	Crossmatch TCETC1/TCETD1
WLAN 802.11	INTEL-AC 9260	INTEL-AC 9260
4G/3G Bands	EM06	EM06
RFID/NFC	NP05(MSI-002)	NP05(MSI-002)
Barcode Scanner	N3680	N6683
Battery (V & mAh)	7.2V 6298mAh, 45.3Wh	7.2V 9447mAh, 68Wh

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
2. After SAR prediction test, EUT2 measurement value was larger than EUT1, so EUT2 was selected for SAR test.

SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASYsystem uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)




Fig-3.2 DASY5

3.2.2 Probes

FCC SAR Test Report

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feedpoint impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W ($f < 1\text{GHz}$), > 40 W ($f > 1\text{GHz}$)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




Fig-3.4 System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664D01, the resolution for Area and Zoom scan is specified in the table below.

Items	≤ 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	≤ 15 mm	≤ 12 mm	≤ 12 mm	≤ 10 mm	≤ 10 mm
Zoom Scan ($\Delta x, \Delta y$)	≤ 8 mm	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 4 mm
Zoom Scan (Δz)	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 3 mm	≤ 2 mm
Zoom Scan Volume	≥ 30 mm	≥ 30 mm	≥ 28 mm	≥ 25 mm	≥ 22 mm

Note:

When zoom scan is required and report SAR is ≤ 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: ≤ 8 mm, 3-4GHz: ≤ 7 mm, 4-6GHz: ≤ 5 mm) may be applied.

3.4.2 VolumeScan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

SAR Measurement Evaluation

4.1 EUT Configuration and Setting**<Considerations Related to Proximity Sensor>**

The device supports WWAN, WLAN, and Bluetooth capabilities. It is designed with a proximity sensor which can trigger/not trigger power reduction for WCDMA and LTE on Rear Face and Left Side of EUT for SAR compliance. Others RF capability (WLAN and Bluetooth) have no power reduction. The power levels for all wireless technologies and the power reduction please refer to section 4.6 of this report.

Proximity Sensor Triggering Distances (KDB 616217 D04 §6.2)

The proximity sensor triggering distance was determined per KDB 616217 for rear face and applicable edge. Summary for power verification per distance was tabulated in the below table.


Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	6	7	8	9	10	11	12	13	14	15	16
WCDMA II	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
WCDMA IV	20.5	20.5	20.5	20.5	20.5	20.5	23.5	23.5	23.5	23.5	23.5
WCDMA V	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
LTE 2	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
LTE 4	21.5	21.5	21.5	21.5	21.5	21.5	23.5	23.5	23.5	23.5	23.5
LTE 5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 7	20.5	20.5	20.5	20.5	20.5	20.5	22.0	22.0	22.0	22.0	22.0
LTE 12	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 13	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 26	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 41	21.5	21.5	21.5	21.5	21.5	21.5	23.0	23.0	23.0	23.0	23.0
LTE 66	22.0	22.0	22.0	22.0	22.0	22.0	23.5	23.5	23.5	23.5	23.5
Output Power Verification in dBm for EUT Left Side											
Distance (mm)	6	7	8	9	10	11	12	13	14	15	16
WCDMA II	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
WCDMA IV	20.5	20.5	20.5	20.5	20.5	20.5	23.5	23.5	23.5	23.5	23.5
WCDMA V	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
LTE 2	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
LTE 4	21.5	21.5	21.5	21.5	21.5	21.5	23.5	23.5	23.5	23.5	23.5
LTE 5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 7	20.5	20.5	20.5	20.5	20.5	20.5	22.0	22.0	22.0	22.0	22.0
LTE 12	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 13	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 26	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5
LTE 41	21.5	21.5	21.5	21.5	21.5	21.5	23.0	23.0	23.0	23.0	23.0
LTE 66	22.0	22.0	22.0	22.0	22.0	22.0	23.5	23.5	23.5	23.5	23.5

Proximity Sensor Coverage (KDB 616217 D04 §6.3)

Since the proximity sensor is collocated with antenna in one component, the procedure for proximity sensor coverage is not required.

Proximity Sensor Tilt Angle Influences (KDB 616217 D04 §6.4)

The proximity sensor tilt angle influence was determined per KDB 616217 for applicable edge. Summary for proximity sensor tilt angle influence is shown in below.



Orientation	Separation Distance (mm)	Tilt Angle										
		-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°
Left Side	11	On	On	On	On	On	On	On	On	On	On	On

Summary for Proximity Sensor Triggering Test

According to the procedures noticed in KDB 616217 D04, the proximity sensor triggering distance is 16 mm for EUT Rear Face, and 11 mm for Left Side. The separation distance of 11 mm determined by the smallest triggering distance on Left Side is used to access the tilt angle influence and the sensor does not release during ± 45 degree. Therefore, the smallest separation distance for tilt angle influence is 11 mm for the Left Side. The conservation triggering distances based on the separation distance for the sensor trigger / not triggered as EUT with power reduction at 0 mm, and EUT without power reduction at 15 mm for EUT Rear Face, and 10 mm for Left Side were used to test SAR.

The power reduction is depends on the proximity sensor input. For a steady SAR test, the power reduction was enabled or disabled manually by engineering software during SAR testing.

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (**R&S CMW500**). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

FCC SAR Test Report

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.

Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	√	√	√	√	√	√
4	√	√	√	√	√	√
5	√	√	√	√		
7			√	√	√	√
12	√	√	√	√		
13			√	√		
26	√	√	√	√	√	
41			√	√	√	√
66			√	√	√	√

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.


For LTE B4 / B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

LTE band 2 SAR test was covered by Band 25; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if

- the maximum output power, including tolerance, for the smaller band is = the larger band to qualify for the SAR test exclusion
- the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over

802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

4.2 EUT Testing Position

4.2.1 Body Exposure Conditions

For full-size tablet, according to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Fig-4.1 Illustration for Tablet Setup

4.2.2 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

<For Antenna for WWAN>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?
WCDMA II	23.0	199.53	5	55.1	Yes	5	55.1	Yes	270	2309 mW	No	175	1359 mW	No	20	13.8	Yes
WCDMA IV	23.5	223.87	5	59.3	Yes	5	59.3	Yes	270	2313	No	175	1363	No	20	14.8	Yes
WCDMA V	23.0	199.53	5	36.7	Yes	5	36.7	Yes	270	1405	No	175	869 mW	No	20	9.2	Yes
LTE 2	23.0	199.53	5	55.1	Yes	5	55.1	Yes	270	2309	No	175	1359	No	20	13.8	Yes
LTE 4	23.5	223.87	5	59.3	Yes	5	59.3	Yes	270	2313	No	175	1363	No	20	14.8	Yes
LTE 5	23.5	223.87	5	41.2	Yes	5	41.2	Yes	270	1405	No	175	869 mW	No	20	10.3	Yes
LTE 7	22.0	158.49	5	50.7	Yes	5	50.7	Yes	270	2294	No	175	1344	No	20	12.7	Yes
LTE 12	24.0	251.19	5	42.5	Yes	5	42.5	Yes	270	1225	No	175	773 mW	No	20	10.6	Yes
LTE 13	24.0	251.19	5	44.5	Yes	5	44.5	Yes	270	1321	No	175	823 mW	No	20	11.1	Yes
LTE 26	23.5	223.87	5	41.3	Yes	5	41.3	Yes	270	1408	No	175	870 mW	No	20	10.3	Yes
LTE 41	23.0	199.53	5	65.4	Yes	5	65.4	Yes	270	2291	No	175	1341	No	20	16.4	Yes
LTE 66	23.5	223.87	5	59.7	Yes	5	59.7	Yes	270	2312	No	175	1362	No	20	14.9	Yes

<For Antenna for WLAN-0 & BT>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	RearFace			LeftSide			RightSide			TopSide			BottomSide		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?
WLAN 2.4G	15.0	31.62	5	9.9	Yes	5	9.9	Yes	270	2296 mW	No	40	1.2	No	165	1246 mW	No
WLAN 5.2G	13.5	22.39	5	10.2	Yes	5	10.2	Yes	270	2266 mW	No	40	1.3	No	165	1216 mW	No
WLAN 5.6G	16.0	39.81	5	19.0	Yes	5	19.0	Yes	270	2263 mW	No	40	2.4	No	165	1213 mW	No
WLAN 5.8G	15.0	31.62	5	15.3	Yes	5	15.3	Yes	270	2262 mW	No	40	1.9	No	165	1212 mW	No
BT	8.5	7.08	5	2.2	No	5	2.2	No	270	2295	No	40	0.3	No	165	1245	No

<For Antenna for WLAN-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	RearFace			LeftSide			RightSide			TopSide			BottomSide		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?
WLAN 2.4G	15.0	31.62	5	9.9	Yes	5	9.9	Yes	270	2296	No	100	596 mW	No	100	596 mW	No
WLAN 5.2G	13.5	22.39	5	10.2	Yes	5	10.2	Yes	270	2266	No	100	566 mW	No	100	566 mW	No
WLAN 5.6G	15.5	35.48	5	16.9	Yes	5	16.9	Yes	270	2263	No	100	563 mW	No	100	563 mW	No
WLAN 5.8G	15.0	31.62	5	15.3	Yes	5	15.3	Yes	270	2262	No	100	562 mW	No	100	562 mW	No

<For WLAN Ant-0 + Ant-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	RearFace			LeftSide			RightSide			TopSide			BottomSide		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing ?
WLAN 2.4G	18.0	63.10	5	19.8	Yes	5	19.8	Yes	270	2296 mW	No	40	2.5	No	100	596 mW	No
WLAN 5.2G	16.5	44.67	5	20.5	Yes	5	20.5	Yes	270	2266	No	40	2.6	No	100	566 mW	No
WLAN 5.6G	19.5	89.13	5	42.6	Yes	5	42.6	Yes	270	2263	No	40	5.3	No	100	563 mW	No
WLAN 5.8G	17.0	50.12	5	24.2	Yes	5	24.2	Yes	270	2262	No	40	3.0	No	100	562 mW	No

Note:

1. When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 for SAR-1g exposure condition, or ≤ 7.5 for SAR-10g exposure condition, the SAR testing exclusion is applied.
2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

4.2.3 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WCDMA II (Data) + WLAN (Data)	Yes
2	WCDMA IV (Data) + WLAN (Data)	Yes
3	WCDMA V (Data) + WLAN (Data)	Yes
4	LTE 2 (Data) + WLAN (Data)	Yes
5	LTE 4 (Data) + WLAN (Data)	Yes
6	LTE 5 (Data) + WLAN (Data)	Yes
7	LTE 7 (Data) + WLAN (Data)	Yes
8	LTE 12 (Data) + WLAN (Data)	Yes
9	LTE 13 (Data) + WLAN (Data)	Yes
10	LTE 26 (Data) + WLAN (Data)	Yes
11	LTE 41 (Data) + WLAN (Data)	Yes
12	LTE 66 (Data) + WLAN (Data)	Yes
13	WCDMA II (Voice / Data) + BT (Data)	Yes
14	WCDMA IV (Voice / Data) + BT (Data)	Yes
15	WCDMA V (Voice / Data) + BT (Data)	Yes
16	LTE 2 (Data) + BT (Data)	Yes
17	LTE 4 (Data) + BT (Data)	Yes
18	LTE 5 (Data) + BT (Data)	Yes
19	LTE 7 (Data) + BT (Data)	Yes
20	LTE 12 (Data) + BT (Data)	Yes
21	LTE 13 (Data) + BT (Data)	Yes
22	LTE 26 (Data) + BT (Data)	Yes
23	LTE 41 (Data) + BT (Data)	Yes
24	LTE 66 (Data) + BT (Data)	Yes

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Aug. 15, 2019	Body	750	21.6	0.976	56.163	0.96	55.50	1.67	1.19
Aug. 14, 2019	Body	835	21.6	0.98	55.833	0.97	55.20	1.03	1.15
Sep. 02, 2019	Body	1750	21.6	1.471	53.676	1.49	53.40	-1.28	0.52
Aug. 17, 2019	Body	1900	21.6	1.571	52.993	1.52	53.30	3.36	-0.58
Aug. 21, 2019	Body	2450	21.6	2.026	53.063	1.95	52.70	3.90	0.69
Aug. 19, 2019	Body	2600	21.6	2.206	52.381	2.16	52.50	2.13	-0.23
Aug. 29, 2019	Body	5200	21.6	5.27	49.057	5.30	49.00	-0.57	0.12
Aug. 29, 2019	Body	5600	21.6	5.871	48.311	5.77	48.50	1.75	-0.39
Aug. 29, 2019	Body	5800	21.6	6.127	47.81	6.00	48.20	2.12	-0.81

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Jun. 20, 2018	3970	Body	750	0.96	55.50	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 20, 2018	3970	Body	835	0.97	55.20	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 20, 2018	3970	Body	1750	1.49	53.40	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 18, 2018	3970	Body	1900	1.52	53.30	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 17, 2018	3970	Body	2450	1.95	52.70	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 19, 2018	3970	Body	2600	2.16	52.50	Pass	Pass	Pass	OFDM	N/A	Pass
Jun.28, 2018	3970	Body	5300	5.30	49.00	Pass	Pass	Pass	OFDM	N/A	Pass
Jun.28, 2018	3970	Body	5600	5.77	48.50	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 28, 2018	3970	Body	5800	6.00	48.20	Pass	Pass	Pass	OFDM	N/A	Pass

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Aug. 15, 2019	Body	750	8.63	2.15	8.6	-0.35	1078	3970	1418
Aug. 14, 2019	Body	835	9.68	2.49	9.96	2.89	4d092	3970	1418
Sep. 02, 2019	Body	1750	36.80	9.33	37.32	1.41	1023	3970	1418
Aug. 17, 2019	Body	1900	40.20	10.6	42.4	5.47	5d142	3970	1418
Aug. 21, 2019	Body	2450	49.80	12.4	49.6	-0.40	835	3970	1418
Aug. 19, 2019	Body	2600	54.40	13.8	55.2	1.47	1058	3970	1418
Aug. 29, 2019	Body	5300	75.20	7.5	75	-0.27	1040	3970	1418
Aug. 29, 2019	Body	5600	81.50	8.28	82.8	1.60	1040	3970	1418
Aug. 29, 2019	Body	5800	77.30	7.91	79.1	2.33	1040	3970	1418

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	WCDMA Band II (without Power Reduction)	WCDMA Band II (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.0	21.0	±1

Mode	WCDMA Band IV (without Power Reduction)	WCDMA Band IV (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.5	21.5	±1

Mode	WCDMA Band V (without Power Reduction)	WCDMA Band V (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.0	21.0	±1

Mode	LTE 2 (without Power Reduction)	LTE 2 (with Power Reduction)	Power Reduction (dB)
QPSK	23.0	21.0	±1

Mode	LTE 4 (without Power Reduction)	LTE 4 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	LTE 5 (without Power Reduction)	LTE 5 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	LTE 7 (without Power Reduction)	LTE 7 (with Power Reduction)	Power Reduction (dB)
QPSK	22.0	20.0	±1

Mode	LTE 12 (without Power Reduction)	LTE 12 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	LTE 13 (without Power Reduction)	LTE 13 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	LTE 26 (without Power Reduction)	LTE 26 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	LTE 41 (without Power Reduction)	LTE 41 (with Power Reduction)	Power Reduction (dB)
QPSK	23.0	21.0	±1

Mode	LTE 66 (without Power Reduction)	LTE 66 (with Power Reduction)	Power Reduction (dB)
QPSK	23.5	21.5	±1

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	15.0	N/A	N/A	N/A	N/A
802.11g	15.0	N/A	N/A	N/A	N/A
802.11a	N/A	13.5	14.0	16.0	15.0
802.11n HT20	18.0	16.5	16.5	18.5	18.0
802.11n HT40	17.0	16.5	17.0	19.5	17.0
802.11ac VHT80	N/A	16.0	16.5	19.0	16.5

Mode	2.4G Bluetooth
GFSK	8.5
π/4-DQPSK	7.5
8-DPSK	8.0
LE	5.5

Band	Mode	Target power	Tolerance
UNII Band I	11a	13.0	±1
	11n(HT20)	14.5	±1
	11n(HT40)	14.5	±1
	11ac(HT20)	14.5	±1
	11ac(HT40)	14.5	±1
	11ac(HT80)	14.0	±1
UNII Band II-A	11a	13.0	±1
	11n(HT20)	14.5	±1
	11n(HT40)	14.5	±1
	11ac(HT20)	14.5	±1
	11ac(HT40)	14.5	±1
	11ac(HT80)	14.0	±1
UNII Band II-C	11a	13.0	±1
	11n(HT20)	14.5	±1
	11n(HT40)	14.5	±1
	11ac(HT20)	14.5	±1
	11ac(HT40)	14.5	±1
	11ac(HT80)	14.0	±1
UNII Band III	11a	11.5	±1
	11n(HT20)	14.0	±1
	11n(HT40)	14.0	±1
	11ac(HT20)	14.0	±1
	11ac(HT40)	14.0	±1
	11ac(HT80)	14.0	±1

Mode	2.4G Bluetooth
GFSK	Ch0~38:6.0 Ch39~77:8.5
$\pi/4$ -DQPSK	Ch0~38:6.0 Ch39~78:9.5
8-DPSK	Ch0~78:1.0
BLE	Ch0~18:6.0 Ch19~39:9.0

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	WCDMA Band II			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	
RMC 12.2K	22.67	22.93	22.75	22.95	22.84	22.77	-
HSDPA Subtest-1	21.46	21.72	21.54	21.74	21.63	21.56	0
HSDPA Subtest-2	21.45	21.71	21.53	21.73	21.62	21.55	0
HSDPA Subtest-3	20.97	21.23	21.05	21.25	21.14	21.07	0.5
HSDPA Subtest-4	20.95	21.21	21.03	21.23	21.12	21.05	0.5
HSUPA Subtest-1	21.54	21.80	21.62	21.82	21.71	21.64	0
HSUPA Subtest-2	19.56	19.82	19.64	19.84	19.73	19.66	2
HSUPA Subtest-3	20.51	20.77	20.59	20.79	20.68	20.61	1
HSUPA Subtest-4	19.40	19.66	19.48	19.68	19.57	19.50	2
HSUPA Subtest-5	21.72	21.98	21.80	22.00	21.89	21.82	0

Band	WCDMA Band IV			3GPP MPR (dB)
Channel	1312	1413	1513	
Frequency (MHz)	1712.4	1732.6	1752.6	
EUT without Power Reduction (P-Sensor NOT Triggered)				
RMC 12.2K	23.07	23.15	22.96	-
HSDPA Subtest-1	21.86	21.94	21.75	0
HSDPA Subtest-2	21.85	21.93	21.74	0
HSDPA Subtest-3	21.37	21.45	21.26	0.5
HSDPA Subtest-4	21.35	21.43	21.24	0.5
HSUPA Subtest-1	21.94	22.02	21.83	0
HSUPA Subtest-2	19.96	20.04	19.85	2
HSUPA Subtest-3	20.91	20.99	20.80	1
HSUPA Subtest-4	19.80	19.88	19.69	2
HSUPA Subtest-5	22.12	22.20	22.01	0
EUT with Power Reduction (P-Sensor Triggered)				
RMC 12.2K	20.02	20.11	19.95	-

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193
				1850.7 MHz	1880.0 MHz	1909.3 MHz
2/1.4	QPSK	1	0	22.46	22.71	22.55
		1	2	22.45	22.70	22.54
		1	5	22.42	22.67	22.51
		3	0	22.45	22.70	22.54
		3	1	22.44	22.69	22.53
		3	3	22.41	22.66	22.50
		6	0	21.52	21.77	21.61
	16QAM	1	0	21.47	21.72	21.56
		1	2	21.44	21.69	21.53
		1	5	21.43	21.68	21.52
		3	0	21.45	21.70	21.54
		3	1	21.42	21.67	21.51
		3	3	21.41	21.66	21.50
		6	0	20.47	20.72	20.56
	64QAM	1	0	20.29	20.67	20.53
		1	7	20.41	20.63	20.46
		1	14	20.38	20.61	20.49
		8	0	20.36	20.51	20.39
		8	3	20.28	20.54	20.32
		8	7	20.41	20.62	20.46
		15	0	19.43	19.52	19.54

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185
				1851.5 MHz	1880.0 MHz	1908.5 MHz
2/3	QPSK	1	0	22.49	22.74	22.58
		1	7	22.48	22.73	22.57
		1	14	22.45	22.70	22.54
		8	0	21.54	21.79	21.63
		8	3	21.52	21.77	21.61
		8	7	21.47	21.72	21.56
		15	0	21.55	21.80	21.64
	16QAM	1	0	21.50	21.75	21.59
		1	7	21.47	21.72	21.56
		1	14	21.46	21.71	21.55
		8	0	20.58	20.83	20.67
		8	3	20.57	20.82	20.66
		8	7	20.52	20.77	20.61
		15	0	20.50	20.75	20.59
	64QAM	1	0	20.49	20.58	20.48
		1	7	20.33	20.59	20.42
		1	14	20.41	20.7	20.39
		8	0	19.5	19.73	19.51
		8	3	19.4	19.77	19.65
		8	7	19.49	19.73	19.54
		15	0	19.43	19.64	19.47

Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175
				1852.5 MHz	1880.0 MHz	1907.5 MHz
2/5	QPSK	1	0	22.52	22.77	22.61
		1	12	22.51	22.76	22.60
		1	24	22.48	22.73	22.57
		12	0	21.57	21.82	21.66
		12	6	21.55	21.80	21.64
		12	13	21.50	21.75	21.59
		25	0	21.58	21.83	21.67
	16QAM	1	0	21.53	21.78	21.62
		1	12	21.50	21.75	21.59
		1	24	21.49	21.74	21.58
		12	0	20.61	20.86	20.70
		12	6	20.60	20.85	20.69
		12	13	20.55	20.80	20.64
		25	0	20.53	20.78	20.62
	64QAM	1	0	20.50	20.72	20.43
		1	12	20.47	20.62	20.46
		1	24	20.43	20.69	20.57
		12	0	19.51	19.84	19.66
		12	6	19.45	19.74	19.66
		12	13	19.39	19.65	19.59
		25	0	19.46	19.72	19.61

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150
				1855.0 MHz	1880.0 MHz	1905.0 MHz
2/10	QPSK	1	0	22.54	22.79	22.63
		1	24	22.53	22.78	22.62
		1	49	22.50	22.75	22.59
		25	0	21.59	21.84	21.68
		25	12	21.57	21.82	21.66
		25	25	21.52	21.77	21.61
		50	0	21.60	21.85	21.69
	16QAM	1	0	21.55	21.80	21.64
		1	24	21.52	21.77	21.61
		1	49	21.51	21.76	21.60
		25	0	20.63	20.88	20.72
		25	12	20.62	20.87	20.71
		25	25	20.57	20.82	20.66
		50	0	20.55	20.80	20.64
	64QAM	1	0	20.54	20.70	20.51
		1	24	20.50	20.62	20.51
		1	49	20.42	20.60	20.55
		25	0	19.49	19.85	19.61
		25	12	19.46	19.68	19.58
		25	25	19.46	19.76	19.49
		50	0	19.53	19.65	19.62

Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125
				1857.5 MHz	1880.0 MHz	1902.5 MHz
2/15	QPSK	1	0	22.57	22.82	22.66
		1	37	22.56	22.81	22.65
		1	74	22.53	22.78	22.62
		36	0	21.62	21.87	21.71
		36	19	21.60	21.85	21.69
		36	39	21.55	21.80	21.64
		75	0	21.63	21.88	21.72
	16QAM	1	0	21.58	21.83	21.67
		1	37	21.55	21.80	21.64
		1	74	21.54	21.79	21.63
		36	0	20.66	20.91	20.75
		36	19	20.65	20.90	20.74
		36	39	20.60	20.85	20.69
		75	0	20.58	20.83	20.67
	64QAM	1	0	20.48	20.75	20.66
		1	37	20.45	20.74	20.52
		1	74	20.45	20.70	20.58
		36	0	19.60	19.82	19.72
		36	19	19.55	19.80	19.56
		36	39	19.41	19.82	19.57
		75	0	19.55	19.75	19.65

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100
				1860.0 MHz	1880.0 MHz	1900.0 MHz
2/20	QPSK	1	0	22.62	22.87	22.71
		1	50	22.61	22.86	22.70
		1	99	22.58	22.83	22.67
		50	0	21.67	21.92	21.76
		50	25	21.65	21.90	21.74
		50	50	21.60	21.85	21.69
		100	0	21.68	21.93	21.77
	16QAM	1	0	21.63	21.88	21.72
		1	50	21.60	21.85	21.69
		1	99	21.59	21.84	21.68
		50	0	20.71	20.96	20.80
		50	25	20.70	20.95	20.79
		50	50	20.65	20.90	20.74
		100	0	20.63	20.88	20.72
	64QAM	1	0	20.49	20.79	20.59
		1	50	20.44	20.82	20.61
		1	99	20.51	20.67	20.57
		50	0	19.65	19.92	19.62
		50	25	19.52	19.77	19.65
		50	50	19.55	19.74	19.55
		100	0	19.56	19.70	19.71

Band/BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz
4/1.4	QPSK	1	0	22.85	22.74	22.66
		1	2	22.84	22.73	22.65
		1	5	22.81	22.70	22.62
		3	0	22.83	22.72	22.64
		3	1	22.82	22.71	22.63
		3	3	22.79	22.68	22.60
		6	0	21.91	21.80	21.72
	16QAM	1	0	21.86	21.75	21.67
		1	2	21.83	21.72	21.64
		1	5	21.82	21.71	21.63
		3	0	21.85	21.74	21.66
		3	1	21.82	21.71	21.63
		3	3	21.81	21.70	21.62
		6	0	20.86	20.75	20.67
	64QAM	1	0	20.67	20.58	20.54
		1	2	20.75	20.62	20.64
		1	5	20.66	20.62	20.44
		3	0	20.74	20.60	20.48
		3	1	20.69	20.52	20.52
		3	3	20.67	20.51	20.43
		6	0	19.86	19.68	19.61

Band/BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz
4/3	QPSK	1	0	22.86	22.75	22.67
		1	7	22.85	22.74	22.66
		1	14	22.82	22.71	22.63
		8	0	21.91	21.80	21.72
		8	3	21.89	21.78	21.70
		8	7	21.84	21.73	21.65
		15	0	21.92	21.81	21.73
	16QAM	1	0	21.87	21.76	21.68
		1	7	21.84	21.73	21.65
		1	14	21.83	21.72	21.64
		8	0	20.95	20.84	20.76
		8	3	20.94	20.83	20.75
		8	7	20.89	20.78	20.70
		15	0	20.87	20.76	20.68
	64QAM	1	0	20.77	20.68	20.53
		1	7	20.79	20.66	20.49
		1	14	20.82	20.70	20.45
		8	0	19.87	19.75	19.75
		8	3	19.89	19.72	19.59
		8	7	19.81	19.76	19.63
		15	0	19.75	19.61	19.59

Band/BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375
---------	------------	---------	-----------	-----------------	-----------------	------------------

				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz
4/5	QPSK	1	0	22.89	22.78	22.70
		1	12	22.88	22.77	22.69
		1	24	22.85	22.74	22.66
		12	0	21.94	21.83	21.75
		12	6	21.92	21.81	21.73
		12	13	21.87	21.76	21.68
		25	0	21.95	21.84	21.76
	16QAM	1	0	21.90	21.79	21.71
		1	12	21.87	21.76	21.68
		1	24	21.86	21.75	21.67
		12	0	20.98	20.87	20.79
		12	6	20.97	20.86	20.78
		12	13	20.92	20.81	20.73
		25	0	20.90	20.79	20.71
	64QAM	1	0	20.74	20.64	20.55
		1	12	20.69	20.74	20.54
		1	24	20.68	20.64	20.52
		12	0	19.83	19.67	19.61
		12	6	19.93	19.67	19.62
		12	13	19.84	19.65	19.69
		25	0	19.89	19.66	19.57

Band/BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz
4/10	QPSK	1	0	22.93	22.82	22.74
		1	24	22.92	22.81	22.73
		1	49	22.89	22.78	22.70
		25	0	21.98	21.87	21.79
		25	12	21.96	21.85	21.77
		25	25	21.91	21.80	21.72
		50	0	21.99	21.88	21.80
	16QAM	1	0	21.94	21.83	21.75
		1	24	21.91	21.80	21.72
		1	49	21.90	21.79	21.71
		25	0	21.02	20.91	20.83
		25	12	21.01	20.90	20.82
		25	25	20.96	20.85	20.77
		50	0	20.94	20.83	20.75
	64QAM	1	0	20.84	20.76	20.68
		1	24	20.73	20.69	20.52
		1	49	20.88	20.62	20.55
		25	0	19.92	19.73	19.65
		25	12	19.97	19.89	19.68
		25	25	19.81	19.67	19.64
		50	0	19.89	19.71	19.63

Band/BW	Modulation	RB Size	RB Offset	Low CH 20025	Mid CH 20175	High CH 20325
				Frequency 1717.5 MHz	Frequency 1732.5 MHz	Frequency 1747.5 MHz
4/15	QPSK	1	0	22.99	22.88	22.80
		1	37	22.98	22.87	22.79
		1	74	22.95	22.84	22.76
		36	0	22.04	21.93	21.85
		36	19	22.02	21.91	21.83
		36	39	21.97	21.86	21.78
		75	0	22.05	21.94	21.86
	16QAM	1	0	22.00	21.89	21.81
		1	37	21.97	21.86	21.78
		1	74	21.96	21.85	21.77
		36	0	21.08	20.97	20.89
		36	19	21.07	20.96	20.88
		36	39	21.02	20.91	20.83
		75	0	21.00	20.89	20.81
	64QAM	1	0	22.00	21.89	21.81
		1	37	21.97	21.86	21.78
		1	74	21.96	21.85	21.77
		36	0	21.08	20.97	20.89
		36	19	21.07	20.96	20.88
		36	39	21.02	20.91	20.83
		75	0	21.00	20.89	20.81

Band/BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz
4/20	QPSK	1	0	23.02	22.91	22.83
		1	50	23.01	22.90	22.82
		1	99	22.98	22.87	22.79
		50	0	22.07	21.96	21.88
		50	25	22.05	21.94	21.86
		50	50	22.00	21.89	21.81
		100	0	22.08	21.97	21.89
	16QAM	1	0	22.03	21.92	21.84
		1	50	22.00	21.89	21.81
		1	99	21.99	21.88	21.80
		50	0	21.11	21.00	20.92
		50	25	21.10	20.99	20.91
		50	50	21.05	20.94	20.86
		100	0	21.03	20.92	20.84
	64QAM	1	0	20.94	20.74	20.71
		1	50	20.97	20.77	20.72
		1	99	20.84	20.82	20.66
		50	0	20.05	19.99	19.80
		50	25	19.94	19.96	19.85
		50	50	20.00	19.90	19.84
		100	0	19.90	19.86	19.76

Band/BW	Modulation	RB Size	RB Offset	Low CH 26697	Mid CH (26915)	High CH 27033
				Frequency (824.7) MHz	Frequency (836.5)MHz	Frequency (848.3) MHz
5/1.4	QPSK	1	0	22.85	23.14	22.92
		1	2	22.84	23.13	22.91
		1	5	22.81	23.10	22.88
		3	0	22.83	23.12	22.90
		3	1	22.82	23.11	22.89
		3	3	22.79	23.08	22.86
		6	0	21.91	22.20	21.98
	16QAM	1	0	21.86	22.15	21.93
		1	2	21.83	22.12	21.90
		1	5	21.82	22.11	21.89
		3	0	21.85	22.14	21.92
		3	1	21.82	22.11	21.89
		3	3	21.81	22.10	21.88
		6	0	20.86	21.15	20.93
	64QAM	1	0	20.74	21.07	20.82
		1	2	20.74	20.97	20.77
		1	5	20.63	20.95	20.85
		3	0	20.66	21.04	20.87
		3	1	20.64	20.99	20.73
		3	3	20.70	21.06	20.78
		6	0	19.70	19.96	19.74

Band/BW	Modulation	RB Size	RB Offset	Low CH (26805)	Mid CH (26915)	High CH (27025)
				Frequency (825.5)MHz	Frequency (836.5)MHz	Frequency (847.5)MHz
5/3	QPSK	1	0	22.89	23.18	22.96
		1	7	22.88	23.17	22.95
		1	14	22.85	23.14	22.92
		8	0	21.94	22.23	22.01
		8	3	21.92	22.21	21.99
		8	7	21.87	22.16	21.94
		15	0	21.95	22.24	22.02
	16QAM	1	0	21.90	22.19	21.97
		1	7	21.87	22.16	21.94
		1	14	21.86	22.15	21.93
		8	0	20.98	21.27	21.05
		8	3	20.97	21.26	21.04
		8	7	20.92	21.21	20.99
		15	0	20.90	21.19	20.97
	64QAM	1	0	20.84	21.06	20.79
		1	7	20.68	21.11	20.82
		1	14	20.72	21.10	20.83
		8	0	19.93	20.20	19.99
		8	3	19.91	20.19	19.85
		8	7	19.85	20.17	19.86
		15	0	19.87	20.09	19.90

FCC SAR Test Report

Band/BW	Modulation	RB Size	RB Offset	Low CH (26805)	Mid CH (26915)	High CH (27025)
				Frequency (825.5)MHz	Frequency (836.5)MHz	Frequency (847.5)MHz
5/5	QPSK	1	0	22.95	23.24	23.02
		1	12	22.94	23.23	23.01
		1	24	22.91	23.20	22.98
		12	0	22.00	22.29	22.07
		12	6	21.98	22.27	22.05
		12	13	21.93	22.22	22.00
		25	0	22.01	22.30	22.08
	16QAM	1	0	21.96	22.25	22.03
		1	12	21.93	22.22	22.00
		1	24	21.92	22.21	21.99
		12	0	21.04	21.33	21.11
		12	6	21.03	21.32	21.10
		12	13	20.98	21.27	21.05
		25	0	20.96	21.25	21.03
	64QAM	1	0	20.88	21.11	21.02
		1	12	20.77	21.16	20.93
		1	24	20.76	21.11	20.96
		12	0	19.86	20.29	20.06
		12	6	19.89	20.26	20.03
		12	13	19.91	20.07	19.87
		25	0	19.91	20.11	19.94

Band/BW	Modulation	RB Size	RB Offset	Low CH (26840)	Mid CH (26915)	High CH (26990)
				Frequency (829)MHz	Frequency (836.5)MHz	Frequency (844)MHz
5/10	QPSK	1	0	22.98	23.27	23.05
		1	24	22.97	23.26	23.04
		1	49	22.94	23.23	23.01
		25	0	22.03	22.32	22.10
		25	12	22.01	22.30	22.08
		25	25	21.96	22.25	22.03
		50	0	22.04	22.33	22.11
	16QAM	1	0	21.99	22.28	22.06
		1	24	21.96	22.25	22.03
		1	49	21.95	22.24	22.02
		25	0	21.07	21.36	21.14
		25	12	21.06	21.35	21.13
		25	25	21.01	21.30	21.08
		50	0	20.99	21.28	21.06
	64QAM	1	0	20.84	21.26	21.05
		1	24	20.90	21.22	20.91
		1	49	20.81	21.13	20.95
		25	0	20.06	20.25	19.97
		25	12	19.89	20.16	20.12
		25	25	19.86	20.14	20.06
		50	0	19.79	20.17	19.99

Band/BW	Modulation	RB Size	RB Offset	Low CH 20775	Mid CH 21100	High CH 21425
				Frequency 2502.5 MHz	Frequency 2535 MHz	Frequency 2567.5 MHz
7/5	QPSK	1	0	21.56	21.31	21.04
		1	12	21.55	21.30	21.03
		1	24	21.52	21.27	21.00
		12	0	20.61	20.36	20.09
		12	6	20.59	20.34	20.07
		12	13	20.54	20.29	20.02
		25	0	20.62	20.37	20.10
	16QAM	1	0	20.57	20.32	20.05
		1	12	20.54	20.29	20.02
		1	24	20.53	20.28	20.01
		12	0	19.65	19.40	19.13
		12	6	19.64	19.39	19.12
		12	13	19.59	19.34	19.07
		25	0	19.57	19.32	19.05
	64QAM	1	0	19.40	19.16	18.98
		1	12	19.54	19.21	18.91
		1	24	19.36	19.25	18.91
		12	0	18.48	18.25	18.12
		12	6	18.64	18.34	17.94
		12	13	18.55	18.21	18.01
		25	0	18.38	18.16	18.03

Band/BW	Modulation	RB Size	RB Offset	Low CH 20800	Mid CH 21100	High CH 21400
				Frequency 2505 MHz	Frequency 2535 MHz	Frequency 2565 MHz
7/10	QPSK	1	0	21.60	21.35	21.08
		1	24	21.59	21.34	21.07
		1	49	21.56	21.31	21.04
		25	0	20.65	20.40	20.13
		25	12	20.63	20.38	20.11
		25	25	20.58	20.33	20.06
		50	0	20.66	20.41	20.14
	16QAM	1	0	20.61	20.36	20.09
		1	24	20.58	20.33	20.06
		1	49	20.57	20.32	20.05
		25	0	19.69	19.44	19.17
		25	12	19.68	19.43	19.16
		25	25	19.63	19.38	19.11
		50	0	19.61	19.36	19.09
	64QAM	1	0	19.51	19.17	18.93
		1	24	19.56	19.21	18.89
		1	49	19.41	19.18	18.93
		25	0	18.60	18.35	18.09
		25	12	18.63	18.30	18.07
		25	25	18.47	18.28	17.99
		50	0	18.56	18.26	17.94

Band/BW	Modulation	RB Size	RB Offset	Low CH 20825	Mid CH 21100	High CH 21375
				Frequency 2507.5 MHz	Frequency 2535 MHz	Frequency 2562.5 MHz
7/15	QPSK	1	0	21.66	21.41	21.14
		1	37	21.65	21.40	21.13
		1	74	21.62	21.37	21.10
		36	0	20.71	20.46	20.19
		36	19	20.69	20.44	20.17
		36	39	20.64	20.39	20.12
		75	0	20.72	20.47	20.20
	16QAM	1	0	20.67	20.42	20.15
		1	37	20.64	20.39	20.12
		1	74	20.63	20.38	20.11
		36	0	19.75	19.50	19.23
		36	19	19.74	19.49	19.22
		36	39	19.69	19.44	19.17
		75	0	19.67	19.42	19.15
	64QAM	1	0	19.65	19.38	18.97
		1	37	19.51	19.34	18.94
		1	74	19.55	19.19	18.99
		36	0	18.73	18.32	18.18
		36	19	18.58	18.34	18.21
		36	39	18.58	18.41	17.98
		75	0	18.63	18.25	18.04

Band/BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz
7/20	QPSK	1	0	21.69	21.44	21.17
		1	50	21.68	21.43	21.16
		1	99	21.65	21.40	21.13
		50	0	20.74	20.49	20.22
		50	25	20.72	20.47	20.20
		50	50	20.67	20.42	20.15
		100	0	20.75	20.50	20.23
	16QAM	1	0	20.70	20.45	20.18
		1	50	20.67	20.42	20.15
		1	99	20.66	20.41	20.14
		50	0	19.78	19.53	19.26
		50	25	19.77	19.52	19.25
		50	50	19.72	19.47	19.20
		100	0	19.70	19.45	19.18
	64QAM	1	0	19.55	19.40	19.11
		1	50	19.54	19.37	19.08
		1	99	19.50	19.40	19.13
		50	0	18.75	18.41	18.14
		50	25	18.74	18.52	18.16
		50	50	18.54	18.39	18.11
		100	0	18.63	18.29	18.01

Band/BW	Modulation	RB Size	RB Offset	Low CH 23017	Mid CH 23095	High CH 23173
				Frequency 699.7 MHz	Frequency 707.5 MHz	Frequency 715.3 MHz
12/1.4	QPSK	1	0	23.29	23.14	22.92
		1	2	23.28	23.13	22.91
		1	5	23.25	23.10	22.88
		3	0	23.27	23.12	22.90
		3	1	23.26	23.11	22.89
		3	3	23.23	23.08	22.86
		6	0	22.30	22.16	21.93
	16QAM	1	0	22.25	22.11	21.88
		1	2	22.22	22.08	21.85
		1	5	22.21	22.07	21.84
		3	0	22.24	22.10	21.87
		3	1	22.21	22.07	21.84
		3	3	22.20	22.06	21.83
		6	0	21.25	21.11	20.88
	64QAM	1	0	21.18	21.04	20.72
		1	2	21.04	20.90	20.66
		1	5	21.06	20.94	20.74
		3	0	21.09	21.01	20.86
		3	1	21.06	20.87	20.78
		3	3	21.13	20.91	20.76
		6	0	20.18	20.04	19.86

Band/BW	Modulation	RB Size	RB Offset	Low CH 23025	Mid CH 23095	High CH 23165
				Frequency 700.5 MHz	Frequency 707.5 MHz	Frequency 714.5 MHz
12/3	QPSK	1	0	23.33	23.18	22.96
		1	7	23.32	23.17	22.95
		1	14	23.29	23.14	22.92
		8	0	22.33	22.19	21.96
		8	3	22.31	22.17	21.94
		8	7	22.26	22.12	21.89
		15	0	22.34	22.20	21.97
	16QAM	1	0	22.29	22.15	21.92
		1	7	22.26	22.12	21.89
		1	14	22.25	22.11	21.88
		8	0	21.37	21.23	21.00
		8	3	21.36	21.22	20.99
		8	7	21.31	21.17	20.94
		15	0	21.29	21.15	20.92
	64QAM	1	0	21.13	21.03	20.91
		1	7	21.15	20.96	20.82
		1	14	21.14	21.09	20.85
		8	0	20.20	20.20	19.95
		8	3	20.29	20.08	19.85
		8	7	20.13	20.16	19.75
		15	0	20.18	20.03	19.87

Band/BW	Modulation	RB Size	RB Offset	Low CH 23035	Mid CH 23095	High CH 23155
				Frequency 701.5 MHz	Frequency 707.5 MHz	Frequency 713.5 MHz
12/5	QPSK	1	0	23.39	23.24	23.02
		1	12	23.38	23.23	23.01
		1	24	23.35	23.20	22.98
		12	0	22.39	22.25	22.02
		12	6	22.37	22.23	22.00
		12	13	22.32	22.18	21.95
		25	0	22.40	22.26	22.03
	16QAM	1	0	22.35	22.21	21.98
		1	12	22.32	22.18	21.95
		1	24	22.31	22.17	21.94
		12	0	21.43	21.29	21.06
		12	6	21.42	21.28	21.05
		12	13	21.37	21.23	21.00
		25	0	21.35	21.21	20.98
	64QAM	1	0	21.32	21.04	20.81
		1	12	21.23	21.14	20.94
		1	24	21.25	21.10	20.81
		12	0	20.37	20.25	19.98
		12	6	20.26	20.11	19.97
		12	13	20.33	20.23	19.85
		25	0	20.32	20.12	19.97

Band/BW	Modulation	RB Size	RB Offset	Low CH 23060	Mid CH 23095	High CH 23130
				Frequency 704 MHz	Frequency 707.5 MHz	Frequency 711 MHz
12/10	QPSK	1	0	23.42	23.27	23.05
		1	24	23.41	23.26	23.04
		1	49	23.38	23.23	23.01
		25	0	22.42	22.28	22.05
		25	12	22.40	22.26	22.03
		25	25	22.35	22.21	21.98
		50	0	22.43	22.29	22.06
	16QAM	1	0	22.38	22.24	22.01
		1	24	22.35	22.21	21.98
		1	49	22.34	22.20	21.97
		25	0	21.46	21.32	21.09
		25	12	21.45	21.31	21.08
		25	25	21.40	21.26	21.03
		50	0	21.38	21.24	21.01
	64QAM	1	0	21.21	21.24	20.99
		1	24	21.26	21.15	20.87
		1	49	21.27	21.00	20.90
		25	0	20.31	20.20	20.07
		25	12	20.39	20.25	19.91
		25	25	20.34	20.06	19.84
		50	0	20.20	20.14	19.90

FCC SAR Test Report

Band/BW	Modulation	RB Size	RB Offset	Low CH 23205	Mid CH 23230	High CH 23255
				Frequency 779.5 MHz	Frequency 782.0 MHz	Frequency 784.5 MHz
13/5	QPSK	1	0	22.24	23.46	22.08
		1	12	22.68	23.45	22.07
		1	24	22.65	23.42	22.04
		12	0	21.75	22.51	21.13
		12	6	21.74	22.49	21.11
		12	13	21.62	22.44	21.06
		25	0	21.73	22.52	21.14
	16QAM	1	0	21.64	22.47	21.09
		1	12	21.68	22.44	21.06
		1	24	21.67	22.43	21.05
		12	0	20.74	21.55	20.17
		12	6	20.79	21.54	20.16
		12	13	20.68	21.49	20.11
		25	0	20.73	21.47	20.09
	64QAM	1	0	20.57	21.43	20.04
		1	12	20.62	21.36	19.89
		1	24	20.58	21.41	19.86
		12	0	19.62	20.39	19.06
		12	6	19.71	20.51	19.00
		12	13	19.62	20.31	18.94
		25	0	19.73	20.33	19.05

Band/BW	Modulation	RB Size	RB Offset	/	Mid CH 23230	/
				/	Frequency 782.0 MHz	/
13/10	QPSK	1	0	/	23.49	/
		1	24	/	23.48	/
		1	49	/	23.45	/
		25	0	/	22.43	/
		25	12	/	22.41	/
		25	25	/	22.36	/
		50	0	/	22.44	/
	16QAM	1	0	/	22.39	/
		1	24	/	22.36	/
		1	49	/	22.35	/
		25	0	/	21.47	/
		25	12	/	21.46	/
		25	25	/	21.41	/
		50	0	/	21.39	/
	64QAM	1	0	/	21.29	/
		1	24	/	21.19	/
		1	49	/	21.25	/
		25	0	/	20.45	/
		25	12	/	20.43	/
		25	25	/	20.22	/
		50	0	/	20.34	/

Band/BW	Modulation	RB Size	RB Offset	Low CH 26697	Mid CH 26865	High CH 27033
				Frequency 814.7 MHz	Frequency 831.5 MHz	Frequency 848.3 MHz
26/1.4	QPSK	1	0	23.10	23.23	22.85
		1	2	23.09	23.22	22.84
		1	5	23.06	23.19	22.81
		3	0	23.08	23.21	22.83
		3	1	23.07	23.20	22.82
		3	3	23.04	23.17	22.79
		6	0	22.16	22.29	21.91
	16QAM	1	0	22.11	22.24	21.86
		1	2	22.08	22.21	21.83
		1	5	22.07	22.20	21.82
		3	0	22.10	22.23	21.85
		3	1	22.07	22.20	21.82
		3	3	22.06	22.19	21.81
		6	0	21.11	21.24	20.86
	64QAM	1	0	21.09	21.14	20.75
		1	2	21.00	21.19	20.66
		1	5	21.02	21.03	20.78
		3	0	20.97	21.16	20.80
		3	1	20.91	21.16	20.67
		3	3	20.91	21.10	20.76
		6	0	20.08	20.15	19.84

Band/BW	Modulation	RB Size	RB Offset	Channel 26705	Channel 26865	Channel 27025
				Frequency 815.5 MHz	Frequency 831.5 MHz	Frequency 847.5 MHz
26/3	QPSK	1	0	23.11	23.24	22.86
		1	7	23.10	23.23	22.85
		1	14	23.07	23.20	22.82
		8	0	22.16	22.29	21.91
		8	3	22.14	22.27	21.89
		8	7	22.09	22.22	21.84
		15	0	22.17	22.30	21.92
	16QAM	1	0	22.12	22.25	21.87
		1	7	22.09	22.22	21.84
		1	14	22.08	22.21	21.83
		8	0	21.20	21.33	20.95
		8	3	21.19	21.32	20.94
		8	7	21.14	21.27	20.89
		15	0	21.12	21.25	20.87
	64QAM	1	0	20.98	21.22	20.73
		1	7	21.04	21.18	20.69
		1	14	21.04	21.05	20.73
		8	0	20.17	20.20	19.80
		8	3	20.03	20.24	19.83
		8	7	19.95	20.19	19.87
		15	0	19.96	20.18	19.83

Band/BW	Modulation	RB Size	RB Offset	Channel 26715	Channel 26865	Channel 27015
				Frequency 816.5 MHz	Frequency 831.5 MHz	Frequency 846.5 MHz
26/5	QPSK	1	0	23.13	23.26	22.88
		1	12	23.12	23.25	22.87
		1	24	23.09	23.22	22.84
		12	0	22.18	22.31	21.93
		12	6	22.16	22.29	21.91
		12	13	22.11	22.24	21.86
		25	0	22.19	22.32	21.94
	16QAM	1	0	22.14	22.27	21.89
		1	12	22.11	22.24	21.86
		1	24	22.10	22.23	21.85
		12	0	21.22	21.35	20.97
		12	6	21.21	21.34	20.96
		12	13	21.16	21.29	20.91
		25	0	21.14	21.27	20.89
	64QAM	1	0	21.08	21.13	20.89
		1	12	20.99	21.21	20.84
		1	24	20.97	21.18	20.66
		12	0	20.18	20.26	19.92
		12	6	20.09	20.32	19.80
		12	13	20.02	20.18	19.71
		25	0	19.97	20.24	19.84

Band/BW	Modulation	RB Size	RB Offset	Channel 26740	Channel 26865	Channel 26990
				Frequency 819 MHz	Frequency 831.5 MHz	Frequency 844 MHz
26/10	QPSK	1	0	23.15	23.28	22.90
		1	24	23.14	23.27	22.89
		1	49	23.11	23.24	22.86
		25	0	22.20	22.33	21.95
		25	12	22.18	22.31	21.93
		25	25	22.13	22.26	21.88
		50	0	22.21	22.34	21.96
	16QAM	1	0	22.16	22.29	21.91
		1	24	22.13	22.26	21.88
		1	49	22.12	22.25	21.87
		25	0	21.24	21.37	20.99
		25	12	21.23	21.36	20.98
		25	25	21.18	21.31	20.93
		50	0	21.16	21.29	20.91
	64QAM	1	0	21.15	21.13	20.83
		1	24	21.10	21.09	20.86
		1	49	20.98	21.09	20.80
		25	0	20.13	20.30	19.98
		25	12	20.18	20.33	19.98
		25	25	20.05	20.30	19.80
		50	0	20.16	20.10	19.76

Band/BW	Modulation	RB Size	RB Offset	Channel 26765	Channel 26865	Channel 26965
				Frequency 821.5 MHz	Frequency 831.5 MHz	Frequency 841.5 MHz
26/15	QPSK	1	0	23.17	23.30	22.92
		1	24	23.16	23.29	22.91
		1	49	23.13	23.26	22.88
		25	0	22.22	22.35	21.97
		25	12	22.20	22.33	21.95
		25	25	22.15	22.28	21.90
		50	0	22.23	22.36	21.98
	16QAM	1	0	22.18	22.31	21.93
		1	24	22.15	22.28	21.90
		1	49	22.14	22.27	21.89
		25	0	21.26	21.39	21.01
		25	12	21.25	21.38	21.00
		25	25	21.20	21.33	20.95
		50	0	21.18	21.31	20.93
	64QAM	1	0	21.03	21.14	20.88
		1	24	21.00	21.11	20.77
		1	49	21.04	21.18	20.77
		25	0	20.11	20.28	20.00
		25	12	20.06	20.38	19.92
		25	25	20.03	20.15	19.79
		50	0	20.00	20.15	19.80

Band/BW	Modulation	RB Size	RB Offset	Low CH (39675)	Mid CH (40620)	High CH (41565)
				Frequency (2498.5)MHz	Frequency (2593)MHz	Frequency (2687.5)MHz
41/5	QPSK	1	0	21.09	21.34	20.92
		1	12	21.08	21.33	20.91
		1	24	21.05	21.30	20.88
		12	0	20.14	20.39	19.97
		12	6	20.12	20.37	19.95
		12	13	20.07	20.32	19.90
		25	0	20.15	20.40	19.98
	16QAM	1	0	20.10	20.35	19.93
		1	12	20.07	20.32	19.90
		1	24	20.06	20.31	19.89
		12	0	19.18	19.43	19.01
		12	6	19.17	19.42	19.00
		12	13	19.12	19.37	18.95
		25	0	19.10	19.35	18.93
	64QAM	1	0	18.91	19.30	18.92
		1	12	19.05	19.18	18.84
		1	24	19.01	19.31	18.81
		12	0	18.12	18.29	17.90
		12	6	18.03	18.30	17.84
		12	13	18.12	18.20	17.87
		25	0	18.06	18.19	17.91

Band/BW	Modulation	RB Size	RB Offset	Low CH (39700)	Mid CH (40620)	High CH (41540)
				Frequency (2501)MHz	Frequency (2593)MHz	Frequency (2685)MHz
41/10	QPSK	1	0	21.12	21.37	20.95
		1	24	21.11	21.36	20.94
		1	49	21.08	21.33	20.91
		25	0	20.17	20.42	20.00
		25	12	20.15	20.40	19.98
		25	25	20.10	20.35	19.93
		50	0	20.18	20.43	20.01
	16QAM	1	0	20.13	20.38	19.96
		1	24	20.10	20.35	19.93
		1	49	20.09	20.34	19.92
		25	0	19.21	19.46	19.04
		25	12	19.20	19.45	19.03
		25	25	19.15	19.40	18.98
		50	0	19.13	19.38	18.96
	64QAM	1	0	19.11	19.26	18.96
		1	24	19.09	19.27	18.93
		1	49	19.08	19.16	18.89
		25	0	18.03	18.42	17.91
		25	12	18.15	18.44	18.01
		25	25	17.97	18.40	17.82
		50	0	17.97	18.20	17.82

Band/BW	Modulation	RB Size	RB Offset	Low CH (39725)	Mid CH (40620)	High CH (41515)
				Frequency (2503.5)MHz	Frequency (2593)MHz	Frequency (2682.5)MHz
41/15	QPSK	1	0	21.16	21.41	20.99
		1	37	21.15	21.40	20.98
		1	74	21.12	21.37	20.95
		36	0	20.21	20.46	20.04
		36	19	20.19	20.44	20.02
		36	39	20.14	20.39	19.97
		75	0	20.22	20.47	20.05
	16QAM	1	0	20.17	20.42	20.00
		1	37	20.14	20.39	19.97
		1	74	20.13	20.38	19.96
		36	0	19.25	19.50	19.08
		36	19	19.24	19.49	19.07
		36	39	19.19	19.44	19.02
		75	0	19.17	19.42	19.00
	64QAM	1	0	19.11	19.32	18.90
		1	37	18.96	19.30	18.82
		1	74	18.95	19.38	18.89
		36	0	18.07	18.31	17.94
		36	19	18.24	18.46	18.01
		36	39	18.07	18.26	17.96
		75	0	18.14	18.23	17.81

Band/BW	Modulation	RB Size	RB Offset	Low CH (39750)	Mid CH (40620)	High CH (41490)
				Frequency (2506)MHz	Frequency (2593)MHz	Frequency (2680)MHz
41/20	QPSK	1	0	21.22	21.47	21.05
		1	50	21.21	21.46	21.04
		1	99	21.18	21.43	21.01
		50	0	20.27	20.52	20.10
		50	25	20.25	20.50	20.08
		50	50	20.20	20.45	20.03
		100	0	20.28	20.53	20.11
	16QAM	1	0	20.23	20.48	20.06
		1	50	20.20	20.45	20.03
		1	99	20.19	20.44	20.02
		50	0	19.31	19.56	19.14
		50	25	19.30	19.55	19.13
		50	50	19.25	19.50	19.08
		100	0	19.23	19.48	19.06
	64QAM	1	0	19.04	19.45	18.89
		1	50	19.00	19.30	19.03
		1	99	19.12	19.32	18.82
		50	0	18.25	18.45	18.01
		50	25	18.20	18.50	17.98
		50	50	18.19	18.48	18.07
		100	0	18.19	18.47	18.08

Band/BW	Modulation	RB Size	RB Offset	Low CH (131979)	Mid CH (132322)	High CH (132665)
				Frequency (1710.7)MHz	Frequency (1745)MHz	Frequency (1779.3)MHz
66/1.4	QPSK	1	0	22.83	22.68	22.37
		1	2	22.69	22.67	22.42
		1	5	22.79	22.56	22.38
		3	0	21.79	21.65	21.47
		3	1	21.82	21.65	21.39
		3	3	21.71	21.65	21.41
		6	0	21.89	21.73	21.44
	16QAM	1	0	21.79	21.73	21.49
		1	2	21.77	21.66	21.39
		1	5	21.68	21.67	21.39
		3	0	20.88	20.71	20.47
		3	1	20.89	20.78	20.45
		3	3	20.82	20.66	20.37
		6	0	20.83	20.74	20.47
	64QAM	1	0	20.72	20.62	20.34
		1	2	20.61	20.52	20.27
		1	5	20.73	20.58	20.23
		3	0	19.89	19.65	19.50
		3	1	19.75	19.54	19.42
		3	3	19.60	19.56	19.35
		6	0	19.65	19.50	19.32

FCC SAR Test Report

Band/BW	Modulation	RB Size	RB Offset	Low CH (131987)	Mid CH (132422)	High CH (132657)
				Frequency (1711.5)MHz	Frequency (1745)MHz	Frequency (1778.5)MHz
66/3	QPSK	1	0	22.87	22.70	22.45
		1	7	22.79	22.71	22.44
		1	14	22.80	22.65	22.39
		8	0	21.86	21.70	21.52
		8	3	21.89	21.75	21.49
		8	7	21.81	21.70	21.44
		15	0	21.90	21.78	21.50
	16QAM	1	0	21.89	21.74	21.52
		1	7	21.86	21.68	21.41
		1	14	21.76	21.71	21.45
		8	0	20.95	20.74	20.51
		8	3	20.97	20.79	20.53
		8	7	20.83	20.68	20.46
		15	0	20.83	20.74	20.47
	64QAM	1	0	20.72	20.72	20.39
		1	7	20.67	20.61	20.31
		1	14	20.82	20.65	20.25
		8	0	19.93	19.73	19.57
		8	3	19.77	19.60	19.49
		8	7	19.67	19.62	19.35
		15	0	19.70	19.59	19.37

Band/BW	Modulation	RB Size	RB Offset	Low CH (131997)	Mid CH (132422)	High CH (132647)
				Frequency (1712.5)MHz	Frequency (1745)MHz	Frequency (1777.5)MHz
66/5	QPSK	1	0	22.89	22.74	22.52
		1	12	22.88	22.73	22.51
		1	24	22.85	22.70	22.48
		12	0	21.94	21.79	21.57
		12	6	21.92	21.77	21.55
		12	13	21.87	21.72	21.50
		25	0	21.95	21.80	21.58
	16QAM	1	0	21.90	21.75	21.53
		1	12	21.87	21.72	21.50
		1	24	21.86	21.71	21.49
		12	0	20.98	20.83	20.61
		12	6	20.97	20.82	20.60
		12	13	20.92	20.77	20.55
		25	0	20.90	20.75	20.53
	64QAM	1	0	20.72	20.73	20.46
		1	12	20.76	20.71	20.39
		1	24	20.84	20.66	20.34
		12	0	19.94	19.80	19.59
		12	6	19.82	19.68	19.51
		12	13	19.73	19.68	19.45
		25	0	19.75	19.64	19.42

Band/BW	Modulation	RB Size	RB Offset	Low CH (131997)	Mid CH (132422)	High CH (132647)
				Frequency (1715)MHz	Frequency (1745)MHz	Frequency (1775)MHz
66/10	QPSK	1	0	22.92	22.77	22.55
		1	24	22.91	22.76	22.54
		1	49	22.88	22.73	22.51
		25	0	21.97	21.82	21.60
		25	12	21.95	21.80	21.58
		25	25	21.90	21.75	21.53
		50	0	21.98	21.83	21.61
	16QAM	1	0	21.93	21.78	21.56
		1	24	21.90	21.75	21.53
		1	49	21.89	21.74	21.52
		25	0	21.01	20.86	20.64
		25	12	21.00	20.85	20.63
		25	25	20.95	20.80	20.58
		50	0	20.93	20.78	20.56
	64QAM	1	0	20.84	20.76	20.48
		1	24	20.86	20.67	20.41
		1	49	20.80	20.62	20.33
		25	0	19.97	19.70	19.46
		25	12	19.86	19.68	19.52
		25	25	19.75	19.71	19.57
		50	0	19.76	19.66	19.44

Band/BW	Modulation	RB Size	RB Offset	Low CH (132047)	Mid CH (132422)	High CH (132665)
				Frequency (1717.5)MHz	Frequency (1745)MHz	Frequency (1772.5)MHz
66/15	QPSK	1	0	22.96	22.81	22.59
		1	50	22.95	22.80	22.58
		1	99	22.92	22.77	22.55
		50	0	22.01	21.86	21.64
		50	25	21.99	21.84	21.62
		50	50	21.94	21.79	21.57
		100	0	22.02	21.87	21.65
	16QAM	1	0	21.97	21.82	21.60
		1	50	21.94	21.79	21.57
		1	99	21.93	21.78	21.56
		50	0	21.05	20.90	20.68
		50	25	21.04	20.89	20.67
		50	50	20.99	20.84	20.62
		100	0	20.97	20.82	20.60
	64QAM	1	0	20.84	20.69	20.56
		1	50	20.82	20.72	20.38
		1	99	20.78	20.73	20.38
		50	0	20.00	19.84	19.54
		50	25	19.92	19.75	19.62
		50	50	19.84	19.78	19.62
		100	0	19.92	19.70	19.51

Band/BW	Modulation	RB Size	RB Offset	Low CH (132072)	Mid CH (132422)	High CH (132572)
				Frequency (1720)MHz	Frequency (1745)MHz	Frequency (1770)MHz
66/20	QPSK	1	0	23.02	22.87	22.65
		1	37	23.01	22.86	22.64
		1	74	22.98	22.83	22.61
		36	0	22.07	21.92	21.70
		36	19	22.05	21.90	21.68
		36	39	22.00	21.85	21.63
		75	0	22.08	21.93	21.71
	16QAM	1	0	22.03	21.88	21.66
		1	37	22.00	21.85	21.63
		1	74	21.99	21.84	21.62
		36	0	21.11	20.96	20.74
		36	19	21.10	20.95	20.73
		36	39	21.05	20.90	20.68
		75	0	21.03	20.88	20.66
	64QAM	1	0	20.89	20.82	20.56
		1	37	20.80	20.68	20.52
		1	74	20.87	20.76	20.46
		36	0	19.97	19.81	19.66
		36	19	19.94	19.88	19.54
		36	39	19.93	19.83	19.59
		75	0	19.87	19.78	19.60

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+20	QPSK	0	0	1	99	24.39	24.45	24.47
		1	99	0	0	24.88	24.85	24.91
		100	0	0	0	23.88	23.71	23.93
		100	0	100	0	22.82	23.24	24.24
		1	0	1	99	19.47	19.57	19.49
		1	0	1	0	19.87	20.06	19.93
		1	99	1	0	24.14	24.50	24.15
		100	0	1	99	20.96	21.01	20.80
	16QAM	0	0	1	99	23.87	23.84	23.77
		1	99	0	0	24.36	24.41	24.28
		100	0	0	0	22.84	22.95	22.82
		100	0	100	0	22.40	22.34	23.56
		1	0	1	99	19.56	19.56	19.42
		1	0	1	0	20.05	19.97	19.94
		1	99	1	0	23.94	23.77	23.65
	64QAM	0	0	1	99	20.83	20.82	20.74
		1	99	0	0	22.78	22.77	22.83
		100	0	0	0	23.19	23.32	23.34
		100	0	100	0	21.99	21.81	22.00
		1	0	1	99	21.16	21.44	20.25
		1	0	1	0	18.18	18.23	18.35
		1	99	1	0	18.68	18.73	18.64
		100	0	1	99	20.21	20.57	20.41

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+15	QPSK	100	0	75	0	22.82	22.66	22.64
		1	0	1	74	19.37	19.28	19.51
		1	99	1	0	24.35	24.29	24.21
	16QAM	100	0	75	0	22.31	22.15	22.22
		1	0	1	74	19.51	19.60	19.54
		1	99	1	0	23.83	23.92	23.80
	64QAM	100	0	75	0	21.26	21.17	21.22
		1	0	1	74	18.17	18.18	18.16
		1	99	1	0	20.26	20.59	20.32
15+20	QPSK	75	0	100	0	22.65	22.49	22.60
		1	74	1	0	19.42	19.18	19.28
		1	0	1	99	24.26	24.21	24.18
	16QAM	75	0	100	0	22.34	22.16	22.18
		1	74	1	0	19.44	19.54	19.58
		1	0	1	99	23.89	23.87	23.69
	64QAM	75	0	100	0	21.27	21.13	21.04
		1	74	1	0	18.13	18.21	18.15
		1	0	1	99	20.16	20.50	20.42

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
15+15	QPSK	75	0	75	0	22.74	22.69	22.68
		1	0	1	0	19.51	19.28	19.42
		1	74	1	74	24.34	24.33	24.31
	16QAM	75	0	75	0	22.27	22.22	22.23
		1	0	1	0	19.51	19.43	19.42
		1	74	1	74	23.87	23.90	23.83
	64QAM	75	0	75	0	21.17	21.09	21.14
		1	0	1	0	18.19	18.07	18.18
		1	74	1	74	20.26	20.36	20.35

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
15+10	QPSK	75	0	50	0	22.77	22.59	22.55
		1	0	1	49	19.36	19.33	19.43
		1	74	1	0	24.18	24.21	24.23
	16QAM	75	0	50	0	22.16	22.14	22.16
		1	0	1	49	19.62	19.64	19.59
		1	74	1	0	23.97	23.87	23.85
	64QAM	75	0	50	0	21.02	21.23	21.03
		1	0	1	49	18.20	18.20	18.06
		1	74	1	0	20.31	20.30	20.34

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+10	QPSK	100	0	50	0	22.69	22.58	22.54
		1	0	1	49	19.50	19.28	19.41
		1	99	1	0	24.28	24.23	24.35
	16QAM	100	0	50	0	22.33	22.22	22.11
		1	0	1	49	19.55	19.41	19.50
		1	99	1	0	23.91	23.83	23.73
	64QAM	100	0	50	0	21.09	21.22	21.14
		1	0	1	49	18.25	18.13	18.04
		1	99	1	0	20.14	20.42	20.32
10+20	QPSK	50	0	100	0	22.68	22.61	22.69
		1	49	1	0	19.51	19.38	19.41
		1	0	1	99	24.15	24.13	24.31
	16QAM	50	0	100	0	22.27	22.25	22.20
		1	49	1	0	19.50	19.53	19.61
		1	0	1	99	23.90	23.74	23.81
	64QAM	50	0	100	0	21.07	21.15	21.15
		1	49	1	0	18.23	18.14	18.14
		1	0	1	99	20.29	20.42	20.26

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+20	QPSK	0	0	1	99	25.57	25.53	25.48
		1	99	0	0	25.76	25.65	25.78
		100	0	0	0	24.85	24.76	24.95
		100	0	100	0	23.82	23.81	23.78
		1	0	1	99	21.08	20.81	20.72
		1	0	1	0	21.31	21.25	21.12
		1	99	1	0	25.43	25.47	25.41
		100	0	1	99	21.89	21.89	21.81
	16QAM	0	0	1	99	24.99	25.04	24.99
		1	99	0	0	25.45	25.45	25.47
		100	0	0	0	23.80	23.71	23.76
		100	0	100	0	23.33	23.15	23.08
		1	0	1	99	21.03	20.85	20.82
		1	0	1	0	21.27	21.45	21.17
		1	99	1	0	25.48	25.51	25.51
	64QAM	0	0	1	99	22.11	22.18	21.98
		1	99	0	0	23.83	23.62	23.83
		100	0	0	0	24.32	24.28	24.35
		100	0	100	0	22.74	22.87	23.03
		1	0	1	99	22.45	22.39	22.12
		1	0	1	0	19.68	19.40	19.29
		1	99	1	0	19.80	19.74	19.93
		100	0	1	99	21.05	21.01	21.05

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+15	QPSK	100	0	75	0	23.85	23.82	23.71
		1	0	1	74	21.07	21.04	20.98
		1	99	1	0	25.38	25.28	25.28
	16QAM	100	0	75	0	23.26	23.19	23.06
		1	0	1	74	20.94	20.95	20.91
		1	99	1	0	25.47	25.26	25.44
	64QAM	100	0	75	0	22.43	22.32	22.29
		1	0	1	74	19.65	19.42	19.49
		1	99	1	0	20.92	20.98	21.13
15+20	QPSK	75	0	100	0	23.69	23.71	23.57
		1	74	1	0	20.93	21.00	20.93
		1	0	1	99	25.30	25.14	25.25
	16QAM	75	0	100	0	23.11	23.18	23.24
		1	74	1	0	20.90	20.89	20.90
		1	0	1	99	25.40	25.34	25.41
	64QAM	75	0	100	0	22.32	22.20	22.23
		1	74	1	0	19.52	19.45	19.39
		1	0	1	99	21.03	21.08	20.91

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
15+15	QPSK	75	0	75	0	23.73	23.70	23.66
		1	0	1	0	20.85	20.77	20.95
		1	74	1	74	25.46	25.27	25.20
	16QAM	75	0	75	0	23.08	23.13	23.17
		1	0	1	0	20.89	20.91	20.88
		1	74	1	74	25.44	25.34	25.35
	64QAM	75	0	75	0	22.32	22.17	22.22
		1	0	1	0	19.58	19.43	19.48
		1	74	1	74	21.01	21.10	21.10

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+10	QPSK	100	0	50	0	23.71	23.61	23.58
		1	0	1	49	21.04	20.90	20.98
		1	99	1	0	25.33	25.18	25.30
	16QAM	100	0	50	0	23.18	23.13	23.09
		1	0	1	49	20.83	20.83	20.83
		1	99	1	0	25.26	25.27	25.40
	64QAM	100	0	50	0	22.38	22.38	22.29
		1	0	1	49	19.57	19.38	19.41
		1	99	1	0	20.98	21.08	21.06
10+20	QPSK	50	0	100	0	23.81	23.74	23.76
		1	49	1	0	21.05	20.84	20.89
		1	0	1	99	25.38	25.23	25.33
	16QAM	50	0	100	0	23.17	23.06	23.10
		1	49	1	0	20.97	20.94	20.87
		1	0	1	99	25.27	25.40	25.37
	64QAM	50	0	100	0	22.42	22.16	22.30
		1	49	1	0	19.52	19.50	19.46
		1	0	1	99	21.18	20.97	21.01

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
10+15	QPSK	75	0	50	0	23.86	23.72	23.77
		1	0	1	49	21.00	20.83	20.84
		1	74	1	0	25.30	25.28	25.34
	16QAM	75	0	50	0	23.07	23.02	23.10
		1	0	1	49	21.05	20.86	20.86
		1	74	1	0	25.32	25.38	25.45
	64QAM	75	0	50	0	22.39	22.14	22.26
		1	0	1	49	19.48	19.44	19.53
		1	74	1	0	21.12	21.04	21.06

LTE Band 41_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+5	QPSK	100	0	25	0	23.89	23.75	23.76
		1	0	1	24	21.10	20.88	21.00
		1	99	1	0	25.46	25.25	25.32
	16QAM	100	0	25	0	23.11	23.19	23.13
		1	0	1	24	20.89	20.83	20.85
		1	99	1	0	25.47	25.22	25.48
	64QAM	100	0	25	0	22.43	22.16	22.26
		1	0	1	24	19.45	19.44	19.43
		1	99	1	0	21.03	20.98	21.11
5+20	QPSK	25	0	100	0	23.86	23.68	23.71
		1	24	1	0	20.90	21.00	21.00
		1	0	1	99	25.42	25.16	25.21
	16QAM	25	0	100	0	23.27	23.16	23.19
		1	24	1	0	20.88	20.85	20.91
		1	0	1	99	25.34	25.26	25.25
	64QAM	25	0	100	0	22.26	22.22	22.32
		1	24	1	0	19.69	19.52	19.62
		1	0	1	99	21.17	20.99	21.12

Proximity sensors Data:

Band/BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz
4/20	QPSK	1	0	21.07	20.85	20.81
		1	50	21.06	20.84	20.80
		1	99	21.03	20.81	20.77
		50	0	20.12	19.90	19.86
		50	25	20.10	19.88	19.84
		50	50	20.05	19.83	19.79
		100	0	20.13	19.91	19.87

Band/BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz
7/20	QPSK	1	0	20.33	20.21	20.02
		1	50	21.65	21.40	21.13
		1	99	21.62	21.37	21.10
		50	0	20.71	20.46	20.19
		50	25	20.69	20.44	20.17
		50	50	20.64	20.39	20.12
		100	0	20.72	20.47	20.20

Band/BW	Modulation	RB Size	RB Offset	Low CH (132072)	Mid CH (132422)	High CH (132572)
				Frequency (1720)MHz	Frequency (1745)MHz	Frequency (1770)MHz
66/20	QPSK	1	0	21.61	21.44	21.35
		1	37	21.60	21.43	21.34
		1	74	21.57	21.40	21.31
		36	0	20.66	20.49	20.40
		36	19	20.64	20.47	20.38
		36	39	20.59	20.42	20.33
		75	0	20.67	20.50	20.41

LTE Band 7_CA Maximum Average Power (dBm)								
BW(MHz)	Modulation	PCC		SCC		Lowest	Middle	Highest
20+20	QPSK	0	0	1	99	22.69	22.45	22.47
		1	99	0	0	22.08	21.85	21.01
		100	0	0	0	21.56	21.51	21.93
		100	0	100	0	21.02	21.24	22.24
		1	0	1	99	18.47	18.52	18.54
		1	0	1	0	18.78	19.16	18.63
		1	99	1	0	22.41	22.62	22.13
		100	0	1	99	19.45	19.65	18.66

Note:

When The device can trigger proximity sensors when used near a human body, the EUT with Power reduction for WCDMA Band 4(3dB) ,LTE Band 4(2dB) ,LTE Band 7(1.5dB),LTE Band 66(1.5dB)

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	14.52	14.42	14.69
Average Power (Ant-1)	14.45	14.44	14.71
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	14.33	14.78	14.64
Average Power (Ant-1)	14.32	14.49	14.56
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	14.37	14.71	14.63
Average Power (Ant-1)	14.14	14.52	14.42
Average Power (Ant-0 + Ant-1)	17.27	17.63	17.54
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Average Power (Ant-0)	11.87	14.12	12.98
Average Power (Ant-1)	11.71	13.02	12.86
Average Power (Ant-0 + Ant-1)	14.80	16.61	15.93

<WLAN 5.2G>

Power (dBm)

Mode	802.11a			
Channel / Frequency (MHz)	36 (5180)	40 (5200)	44 (5220)	48 (5240)
Average Power (Ant-0)	12.79	12.52	12.27	13.09
Average Power (Ant-1)	13.12	12.65	12.22	12.32
Mode	802.11n (HT20)			
Channel / Frequency (MHz)	36 (5180)	40 (5200)	44 (5220)	48 (5240)
Average Power (Ant-0)	12.09	14.48	12.37	12.99
Average Power (Ant-1)	11.37	10.96	11.15	11.54
Average Power (Ant-0 + Ant-1)	14.75	16.08	14.81	15.34
Mode	802.11n (HT40)			
Channel / Frequency (MHz)	38 (5190)		46 (5230)	
Average Power (Ant-0)	13.89		14.13	
Average Power (Ant-1)	12.41		11.94	
Average Power (Ant-0 + Ant-1)	16.22		16.18	
Mode	802.11ac (VHT80)			
Channel / Frequency (MHz)	42 (5210)			
Average Power (Ant-0)	13.59			
Average Power (Ant-1)	11.71			
Average Power (Ant-0 + Ant-1)	15.76			

<WLAN 5.3G>

Mode	802.11a			
Channel / Frequency (MHz)	52 (5260)	56 (5280)	60 (5300)	64 (5320)
Average Power (Ant-0)	12.94	12.65	12.55	12.78
Average Power (Ant-1)	13.11	13.07	13.24	13.58
Mode	802.11n (HT20)			
Channel / Frequency (MHz)	52 (5260)	56 (5280)	60 (5300)	64 (5320)
Average Power (Ant-0)	12.96	12.56	12.62	12.71
Average Power (Ant-1)	13.42	13.21	13.25	13.54
Average Power (Ant-0 + Ant-1)	16.21	15.91	15.96	16.15
Mode	802.11n (HT40)			
Channel / Frequency (MHz)	54 (5270)		62 (5310)	
Average Power (Ant-0)	14.57		13.92	
Average Power (Ant-1)	12.56		12.10	
Average Power (Ant-0 + Ant-1)	16.69		16.11	
Mode	802.11ac (VHT80)			
Channel / Frequency (MHz)	58 (5290)			
Average Power (Ant-0)	14.20			
Average Power (Ant-1)	12.07			
Average Power (Ant-0 + Ant-1)	16.27			

<WLAN 5.6G>

Mode	802.11a							
Channel / Frequency (MHz)	100(5500)	104 (5520)	108 (5540)	112 (5560)	116 (5580)	132 (5660)	136 (5680)	140 (5700)
Average Power (Ant-0)	15.19	15.14	15.07	15.22	15.32	15.16	15.31	15.54
Average Power (Ant-1)	15.18	15.02	15.11	15.05	15.06	14.95	14.83	14.77
Mode	802.11n (HT20)							
Channel / Frequency (MHz)	100(5500)	104 (5520)	108 (5540)	112 (5560)	116 (5580)	132 (5660)	136 (5680)	140 (5700)
Average Power (Ant-0)	15.21	15.06	15.24	15.33	15.17	15.12	15.28	15.49
Average Power (Ant-1)	15.03	14.36	14.59	14.66	14.74	14.39	14.58	14.84
Average Power (Ant-0 + Ant-1)	18.13	17.73	17.94	18.02	17.97	17.78	17.95	18.19
Mode	802.11n (HT40)							
Channel / Frequency (MHz)	102 (5510)				134 (5670)			
Average Power (Ant-0)	16.34				17.17			
Average Power (Ant-1)	14.95				15.48			
Average Power (Ant-0 + Ant-1)	18.71				19.42			
Mode	802.11ac (VHT80)							
Channel / Frequency (MHz)	106 (5530)							
Average Power (Ant-0)	16.64							
Average Power (Ant-1)	14.07							
Average Power (Ant-0 + Ant-1)	18.55							

<WLAN 5.8G>

Mode	802.11a				
Channel / Frequency (MHz)	149 (5745)	153 (5765)	157 (5785)	161 (5805)	165 (5825)
Average Power (Ant-0)	13.37	13.64	13.86	14.33	14.64
Average Power (Ant-1)	13.71	13.71	13.80	14.36	14.67
Mode	802.11n (HT20)				
Channel / Frequency (MHz)	149 (5745)	153 (5765)	157 (5785)	161 (5805)	165 (5825)
Average Power (Ant-0)	14.22	14.31	13.72	13.85	14.68
Average Power (Ant-1)	14.48	14.66	14.07	14.07	14.92
Average Power (Ant-0 + Ant-1)	17.36	17.50	16.91	16.97	17.81
Mode	802.11n (HT40)				
Channel / Frequency (MHz)	151 (5755)		159 (5795)		
Average Power (Ant-0)	14.00		14.30		
Average Power (Ant-1)	13.31		13.51		
Average Power (Ant-0 + Ant-1)	16.68		16.93		
Mode	802.11ac (VHT80)				
Channel / Frequency (MHz)	155 (5775)				
Average Power (Ant-0)	13.17				
Average Power (Ant-1)	13.51				
Average Power (Ant-0 + Ant-1)	16.35				

<Bluetooth>

Mode	Bluetooth GFSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	6.75	7.87	8.35
Mode	Bluetooth $\pi/4$ -DQPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	6.38	7.08	7.45
Mode	Bluetooth 8-DPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	6.52	7.17	7.59
Mode	Bluetooth BLE		
Channel / Frequency (MHz)	0 (2402)	19 (2440)	39 (2480)
Average Power	4.10	4.80	5.08

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

- (1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

- (2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

- (3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

- (4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

4.7.2 SAR Results for Body Exposure Condition

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Fr.(MHz)	Power Sensor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
1	WCDMA II	RMC12.2K	Rear Face	0	1880	-	23.0	22.93	-0.15	0.464	1.02	0.47
	WCDMA II	RMC12.2K	Bottom Side	0	1880	-	23.0	22.93	0.05	0.266	1.02	0.27
	WCDMA II	RMC12.2K	Left Side	0	1880	-	23.0	22.93	0.13	0.885	1.02	0.90
	WCDMA II	RMC12.2K	Left Side	0	1852.4	-	23.0	22.67	-0.04	0.917	1.08	0.99
	WCDMA II	RMC12.2K	Left Side	0	1907	-	23.0	22.75	-0.11	0.833	1.06	0.88
2	WCDMA IV	RMC12.2K	Rear Face	0	1732.6	OFF	23.5	23.15	0.07	0.127	1.08	0.14
	WCDMA IV	RMC12.2K	Bottom Side	0	1732.6	OFF	23.5	23.15	-0.06	0.252	1.08	0.27
	WCDMA IV	RMC12.2K	Left Side	0	1732.6	OFF	23.5	23.15	-0.13	1.9	1.08	2.06
	WCDMA IV	RMC12.2K	Left Side	0	1732.6	ON	20.5	20.11	-0.09	0.757	1.09	0.83
	WCDMA IV	RMC12.2K	Left Side	0	1712.4	ON	20.5	20.02	-0.05	0.779	1.12	0.87
	WCDMA IV	RMC12.2K	Left Side	0	1752.6	ON	20.5	19.95	-0.02	0.724	1.14	0.82
3	WCDMA V	RMC12.2K	Rear Face	0	826.4	-	23.0	22.95	0.01	0.375	1.01	0.38
	WCDMA V	RMC12.2K	Bottom Side	0	826.4	-	23.0	22.95	0	0.903	1.01	0.91
	WCDMA V	RMC12.2K	Left Side	0	826.4	-	23.0	22.95	0.03	0.513	1.01	0.52
	WCDMA V	RMC12.2K	Bottom Side	0	836.6	-	23.0	22.84	-0.01	0.865	1.04	0.90
	WCDMA V	RMC12.2K	Bottom Side	0	846.6	-	23.0	22.77	-0.02	0.827	1.05	0.87

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Fr.(MHz)	Power Sensor	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
4	LTE 2	QPSK20M	Rear Face	0	1880	-	1	0	23.0	22.87	-0.14	0.295	1.03	0.30
	LTE 2	QPSK20M	Bottom Side	0	1880	-	1	0	23.0	22.87	-0.05	0.137	1.03	0.14
	LTE 2	QPSK20M	Left Side	0	1880	-	1	0	23.0	22.87	-0.14	0.552	1.03	0.57
	LTE 2	QPSK20M	Left Side	0	1880	-	50	0	23.0	22.87	0.06	0.537	1.03	0.55
5	LTE 7	QPSK20M	Rear Face	0	2510	OFF	1	0	22.0	21.69	-0.06	0.459	1.07	0.49
	LTE 7	QPSK20M	Bottom Side	0	2510	OFF	1	0	22.0	21.69	-0.17	0.312	1.07	0.34
	LTE 7	QPSK20M	Left Side	0	2510	OFF	1	0	22.0	21.69	0.04	1.19	1.07	1.28
	LTE 7	QPSK20M	Left Side	0	2510	ON	1	0	20.5	20.33	-0.09	0.614	1.04	0.64
	LTE 7	QPSK20M	Left Side	0	2510	ON	50	0	20.5	20.33	-0.11	0.602	1.04	0.63
	LTE 7	QPSK20M	Left Side	0	2535	ON	1	0	20.5	20.21	0.09	0.578	1.07	0.62
	LTE 7	QPSK20M	Left Side	0	2560	ON	1	0	20.5	20.02	-0.14	0.544	1.12	0.61
	LTE 7	2CA(20M+20M)	Left Side	0	2510	ON	1	0	23.0	22.69	0.02	0.524	1.07	0.56
6	LTE 12	QPSK10M	Rear Face	0	707.5	-	1	0	23.5	23.27	0.06	0.375	1.05	0.40
	LTE 12	QPSK10M	Bottom Side	0	707.5	-	1	0	23.5	23.27	-0.01	0.597	1.05	0.63
	LTE 12	QPSK10M	Left Side	0	707.5	-	1	0	23.5	23.27	-0.03	0.210	1.05	0.22
	LTE 12	QPSK10M	Bottom Side	0	707.5	-	25	0	23.5	23.27	-0.10	0.585	1.05	0.62
7	LTE 13	QPSK10M	Rear Face	0	782	-	1	0	23.5	23.49	0.03	0.212	1.00	0.24
	LTE 13	QPSK10M	Bottom Side	0	782	-	1	0	23.5	23.49	0	0.388	1.00	0.44
	LTE 13	QPSK10M	Left Side	0	782	-	1	0	23.5	23.49	-0.09	0.176	1.00	0.20
	LTE 13	QPSK10M	Bottom Side	0	782	-	25	0	23.5	23.49	0.11	0.365	1.00	0.41
8	LTE 26	QPSK15M	Rear Face	0	836.5	-	1	0	23.5	23.30	-0.04	0.394	1.05	0.41
	LTE 26	QPSK15M	Bottom Side	0	836.5	-	1	0	23.5	23.30	0.06	0.728	1.05	0.76
	LTE 26	QPSK15M	Left Side	0	836.5	-	1	0	23.5	23.30	0.06	0.397	1.05	0.42
	LTE 26	QPSK15M	Bottom Side	0	836.5	-	36	0	23.5	23.30	-0.09	0.711	1.05	0.74
9	LTE 41	QPSK20M	Rear Face	0	2593	-	1	0	22.0	21.47	0.11	0.126	1.13	0.14
	LTE 41	QPSK20M	Bottom Side	0	2593	-	1	0	22.0	21.47	-0.17	0.252	1.13	0.28
	LTE 41	QPSK20M	Left Side	0	2593	-	1	0	22.0	21.47	-0.10	0.366	1.13	0.41
	LTE 41	QPSK20M	Left Side	0	2593	-	50	0	22.0	21.47	0.14	0.351	1.13	0.40
	LTE 41	2CA(20M+20M)	Left Side	0	2593	-	1	0	26.0	25.48	-0.16	0.345	1.13	0.39
10	LTE 66	QPSK20M	Rear Face	0	1720	OFF	1	0	23.5	23.02	0.14	0.39	1.12	0.44
	LTE 66	QPSK20M	Bottom Side	0	1720	OFF	1	0	23.5	23.02	-0.06	0.205	1.12	0.23
	LTE 66	QPSK20M	Left Side	0	1720	OFF	1	0	23.5	23.02	0.15	1.24	1.12	1.38
	LTE 66	QPSK20M	Left Side	0	1720	ON	1	0	22.0	21.61	-0.15	0.578	1.09	0.63
	LTE 66	QPSK20M	Left Side	0	1720	ON	50	0	22.0	21.61	-0.11	0.554	1.09	0.61

FCC SAR Test Report

LTE 66	QPSK20M	Left Side	0	1745	ON	1	0	21.5	21.44	0.13	0.525	1.01	0.53
LTE 66	QPSK20M	Left Side	0	1770	ON	1	0	21.5	21.35	0.05	0.533	1.04	0.55

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
11	802.11b	-	Rear Face	0	11	0	15.0	14.69	-0.05	0.222	1.07	0.24
	802.11b	-	Left Side	0	11	0	15.0	14.69	-0.13	0.515	1.07	0.55
	802.11b	-	Rear Face	0	11	1	15.0	14.71	-0.11	0.153	1.07	0.16
	802.11b	-	Left Side	0	11	1	15.0	14.71	0.12	0.356	1.07	0.38
	802.11n	HT20	Rear Face	0	11	0+1	18.0	17.54	-0.12	0.147	1.11	0.16
	802.11n	HT20	Left Side	0	11	0+1	18.0	17.54	0.07	0.386	1.11	0.43
12	802.11a	-	Rear Face	0	48	0	13.5	13.09	0.03	0.335	1.10	0.37
	802.11a	-	Left Side	0	48	0	13.5	13.09	-0.04	0.507	1.10	0.56
	802.11a	-	Rear Face	0	36	1	13.5	13.12	-0.06	0.287	1.09	0.31
	802.11a	-	Left Side	0	36	1	13.5	13.12	-0.11	0.442	1.09	0.48
	802.11n	HT40	Rear Face	0	38	0+1	16.5	16.22	-0.12	0.234	1.07	0.25
	802.11n	HT40	Left Side	0	38	0+1	16.5	16.22	-0.03	0.415	1.07	0.44
13	802.11a	-	Rear Face	0	140	0	16.0	15.54	0.11	0.325	1.11	0.36
	802.11a	-	Left Side	0	140	0	16.0	15.54	-0.08	0.512	1.11	0.57
	802.11a	-	Rear Face	0	100	1	15.5	15.18	-0.14	0.251	1.08	0.27
	802.11a	-	Left Side	0	100	1	15.5	15.18	0.06	0.493	1.08	0.53
	802.11n	HT40	Rear Face	0	134	0+1	19.5	19.42	-0.03	0.205	1.02	0.21
	802.11n	HT40	Left Side	0	134	0+1	19.5	19.42	0.05	0.443	1.02	0.45
14	802.11a	-	Rear Face	0	165	0	15.0	14.64	0.11	0.295	1.09	0.32
	802.11a	-	Bottom Side	0	165	0	15.0	14.64	-0.10	0.503	1.09	0.55
	802.11a	-	Rear Face	0	165	1	15.0	14.67	-0.03	0.287	1.08	0.31
	802.11a	-	Top Side	0	165	1	15.0	14.67	0.11	0.496	1.08	0.54
	802.11n	HT20	Bottom Side	0	165	0+1	18.0	17.81	0.06	0.222	1.04	0.23
	802.11n	HT20	Left Side	0	165	0+1	18.0	17.81	-0.14	0.439	1.04	0.46

Note:

- 1.SAR for LTE Band 4 (Frequency range: 1710 - 1755 MHz) is covered by LTE Band 66 (Frequency range: 1710 - 1780 MHz) due to overlapping frequency range, same maximum tune-up limit and similar channel bandwidth.
- 2.SAR for LTE Band 5 (Frequency range: 824 - 849 MHz) is covered by LTE Band 26 (Frequency range:814 – 849 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel.

4.7.3 2.4GHz 802.11g/n OFDM SAR Test Exclusion Consideration:

Modulation Mode	P _{avg} (dBm)	P _{avg} (mW)	Reported SAR (W/Kg)	Adjusted SAR (W/kg)	Limit (W/Kg)	SAR Test Exclusion
802.11b(DSSS)	14.69	29.44	0.55	/	/	/
802.11g(OFDM)	14.78	30.06	/	0.56	1.2	Yes
802.11n(OFDM)	14.71	29.58	/	0.55	1.2	Yes

Note:

When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

4.7.4 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probecalibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Test Position	Fr.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WCDMA II	Left Side	1852.4	0.917	0.912	1.01	N/A	N/A	N/A	N/A
WCDMA V	Bottom Side	826.4	0.903	0.909	1.01	N/A	N/A	N/A	N/A

4.7.5 Simultaneous Multi-band Transmission Evaluation

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	8.5	Body	5	0.3

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	WCDMA II + WLAN(DTS)	Body	Left Side	0.99	0.55	1.54	ΣSAR < 1.6, Not required
2	WCDMA II + WLAN(NII)	Body	Left Side	0.99	0.57	1.56	ΣSAR < 1.6, Not required
3	WCDMA II + BT	Body	Left Side	0.99	0.11	1.10	ΣSAR < 1.6, Not required

Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1078	Jun. 20, 2018	3 Year
System Validation Dipole	SPEAG	D835V2	4d092	Jun. 20, 2018	3 Year
System Validation Dipole	SPEAG	D900V2	1d121	Apr. 20, 2018	3 Year
System Validation Dipole	SPEAG	D1750V2	1023	Jun. 18, 2018	3 Year
System Validation Dipole	SPEAG	D1900V2	5d142	Jun. 12, 2018	3 Year
System Validation Dipole	SPEAG	D2450V2	835	Jun. 19, 2018	3 Year
System Validation Dipole	SPEAG	D2600V2	1058	Jun. 19, 2018	3 Year
System Validation Dipole	SPEAG	D5GHzV2	1040	Jun. 28, 2018	3 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3970	Nov. 12, 2018	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1418	Oct. 29, 2018	1 Year
Wideband Radio Communication Tester	R&S	CMW500	140822	May. 19, 2019	1 Year
ENA Series Network Analyzer	Agilent	E5071B	MY42404246	May. 19, 2019	1 Year
Signal Analyzer	Agilent	N9010A	My53470879	May. 19, 2019	1 Year
Signal Generator	Agilent	N5181A	MY50145187	May. 19, 2019	1 Year
Power Meter	BOONTON	4232A	10539	May. 19, 2019	1 Year
Power Sensor	BOONTON	51011EMC	34236/34238	May. 19, 2019	1 Year
Temp. & Humi. Recorder	CLOCK	HTC-1	EE-334	Nov. 28, 2018	1 Year
Electronic Thermometer	FeiHong	HY	TP101	May. 19, 2019	1 Year
Coupler	Woken	0110A056020	COM27RW1A3	Sep. 27, 2018	1 Year

Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.05	6.05	∞
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	3.9	3.9	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Probe Modulation Response	2.4	Rectangular	√3	1	1	1.4	1.4	∞
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mech. Restrictions	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Post-processing	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Test Sample Related								
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Power Scaling	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Power Drift of Measured SAR	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Setup								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	∞
Algorithm for Correcting SAR for Deviations in Permittivity and Conductivity	1.2 / 0.97	Normal	1	1	0.84	1.2	0.8	∞
Liquid Conductivity (Meas.)	1.0	Normal	1	0.78	0.71	0.8	0.7	25

Liquid Permittivity (Meas.)	0.5	Normal	1	0.23	0.26	0.1	0.1	25
Liquid Conductivity– Temperature Uncertainty	2.2	Rectangular	$\sqrt{3}$	0.78	0.71	1.0	0.9	∞
Liquid Permittivity– Temperature Uncertainty	1.9	Rectangular	$\sqrt{3}$	0.23	0.26	0.3	0.3	∞
Combined Standard Uncertainty						$\pm 12.1\%$	$\pm 11.4\%$	
Expanded Uncertainty (K=2)						$\pm 24.2\%$	$\pm 22.8\%$	

Uncertainty budget for frequency range 300 MHz to 3 GHz

Source of Uncertainty	Tolerance ($\pm$ %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty ($\pm$ %, 1g)	Standard Uncertainty ($\pm$ %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.65	6.65	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
Probe Modulation Response	2.4	Rectangular	$\sqrt{3}$	1	1	1.4	1.4	∞
Detection Limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	∞
Boundary Effect	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	$\sqrt{3}$	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	$\sqrt{3}$	1	1	1.0	1.0	∞
RF Ambient Conditions – Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner Mech. Restrictions	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	$\sqrt{3}$	1	1	3.9	3.9	∞
Post-processing	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Test Sample Related								
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Power Scaling	0.0	Rectangular	$\sqrt{3}$	1	1	0.0	0.0	∞
Power Drift of Measured SAR	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and Setup								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	∞
Algorithm for Correcting SAR for Deviations in Permittivity and Conductivity	1.2 / 0.97	Normal	1	1	0.84	1.2	0.8	∞
Liquid Conductivity (Meas.)	1.0	Normal	1	0.78	0.71	0.8	0.7	25
Liquid Permittivity (Meas.)	0.5	Normal	1	0.23	0.26	0.1	0.1	25

Liquid Conductivity– Temperature Uncertainty	2.2	Rectangular	$\sqrt{3}$	0.78	0.71	1.0	0.9	∞
Liquid Permittivity– Temperature Uncertainty	1.9	Rectangular	$\sqrt{3}$	0.23	0.26	0.3	0.3	∞
Combined Standard Uncertainty						±13.2%	±12.5	
Expanded Uncertainty (K=2)						±26.4%	±25.0%	

Uncertainty budget for frequency range 3 GHz to 6 GHz

Information on the Testing Laboratories

We, EMTEK (SHENZHEN) CO., LTD., were founded in 2000 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Site Description

EMC Lab. : Accredited by CNAS, 2016.10.24
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2018.3.30
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, August 06, 2018
The certificate is valid until August 07, 2020
Designation Number: CN1204
Test Firm Registration Number: 882943

Accredited by Industry Canada, November 24, 2015
The Certificate Registration Number is 4480A

Name of Firm : EMTEK(SHENZHEN) CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

If you have any comments, please feel free to contact us at the following:

Add: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282

Email: csg@emtek.com.cn

Web Site: www.emtek.com.cn

The road map of all our labs can be found in our web site also.

---END---

Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

System Check_B750

DUT: Dipole:750 MHz;Type:D750V3;SN:1078

Communication System: CW; Frequency: 750 MHz;Duty Cycle: 1:1

Medium: B750 Medium parameters used: $f = 750$ MHz; $\sigma = 0.976$ S/m; $\epsilon_r = 56.163$; $\rho = 1000$ kg/m³


Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.62, 10.62, 10.62); Calibrated: 2018/11/12;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 3.35 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 57.618 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 3.84 W/kg
SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.46 W/kg
Maximum value of SAR (measured) = 3.27 W/kg



System Check_B835

DUT: Dipole:835 MHz; Type:D835V2; SN:4d029

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: B835 Medium parameters used: $f = 835$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 55.833$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.31, 10.31, 10.31); Calibrated: 2018/11/12;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.75 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 63.819 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 4.35 W/kg

SAR(1 g) = 2.49 W/kg; SAR(10 g) = 1.66 W/kg

Maximum value of SAR (measured) = 3.75 W/kg



System Check_B1750

DUT: Dipole 1750 MHz;Type:D1750V2; SN:1023

Communication System: UID 0, CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: B1750 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.471$ S/m; $\epsilon_r = 53.676$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.42, 8.42, 8.42); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 19.2 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 111.1 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 23.6 W/kg

SAR(1 g) = 9.33 W/kg; SAR(10 g) = 5.02 W/kg

Maximum value of SAR (measured) = 20.1 W/kg



System Check_B1900

DUT: Dipole 1900 MHz;Type:D1900V2; SN:5d142

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1

Medium: B1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.571$ S/m; $\epsilon_r = 52.993$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.07, 8.07, 8.07); Calibrated: 2018/11/12;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 23.3 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 115.7 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 27.3 W/kg

SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.49 W/kg

Maximum value of SAR (measured) = 21.8 W/kg



System Check_B2450

DUT: Dipole 2450 MHz; Type:D2450V2; SN:835

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: B2450 Medium parameters used: $f = 2450$ MHz; $\sigma = 2.026$ S/m; $\epsilon_r = 53.063$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.89, 7.89, 7.89); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 27.2 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.8 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 32.3 W/kg

SAR(1 g) = 12.4 W/kg; SAR(10 g) = 5.76 W/kg

Maximum value of SAR (measured) = 26.3 W/kg



System Check_B2600

DUT: Dipole 2600 MHz; Type:D2600V2; SN:1058

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: B2600 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.206$ S/m; $\epsilon_r = 52.381$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.61, 7.61, 7.61); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 32.1 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.6 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 37.8 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.15 W/kg

Maximum value of SAR (measured) = 30.8 W/kg



System Check_B5200

DUT: Dipole D5GHzV2; Type:D5GHzV2; SN:1040

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5200$ MHz; $\sigma = 5.27$ S/m; $\epsilon_r = 49.057$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(5.14, 5.14, 5.14); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.0 W/kg


Pin=100mW/Zoom Scan (4x4x2.5mm)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 50.241 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 31.9 W/kg

SAR(1 g) = 7.5 W/kg; SAR(10 g) = 2.09 W/kg

Maximum value of SAR (measured) = 20.0 W/kg



System Check_B5600

DUT: Dipole D5GHzV2; Type:D5GHzV2; SN:1040

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5600$ MHz; $\sigma = 5.871$ S/m; $\epsilon_r = 48.311$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(4.4, 4.4, 4.4); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 24.5 W/kg


Pin=100mW/Zoom Scan (4x4x2.5mm) /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 54.748 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 40.4 W/kg

SAR(1 g) = 8.28 W/kg; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 25.7 W/kg



System Check_B5800

DUT: Dipole D5GHzV2; Type:D5GHzV2; SN:1040

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5800$ MHz; $\sigma = 6.127$ S/m; $\epsilon_r = 47.81$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(4.49, 4.49, 4.49); Calibrated: 2018/11/12;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 25.0 W/kg


Pin=100mW/Zoom Scan (4x4x2.5mm)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 54.649 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 40.8 W/kg

SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.23 W/kg

Maximum value of SAR (measured) = 26.2 W/kg



Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

WCDMA_band2_left_low

DUT: ND53

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: B1900 Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r =$

53.185; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.07, 8.07, 8.07); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.04 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.570 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.917 W/kg; SAR(10 g) = 0.485 W/kg

Maximum value of SAR (measured) = 1.03 W/kg



WCDMA_band4_left_low-p sensor

DUT: ND53

Communication System: WCDMA; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: B1750 Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.448$ S/m; $\epsilon_r =$

52.936; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.42, 8.42, 8.42); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.748 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.421 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 0.779 W/kg; SAR(10 g) = 0.364 W/kg

Maximum value of SAR (measured) = 0.729 W/kg



WCDMA_band5_bottom_low**DUT: ND53**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: B835 Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.984$ S/m; $\epsilon_r = 55.703$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.31, 10.31, 10.31); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Bottom/Area Scan (51x321x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.956 W/kg


Body Bottom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.546 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.903 W/kg; SAR(10 g) = 0.627 W/kg

Maximum value of SAR (measured) = 0.972 W/kg



LTE_band2_left_mid

DUT: ND53

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.527$ S/m; $\epsilon_r = 53.049$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.07, 8.07, 8.07); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.642 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.706 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.552 W/kg; SAR(10 g) = 0.280 W/kg

Maximum value of SAR (measured) = 0.627 W/kg



LTE_band7_left_low_P sensor

DUT: ND53

Communication System: LTE; Frequency: 2510 MHz; Duty Cycle: 1:1

Medium: B2600 Medium parameters used: $f = 2510$ MHz; $\sigma = 2.12$ S/m; $\epsilon_r = 52.621$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.89, 7.89, 7.89); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.682 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.320 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.614 W/kg; SAR(10 g) = 0.291 W/kg

Maximum value of SAR (measured) = 0.668 W/kg



LTE_band12_bottom_mid**DUT: ND53**

Communication System: LTE; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: B750 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.604$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.62, 10.62, 10.62); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Bottom/Area Scan (51x321x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.649 W/kg


Body Bottom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.167 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.856 W/kg

SAR(1 g) = 0.597 W/kg; SAR(10 g) = 0.398 W/kg

Maximum value of SAR (measured) = 0.648 W/kg



LTE_band13_bottom_mid

DUT: ND53

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.992 \text{ S/m}$; $\epsilon_r = 54.936$; $\rho = 1000 \text{ kg/m}^3$


Ambient Temperature : $22.5 \text{ }^\circ\text{C}$; Liquid Temperature : $21.6 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.62, 10.62, 10.62); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Bottom/Area Scan (51x321x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$
Maximum value of SAR (interpolated) = 0.435 W/kg

Body Bottom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 17.551 V/m ; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 0.789 W/kg
SAR(1 g) = 0.388 W/kg ; SAR(10 g) = 0.215 W/kg
Maximum value of SAR (measured) = 0.436 W/kg



LTE_band26_bottom_mid**DUT: ND53**

Communication System: LTE; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: B835 Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.988$ S/m; $\epsilon_r = 55.65$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(10.31, 10.31, 10.31); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Bottom/Area Scan (51x321x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.780 W/kg


Body Bottom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.053 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.728 W/kg; SAR(10 g) = 0.501 W/kg

Maximum value of SAR (measured) = 0.775 W/kg



LTE_band41_left_mid**DUT: ND53**

Communication System: LTE; Frequency: 2593 MHz; Duty Cycle: 1:1

Medium: B2600 Medium parameters used: $f = 2593$ MHz; $\sigma = 2.196$ S/m; $\epsilon_r = 52.406$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.61, 7.61, 7.61); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.438 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.564 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.837 W/kg

SAR(1 g) = 0.366 W/kg; SAR(10 g) = 0.159 W/kg

Maximum value of SAR (measured) = 0.411 W/kg



LTE_band66_left_low_P sensor

DUT: ND53

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: B1750 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.483$ S/m; $\epsilon_r = 52.853$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(8.42, 8.42, 8.42); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.638 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.808 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.578 W/kg; SAR(10 g) = 0.313 W/kg

Maximum value of SAR (measured) = 0.629 W/kg



802.11b_ant0_left_ch11**DUT: ND53**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: B2450 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.972$ S/m; $\epsilon_r = 53.152$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.89, 7.89, 7.89); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.727 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.438 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.515 W/kg; SAR(10 g) = 0.274 W/kg

Maximum value of SAR (measured) = 0.694 W/kg



802.11a_ant0_left_ch48**DUT: ND53**

Communication System: 802.11a; Frequency: 5240 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5240$ MHz; $\sigma = 5.252$ S/m; $\epsilon_r = 49.164$; $\rho = 1000$ kg/m³


Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(5.14, 5.14, 5.14); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.822 W/kg

Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.768 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 3.37 W/kg
SAR(1 g) = 0.507 W/kg; SAR(10 g) = 0.294 W/kg
Maximum value of SAR (measured) = 0.792 W/kg



802.11a_ant0_left_ch140

DUT: ND53

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5700$ MHz; $\sigma = 5.714$ S/m; $\epsilon_r = 48.566$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(4.4, 4.4, 4.4); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.812 W/kg


Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.874 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 3.96 W/kg

SAR(1 g) = 0.512 W/kg; SAR(10 g) = 0.307 W/kg

Maximum value of SAR (measured) = 0.789 W/kg



802.11a_ant0_left_ch165**DUT: ND53**

Communication System: 802.11a; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: B5G Medium parameters used: $f = 5745$ MHz; $\sigma = 6.026$ S/m; $\epsilon_r = 48.167$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(4.49, 4.49, 4.49); Calibrated: 2018/11/12;
- Sensor-Surface: 4mm (Mechanical Surface Detection), Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2018/10/29
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Body Left/Area Scan (51x241x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.768 W/kg


Body Left/Zoom Scan (7x7x4)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.134 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 2.91 W/kg

SAR(1 g) = 0.503 W/kg; SAR(10 g) = 0.290 W/kg

Maximum value of SAR (measured) = 1.68 W/kg



Appendix C. Calibration Certificate for Probe and Dipole

The calibration certificates are shown as follows.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Client : **Emtek**

Certificate No: **Z18-60412**

CALIBRATION CERTIFICATE

Object **DAE4 - SN: 1418**

Calibration Procedure(s) **FF-Z11-002-01**
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: **October 29, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	20-Jun-18 (CTTL, No.J18X05034)	June-19

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: October 31, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2512

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

[Http://www.chinattl.cn](http://www.chinattl.cn)

Glossary:

DAE

data acquisition electronics

Connector angle

information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.