



# RF Exposure Evaluation Report

FCC ID : E2K-N03G001  
Equipment : Internet of Things Gateway  
Brand Name : DELL  
Model No. : N03G001  
Applicant/  
Manufacturer : Dell Inc.  
One Dell Way, Round Rock, Texas 78682, USA  
Standard : 47 CFR Part 2.1091

The product was received on Jan. 26, 2017, and testing was started from May 03, 2017 and completed on May 03, 2017. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091, KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.  
reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	EUT General Information .....	4
1.2	Table for Permissive Change .....	4
1.3	Testing Location .....	4
<b>2</b>	<b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>5</b>
2.1	Limit of Maximum Permissible Exposure .....	5
2.2	MPE Calculation Method .....	5
2.3	Calculated Result and Limit.....	6

### **PHOTOGRAPHS OF EUT v01**

## REVISION HISTORY

[illegible]

# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2472	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK) LE: DSSS (GFSK)

## 1.2 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA712529-01

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Antenna was added	N/A

## 1.3 Table for Multiple Listing

SKU		Description
1	Base	The only difference among these SKUs is I/O port.
2	GPA	
3	Media	

Note. SKU 3 configuration was pretested and found to be the worst case and measured during the test.

## 1.4 Testing Location

Testing Location		
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973 Test site Designation No. TW1190 with FCC.
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065 FAX : 886-3-656-9085 Test site Designation No. TW0006 with FCC.

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;G1D	1.30	13.78	15.08	0.03221	20	0.00641	1.00000	0.00641
2.4G;BT-BR	1.30	12.91	14.21	0.02636	20	0.00524	1.00000	0.00524

————THE END————