



Maximum Permissible Exposure Evaluation

FCC ID: 2A5OS-DP01

1. Client Information

Applicant	:	Shenzhen Tino Security Corp., LTD
Address	:	201, No.7, HeDian Industry Park FuMin Community, FuCheng Street, LongHua District, Shenzhen, China
Manufacturer	:	Shenzhen Tino Security Corp., LTD
Address	:	201, No.7, HeDian Industry Park FuMin Community, FuCheng Street, LongHua District, Shenzhen, China

2. General Description of EUT

EUT Name	:	IP Camera
Models No.	:	DP01, DP02, DP03, DP04, DP05, DP06, DP07, DP08, DP09, DP10, DP11, DP12, DP13, DP15, DP16, DP17, DP18, DP19, DP20
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is different customers, different model name.
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz Bluetooth 5.0(BLE): 2402~2480MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels 40 channels for BLE
	Antenna Gain:	0.92dBi FPC Antenna for 2.4G WiFi 0.5dBi PCB Antenna for BLE
Power Rating	:	Input: AC 110V~230V
Software Version	:	----
Hardware Version	:	----
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	the evaluation report used the EUT(RW-C-202304-0103-6-2#).

MPE Calculations for WIFI

1. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

3. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$

4. Test Result:

2.4G WiFi & Bluetooth LE worst reported.

Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Limit of Power Density (mW/ cm ²) (S)
Bluetooth LE	2402	0.421	0±1	1	0.5	20	0.0003	1
	2440	0.466	0±1	1	0.5	20	0.0003	1
	2480	0.356	0±1	1	0.5	20	0.0003	1



Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Limit of Power Density (mW/ cm ²) (S)
802.11b	2412	17.745	18±1	19	0.92	20	0.0195	1
	2437	17.776	18±1	19	0.92	20	0.0195	1
	2462	17.671	18±1	19	0.92	20	0.0195	1
802.11g	2412	15.798	16±1	17	0.92	20	0.0123	1
	2437	15.415	15±1	16	0.92	20	0.0098	1
	2462	15.369	15±1	16	0.92	20	0.0098	1
802.11n(HT20)	2412	14.729	15±1	16	0.92	20	0.0098	1
	2437	15.209	15±1	16	0.92	20	0.0098	1
	2462	14.166	14±1	15	0.92	20	0.0078	1

Maximum Simultaneous transmission MPE Ratios for 2.4GHz WiFi and Bluetooth LE.

Maximum MPE ratio 2.4GWIFI	Maximum MPE ratio Bluetooth LE	ΣMPE	Limit	Results
0.0003	0.0195	0.0198	1.0	PASS

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI:2412~2462 MHz and Bluetooth LE

MPE limit S: 1mW/ cm²

The MPE is calculated as **0.0198 < limit 1mW / cm²**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----

