



RF TEST REPORT

Product Name: DTEN D7X

Model Name: DB71455, DB71455-S1

Issued For : DTEN Inc

97 E Brokaw Road suite 180 San Jose CA 95112

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Chen Hsong Industrial Park,
No.177 Renmin West Road, Jinsha Community, Kengzi
Street, Pingshan New District, Shenzhen, China

Report Number: LGT22G011RF14

Sample Received Date: July 25, 2022

Date of Tested: July 25, 2022 – August 29, 2022

Date of Issue: September 09, 2022

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant DTEN Inc
Address 97 E Brokaw Road suite 180 San Jose CA 95112
Manufacturer DTEN Inc
Address 97 E Brokaw Road suite 180 San Jose CA 95112
Product Name DTEN D7X
Trade Mark DTEN
Model Name DB71455, DB71455-S1
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 FREQUENCY HOPPING SYSTEM REQUIREMENTS	10
2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	12
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	20
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	35
4.1 LIMIT	35
4.2 TEST PROCEDURE	35
4.3 TEST SETUP	36
4.4 EUT OPERATION CONDITIONS	36
4.5 TEST RESULTS	37
5. NUMBER OF HOPPING CHANNEL	38
5.1 LIMIT	38
5.2 TEST PROCEDURE	38
5.3 TEST SETUP	38
5.4 EUT OPERATION CONDITIONS	38
5.5 TEST RESULTS	39
6. AVERAGE TIME OF OCCUPANCY	40
6.1 LIMIT	40
6.2 TEST PROCEDURE	40
6.3 TEST SETUP	40
6.4 EUT OPERATION CONDITIONS	40
6.5 TEST RESULTS	41
7. HOPPING CHANNEL SEPARATION MEASUREMENT	42
7.1 LIMIT	42
7.2 TEST PROCEDURE	42



Table of Contents	Page
7.3 TEST SETUP	42
7.4 EUT OPERATION CONDITIONS	42
7.5 TEST RESULTS	42
8. BANDWIDTH TEST	43
8.1 LIMIT	43
8.2 TEST PROCEDURE	43
8.3 TEST SETUP	43
8.4 EUT OPERATION CONDITIONS	43
8.5 TEST RESULTS	43
9. OUTPUT POWER TEST	44
9.1 LIMIT	44
9.2 TEST PROCEDURE	44
9.3 TEST SETUP	44
9.4 EUT OPERATION CONDITIONS	44
9.5 TEST RESULTS	45
10. ANTENNA REQUIREMENT	46
10.1 STANDARD REQUIREMENT	46
10.2 EUT ANTENNA	46
APPENDIX I:TEST RESULTS	47
DWELL TIME	47
MAXIMUM PEAK CONDUCTED OUTPUT POWER	57
-20DB BANDWIDTH	58
OCCUPIED CHANNEL BANDWIDTH	64
CARRIER FREQUENCIES SEPARATION	70
BAND EDGE	76
BAND EDGE(HOPPING)	83
CONDUCTED RF SPURIOUS EMISSION	90
DUTY CYCLE	100
NUMBER OF HOPPING CHANNEL	103
APPENDIX II: PHOTOS OF TEST SETUP	106



Revision History

Rev.	Issue Date	Contents
00	September 09, 2022	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	PASS	--
15.247(a)(1)&(b)(1)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247(a)(1)(iii)	Number of Hopping Frequency	PASS	--
15.247(a)(1)(iii)	Dwell Time	PASS	--
15.247(a)(1)	Bandwidth	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.

(3) For model DB71455 and DB71455-S1, the TP board have two types of A and B.

DB71455-S1 with type A and DB71455 with type B were selected as the typical models for all necessary tests performed. For the details of type A&B, please refer to the EUT photos.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Chen Hsong Industrial Park, No.177 Renmin West Road, Jinsha Community, Kengzi Street, Pingshan New District, Shenzhen, China
Accreditation Certificate	FCC Registration No.: 746540
	A2LA Certificate No.: 6727.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	DTEN D7X
Trade Name	DTEN
Model Name	DB71455
Series Model	DB71455-S1
Model Difference	DB71455-S1 is based on DB71455 to add a camera module on the left and right sides, the other parts are identical.
Channel List	Please refer to the Note 2.
Bluetooth	Frequency: 2402 – 2480 MHz Modulation: GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps)
Bluetooth Version	5.2
Antenna Type	Please refer to the Note 3.
Rating	Input: 100-240V~ 50/60Hz 3.0A
Hardware version number	OPSC17_V12
Software version number	3.0.10
Connecting I/O Port(s)	Please refer to the Note 1.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.



2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	DTEN	DB71455	Copper tube antenna	N/A	2.25	BT ANT

The antenna information provide by manufacturer, applicable only to the tested sample identified in the report.



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate/Modulation
Mode 1	TX CH00	1Mbps/GFSK
Mode 2	TX CH39	1Mbps/GFSK
Mode 3	TX CH78	1Mbps/GFSK
Mode 4	TX CH00	2 Mbps/ π /4-DQPSK
Mode 5	TX CH39	2 Mbps/ π /4-DQPSK
Mode 6	TX CH78	2 Mbps/ π /4-DQPSK
Mode7	TX CH00	3 Mbps/8DPSK
Mode 8	TX CH39	3 Mbps/8DPSK
Mode 9	TX CH78	3 Mbps/8DPSK
Mode 10	Hopping	GFSK
Mode 11	Hopping	π /4-DQPSK
Mode 12	Hopping	8DPSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) We tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/ 60Hz is shown in the report.

(3) The battery is fully-charged during the radiated and RF conducted test.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 13 : Keeping BT TX

2.3 FREQUENCY HOPPING SYSTEM REQUIREMENTS

(1) Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.




The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

(2)The Pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones: i.e. the shift register is initialized with nine ones.

Numver of shift register stages:9


Length of pseudo-random sequence: $2^9-1=511$ bits

Longest sequence of zeros: 8(non-inverted signal)



Linear Feedback Shift Register for Generator of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on th average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies ini synchronization with the transmitted signals.

(3)Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with a bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements FCC Part 15.247 rule.



2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS.

Test software Version	Test program: Bluetooth		
(Power control software) Parameters(1/2/3Mbps)	Power class: DH1 rate:4:27 2DH1 rate:20:54 3DH1 rate:24:83	Power class: DH3 rate:11:183 2DH3 rate:26:367 3DH3 rate:27:552	Power class: DH5 rate:15:339 2DH5 rate:30:679 3DH5 rate:31:1021

2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
USB C-to-C cable	DTEN	N/A	N/A	1.9m
stylus	DTEN	N/A	N/A	N/A
Power cord	XIEKANG ELECTRONIC	N/A	N/A	3m, US plug
Camera	DTEN	N/A	N/A	2pcs

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Keyboard	Lenovo	EKB-536A	N/A	N/A
Mouse	Lenovo	EMS-537A	N/A	N/A
USB Flash disk	Hewlett-Packard	V206	N/A	2pcs
Laptop	Lenovo	小新 Air 14	N/A	N/A
HDMI cable	GIMI	E81280-D	N/A	1.8m, shielded
HDMI cable	SONY	N/A	N/A	1.1m, shielded
Monitor	HKC	T275IU	N/A	N/A
Earphone	N/A	39630078	N/A	N/A
RJ45 cable	N/A	N/A	N/A	1m, unshielded
Router	CHINA TELECOM	WTA541	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST

Conducted Emission

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU	100372	2022.04.12	2023.04.11
LISN	COM-POWER	LI-115	02032	2022.04.13	2023.04.12
LISN	SCHWARZBECK	NNLK 8121	00847	2022.08.19	2023.08.18
CE Cable	N.A	C01	N.A	2022.05.05	2023.05.04
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2022.06.02	2023.06.01
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESU	100372	2022.04.12	2023.04.11
Spectrum Analyzer	Kesight	N9010B	MY60242508	2022.04.29	2023.04.28
Bilog Antenna	SCHAFFNER	CBL6112B	270S	2022.06.05	2025.06.04
Horn Antenna	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Pre-amplifier(0.1M-3GHz)	HP	8447D	2727A05655	2022.04.11	2023.04.10
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2022.04.12	2023.04.11
RE Cable (9K-1G)	N.A	R01	N.A	2022.05.05	2023.05.04
RE Cable (1-26G)	N.A	R02	N.A	2022.05.05	2023.05.04
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Connected Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Generator	Keysight	N5182B	MY59100717	2022.04.30	2023.04.29
Signal Analyzer	Keysight	N9010B	MY60242508	2022.04.29	2023.04.28
Temperature & Humidity	KTJ	TA218B	N/A	2022.05.05	2023.05.04
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2022.05.10	2023.05.09
Attenuator	eastsheep	90db	N/A	2022.04.29	2023.04.28
Testing Software	MTS 8310_2.0.0.0_MWRF-TEST				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-18



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1*	158.000kHz	65.57	44.40	-21.16	33.90	10.50	QP	N
2*	434.000kHz	57.18	47.16	-10.02	36.66	10.50	QP	N
3*	1.218MHz	56.00	48.38	-7.62	37.81	10.57	QP	N
4*	11.986MHz	60.00	52.74	-7.26	41.74	11.00	QP	N
5*	190.000kHz	54.04	33.76	-20.27	23.26	10.50	AV	N
6*	430.000kHz	47.25	37.21	-10.05	26.71	10.50	AV	N
7*	5.758MHz	50.00	32.57	-17.43	21.73	10.84	AV	N
8*	13.266MHz	50.00	39.39	-10.61	28.38	11.01	AV	N




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-18



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1*	286.000kHz	60.64	52.47	-8.17	41.97	10.50	QP	L1
2*	1.238MHz	56.00	50.23	-5.77	39.65	10.58	QP	L1
3*	5.438MHz	60.00	49.78	-10.22	38.95	10.83	QP	L1
4*	12.286MHz	60.00	53.10	-6.90	42.11	10.99	QP	L1
5*	426.000kHz	47.33	41.98	-5.35	31.48	10.50	AV	L1
6*	858.000kHz	46.00	35.36	-10.64	24.84	10.52	AV	L1
7*	5.534MHz	50.00	33.04	-17.00	22.21	10.83	AV	L1
8*	13.266MHz	50.00	40.12	-9.90	29.11	11.01	AV	L1




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455-S1	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-15



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1*	434.000kHz	57.20	52.98	-4.20	42.48	10.50	QP	N
2*	850.000kHz	56.00	49.12	-6.90	38.60	10.52	QP	N
3*	1.218MHz	56.00	49.42	-6.60	38.85	10.57	QP	N
4*	1.750MHz	56.00	46.08	-9.90	35.39	10.69	QP	N
5*	6.530MHz	60.00	48.57	-11.40	37.70	10.87	QP	N
6*	11.986MHz	60.00	54.69	-5.30	43.69	11.00	QP	N
7*	430.000kHz	47.30	40.68	-6.60	30.18	10.50	AV	N
8*	858.000kHz	46.00	35.41	-10.60	24.89	10.52	AV	N
9*	1.242MHz	46.00	32.45	-13.50	21.87	10.58	AV	N
10*	5.758MHz	50.00	32.73	-17.30	21.89	10.84	AV	N
11*	10.202MHz	50.00	33.48	-16.50	22.52	10.96	AV	N
12*	13.266MHz	50.00	40.15	-9.90	29.14	11.01	AV	N



Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455-S1	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-15



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1*	246.000kHz	61.90	52.32	-9.60	41.82	10.50	QP	L1
2	442.000kHz	57.00	53.31	-3.70	42.81	10.50	QP	L1
3*	1.274MHz	56.00	50.14	-5.90	39.55	10.59	QP	L1
4*	1.758MHz	56.00	46.89	-9.10	36.20	10.69	QP	L1
5*	5.478MHz	60.00	50.32	-9.70	39.49	10.83	QP	L1
6*	12.082MHz	60.00	53.58	-6.40	42.59	10.99	QP	L1
7*	434.000kHz	47.20	42.69	-4.50	32.19	10.50	AV	L1
8*	854.000kHz	46.00	35.53	-10.50	25.01	10.52	AV	L1
9*	1.602MHz	46.00	32.99	-13.00	22.34	10.65	AV	L1
10*	1.786MHz	46.00	32.68	-13.30	21.99	10.69	AV	L1
11*	5.838MHz	50.00	34.17	-15.80	23.33	10.84	AV	L1
12*	13.274MHz	50.00	39.98	-10.00	28.97	11.01	AV	L1



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2476 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation.

3.2.4 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example


Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.7 TEST RESULTS


Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 23.5°C
S/N:	Humidity: 54%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-05



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	37.154MHz	40.0	32.6	-7.4	40.5	-7.9	QP	Ver	100.0	290.0
2*	143.975MHz	43.5	32.8	-10.7	43.5	-10.7	QP	Ver	100.0	175.0
3*	242.673MHz	46.0	34.5	-11.5	44.5	-10.0	QP	Ver	100.0	44.0
4*	383.929MHz	46.0	36.5	-9.5	42.0	-5.5	QP	Ver	100.0	14.0
5*	510.878MHz	46.0	39.3	-6.7	43.6	-4.3	QP	Ver	100.0	353.0
6*	959.988MHz	46.0	39.9	-6.1	36.9	3.0	QP	Ver	100.0	2.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 23.5°C
S/N:	Humidity: 54%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-05



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	83.956MHz	40.0	31.5	-8.5	44.6	-13.1	QP	Hor	200.0	347.0
2*	107.964MHz	43.5	35.5	-8.0	46.2	-10.7	QP	Hor	200.0	329.0
3*	131.971MHz	43.5	37.5	-6.0	48.2	-10.7	QP	Hor	150.0	0.0
4*	164.588MHz	43.5	35.5	-8.0	46.5	-11.0	QP	Hor	190.0	32.0
5*	179.986MHz	43.5	35.5	-8.0	47.4	-11.9	QP	Hor	100.0	36.0
6*	980.115MHz	54.0	40.0	-14.0	36.7	3.3	QP	Hor	100.0	58.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-09



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	59.949MHz	40.0	31.8	-8.2	45.9	-14.1	QP	Ver	100.0	0.0
2*	76.803MHz	40.0	32.1	-7.9	48.4	-16.3	QP	Ver	100.0	3.0
3*	119.968MHz	43.5	34.5	-9.0	47.5	-13.0	QP	Ver	100.0	338.0
4*	144.218MHz	43.5	33.2	-10.3	43.9	-10.7	QP	Ver	100.0	7.0
5*	431.944MHz	46.0	35.4	-10.6	40.4	-5.0	QP	Ver	100.0	359.0
6*	905.425MHz	46.0	37.1	-8.9	34.4	2.7	QP	Ver	100.0	359.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX BT	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-09



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	74.620MHz	40.0	35.7	-4.3	50.5	-14.8	QP	Hor	200.0	232.0
2*	107.479MHz	43.5	33.2	-10.3	43.9	-10.7	QP	Hor	173.0	17.0
3*	212.724MHz	43.5	34.4	-9.1	45.3	-10.9	QP	Hor	100.0	311.0
4*	666.563MHz	46.0	37.3	-8.7	39.3	-2.0	QP	Hor	100.0	57.0
5*	761.138MHz	46.0	41.4	-4.6	41.6	-0.2	QP	Hor	100.0	297.0
6*	933.191MHz	46.0	38.7	-7.3	36.2	2.5	QP	Hor	100.0	57.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Lowest_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.628GHz	74.00	49.69	-24.31	60.00	-10.31	QP	Hor	100.0	0.0
2*	2.976GHz	74.00	63.47	-10.53	71.94	-8.47	QP	Hor	100.0	0.0
3*	13.852GHz	74.00	51.22	-22.78	45.86	5.36	QP	Hor	100.0	0.0
4*	2.630GHz	54.00	41.61	-12.39	51.91	-10.30	AV	Hor	100.0	0.0
5*	2.978GHz	54.00	48.85	-5.15	57.30	-8.45	AV	Hor	100.0	0.0
6*	17.099GHz	54.00	44.02	-9.98	33.83	10.19	AV	Hor	100.0	0.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Lowest_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.666GHz	74.00	47.50	-26.50	57.61	-10.11	QP	Ver	100.0	0.0
2*	3.038GHz	74.00	64.76	-9.24	73.11	-8.35	QP	Ver	100.0	0.0
3*	13.865GHz	74.00	51.54	-22.46	46.14	5.40	QP	Ver	100.0	0.0
4*	2.668GHz	54.00	40.13	-13.87	50.23	-10.10	AV	Ver	100.0	0.0
5*	3.032GHz	54.00	50.22	-3.78	58.57	-8.35	AV	Ver	100.0	0.0
6*	17.099GHz	54.00	43.98	-10.02	33.79	10.19	AV	Ver	100.0	0.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Middle_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.666GHz	74.00	46.14	-27.86	56.25	-10.11	QP	Ver	100.0	0.0
2*	3.038GHz	74.00	64.96	-9.04	73.31	-8.35	QP	Ver	100.0	0.0
3*	13.973GHz	74.00	50.88	-23.12	45.10	5.78	QP	Ver	100.0	0.0
4*	2.668GHz	54.00	39.68	-14.32	49.78	-10.10	AV	Ver	100.0	0.0
5*	3.040GHz	54.00	49.93	-4.07	58.28	-8.35	AV	Ver	100.0	0.0
6*	17.099GHz	54.00	43.45	-10.55	33.26	10.19	AV	Ver	100.0	0.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Middle_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.666GHz	74.00	47.61	-26.39	57.72	-10.11	QP	Hor	100.0	0.0
2*	2.976GHz	74.00	63.34	-10.66	71.81	-8.47	QP	Hor	100.0	0.0
3*	13.975GHz	74.00	50.79	-23.21	45.01	5.78	QP	Hor	100.0	0.0
4*	2.668GHz	54.00	39.87	-14.13	49.97	-10.10	AV	Hor	100.0	0.0
5*	2.978GHz	54.00	48.42	-5.58	56.87	-8.45	AV	Hor	100.0	0.0
6*	14.277GHz	54.00	43.22	-10.78	37.33	5.89	AV	Hor	100.0	0.0




Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Highest_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.666GHz	74.00	47.25	-26.75	57.36	-10.11	QP	Hor	100.0	0.0
2*	2.976GHz	74.00	62.91	-11.09	71.38	-8.47	QP	Hor	100.0	0.0
3*	14.876GHz	74.00	51.50	-22.50	45.55	5.95	QP	Hor	100.0	0.0
4*	2.668GHz	54.00	40.29	-13.71	50.39	-10.10	AV	Hor	100.0	0.0
5*	2.998GHz	54.00	48.32	-5.68	56.67	-8.35	AV	Hor	100.0	0.0
6*	17.099GHz	54.00	44.39	-9.61	34.20	10.19	AV	Hor	100.0	0.0



Test Lab: LGT EMC Lab	Project: LGT22G011
EUT: DTEN D7X	Test Engineer: Terry.zhao
M/N: DB71455	Temperature: 29.3°C
S/N:	Humidity: 54%RH
Test Mode: BR_Highest_CH	Test Voltage: AC 120V/60Hz
Note:	Test Data: 2022-08-22



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	2.666GHz	74.00	46.94	-27.06	57.05	-10.11	QP	Ver	100.0	0.0
2*	3.038GHz	74.00	64.65	-9.35	73.00	-8.35	QP	Ver	100.0	0.0
3*	13.861GHz	74.00	50.76	-23.24	45.37	5.39	QP	Ver	100.0	0.0
4*	2.668GHz	54.00	39.89	-14.11	49.99	-10.10	AV	Ver	100.0	0.0
5*	3.032GHz	54.00	50.46	-3.54	58.81	-8.35	AV	Ver	100.0	0.0
6*	17.099GHz	54.00	44.68	-9.32	34.49	10.19	AV	Ver	100.0	0.0



4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2407 MHz Upper Band Edge: 2475 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Hopping Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300– 2403 MHz Upper Band Edge: 2479 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold



4.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Tune the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, the span is set to be greater than RBW.

4.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.



4.5 TEST RESULTS

For the measurement records, refer to the appendix I.



5. NUMBER OF HOPPING CHANNEL

5.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	300KHz
VB	300KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 300KHz, VBW=300KHz, Sweep time = Auto.

5.3 TEST SETUP



5.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.



5.5 TEST RESULTS

For the measurement records · refer to the appendix I.



6. AVERAGE TIME OF OCCUPANCY

6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW = 1MHz/VBW = 3MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
Set the center frequency on any frequency would be measure and set the frequency span to
- zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $3.37 \times 31.6 = 106.6$.
- DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $5.06 \times 31.6 = 160$.
- DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $10.12 \times 31.6 = 320$.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.



6.5 TEST RESULTS

For the measurement records · refer to the appendix I.



7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 LIMIT

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.5 TEST RESULTS

For the measurement records · refer to the appendix I.



8. BANDWIDTH TEST

8.1 LIMIT

FCC Part15 15.247, Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)	Bandwidth	N/A	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

8.5 TEST RESULTS

For the measurement records · refer to the appendix I.



9. OUTPUT POWER TEST

9.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)&(b)(1)	Output Power	1 W or 0.125W	2400-2483.5	PASS
		if channel separation > 2/3 bandwidth provided the systems operate with an output power no greater than 125 mW (20.97dBm)		

9.2 TEST PROCEDURE

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.

2) RBW > 20 dB bandwidth of the emission being measured.

3) VBW ≥ RBW.

4) Sweep: Auto.

5) Detector function: Peak.

6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.


e) A plot of the test results and setup description shall be included in the test report.

NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DSS bandwidth and shall use a fast-responding diode detector.

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.



9.5 TEST RESULTS

For the measurement records , refer to the appendix I.



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA


The EUT antenna is Copper tube Antenna. It comply with the standard requirement.





APPENDIX I:TEST RESULTS



DWELL TIME



Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.381	121.158	318	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.637	230.817	141	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.884	297.052	103	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.389	123.313	317	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.641	246.15	150	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.889	317.79	110	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.389	122.535	315	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.64	246	150	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.891	297.773	103	31600	400	Pass





























MAXIMUM PEAK CONDUCTED OUTPUT POWER



Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	8.64	0	8.64	21	Pass
NVNT	1-DH5	2441	Ant1	9.81	0	9.81	21	Pass
NVNT	1-DH5	2480	Ant1	9.28	0	9.28	21	Pass
NVNT	2-DH5	2402	Ant1	6.59	0	6.59	21	Pass
NVNT	2-DH5	2441	Ant1	8.08	0	8.08	21	Pass
NVNT	2-DH5	2480	Ant1	7.41	0	7.41	21	Pass
NVNT	3-DH5	2402	Ant1	6.8	0	6.8	21	Pass
NVNT	3-DH5	2441	Ant1	8.2	0	8.2	21	Pass
NVNT	3-DH5	2480	Ant1	7.52	0	7.52	21	Pass





-20DB BANDWIDTH


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	0.934	0	Pass
NVNT	1-DH5	2441	Ant1	0.945	0	Pass
NVNT	1-DH5	2480	Ant1	0.957	0	Pass
NVNT	2-DH5	2402	Ant1	1.416	0	Pass
NVNT	2-DH5	2441	Ant1	1.424	0	Pass
NVNT	2-DH5	2480	Ant1	1.512	0	Pass
NVNT	3-DH5	2402	Ant1	1.47	0	Pass
NVNT	3-DH5	2441	Ant1	1.426	0	Pass
NVNT	3-DH5	2480	Ant1	1.429	0	Pass
















OCCUPIED CHANNEL BANDWIDTH


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH5	2402	Ant1	0.876
NVNT	1-DH5	2441	Ant1	0.882
NVNT	1-DH5	2480	Ant1	0.883
NVNT	2-DH5	2402	Ant1	1.364
NVNT	2-DH5	2441	Ant1	1.364
NVNT	2-DH5	2480	Ant1	1.359
NVNT	3-DH5	2402	Ant1	1.36
NVNT	3-DH5	2441	Ant1	1.369
NVNT	3-DH5	2480	Ant1	1.353



















CARRIER FREQUENCIES SEPARATION


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2401.974	2403.01	1.036	0.613	Pass
NVNT	1-DH5	Ant1	2440.978	2442.048	1.07	0.619	Pass
NVNT	1-DH5	Ant1	2478.984	2479.982	0.998	0.624	Pass
NVNT	2-DH5	Ant1	2401.944	2402.98	1.036	0.86	Pass
NVNT	2-DH5	Ant1	2440.988	2441.984	0.996	0.878	Pass
NVNT	2-DH5	Ant1	2478.998	2480.124	1.126	1.008	Pass
NVNT	3-DH5	Ant1	2401.986	2403.016	1.03	0.864	Pass
NVNT	3-DH5	Ant1	2441.156	2442.092	0.936	0.871	Pass
NVNT	3-DH5	Ant1	2478.928	2479.996	1.068	0.883	Pass

















BAND EDGE


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-43.14	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-61.73	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-46.51	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-54.35	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-42.74	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-49.38	-20	Pass


















BAND EDGE(HOPPING)


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-58.28	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-60.17	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-54.51	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-56.41	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-56.77	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-56.47	-20	Pass





















CONDUCTED RF SPURIOUS EMISSION


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-60.97	-20	Pass
NVNT	1-DH5	2441	Ant1	-61.61	-20	Pass
NVNT	1-DH5	2480	Ant1	-61.39	-20	Pass
NVNT	2-DH5	2402	Ant1	-57.11	-20	Pass
NVNT	2-DH5	2441	Ant1	-57.49	-20	Pass
NVNT	2-DH5	2480	Ant1	-58.29	-20	Pass
NVNT	3-DH5	2402	Ant1	-57.45	-20	Pass
NVNT	3-DH5	2441	Ant1	-57.73	-20	Pass
NVNT	3-DH5	2480	Ant1	-57.09	-20	Pass





























DUTY CYCLE

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	1-DH5	2441	Ant1	76.96	1.14	0.35
NVNT	2-DH5	2441	Ant1	77.12	1.13	0.35
NVNT	3-DH5	2441	Ant1	77.15	1.13	0.35










NUMBER OF HOPPING CHANNEL

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass






APPENDIX II: PHOTOS OF TEST SETUP

Conducted Emission Test Setup Photo



Radiated Emission Test Setup Photo - Below 1GHz





Radiated Emission Test Setup Photo - Above 1GHz



*****END OF THE REPORT*****