Page 1 of 10

5.1 DYNAMIC FREQUENCY SELECTION

Test Requirement: FC

FCC 47 CFR Part 15 Subpart E Section 15.407 (h)

RSS-247 Issue 3 Section 6.3

Test Method:

KDB 905462 D03 Client Without DFS New Rules v01r02

EUT Operating Mode:

DES Operational mode	Operating Frequency Range			
DF3 Operational mode	5250 MHz to 5350 MHz	5470 MHz to 5725 MHz		
Slave without radar Interference detection function	\checkmark	\checkmark		

Applicability:

The following table from KDB905462 and the lists of the applicable requirements for the DFS testing. **Applicability of DFS Requirements Prior to Use of a Channel:**

	Operational Mode			
Requirement	Master	Client Without Radar Detection	Client With Radar Detection	
Non-Occupancy Period	\checkmark	Not required	Yes	
DFS Detection Threshold	\checkmark	Not required	Yes	
Channel Availability Check Time	\checkmark	Not required	Not required	
U-NII Detection Bandwidth	\checkmark	Not required	Yes	

Applicability of DFS requirements during normal operation:

	Operational Mode			
Requirement	Master Device or Client with Radar Detection	Client Without Radar Detection		
DFS Detection Threshold	Yes	Not required		
Channel Closing Transmission Time	Yes	Yes		
Channel Move Time	Yes	Yes		
U-NII Detection Bandwidth	Yes	Not required		
A dell'(la se all second as second as faire				
devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection		
Additional requirements for devices with multiple bandwidth modes U-NII Detection Bandwidth and Statistical Performance Check	Master Device or Client with Radar Detection All BW modes must be tested	Client Without Radar Detection Not required		
Additional requirements for devices with multiple bandwidth modes U-NII Detection Bandwidth and Statistical Performance Check Channel Move Time and Channel Closing Transmission Time	Master Device or Client with Radar DetectionAll BW modes must be testedTest using widest BW mode available	Client Without Radar Detection Not required Test using the widest BW mode available for the link		
Additional requirements for devices with multiple bandwidth modes U-NII Detection Bandwidth and Statistical Performance Check Channel Move Time and Channel Closing Transmission Time All other tests	Master Device or Client with Radar DetectionAll BW modes must be testedTest using widest BW mode availableAny single BW mode	Client Without Radar Detection Not required Test using the widest BW mode available for the link Not required		

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection:

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

DFS Radar Signal Parameter Values:

Parameter	Value		
Non-occupancy period	Minimum 30 minutes		
Channel Availability Check Time	60 seconds		
Channel Move Time	10 seconds (See Note 1.)		
	200 milliseconds + an aggregate of 60		
Channel Closing Transmission Time	milliseconds over remaining 10 second period.		
	(See Notes 1 and 2.)		
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission		
	power bandwidth. (See Note 3.)		

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

- **Note 2:** The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.
- **Note 3:** During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

DFS Radar Signal Parameter:

Radar Type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time

Radar Type	Pulse Width (µsec)	PRI (µsec)	Number of Pulses	mber of Pulses Minimum Percentage of Successful Detection	
0	1	1428	18	See Note 1.	See Note 1.
1	1	Test A Test B	$\operatorname{Roundup} \left\{ \begin{array}{c} \left(\frac{1}{360}\right) \\ \left(\frac{19 \cdot 10^{6}}{\operatorname{PRI}_{\mu sec}}\right) \end{array} \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)		80%	120		

Table 1-Short Pulse Radar Test Waveforms

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 µsec, with a minimum increment of 1 µsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4

Radar Type	Pulse Width (µsec)	Chirp Width (MHz)	PRI (µsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 2-Long Pulse Radar Test Waveform

Rada Type	, Pulse Width (μsec)	PRI (µsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

Table 3-Frequency Hopping Radar Test Waveform

In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

Limit of In-Service Monitoring:

Reference to DFS Radar Signal Parameter Values.

Test Procedures:

- a) One frequency will be chosen from the Operating Channels of the EUT within the 5250-5350 MHz or 5470-5725 MHz bands. For 802.11 devices, the test frequency must contain control signals. This can be verified by disabling channel loading and monitoring the spectrum analyzer. If no control signals are detected, another frequency must be selected within the emission bandwidth where control signals are detected.
- b) In case the EUT is a Master Device, a U-NII device operating as a Client Device will be used and it is assumed that the Client will associate with the EUT (Master). For radiated tests, the emissions of the Radar Waveform generator will be directed towards the Master Device. If the Master Device has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.
- c) The TCP protocol unicast data stream was generated by the iperf software command line with at least 17% activity ratio over any 100ms period.
- d) Timing plots are reported with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time).
- e) At time T0 the Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 1-4 at DFS Detection Threshold levels on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- f) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.
- g) When operating as a Master Device, monitor the EUT for more than 30 minutes following instant T2 to verify that the EUT does not resume any transmissions on this Channel. Perform this test once and record the measurement result.



Figure 17: Channel Closing Transmission Time, Channel Move Time and Non-Occupancy Period





Setup for Client with injection at the Master

Equipment Used:

: Refer to section 3 for details.

Test Result:Result of Channel Move Time, Channel Closing Transmission Time and
Non-Occupancy Period for Client Beacon Tes

The measurement data as follows:

BW / Channel	Test Item	Test Result	Limit	Pass/Fail
	Channel Move Time	0.9222 s	< 10s	Pass
20 MHz / 5300 MHz	Channel Closing Transmission Time	5.7 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
	Channel Move Time	0.9724 s	< 10s	Pass
20 MHz / 5500 MHz	Channel Closing Transmission Time	9.0 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
	Channel Move Time	0.980 s	< 10s	Pass
40MHz / 5310 MHz	Channel Closing Transmission Time	8.1 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
	Channel Move Time	0.9778 s	< 10s	Pass
40MHz / 5510 MHz	Channel Closing Transmission Time	5.1 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass

Page 5 of 10

Radar Waveform calibration Plot





Page 7 of 10



Page 8 of 10



Page 9 of 10



Page 10 of 10

