

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5808W3**

Date : 12/1/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5808W3

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	80.5	1.3	14.78	67452.8	10.0%	6745.3	7292
690	H	55.6	1.7	19.10	6606.9	10.0%	660.7	729
1035	H	42.7	2.3	22.70	2426.6	10.0%	242.7	500
1380	H	33.5	3.0	25.10	1202.3	10.0%	120.2	500
1725	H	31.5	3.3	27.55	1310.7	10.0%	131.1	729
2070	H	37.0	3.8	29.42	3243.4	10.0%	324.3	729
2415	H	36.9	4.1	31.85	4390.4	10.0%	439.0	729
2760	H	27.0	4.1	32.20	1462.2	10.0%	146.2	729
3105	H	27.0	5.7	31.75	1669.2	10.0%	166.9	729
3450	H	26.4	6.2	32.28	1753.9	10.0%	175.4	729
4000			CABLE "A"	BICONILOG				