Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\left[\sqrt{f(GHZ)}\right] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GH2)	Conduct ectpower (cBm)	Condude	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
802.11b	2412	9	7.94	8.5±1	9.5	8.91	<5	276834	3.00	YES
	2437	8.99	7.93	8.5±1	9.5	8.91	<5	278264	3.00	YES
	2462	82	6.61	8.5±1	9.5	8.91	<5	279688	3.00	YES
802.11g	2412	8.61	7 <i>2</i> 6	8.5±1	9.5	8.91	\$	276834	3.00	YES
	2437	8.19	6.59	8.5±1	9.5	8.91	<5	278264	3.00	YES
	2462	8.63	7 <i>2</i> 9	8.5±1	9.5	8.91	<5	279688	3.00	YES
802-11n H20	2412	822	6.64	8.5±1	9.5	8.91	<5	276834	3.00	YES
	2437	8.84	7.66	8.5±1	9.5	8.91	<5	278264	3.00	YES
	2462	8.67	7.36	8.5±1	9.5	891	<b>4</b> 5	279688	3.00	YES

## Conclusion:

For the max result : 2.79688≤3.0 for 1g SAR, SAR is not required.

Alw Signature:

Date: 2023-09-25

NAME AND TITLE (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.