



RF TEST REPORT

Applicant	Play For Dream (Shanghai)	
	Technologies Co., Ltd.	
FCC ID	2BMM9-MRD3B01	
Product	DREAM BOX	
Brand	PLAY FOR DREAM	
Model	D3-B	
Report No.	R2411A1739-R3	
Issue Date	January 10, 2025	

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15E (2024)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Tes	st Laboratory	4
1.1.	Notes of the test report	4
1.2.	Test facility	4
1.3.	Testing Location	4
2. Ger	neral Description of Equipment under Test	5
2.1.	Applicant and Manufacturer Information	5
2.2.	General information	5
3. Арр	blied Standards	7
4. Tes	t Configuration	8
5. Tes	t Case Results	12
5.1.	Occupied Bandwidth	12
5.2.	Average Power Output	111
5.3.	Frequency Stability	148
5.4.	Power Spectral Density	152
5.5.	Unwanted Emission	471
5.6.	Conducted Emission	616
6. Mai	in Test Instruments	619
ANNEX	A: The EUT Appearance	620
ANNEX	B: Test Setup Photos	621

Number	Test Case	Clause in FCC rules	Verdict		
1	Average output power	15.407(a)	PASS		
2	Occupied bandwidth	15.407(e)	PASS		
3	Frequency stability	15.407(g)	PASS		
4	Power spectral density	15.407(a)	PASS		
5	Unwanted Emissions	15.407(b)	PASS		
6	Conducted Emissions	15.207	PASS		
Date of Testing: December 9, 2024 ~ December 28, 2024					
Date of Sa	Date of Sample Received: December 6, 2024				
Note: PASS: The EUT complies with the essential requirements in the standard.					
FAIL: The EUT does not comply with the essential requirements in the standard.					
All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology					
(Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement					
Uncertainties were not taken into account and are published for informational purposes only.					

Summary of measurement results

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of Eurofins TA

Technology (Shanghai) Co., Ltd. The results documented in this report apply only to the tested

sample, under the conditions and modes of operation as described herein. Measurement

Uncertainties were not taken into account and are published for informational purposes only. This

report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3. Testing Location

Company:	Eurofins TA Technology (Shanghai) Co., Ltd.
Address:	Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	https://www.eurofins.com/electrical-and-electronics
E-mail:	Kain.Xu@cpt.eurofinscn.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Play For Dream (Shanghai) Technologies Co., Ltd.		
Applicant address	Room 501, Building No 3, Caosong Road No.1, Xinqiao Town, Songjiang District, Shanghai City, China		
Manufacturer	Play For Dream (Shanghai) Technologies Co., Ltd.		
Manufacturer address	Room 501, Building No 3, Caosong Road No.1, Xinqiao Town, Songjiang District, Shanghai City, China		

2.2. General information

EUT Description					
Model	Model D3-B				
Lab internal SN	R2411A173	9/S01			
Hardware Version	V3.0				
Software Version	V2.0.22				
Power Supply	AC adapter				
Antenna Type	Internal Ante	enna			
Antenna Connector	A permanen Part 15.203	tly attached a requirement)	antenna (mee	et with the sta	andard FCC
		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
Antenna Gain	Antenna 1	2.41 dBi	2.17 dBi	2.57 dBi	2.72 dBi
	Antenna 2	2.23 dBi	1.78 dBi	2.94 dBi	2.56 dBi
		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
Directional Gain	Power	2.41 dBi	2.17 dBi	2.94 dBi	2.72 dBi
	PSD	5.42 dBi	5.18 dBi	5.95 dBi	5.73 dBi
	U-NII-1: 515	0MHz-5250N	/Hz		
Operating Frequency	U-NII-2A: 52	50MHz -535	0MHz		
Range(s)	U-NII-2C: 54	70MHz-5725	5MHz		
	U-NII-3: 572	5MHz -5850	MHz		
	802.11a: OFDM				
Modulation Type	802.11n(H120/H140): OFDM				
	802 11ax (HE20/HE40/HE80): OFDMA				
Max. Output Power	20.54 dBm			-	
Operating temperature range	= 0 ° C to 40 ° C				
Operating voltage range	3.6 VDC to 4.4 VDC				
Testing temperature range	esting temperature range -30 ° C to 50° C				
State voltage	State voltage 4 VDC				
EUT Accessory					

 Eurofins
 TA Technology (Shanghai)
 Co., Ltd.
 TA-MB-04-006R
 Page

 This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.
 Page

🛟 eurofins

RF Test Report

RF Test Report	Report No.: R2411A1739-R3
Data Cabla	Manufacturer: Guangdong Pinsheng Electronics Co., LTD
Data Cable	1000±30mm Cable
	Manufacturer: Shenzhen Zhishang Technology Co., LTD
	1000mm Cable

. . .

D0444 44700 D0

Note:

1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.

2. This device support automatically discontinue transmission, while the device is not transmitting any information, the device can automatically discontinue transmission and become standby mode for power saving. The device can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3. (a) Manufacturers implements security features in any digitally modulated devices capable of operating in any of the U-NII bands, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software prevents the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers uses means including, but not limited to the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment authorization.

(b) Manufacturers take steps to ensure that DFS functionality cannot be disabled by the operator of the U-NII device.

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15E (2024) Unlicensed National Information Infrastructure Devices

ANSI C63.10-2013

Reference standard:

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (X axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Mada	Data Rate			
Mode	Antenna 1	Antenna 2	MIMO	
802.11a	6 Mbps	6 Mbps	6 Mbps	
802.11n HT20	MCS0	MCS0	MCS8	
802.11n HT40	MCS0	MCS0	MCS8	
802.11ac VHT20	MCS0	MCS0	MCS0	
802.11ac VHT40	MCS0	MCS0	MCS0	
802.11ac VHT80	MCS0	MCS0	MCS0	
802.11ax HE20	MCS0	MCS0	MCS0	
802.11ax HE40	MCS0	MCS0	MCS0	
802.11ax HE80	MCS0	MCS0	MCS0	

The worst case Antenna mode for each of the following tests for Wi-Fi:

Test Cases	Antenna 1	Antenna 2	MIMO
Average conducted output power	0	0	0
Occupied bandwidth	0		
Frequency stability	0		
Power Spectral Density	0	0	0
Unwanted Emissions	-		0
Conducted Emissions	-		0

TB Mode

Test Cases	Antenna 1	Antenna 2	MIMO
Average conducted output power	0	0	0
Occupied bandwidth	0	-	-
Frequency stability	-	-	-
Power Spectral Density	0	0	0
Unwanted Emissions	-	-	0
Conducted Emissions	-	-	-

Wireless Technology and Frequency Range

Wireless	5 Technology	Bandwidth	Channel	Frequency
			36	5180MHz
		20 MU	40	5200MHz
		20 1011 12	44	5220MHz
	U-NII-1		48	5240MHz
		40 MHz	38	5190MHz
		40 10112	46	5230MHz
		80 MHz	42	5210MHz
			52	5260MHz
		20 MHz	56	5280MHz
		20 10112	60	5300MHz
	U-NII-2A		64	5320MHz
		40 MHz	54	5270MHz
		40 10112	62	5310MHz
		80 MHz	58	5290MHz
			100	5500MHz
			104	5520MHz
			108	5540MHz
		20 MHz U-NII-2C	112	5560MHz
			116	5580MHz
Wi-Fi			120	5600MHz
			124	5620MHz
			128	5640MHz
			132	5660MHz
			136	5680MHz
	U-NII-2C		140	5700MHz
			144	5720MHz
	40 MHz		102	5510MHz
			110	5550MHz
		118	5590MHz	
			126	5630MHz
			134	5670MHz
			142	5710MHz
			106	5530MHz
		80 MHz	122	5610MHz
			138	5690MHz
			149	5745MHz
		U-NII-3 20 MHz	153	5765MHz
	U-NII-3		157	5785MHz
		161	5805MHz	
			165	5825MHz

🛟 eurofins

 RF Test Report
 Report No.: R2411A1739-R3

 40 MHz
 151
 5755MHz

 159
 5795MHz

 80 MHz
 155
 5775MHz

 Does this device support TPC Function? ⊠Yes □No

 Does this device support TDWR Band? ⊠Yes □No

5. Test Case Results

5.1. Occupied Bandwidth

Ambient condition

Temperature	erature Relative humidity Pressure	
15°C ~ 35°C	20% ~ 80%	86 kPa ~ 106 kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.

For U-NII-1/U-NII-2A/U-NII-2C, set RBW \approx 1% OCB kHz, VBW \geq 3 × RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

For U-NII-3, Set RBW = 100 kHz, VBW \ge 3 × RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

Use the 99 % power bandwidth function of the instrument

Test Setup



Limits

For U-NII-1/U-NII-2A/U-NII-2C No specific occupied bandwidth requirements in Part 15.407. For U-NII-3 Rule FCC Part §15.407(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 936 Hz.



RF Test Report Test Results:

	Comios from uno	Minimum 26 dB		
Mode	Carrier frequency	bandwidth	Conclusion	
		(MHz)		
	5180	18.85	PASS	
	5200	19.07	PASS	
	5240	20.07	PASS	
	5260	20.00	PASS	
	5280	19.78	PASS	
	5320	18.49	PASS	
802.11a	5500	19.61	PASS	
	5580	18.69	PASS	
	5700	18.88	PASS	
	5720	19.30	PASS	
	5745	18.76	PASS	
	5785	19.63	PASS	
	5825	18.82	PASS	
	5180	19.86	PASS	
	5200	19.91	PASS	
	5240	19.93	PASS	
	5260	19.70	PASS	
	5280	19.85	PASS	
	5320	19.90	PASS	
802.11n HT20	5500 19.86		PASS	
	5580	20.07	PASS	
	5700	19.81	PASS	
	5720	19.88	PASS	
	5745	19.91	PASS	
	5785	19.73	PASS	
	5825	19.59	PASS	
	5190	39.43	PASS	
	5230	39.12	PASS	
	5270	39.39	PASS	
	5310	39.30	PASS	
900 11 n LIT 40	5510	38.99	PASS	
802.110 1140	5550	39.34	PASS	
	5670	39.11	PASS	
	5710	39.46	PASS	
	5755	39.55	PASS	
	5795	39.36	PASS	
	5180	19.73	PASS	
902 11 co \/UT20	5200	00 20.07		
002.11aC VH120	5240	19.70	PASS	
	5260	19.78	PASS	

 Eurofins TA Technology (Shanghai) Co., Ltd.
 TA-MB-04-006R
 Page 13 of 621

 This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.
 Page 13 of 621

RF Test Report		Repo	r <u>t No.: R2411A1739-R3</u>
	5280	19.79	PASS
	5320	19.97	PASS
	5500	19.79	PASS
	5580	19.78	PASS
	5700	19.66	PASS
	5720	19.98	PASS
	5745	19.86	PASS
	5785	19.79	PASS
	5825	19.83	PASS
	5190	39.25	PASS
	5230	39.47	PASS
	5270	39.43	PASS
	5310	39.27	PASS
	5510	39.28	PASS
802.11ac VH140	5550	39.38	PASS
	5670	39.35	PASS
	5710	39.43	PASS
	5755	39.38	PASS
	5795	39.25	PASS
	5210	82.08	PASS
	5290	81.24	PASS
802.11ac VHT80	5530	81.98	PASS
	5690	81.14	PASS
	5775	80.87	PASS
	5180	20.50	PASS
	5200	21.10	PASS
	5240	20.74	PASS
	5260	20.57	PASS
	5280	20.98	PASS
	5320	20.50	PASS
802.11ax HE20	5500	20.64	PASS
	5580	20.57	PASS
	5700	20.45	PASS
	5720	20.82	PASS
	5745	20.57	PASS
	5785	20.82	PASS
	5825	20.92	PASS
	5190	40.16	PASS
	5230	39.79	PASS
902 11 ov Ц⊑ 40	5270	40.06	PASS
002.118X ME40	5310	39.85	PASS
	5510	39.99	PASS
	5550	40.25	PASS

RF Test Report		Report No.: R2411A1739-R3				
	5670	40.26	PASS			
	5710	40.23	PASS			
	5755	39.96	PASS			
	5795	40.46	PASS			
802.11ax HE80	5210	81.58	PASS			
	5290	81.92	PASS			
	5530	81.40	PASS			
	5690	81.54	PASS			
	5775	80.99	PASS			

	Carrier frequency	Minimum 6 dB			
Mode		bandwidth	Conclusion		
		(MHz)			
	5720	16.320	PASS		
902 110	5745	16.320	PASS		
002.118	5785	16.360	PASS		
	5825	16.280	PASS		
	5720	17.160	PASS		
902 11n UT20	5745	17.640	PASS		
002.11111120	5785	17.560	PASS		
	5825	17.600	PASS		
	5710	36.320	PASS		
802.11n HT40	5755	35.920	PASS		
	5795	36.320	PASS		
	5720	17.560	PASS		
	5745	17.040	PASS		
802.11ac VH120	5785	17.560	PASS		
	5825	17.560	PASS		
	5710	35.280	PASS		
802.11ac VHT40	5755	36.320	PASS		
	5795	36.320	PASS		
	5690	75.680	PASS		
802.11ac VH180	5775	75.040	PASS		
	5720	18.600	PASS		
000 11 ov LIE 20	5745	18.680	PASS		
802.11ax HE20	5785	18.960	PASS		
	5825	18.760	PASS		
802.11ax HE40	5710	37.680	PASS		
	5755	37.840	PASS		
	5795	37.920	PASS		
900 11 ev UE 00	5690	77.600	PASS		
002.118X HEOU	5775	77.280	PASS		

RF Test Report

TB Mode

U-NII-1

	RU	Carrier	99%	Minimum 26	
Mode	Index	frequency	bandwidth	dB bandwidth	Conclusion
		(MHz)	(MHz)	(MHz)	
802.11ax HE20 106-Tones	53	5180	17.793	19.512	PASS
802.11ax HE20 106-Tones	53	5200	14.524	21.041	PASS
802.11ax HE20 106-Tones	54	5240	17.937	20.572	PASS
802.11ax HE20 242-Tones	61	5180	19.083	22.404	PASS
802.11ax HE20 242-Tones	61	5200	19.056	23.353	PASS
802.11ax HE20 242-Tones	61	5240	19.055	23.482	PASS
802.11ax HE20 26-Tones	0	5180	18.106	19.152	PASS
802.11ax HE20 26-Tones	4	5200	16.958	18.254	PASS
802.11ax HE20 26-Tones	8	5240	16.321	17.633	PASS
802.11ax HE20 52-Tones	37	5180	17.948	19.073	PASS
802.11ax HE20 52-Tones	39	5200	14.277	17.255	PASS
802.11ax HE20 52-Tones	40	5240	18.358	20.180	PASS
802.11ax HE40 26-Tones	0	5190	37.950	39.801	PASS
802.11ax HE40 26-Tones	17	5230	36.615	38.14	PASS
802.11ax HE40 484-Tones	65	5190	38.001	44.272	PASS
802.11ax HE40 484-Tones	65	5230	38.107	44.83	PASS
802.11ax HE80 26-Tones	36	5210	63.828	66.942	PASS
802.11ax HE80 26-Tones	0	5210	76.792	80.155	PASS
802.11ax HE80 996-Tones	67	5210	77.744	86.057	PASS

RF Test Report

	RU	Carrier	99%	Minimum 26 dB	Conclusio
Mode	Index	frequency	bandwidth	bandwidth	n
	macx	(MHz)	(MHz)	(MHz)	
802.11ax HE20 106-Tones	53	5260	17.395	20.806	PASS
802.11ax HE20 106-Tones	53	5300	17.951	20.388	PASS
802.11ax HE20 106-Tones	54	5320	16.264	21.304	PASS
802.11ax HE20 242-Tones	61	5260	19.064	23.600	PASS
802.11ax HE20 242-Tones	61	5300	19.079	24.167	PASS
802.11ax HE20 242-Tones	61	5320	19.060	22.634	PASS
802.11ax HE20 26-Tones	0	5260	18.422	19.602	PASS
802.11ax HE20 26-Tones	4	5300	16.252	17.429	PASS
802.11ax HE20 26-Tones	8	5320	16.119	16.922	PASS
802.11ax HE20 52-Tones	37	5260	18.253	19.577	PASS
802.11ax HE20 52-Tones	39	5300	14.929	19.043	PASS
802.11ax HE20 52-Tones	40	5320	18.317	19.930	PASS
802.11ax HE40 26-Tones	0	5270	32.654	34.258	PASS
802.11ax HE40 26-Tones	17	5310	37.645	39.599	PASS
802.11ax HE40 484-Tones	65	5270	38.020	43.038	PASS
802.11ax HE40 484-Tones	65	5310	37.990	43.151	PASS
802.11ax HE80 26-Tones	36	5290	78.709	81.086	PASS
802.11ax HE80 26-Tones	0	5290	51.781	54.554	PASS
802.11ax HE80 996-Tones	67	5290	77.637	87.154	PASS

RF Test Report

U-NII-2C

		Carrier	99%	Minimum 26	
Mode	RU Index	frequency	bandwidth	dB bandwidth	Conclusion
		(MHz)	(MHz)	(MHz)	
802.11ax HE20 106-Tones	53	5500	14.359	20.986	PASS
802.11ax HE20 106-Tones	53	5600	18.356	21.575	PASS
802.11ax HE20 106-Tones	54	5700	18.309	20.000	PASS
802.11ax HE20 242-Tones	61	5500	19.070	23.022	PASS
802.11ax HE20 242-Tones	61	5600	19.055	22.598	PASS
802.11ax HE20 242-Tones	61	5700	19.060	22.418	PASS
802.11ax HE20 26-Tones	0	5500	16.172	17.260	PASS
802.11ax HE20 26-Tones	4	5600	17.218	18.508	PASS
802.11ax HE20 26-Tones	8	5700	18.045	19.222	PASS
802.11ax HE20 52-Tones	37	5500	18.195	20.402	PASS
802.11ax HE20 52-Tones	39	5600	12.014	16.027	PASS
802.11ax HE20 52-Tones	40	5700	18.293	19.583	PASS
802.11ax HE40 26-Tones	0	5510	34.765	36.547	PASS
802.11ax HE40 26-Tones	17	5670	32.628	34.788	PASS
802.11ax HE40 484-Tones	65	5510	38.026	44.346	PASS
802.11ax HE40 484-Tones	65	5590	37.967	43.148	PASS
802.11ax HE40 484-Tones	65	5670	38.036	43.143	PASS
802.11ax HE80 26-Tones	36	5610	68.249	70.424	PASS
802.11ax HE80 26-Tones	0	5610	75.970	78.897	PASS
802.11ax HE80 996-Tones	67	5610	77.815	86.984	PASS



RF Test Report

	RU	Carrier	99% Minimum 6 dB		Limit		
Mode	Index	frequency (MHz)	bandwidth (MHz)	bandwidth (MHz)	(kHz)	Conclusion	
802.11ax HE20 106-Tones	53	5745	16.290	17.017	500	PASS	
802.11ax HE20 106-Tones	53	5785	17.478	17.062	500	PASS	
802.11ax HE20 106-Tones	54	5825	15.781	17.787	500	PASS	
802.11ax HE20 242-Tones	61	5745	19.049	19.020	500	PASS	
802.11ax HE20 242-Tones	61	5785	19.074	19.012	500	PASS	
802.11ax HE20 242-Tones	61	5825	19.033	19.045	500	PASS	
802.11ax HE20 26-Tones	0	5745	17.925	2.014	500	PASS	
802.11ax HE20 26-Tones	4	5785	14.899	2.563	500	PASS	
802.11ax HE20 26-Tones	8	5825	17.378	2.016	500	PASS	
802.11ax HE20 52-Tones	37	5745	17.092	7.035	500	PASS	
802.11ax HE20 52-Tones	39	5785	15.912	9.155	500	PASS	
802.11ax HE20 52-Tones	40	5825	17.885	8.216	500	PASS	
802.11ax HE40 26-Tones	0	5755	36.302	2.062	500	PASS	
802.11ax HE40 26-Tones	17	5795	37.438	2.029	500	PASS	
802.11ax HE40 484-Tones	65	5755	38.071	37.972	500	PASS	
802.11ax HE40 484-Tones	65	5795	38.052	38.070	500	PASS	
802.11ax HE80 26-Tones	36	5775	77.296	2.065	500	PASS	
802.11ax HE80 26-Tones	0	5775	78.568	2.067	500	PASS	
802.11ax HE80 996-Tones	67	5775	77.669	78.006	500	PASS	



RF Test Report

Report No.: R2411A1739-R3

99% bandwidth









RF Test Report Report No.: R2411A1739-R3 11A_Ant1_5500 12:12:46 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURCE Center Freq: 5.500000 Trig: Free Run #Atten: 30 dB Frequency eq 5.500000000 GHz Center Fr Avg Radio Device: BTS 5.49876 G 6.5402 d Ref Offset 11.3 dB Ref 20.00 dBm ٠ Center Fred 5.50000000 GH; Center 5.5 GHz #Res B₩ 220 kHz Span 40 MHz Sweep 1 ms CF Step #VBW 680 kHz 4.00 23.0 dBm Total Power Occupied Bandwidth 16.395 MHz Freq Offse 12.435 kHz 0 H % of OBW Power 99.00 % Transmit Freg Error x dB Bandwidth 19.61 MHz x dB -26.00 dB 11A_Ant1_5580 12:12:56 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURC Center Freq: 5.580000 Trig: Free Run #Atten: 30 dB q 5.580000000 GHz 000 GHz Avg|Hold: 100/100 Radio Device: BTS 5.57892 G 6.3204 dl Ref Offset 11.3 dB Ref 20.00 dBm ¢¹ Center Freq 5.58000000 GH enter 5.58 GHz Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MHz #VBW 680 kHz Auto Ma Occupied Bandwidth Total Power 22.7 dBm 16.383 MHz Freq Offse 0 H Transmit Freq Error 5.464 kHz % of OBW Power 99.00 % 18.69 MHz -26.00 dB x dB Bandwidth x dB 11A_Ant1_5700 12:13:07 PM Dec 30, 2024 Radio Std: None SENSE:INT | SOURCE OFF | ALIGN AUT Center Freq: 5.70000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB Aut Avg|Hold: 100/100 r Freq 5.700000000 GHz Radio Device: BTS 5.70128 C 4.5785 d Ref Offset 11.3 dB Ref 20.00 dBm . ♦ 1 Center Freq 5 70000000 GH: Span 40 MHz Sweep 1 ms Center 5.7 GHz Res BW 220 kHz CF Step #VBW 680 kHz 4.0000 Auto Ma Total Power 20.8 dBm Occupied Bandwidth 16.386 MHz Freq Offset 0 Ha Transmit Freq Error 13.284 kHz % of OBW Power 99.00 % x dB Bandwidth 18.88 MHz -26.00 dB x dB



RF Test Report Report No.: R2411A1739-R3 11A_Ant1_5720 SENSE:INT SOURCE OFF ALIGN AUT Center Freq: 5.72000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB Automatic Automatic 12:13:17 PM Dec 30, 2024 Radio Std: None Frequency Center Freg 5,720000000 GHz Radio Device: BTS 5.71776 C Ref Offset 11.3 dB Ref 20.00 dBm Center Free 5.72000000 GHz Center 5.72 GHz #Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 M #VBW 680 kHz 21.8 dBm Total Power Occupied Bandwidth 16.389 MHz Freq Offse 18.969 kHz 0 H % of OBW Power 99.00 % Transmit Freq Error 19.30 MHz x dB Bandwidth x dB -26.00 dB 11A_Ant1_5745 12:13:39 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURCE OFF ALIGN AUT Center Freq: 5.745000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB Aut Avg|Hold: 100/100 eq 5.745000000 GHz Radio Device: BTS (r1 5.7428 G 5.5374 dE Ref Offset 11.3 dB Ref 20.00 dBm **♦**¹ Center Freq 5.74500000 GH enter 5.745 GHz Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MHz #VBW 680 kHz Auto Ma Total Power 21.9 dBm **Occupied Bandwidth** 16.378 MHz Freq Offse 0 H Transmit Freq Error 19.180 kHz % of OBW Power 99.00 % 18.76 MHz -26.00 dB x dB Bandwidth x dB 11A_Ant1_5785 12:13:59 PM Dec 30, 2024 Radio Std: None Center Freq: 5.78500000 GHz Trig: Free Run Avg|Hold: 100/100 r Freq 5.785000000 GHz ee Rur 30 dB Radio Device: BTS 5.78128 5.6490 c Ref Offset 11.3 dB Ref 20.00 dBm Center Freq 5 78500000 GH Span 40 MHz Sweep 1 ms Center 5.785 GHz Res BW 220 kHz CF Step #VBW 680 kHz 4.0000 Auto Ma Total Power 22.0 dBm Occupied Bandwidth 16.409 MHz Freq Offset 0 Ha Transmit Freq Error 16.381 kHz % of OBW Power 99.00 % x dB Bandwidth 19.63 MHz -26.00 dB x dB

Page 23 of 621



RF Test Report Report No.: R2411A1739-R3 11A_Ant1_5825 SENSE:INT SOURCE OFF ALIGN AUT Center Freq: 5.825000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB Automatic Automatic 12:14:18 PM Dec 30, 2024 Radio Std: None Frequency Center Freg 5.825000000 GHz Radio Device: BTS 5.82772 G 6.4961 d Ref Offset 11.3 dB Ref 20.00 dBm Center Freq 5.82500000 GHz Center 5.825 GHz #Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MI #VBW 680 kHz Total Power 22.4 dBm Occupied Bandwidth 16.400 MHz Freq Offse 15.433 kHz 0 H % of OBW Power 99.00 % Transmit Freg Error x dB Bandwidth 18.82 MHz x dB -26.00 dB 11N20SISO_Ant1_5180 12:14:37 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURCE OFF ALIGN AUTO Center Freq: 5.180000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB r Freq 5.180000000 GHz Radio Device: BTS 5.18128 G 6.4730 dl lkr1 Ref Offset 11.3 dB Ref 20.00 dBm ۵ Center Freq 5.18000000 GH enter 5.18 GHz Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MHz #VBW 680 kHz Auto Ma Occupied Bandwidth Total Power 22.6 dBm 17.571 MHz Freq Offse Transmit Freq Error 22.938 kHz % of OBW Power 99.00 % 0 H 19.86 MHz x dB Bandwidth -26.00 dB x dB 11N20SISO_Ant1_5200 12:14:47 PM Dec 30, 2024 Radio Std: None SENSE:INT | SOURCE OFF | ALIGN AUTO Center Freq: 5.20000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB Auto Auto r Freq 5.200000000 GHz Radio Device: BTS 5.20088 (6.1763 d Ref Offset 11.3 dB Ref 20.00 dBm Center Freq 5 20000000 GH: Span 40 MHz Sweep 1 ms Center 5.2 GHz Res B₩ 220 kHz CF Step 00000 MH #VBW 680 kHz 4.0000 Auto Ma Total Power 22.7 dBm Occupied Bandwidth 17.591 MHz Freq Offset 0 Ha Transmit Freq Error 23.439 kHz % of OBW Power 99.00 % x dB Bandwidth 19.91 MHz -26.00 dB x dB





Page 25 of 621





Page 26 of 621













Page 29 of 621





Page 30 of 621



















RF Test Report Report No.: R2411A1739-R3 11AC20SISO_Ant1_5720 SENSE:INT SOURCE OFF ALIGN AUTO Center Freq: 5.720000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB 12:21:25 PM Dec 30, 2024 Radio Std: None Frequency Center Freg 5.720000000 GHz Radio Device: BTS 5.71772 C Ref Offset 11.3 dB Ref 20.00 dBm ٠ Center Freq 5.72000000 GHz Center 5.72 GHz #Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MI #VBW 680 kHz 20.7 dBm Total Power Occupied Bandwidth 17.581 MHz Freq Offse 27.901 kHz 0 Hz % of OBW Power 99.00 % Transmit Freg Error x dB Bandwidth 19.98 MHz x dB -26.00 dB 11AC20SISO_Ant1_5745 12:21:45 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURCE OFF ALIGN AUTO Center Freq: 5.745000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB r Freq 5.745000000 GHz Radio Device: BTS n:Low kr1 5.7436 G 4.3164 dE Ref Offset 11.3 dB Ref 20.00 dBm **→**¹ Center Freq 5.745000000 GH enter 5.745 GHz Res BW 220 kHz Span 40 MHz Sweep 1 ms CF Step 4.000000 MHz #VBW 680 kHz Auto Ma Total Power 20.7 dBm Occupied Bandwidth 17.577 MHz Freq Offse Transmit Freq Error 18.673 kHz % of OBW Power 99.00 % 0 H 19.86 MHz x dB Bandwidth -26.00 dB x dB 11AC20SISO_Ant1_5785 12:22:04 PM Dec 30, 2024 Radio Std: None SENSE:INT SOURCE OFF ALIGN AUTO Center Freq: 5.785000000 GHz Trig: Free Run Avg|Hold: 100/100 #Atten: 30 dB er Freq 5.785000000 GHz Radio Device: BTS 5.78128 C 4.7726 d Ref Offset 11.3 dB Ref 20.00 dBm Center Freq 5 78500000 GH: Span 40 MHz Sweep 1 ms Center 5.785 GHz Res BW 220 kHz CF Step 00000 MH #VBW 680 kHz 4.0000 Auto Ma Total Power 21.0 dBm Occupied Bandwidth 17.583 MHz Freq Offset 0 Ha Transmit Freq Error 21.406 kHz % of OBW Power 99.00 % x dB Bandwidth 19.79 MHz -26.00 dB x dB