

FCC - TEST REPORT

Report Number : **709502204638-00A** Date of Issue: July 12,2022Model : WL2H-UProduct Type : Wi-Fi and Bluetooth ModuleApplicant : Hangzhou Tuya Information Technology Co.,LtdAddress : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang ChinaManufacturer : Hangzhou Tuya Information Technology Co.,LtdAddress : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang ChinaTest Result : ☒ **Positive** ☐ **Negative**Total pages including
Appendices : 49

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test	4
4	Summary of Test Standards.....	6
5	Summary of Test Results.....	7
6	General Remarks	8
7	Test Setups	9
8	Systems test configuration.....	12
9	Technical Requirement	13
9.1	Conducted Emission	13
9.2	Conducted peak output power.....	16
9.3	6dB bandwidth	17
9.4	Power spectral density.....	21
9.5	Spurious RF conducted emissions	25
9.6	Band edge	35
9.7	Spurious radiated emissions for transmitter	39
10	Test Equipment List.....	46
11	System Measurement Uncertainty	47
12	Photographs of Test Set-ups	48
13	Photographs of EUT	49



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Test Firm FCC
Registration
Number: 820234

Designation
number: CN1183

IC Company
Number: 25988

CAB identifier: CN0101

Telephone: +86 21 6141 0123
Fax: +86 21 6140 8600

3 Description of the Equipment under Test

Product: Wi-Fi and Bluetooth Module

Model no.: WL2H-U

FCC ID: 2ANDL-WL2H-U

Options and accessories: NA

Rating: 3.0V-3.6V DC

RF Transmission Frequency: For 802.11b/g/n(HT20): 2412~2462 MHz (Wi-Fi)
For 802.15.1:2402~2480 MHz

No. of Operated Channel: 2.4GHz WIFI: 11 for 802.11b/g/n(HT20)
2.4GHz BLE: 40

Modulation: Direct Sequence Spread Spectrum (DSSS) for 802.11b
Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g/n; 2.4GHz BLE: GFSK

Channel list:

802.11b/g/n(HT20)			
Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Antenna Type: onboard PCB antenna



China

Antenna Gain: 1.39dBi

Description of the EUT: The Equipment Under Test (EUT) is a Wi-Fi and Bluetooth module which support 2.4GHz Wi-Fi and BLE 5.1(support 1Mbps and 2Mbps data rate). We tested it and listed the worst data in this report.

Test sample no.: SHA-656253-1

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	13-15	Site 1	☒	☐	☐
§15.247 (b) (1)	Conducted peak output power	16	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	17-20	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	21-24	Site 1	☒	☐	☐
§15.247(d)	Spurious RF conducted emissions	25-34	Site 1	☒	☐	☐
§15.247(d)	Band edge	35-38	Site 1	☒	☐	☐
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	39-45	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an onboard PCB antenna, which gain is 1.39dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-WL2H-U, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

This report is only for the 2.4GHz Wi-Fi test report, for the 2.4GHz BLE test report please refer to 709502204638-00B.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: June 1, 2022

Testing Start Date: June 8, 2022

Testing End Date: July 8, 2022

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:

Hui TONG
Review Engineer




Jiaxi XU
Project Engineer

Cheng Huali
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	E470	PF-OU5TS7 17/09

Test software: sscom5.13.1

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n(HT20) test.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Wi-Fi and Bluetooth module
 M/N : WL2H-U
 Operating Condition : Mode 1: Tx_2412MHz for 802.11g
 Test Specification : L-line
 Comment : AC 120V/60Hz (powered by notebook)




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.181500	46.82	---	64.42	17.60	1000.0	9.000	L1	19.5
0.195000	---	30.26	53.82	23.56	1000.0	9.000	L1	19.5
0.487500	33.24	---	56.21	22.97	1000.0	9.000	L1	19.5
0.604500	---	21.15	46.00	24.85	1000.0	9.000	L1	19.5
2.067000	---	23.73	46.00	22.27	1000.0	9.000	L1	19.5
2.107500	34.99	---	56.00	21.01	1000.0	9.000	L1	19.5
3.070500	---	30.50	46.00	15.50	1000.0	9.000	L1	19.6
3.156000	37.59	---	56.00	18.41	1000.0	9.000	L1	19.6
13.137000	---	29.94	50.00	20.06	1000.0	9.000	L1	19.7
13.276500	35.62	---	60.00	24.38	1000.0	9.000	L1	19.7
17.511000	36.17	---	60.00	23.83	1000.0	9.000	L1	19.8
17.853000	---	29.63	50.00	20.37	1000.0	9.000	L1	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

Product Type : Wi-Fi and Bluetooth module
 M/N : WL2H-U
 Operating Condition : Mode 1: Tx_2412MHz for 802.11g
 Test Specification : N-line
 Comment : AC 120V/60Hz (powered by notebook)



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.186000	---	31.27	54.21	22.94	1000.0	9.000	N	19.5
0.199500	44.19	---	63.63	19.44	1000.0	9.000	N	19.5
0.600000	---	18.77	46.00	27.23	1000.0	9.000	N	19.5
0.829500	29.35	---	56.00	26.65	1000.0	9.000	N	19.5
2.098500	31.67	---	56.00	24.33	1000.0	9.000	N	19.5
2.107500	---	20.25	46.00	25.75	1000.0	9.000	N	19.5
3.070500	---	29.65	46.00	16.35	1000.0	9.000	N	19.5
3.952500	35.52	---	56.00	20.48	1000.0	9.000	N	19.5
12.313500	---	30.92	50.00	19.08	1000.0	9.000	N	19.7
12.340500	37.13	---	60.00	22.87	1000.0	9.000	N	19.7
13.078500	---	33.84	50.00	16.16	1000.0	9.000	N	19.7
13.078500	40.29	---	60.00	19.71	1000.0	9.000	N	19.7

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

Test result

802.11b

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	19.17	Pass
Middle channel 2437MHz	18.10	Pass
High channel 2462MHz	17.95	Pass

802.11g

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	22.35	Pass
Middle channel 2437MHz	21.99	Pass
High channel 2462MHz	21.81	Pass

802.11n(HT20)

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	22.25	Pass
Middle channel 2437MHz	21.97	Pass
High channel 2462MHz	21.81	Pass

9.3 6dB bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]

≥ 500

Test result

802.11b

Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	10.072	Pass
Middle channel 2437MHz	9.559	Pass
Bottom channel 2462MHz	10.052	Pass

802.11g


Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	15.115	Pass
Middle channel 2437MHz	15.479	Pass
Bottom channel 2462MHz	15.456	Pass

802.11n(HT20)

Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	15.340	Pass
Middle channel 2437MHz	15.129	Pass
Bottom channel 2462MHz	15.665	Pass


6 dB Bandwidth

802.11b
11B_Ant1_2412




Date: 27 JUN 2022 11:13:45

11B_Ant1_2437



Date: 27 JUN 2022 11:16:49


11B_Ant1_2462



Date: 27 JUN 2022 11:18:42


802.11g

11G_Ant1_2412




Date: 27 JUN 2022 11:20:56

11G_Ant1_2437



Date: 27 JUN 2022 11:22:33


11G_Ant1_2462



Date: 27 JUN 2022 11:24:24




802.11n(HT20)
11N20SISO_Ant1_2412




Date: 27 JUN 2022 11:26:37

11N20SISO_Ant1_2437



Date: 27 JUN 2022 11:29:46

11N20SISO_Ant1_2462



Date: 27 JUN 2022 11:31:24

9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]

≤ 8

Test result

802.11b

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-7.02	Pass
Middle channel 2437MHz	-7.25	Pass
High channel 2462MHz	-7.42	Pass

802.11g

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-13.41	Pass
Middle channel 2437MHz	-13.79	Pass
High channel 2462MHz	-13.69	Pass


802.11 n(HT20)

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-13.12	Pass
Middle channel 2437MHz	-14.11	Pass
High channel 2462MHz	-13.70	Pass

Power spectral density


802.11b

11B_Ant1_2412




Date: 27 JUN 2022 11:14:06

11B_Ant1_2437




Date: 27 JUN 2022 11:17:26

11B_Ant1_2462




Date: 27 JUN 2022 11:19:22

802.11g
11G_Ant1_2412


Date: 27 JUN 2022 11:21:17

11G_Ant1_2437




Date: 27 JUN 2022 11:23:01

11G_Ant1_2462




Date: 27 JUN 2022 11:24:52

802.11n (HT20)
11N20SISO_Ant1_2412


Date: 27 JUN 2022 11:26:57

11N20SISO_Ant1_2437



Date: 27 JUN 2022 11:30:13

11N20SISO_Ant1_2462



Date: 27 JUN 2022 11:31:51

9.5 Spurious RF conducted emissions

Test Method

1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20

Spurious RF conducted emissions


802.11b

Out-of-Band Emissions


Channel 1 (2412MHz)

Reference point**Spurious Emission (30MHz – 1GHz)**


Date: 27 JUN 2022 11:14:21



Date: 27 JUN 2022 11:14:25

Spurious Emission (1GHz – 5GHz)**Spurious Emission (5GHz – 26.5GHz)**

Date: 27 JUN 2022 11:14:37




Date: 27 JUN 2022 11:15:08

Out-of-Band Emissions


Channel 6 (2437MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:17:30




Date: 27 JUN 2022 11:17:35

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:17:47




Date: 27 JUN 2022 11:18:18

Out-of-Band Emissions


Channel 11 (2462MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:19:36




Date: 27 JUN 2022 11:19:41

Spurious Emission (1GHz –5GHz)

Spurious Emission (5GHz –26.5GHz)



Date: 27 JUN 2022 11:19:53



Date: 27 JUN 2022 11:20:24


802.11g

Out-of-Band Emissions


Channel 1 (2412MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:21:31




Date: 27 JUN 2022 11:21:35

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:21:47




Date: 27 JUN 2022 11:22:18

Out-of-Band Emissions


Channel 6 (2437MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:23:06




Date: 27 JUN 2022 11:23:10

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:23:22




Date: 27 JUN 2022 11:23:54

Out-of-Band Emissions


Channel 11 (2462MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:25:06




Date: 27 JUN 2022 11:25:10

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:25:22



Date: 27 JUN 2022 11:25:53


802.11n(HT20)

Out-of-Band Emissions


Channel 1 (2412MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:27:11




Date: 27 JUN 2022 11:27:16

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:27:28




Date: 27 JUN 2022 11:27:59

Out-of-Band Emissions


Channel 6 (2437MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:30:18




Date: 27 JUN 2022 11:30:23

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:30:35




Date: 27 JUN 2022 11:31:06

Out-of-Band Emissions


Channel 11 (2462MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 27 JUN 2022 11:32:05




Date: 27 JUN 2022 11:32:10

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 27 JUN 2022 11:32:22



Date: 27 JUN 2022 11:32:53

9.6 Band edge

Test Method


- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

Limit

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.


Test result

802.11b
2412



Date: 27.JUN 2022 11:14:15


2462



Date: 27.JUN 2022 11:19:31


802.11g

2412



Date: 27.JUN.2022 11:21:25


2462



Date: 27.JUN.2022 11:25:00


802.11n(HT20)

2412



Date: 27.JUN.2022 11:27:06

2462



Date: 27.JUN.2022 11:32:00

9.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW ≥ $[3 \times \text{RBW}]$.
- c) Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq \text{RBW} / 2$.
 Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the

emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBμV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

Pre-scan with three orthogonal axis and worst case as X axis listed below table

Test mode:802.11B (2412MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2389.04	52.39	74	21.61	PK	Horizontal
4823.86	50.75	74	23.25	PK	Horizontal
2377.12	43.15	74	30.85	PK	Vertical
4823.86	44.37	74	29.63	PK	Vertical

Test mode:802.11B (2437MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.73	46.96	74.00	27.04	PK	Horizontal
4873.73	42.80	74.00	31.20	PK	Vertical

Test mode:802.11B (2462MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2486.80	47.65	74.00	26.35	PK	Horizontal
4924.10	46.85	74.00	27.15	PK	Horizontal
2483.60	44.64	74.00	29.36	PK	Vertical
4923.60	42.36	74.00	31.64	PK	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

Test mode:802.11G (2412MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2388.88	57.45	74	16.55	PK	Horiznotal
2388.88	43.30	54	10.70	PK	Horiznotal
4824.13	42.54	74	31.46	PK	Horiznotal
2388.40	50.18	74	23.82	PK	Vertical
4824.13	42.92	74	31.08	PK	Vertical

Test mode:802.11G (2437MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.03	43.02	74.00	30.98	PK	Horiznotal
4874.03	43.15	74.00	30.85	PK	Vertical

Test mode:802.11G (2462MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.60	56.78	74.00	17.22	PK	Horiznotal
2483.60	41.88	54.00	12.12	AV	Horiznotal
4924.21	43.65	74.00	30.35	PK	Horiznotal
2483.60	48.21	74.00	25.79	PK	Vertical
4923.60	43.28	74.00	30.72	PK	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

Test mode:802.11N (2412MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M	Margin (dB)	Detector	Polarization
2388.00	58.69	74	15.31	PK	Horiznotal
2388.00	42.80	54	11.20	AV	Horiznotal
4823.78	43.75	74	30.25	PK	Horiznotal
2388.00	49.35	74	24.65	PK	Vertical
4823.86	42.33	74	31.67	PK	Vertical

Test mode:802.11N (2437MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M	Margin (dB)	Detector	Polarization
4874.01	43.12	74.00	30.88	PK	Horiznotal
4874.01	42.19	74.00	31.81	PK	Vertical

Test mode:802.11N (2462MHz)					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M	Margin (dB)	Detector	Polarization
2483.70	57.48	74.00	16.52	PK	Horiznotal
2483.70	41.70	54.00	12.30	AV	Horiznotal
4923.98	42.43	74.00	31.57	PK	Horiznotal
2483.77	47.38	74.00	26.62	PK	Vertical
4923.60	42.46	74.00	31.54	PK	Vertical


Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

The worst case of Radiated Emission below 1GHz:

Site: 3-meter chamber	Time: 2022/07/03 - 11:50
Limit: FCC_Part15.109_RE(3m)_ClassB	Engineer: Cheng Huali
Probe: VULB9168	Polarity: Horizontal
EUT: Wi-Fi and Bluetooth module, Model no: WL2H-U	Power: DC 3.3V by debug board for EUT, AC 120V,60Hz for notebook
Note: Transmit by 802.11g at channel 2412MHz.	
Note: Pre-scan with three orthogonal axis and worst case as X axis.	

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
120.000000	26.9	1000.0	120.000	100.0	H	354.0	18.1	16.7	43.5
143.240000	31.7	1000.0	120.000	100.0	H	108.0	20.6	11.8	43.5
168.000000	32.8	1000.0	120.000	100.0	H	54.0	20.4	10.7	43.5
215.960000	32.9	1000.0	120.000	100.0	H	287.0	17.5	10.6	43.5
320.040000	34.6	1000.0	120.000	100.0	H	241.0	22.2	11.4	46.0
360.000000	35.3	1000.0	120.000	100.0	H	174.0	23.0	10.7	46.0


Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

Site: 3-meter chamber	Time: 2022/07/03 - 11:21
Limit: FCC_Part15.109_RE(3m)_ClassB	Engineer: Cheng Huali
Probe: VULB9168	Polarity: Vertical
EUT: Wi-Fi and Bluetooth module, Model no: WL2H-U	Power: DC 3.3V by debug board for EUT, AC 120V,60Hz for notebook
Note: Transmit by 802.11g at channel 2412MHz. Note: Pre-scan with three orthogonal axis and worst case as X axis.	

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
71.960000	25.6	1000.0	120.000	100.0	V	123.0	18.2	14.4	40.0
119.960000	28.1	1000.0	120.000	100.0	V	82.0	18.1	15.4	43.5
143.240000	24.6	1000.0	120.000	100.0	V	325.0	20.6	18.9	43.5
168.000000	31.0	1000.0	120.000	100.0	V	28.0	20.4	12.5	43.5
216.040000	26.4	1000.0	120.000	100.0	V	286.0	17.5	19.6	46.0
360.040000	32.6	1000.0	120.000	100.0	V	176.0	23.0	13.4	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

10 Test Equipment List

List of Test Instruments
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
	Wideband power sensor	Rohde & Schwarz	NRP-Z81	105903	2022-03-18	2023-3-19
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2021-8-2	2022-8-1
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2021-9-23	2024-9-22
	Double-ridged waveguide horn antenna	Rohde & Schwarz	HF907	102868	2021-3-15	2024-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2021-8-2	2022-8-1
	Loop antenna	Rohde & Schwarz	HFH2-Z2E	100933	2022-6-13	2023-6-12
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2023-9-22
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2021-8-2	2022-8-1
	LISN	Rohde & Schwarz	ENV216	101924	2021-8-2	2022-8-1

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	Bluetooth and WiFi Test System	Shenzhen JS tonscent co.,ltd	2.6.77.0518
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, $\pm 3.16\text{dB}$
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03\text{dB}$ (Horizontal) $\pm 5.12\text{dB}$ (Vertical) 1GHz to 18GHz, $\pm 5.49\text{dB}$ 18GHz to 40GHz, $\pm 5.63\text{dB}$
Carrier power conducted measurement	50MHz~18GHz, $\pm 1.238\text{dB}$
Spurious Emission Conducted Measurement	9kHz ~40GHz, $\pm 1.224\text{dB}$

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.



12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

THE END