

FCC ID: 2AKU53M

Portable device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right]^* \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

	Channel Freq. (MHz)	Max Transmit Power (dBm)	Max tune-up power (dBm)	Result calculation	1-g SAR
GFSK	2402	-5.57	-4	0.12	3.0
	2440	-3.87	-2	0.20	3.0
	2480	-2.85	-1	0.25	3.0

Conclusion:

For the max result : $0.25 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2021.9.24

NAME AND TITLE (Please print or type): Lisa Wang/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China