

FCC PART 15, SUBPART F ISEDC RSS-220, ISSUE 1, JULY 2018

TEST REPORT

For

Tesla, Inc.

3500 Deer Creek Road Palo Alto, CA 94304, USA

FCC ID: 2AEIM-1783148 IC: 20098-1783148

Report Type:		Product Type:	
Original Report		Automotive Part	
Prepared By	Christian McCaig RF Lead Engineer		
Report Number	R2203281-03		
Report Date	2022-06-15		
Reviewed By	Simon Ma RF Supervisor		
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162, Fax: (408) 732 9164			



Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

1 G	eneral Description	
1.1	Product Description for Equipment Under Test (EUT)	4
1.2	Mechanical Description of EUT	4
1.3	Objective	4
1.4	Related Submittal(s)/Grant(s)	4
1.5	Test Methodology	4
1.6	Measurement Uncertainty	
1.7	Test Facility Registrations	
1.8	Test Facility Accreditations	
	ystem Test Configuration	
2.1	Justification	
2.2	EUT Exercise Software	
2.3	Equipment Modifications	
2.4	Remote Support Equipment	
2.5	Local Support Equipment	
2.6	Interface Ports and Cabling	
3 SI	ummary of Test Results	
	CC §15.203 & ISEDC RSS-220 §5.1(b), RSS-Gen §6.8 - Antenna Requirements	
4.1	Applicable Standards	
4.2	Antenna Description	
	CC §15.209, §15.519(c), (d) & ISEDC RSS-220 §3.4, §5.3.1(d), (e), RSS-Gen §8.9, §8.10 - Spurious	
	ssions	
5.1	Applicable Standards	
5.2	Test Setup	
5.3	Measurement Procedure	
5.4	Corrected Amplitude and Margin Calculation	
5.5	Test Setup Block Diagram	
5.6	Test Equipment List and Details	
5.7	Test Environmental Conditions	
5.8	Test Results below 1 GHz measured at 3 meters	
5.9	Test Results above 1 GHz	
	CC §15.519(e), §15.521(e) & ISEDC RSS-220 §5.3.1(g) - Peak Fundamental Emission	
6.1	Applicable Standards	
6.2	Measurement Procedure	
6.3	Test Setup Block Diagram	
6.4	Test Equipment List and Details	
6.5	Test Environmental Conditions	
6.6	Test Results	
7 F	CC §15.503(d), §15.519(b) & ISEDC RSS-220 §5.1(a), RSS-Gen §6.7 -Emission Bandwidth	
7.1	Applicable Standards	
7.2	Measurement Procedure	51
7.3	Test Setup Block Diagram	51
7.4	Test Equipment List and Details	
7.5	Test Environmental Conditions	
7.6	Test Results	
8 F	CC §15.519(a) (1) & ISEDC RSS-220 §5.3.1(b) - Cease Transmission	59
8.1	Applicable Standards	
8.2	Measurement Procedure	59
8.3	Test Setup Block Diagram	
8.4	Test Equipment List and Details	60
8.5	Test Environmental Conditions	60
8.6	Test Results	
	nnex A (Normative) - Test Setup Photographs	
	nnex B (Normative) - EUT External Photographs	
	nnex C (Normative) - EUT Internal Photographs	
12 A	nnex D (Normative) - A2LA Electrical Testing Certificate	

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R2203281-03	Original Report	2022-06-15

1 General Description

1.1 Product Description for Equipment Under Test (EUT)

This test report was prepared on behalf of *Tesla, Inc.*, and their product model: 1783148, *FCC ID: 2AEIM-1783148*; *IC: 20098-1783148* or the "EUT" as referred to in this report. The EUT is an Automotive Part (B Pillar Endpoint) with Ultra Wide-band (UWB) operating in 6489.6-7987.2 MHz, Bluetooth Low Energy, and NFC capabilities.

UWB Subclass as specified by RSS-220 §3.2: Hand-held Communication Devices.

The radio terminal has data port.

1.2 Mechanical Description of EUT

1783148 measures approximately 55 cm (Length) x 15.5 cm (Width) x 1 cm (High), and weighs approximately 0.6kg.

The data gathered are from a typical production sample provided by the manufacturer with serial number: ED322025000037, assigned by Tesla, Inc.

1.3 Objective

This report was prepared on behalf of *Tesla, Inc.*, in accordance with Part 2, Subpart J, and Part 15, Subpart and F of the Federal Communication Commission's rules and ISEDC RSS-220 Issue 1, July 2018.

The objective was to determine compliance with FCC Part 15.519 and ISEDC RSS-220 rules for Peak Fundamental Emission, Antenna Requirements, UWB Bandwidth, Average Radiated Emissions, Radiated Spurious Emissions and Ceasing Transmission requirements.

1.4 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart C, Equipment Class: DTS with FCC ID: 2AEIM-1783148; IC: 20098-1783148 FCC Part 15, Subpart C, Equipment Class: DXX with FCC ID: 2AEIM-1783148; IC: 20098-1783148

1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 393761 D01 UWB FAQ v02: Ultra-Wideband (UWB) Devices Frequently Asked Questions.

1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.57 dB
Power Spectral Density, conducted	±1.48dB
Unwanted Emissions, conducted	±1.57dB
All emissions, radiated	±4.0 dB
AC power line Conducted Emission	±2.0 dB
Temperature	±2 ° C
Humidity	±5 %
DC and low frequency voltages	±1.0 %
Time	±2 %
Duty Cycle	±3 %

1.7 Test Facility Registrations

BACLs test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R.

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

1.8 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

A- An independent, 3rd-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2017 by A2LA (Test Laboratory Accreditation Certificate Number 3297.02), in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2017 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report.

BACL's ISO/IEC 17025:2017 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment

Tesla, Inc.

[including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.03) to certify

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.
- For the Canada (Industry Canada):
 - 1- All Scope 1-Licence-Exempt Radio Frequency Devices;
 - 2- All Scope 2-Licensed Personal Mobile Radio Services;
 - 3- All Scope 3-Licensed General Mobile & Fixed Radio Services;
 - 4- All Scope 4-Licensed Maritime & Aviation Radio Services;
 - 5- All Scope 5-Licensed Fixed Microwave Radio Services
 - 6- All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.
- For Singapore (Info-Communications Development Authority (IDA)):
 - 1- All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
 - 2- All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2
- For the Hong Kong Special Administrative Region:
 - 1- All Radio Equipment, per KHCA 10XX-series Specifications;
 - 2- All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
 - All Fixed Network Equipment, per HKCA 20XX-series Specifications.
- For Japan:

3-

1-

- MIC Telecommunication Business Law (Terminal Equipment):
 - All Scope A1 Terminal Equipment for the Purpose of Calls;
 - All Scope A2 Other Terminal Equipment
- 2- Radio Law (Radio Equipment):
 - All Scope B1 Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
 - All Scope B2 Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
 - All Scope B3 Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.01) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:

- 1 Electronics and Office Equipment:
 - for Telephony (ver. 3.0)
 - for Audio/Video (ver. 3.0)
 - for Battery Charging Systems (ver. 1.1)
 - for Set-top Boxes & Cable Boxes (ver. 4.1)
 - for Televisions (ver. 6.1)
 - for Computers (ver. 6.0)
 - for Displays (ver. 6.0)
 - for Imaging Equipment (ver. 2.0)
 - for Computer Servers (ver. 2.0)

- 2 Commercial Food Service Equipment
 - for Commercial Dishwashers (ver. 2.0)
 - for Commercial Ice Machines (ver. 2.0)
 - for Commercial Ovens (ver. 2.1)
 - for Commercial Refrigerators and Freezers
- 3 Lighting Products
 - For Decorative Light Strings (ver. 1.5)
 - For Luminaires (including sub-components) and Lamps (ver. 1.2)
 - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
 - For Integral LED Lamps (ver. 1.4)
 - Heating, Ventilation, and AC Products
 - for Residential Ceiling Fans (ver. 3.0)
 - for Residential Ventilating Fans (ver. 3.2)
- 5 Other

4

• For Water Coolers (ver. 3.0)

D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:

- Australia: ACMA (Australian Communication and Media Authority) APEC Tel MRA -Phase I;
- Canada: (Innovation, Science and Economic development Canada ISEDC) Foreign Certification Body FCB APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China Taiwan):
 - BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
 - NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
 - EMC Directive 2014/30/EU US-EU EMC & Telecom MRA CAB (NB)
 - Radio Equipment (RE) Directive 2014/53/EU US-EU EMC & Telecom MRA CAB (NB)
 - Low Voltage Directive (LVD) 2014/35/EU
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority OFTA) APEC Tel MRA -Phase I & Phase II
- Israel US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Media Development Authority IMDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
- USA:
 - ENERGY STAR Recognized Test Laboratory US EPA
 - Telecommunications Certification Body (TCB) US FCC;
 - Nationally Recognized Test Laboratory (NRTL) US OSHA
- Vietnam: APEC Tel MRA -Phase I;

2 System Test Configuration

2.1 Justification

The EUT was configured for testing according to ANSI C63.10-2013.

The EUT was tested in a testing mode to represent worst-case results during the final qualification test.

2.2 EUT Exercise Software

Python scripts were provided by Tesla, Inc., and was verified to be compliant with the standard requirements being tested against. The following channel frequencies were selected for testing. All the modes were measured for fundamental field strength, and the corresponding power settings used are listed below.

Radio	Frequency (MHz)	Mode	Power Setting
		0	2.75
	6489.6 MHz (Channel 5)	4	0.75
	(Chaliner 5)	13	1.25
		0	4.5
UWB	6988.8 MHz (Channel 6)	4	3
		13	3.25
	7987.2 MHz (Channel 9)	0	4.5
		4	2.25
		13	2.5

Please refer to the Operational Description for detailed description of the test modes.

2.3 Equipment Modifications

None

2.4 Remote Support Equipment

Manufacturer	Description	Model	S/N
HP	Laptop	Zbook Studio G3	00329-00000-00003-AA284
PJRC	Teensy	Teensy-LC	M26M6VFT1N1SJCRFKCJ

2.5 Local Support Equipment

Manufacturer	Description	Model	S/N
Volteq	DC Power Supply	HY5003D	160402343

2.6 Interface Ports and Cabling

Cable Description	Length (m)	То	From
Power Cables	< 1 m	EUT	DC Power Supply
RF Cable	1 m	EUT	PSA
USB Type A to Micro USB Type B Cable	< 1 m	PC	Teensy
RS-232 Cable	< 1 m	Teensy	EUT

3 Summary of Test Results

Results reported relate only to the product tested.

FCC and ISEDC Rules	Description of Test	Results
FCC §15.203 ISEDC RSS-220 §5.1(b), ISEDC RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207 ISEDC RSS-Gen §8.8	AC Line Conducted Emissions	N/A ¹
FCC §2.1091, §1.1310(d) (3) ISEDC RSS-102	RF Exposure	Compliant ²
FCC §2.1053, §15.205, §15.209, §15.519(c) ISEDC RSS-220 §3.4, 5.3.1(c) ISEDC RSS-Gen §8.9 & §8.10	Radiated Spurious Emissions	Compliant
FCC §15.503(d),§15.519(b) ISEDC RSS-220 §5.1(a) ISEDC RSS-Gen§6.7	Emission Bandwidth	Compliant
FCC §15.519(e) ISEDC RSS-220 §5.3.1(g)	Peak Fundamental Emission	Compliant
FCC §15.519(c), §15.519(d) ISEDC RSS-220 §5.3.1(d), §5.3.1(e)	Average Radiated Emissions	Compliant
FCC §15.519(a)(1) ISEDC RSS-220 §5.3.1(b)	Cease Transmission	Compliant

Note¹: Device is powered by car battery.

Note²: Please refer to Test Report R2203281-04 for FCC RF Exposure Evaluation, Test Report R2203281-05 for IC RF Exposure Evaluation.

4 FCC §15.203 & ISEDC RSS-220 §5.1(b), RSS-Gen §6.8 - Antenna Requirements

4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to ISEDC RSS-Gen §6.8: Transmitter Antenna

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.2 Antenna Description

External/Internal/Integral	Channel Frequency (MHz)	Maximum Antenna Gain (dBi)	Antenna Type
	6489.6	1.74	
Integral	6988.8	2.72	Chip Antenna
	7987.2	1.03	

The antenna is factory-installed and is not modifiable by users. The antenna gain is information provided by the customer.

5 FCC §15.209, §15.519(c), (d) & ISEDC RSS-220 §3.4, §5.3.1(d), (e), RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

5.1 Applicable Standards

As per FCC §15.519(c), the radiated emissions at or below 960 MHz from a device operating under the provisions of this section shall not exceed the emission levels in §15.209

As per FCC §15.35(b): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
$\begin{array}{c} 0.090-0.110\\ 0.495-0.505\\ 2.1735-2.1905\\ 4.125-4.128\\ 4.17725-4.17775\\ 4.20725-4.20775\\ 6.215-6.218\\ 6.26775-6.26825\\ 6.31175-6.31225\\ 8.291-8.294\\ 8.362-8.366\\ 8.37625-8.38675\\ 8.41425-8.41475\\ 12.29-12.293\\ 12.51975-12.52025\\ 12.57675-12.57725\\ 13.36-13.41\\ \end{array}$	$\begin{array}{c} 16.42 - 16.423\\ 16.69475 - 16.69525\\ 25.5 - 25.67\\ 37.5 - 38.25\\ 73 - 74.6\\ 74.8 - 75.2\\ 108 - 121.94\\ 123 - 138\\ 149.9 - 150.05\\ 156.52475 - 156.52525\\ 156.7 - 156.9\\ 162.0125 - 167.17\\ 167.72 - 173.2\\ 240 - 285\\ 322 - 335.4\\ 399.9 - 410\\ 608 - 614\\ \end{array}$	$\begin{array}{r} 960-1240\\ 1300-1427\\ 1435-1626.5\\ 1645.5-1646.5\\ 1660-1710\\ 1718.8-1722.2\\ 2200-2300\\ 2310-2390\\ 2483.5-2500\\ 2690-2900\\ 3260-3267\\ 3332-3339\\ 3345.8-3358\\ 3600-4400\\ \end{array}$	$\begin{array}{c} 4.5-5.15\\ 5.35-5.46\\ 7.25-7.75\\ 8.025-8.5\\ 9.0-9.2\\ 9.3-9.5\\ 10.6-12.7\\ 13.25-13.4\\ 14.47-14.5\\ 15.35-16.2\\ 17.7-21.4\\ 22.01-23.12\\ 23.6-24.0\\ 31.2-31.8\\ 36.43-36.5\\ Above 38.6 \end{array}$

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz.

However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per ISEDC RSS-Gen §8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in the table below. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Frequency (MHz)	Field Strength (µv/m at 3 meters)
30-88	100
88-216	150
216-960	200
Above 960	500

General Field Strength Limits at Frequencies above 30 MHz

As per ISEDC RSS-220 §5.3.1(c), Radiated emissions at or below 960 MHz from a device shall not exceed the limits in section 3.4

As per ISEDC RSS-220 §3.4, Radiated emissions at or below 960 MHz for all subclasses of UWB device shall not exceed the following limits. Measurements of radiated emissions at and below 960 MHz are to be made using a CISPR quasi-peak detector. CISPR measurement bandwidth specifications are to be used

Frequency (MHz)	Field Strength (Microvolts/m)	Measurement Distance (Metres)	E.i.r.p. (dBmW)
0.009-0.490	2,400/F (F in kHz)	300	10 log (17.28 / F²) (F in kHz)
0.490-1.705	24,000/F (F in kHz)	30	10 log (17.28 / F²) (F in kHz)
1.705-30	30	30	-45.7
30-88	100	3	-55.2
88-216	150	3	-51.7
216-960	200	3	-49.2

Radiated Emissions at or below 960 MHz

According to FCC §15.519(c): (c) The radiated emissions at or below 960 MHz from a device operating under the provisions of this section shall not exceed the emission levels in §15.209. The radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz:

Frequency in MHz	EIRP in dBm
960-1610	-75.3
1610-1990	-63.3
1990-3100	-61.3
3100-10600	-41.3
Above 10600	-61.3

According to ISEDC RSS-220 §5.3.1(d): Radiated emissions above 960 MHz from a device shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz.

Frequency	EIRP
960-1610 MHz	-75.3 dBm
1.61-4.75 GHz	-70.0 dBm
4.75-10.6 GHz	-41.3 dBm
Above 10.6 GHz	-61.3 dBm

According to FCC §15.519(c): (d) In addition to the radiated emission limits specified in the table in paragraph (c) of this section, UWB transmitters operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of no less than 1 kHz:

Frequency in MHz	EIRP in dBm
1164-1240	-85.3
1559-1610	-85.3

According to ISEDC RSS-220 §5.3.1(e): In addition to the limits specified in paragraph (d) of this section, radiated emissions shall not exceed the following average limits when measured using a resolution bandwidth greater than or equal to 1 kHz. The measurements shall demonstrate compliance with the stated limits at whatever resolution bandwidth is used.

Frequency	e.i.r.p. in a Resolution Bandwidth of no less than 1 kHz
1164-1240 MHz	-85.3 dBm
1559-1610 MHz	-85.3 dBm

5.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart F and ISEDC RSS-220 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

5.3 Measurement Procedure

The EUT host, and all support equipment power cords were connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

For radiated testing the EUT was set 1 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 960 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna's polarity should be changed between horizontal and vertical.

The spectrum analyzer or receiver was set as:

Below 960 MHz:

RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto

Above 960 MHz:

The measurements were based on ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices section 10.3: Radiated measurement procedure above 960MHz.

5.4 Corrected Amplitude and Margin Calculation

For emissions below 1 GHz,

The Corrected Amplitude (CA) is calculated by adding the Correction Factor to the S.A. Reading. The basic equation is as follows:

CA = S.A. Reading + Correction Factor

For example, a corrected amplitude of 40.3 dBuV/m = S.A. Reading (32.5 dBuV) + Correction Factor (7.8 dB/m)

The Correction Factor is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) together. This calculation is done in the measurement software, and reported in the test result section. The basic equation is as follows:

Correction Factor = AF + CL + Atten - Ga

For emission above 1 GHz,

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$CA = Ai + AF + CL + Atten - Ga$$


For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5 dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Corrected Amplitude – Limit

5.5 Test Setup Block Diagram


Below 1GHz:



Ground Plane


Above 1GHz:


At 3 meters:



Ground Plane


At 1 meter





Ground Plane

18 GHz to 40 GHz (Asset #91 and #230 Antennas used):



Ground Plane

Bacl No.	Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
655	Rhode & Schwarz	Spectrum Analyzer	FSQ26	200749	2022-02-07	2 years
-	Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
1192	ETS Lindgren	Horn Antenna	3117	00218973	2021-09-14	2 years
32	HP	Pre-Amplifier	8449B	3008A019 78	2022-05-09	1 year
-	-	SMA cable	-	-	Each time ¹	N/A
1077	Insulated Wire Corp	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN- 3960-KPS	DC 1917	2022-03-03	1 year
124	Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100044	2021-05-14	2 years
912	Rhode & Schwarz	Spectrum Analyzer	FSV40	1321.3008 K39- 101203- UW	2022-05-05	1 year
287	Agilent	Spectrum Analyzer	E4446A	MY48250 238	2022-05-05	1 year
321	Sunol Sciences	Biconilog Antenna	JB3	A020106-2	2021-11-22	2 years
874	ETS Lindgren	Horn Antenna w/ built in Preamplifier	3117 PA	203557	2020-06-20	2 years
230	Wisewave	Antenna, Horn	ARH-2823-02	10555-02	2022-03-08	2 years
91	Wisewave	Antenna, Horn	ARH-4223-02	10555-02	2022-03-08	2 years
	-	SMA cable1	-	-	Each time ¹	N/A
	-	SMA cable2	-	-	Each time ¹	N/A
1228	Pasternack	Coaxial Cable, RG213	PE3496- 800CM	2111301	2021-11-30	1 year
459	HP	Amplifier, Pre	8447D	2443A043 74	2021-11-02	1 year
827	AH Systems	Preamplifier	PAM 1840 VH	170	2021-08-03	1 year
	Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

5.6 Test Equipment List and Details

Note¹: cables included in the test set-up will be checked each time before testing.


Statement of Traceability: BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

5.7 Test Environmental Conditions

Temperature:	20-22 °C
Relative Humidity:	42-50 %
ATM Pressure:	102.7 kPa

The testing was performed by Christian McCaig and Deepak Mishra from 2022-05-09 and 2022-06-03 in 5m 3.

5.8 Test Results below 1 GHz measured at 3 meters



Worst case configuration: middle channel 6988.8 MHz, Mode 0

Freq. (MHz)	S.A. Reading (dBµV)	Corr. Factor (dB/m)	Corrected Amp. (dBµV/m)	Height	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBµV/m)	Margin (dB)	Comment
33.1885	33.57	-0.49	33.08	101	V	289	40	-6.92	QP
885.152	16.85	4.2	21.05	282	V	344	46	-24.95	QP
79.7645	28.18	-11.5	16.68	172	V	68	40	-23.32	QP
851.618	16.97	3.93	20.9	293	V	225	46	-25.1	QP
137.872	26.55	-5.68	20.87	236	Н	180	43.5	-22.63	QP
34.7617	19.28	-1.67	17.61	191	V	49	40	-22.39	QP

5.9 Test Results above 1 GHz


Note: Measurements were performed at 3m distance.

Note: Only worst case test antenna polarization (Vertical) results recorded.

Average Radiated Fundamental Field Strength


Channel Number	Channel Frequency (MHz)	Mode	PSA Reading (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Pre Amp Gain (dB)	Corrected Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
		0	40.62	35.74	10.057	33.49	52.93	-42.37	-41.3	-1.07
5 6489.6	6489.6	4	41.58	35.74	10.057	33.49	53.89	-41.41	-41.3	-0.11
		13	41.25	35.74	10.057	33.49	53.56	-41.74	-41.3	-0.44
		0	40.67	35.571	10.28	33.47	53.05	-42.25	-41.3	-0.95
6	6988.8	4	41.35	35.571	10.28	33.47	53.73	-41.57	-41.3	-0.27
		13	41.00	35.571	10.28	33.47	53.38	-41.92	-41.3	-0.62
		0	40.47	35.903	10.883	33.49	53.77	-41.53	-41.3	-0.23
9	7987.2	4	40.43	35.903	10.883	33.49	53.73	-41.57	-41.3	-0.27
		13	40.09	35.903	10.883	33.49	53.39	-41.91	-41.3	-0.61


Please refer to the following plots.




Channel 5 (6489.6 MHz), Fundamental Average Measurements








Mode 13




Channel 6 (6988.8MHz), Fundamental Average Measurements






Report Number: R2203281-03

FCC Part 15F/ISEDC RSS-220 Test Report





Mode 13



Channel 9 (7987.2MHz), Fundamental Average Measurements







Mode 13

Average Radiated Spurious Emissions: 1 GHz - 18 GHz

Note: Measurement was performed at 1m distance. The stricter IC limit was used to demonstrate compliance. Note: For Spurious Emissions testing, pre-scan was performed for all modes, and Mode 0 was selected to demonstrate compliance as the worst case configuration.

Note: For Spurious Emissions testing, pre-scan was performed for both Horizontal and Vertical Antenna Polarizations, and Vertical Polarization was selected to test for compliance as the worst case measurement configuration.

Note: In radiated measurement screenshots from 1GHz to 18GHz, shown emissions account for equipment factors to show corrected values compared to applicable limits.


Note: According to ANSI C63.10 Section 10.3.9, measured field strength in $dB\mu V/m$ was converted to EIRP in dBm to compare with the limit. The equation below was used,

EIRP (dBm) = E (dB μ V/m)-95.3


Measured Emission Frequency (GHz)	Antenna Pol (H/V)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
		2 0.44	10.0		75.0	1 1
1.988	V	28.44	18.9	-76.4	-75.3	-1.1

Channel 5 (6489.6 MHz), Mode 0

Please refer to the following plots.



1 GHz-2 GHz




2GHz - 18GHz

Measured Emission Frequency (GHz)	Antenna Pol (H/V)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1.986	V	29.00	19.46	-75.84	-75.3	-0.54
13.978	V	32.67	23.13	-72.17	-61.3	-10.87

Channel 6 (6988.8 MHz), Mode 0

Please refer to the following plots.



1 GHz-2 GHz


🔆 Agilent Title EMiSoft Vasona: EMi Emission Software Ref 91 dB**µ**V #Atten 0 dB #Avg **PASS LIMIT1** Mkr1 13.977 6 GHz 32.67 dBµV Change Title PASS LIMIT1 Log 10 dB/ **Clear Title** 1 ŧPAvg Start 2.000 0 GHz #Res BW 1 MHz Stop 18.000 0 GHz #Sweep 5 s (5001 pts) ≢VBW 3 MHz Trace (1) Type Freq Marker 1 Amplitude 32.67 dBµV X Axis 13.977 6 GHz No Peak Found

2GHz-18GHz

Measured Emission Frequency (GHz)	Antenna Pol (H/V)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1.064	V	29.09	19.55	-75.75	-70	-5.75
15.974	V	39.55	30.01	-65.29	-61.3	-3.99

Channel 9 (7987.2 MHz), Mode 0

Please refer to the following plots.



1 GHz-2 GHz

Title 🔆 Agilent EMISoft Vasona: EMI Emission Software Ref 91 dB**µ**V •Atten 0 dB •Ava Log 10 dB/ Mkr1 15.974 4 GHz 39.55 dBµV Change Title **Clear Title** ŧPAvg Start 2.000 0 GHz #Res BW 1 MHz Stop 18.000 0 GHz #Sweep 5 s (5001 pts) ≢VBW 3 MHz Trace (1) Type Freq Marker 1 Amplitude 39.55 dBµV X Axis 15.974 4 GHz File Operation Status, C:PICTURE.GIF file saved

2GHz – 18GHz

Average Radiated Spurious Emissions: 18-26.5 GHz

Note: Measurement was performed at 1m distance. The stricter IC limit was used to demonstrate compliance.


Note: For Spurious Emissions testing, pre-scan was performed for all modes, and Mode 0 was selected to demonstrate compliance as the worst case configuration.

Note: For Spurious Emissions testing, pre-scan was performed for both Horizontal and Vertical Antenna Polarizations, and Vertical Polarization was selected to test for compliance as the worst case measurement configuration.

Note: In radiated measurement screenshots from 18GHz to 26.5GHz, shown emissions do not account for equipment factors. In this case, highest emission was chosen and corrected value was calculated given equipment factors in order to compare to limit.

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
20.12	32.29	V	35.506	6.84	37.965	36.671	27.131	-68.17	-61.3	-6.87

Channel 5 (6489.6 MHz), Mode 0




18-26.5GHz

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
20.12	32.43	V	35.506	6.84	37.965	36.811	27.271	-68.03	-61.3	-6.73

Channel 6 (6988.8 MHz), Mode 0

18-26.5GHz




Tesla, Inc.

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
20.12	32.3	V	35.506	6.84	37.965	36.681	27.141	-68.16	-61.3	-6.86

Channel 9 (7987.2 MHz), Mode 0

18-26.5GHz



Average Radiated Spurious Emissions: 26.5-40 GHz

Note: Measurement was performed at 1m distance. The stricter IC limit was used to demonstrate compliance. Note: For Spurious Emissions testing, pre-scan was performed for all modes, and Mode 0 was selected to demonstrate compliance as the worst case configuration.


Note: For Spurious Emissions testing, pre-scan was performed for both Horizontal and Vertical Antenna Polarizations, and Vertical Polarization was selected to test for compliance as the worst case measurement configuration.

Note: In radiated measurement screenshots from 26.5GHz to 40GHz, shown emissions do not account for equipment factors. In this case, highest emission was chosen and corrected value was calculated given equipment factors in order to compare to limit.

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
37.31	28.63	V	39.294	9.2	36.799	40.325	30.785	-64.51	-61.3	-3.21

Channel 5 (6489.6 MHz), Mode 0





Date: 2.JUN.2022 15:07:23

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
36.91	28.72	V	39.294	9.2	36.799	40.415	30.875	-64.43	-61.3	-3.13

Channel 6 (6988.8 MHz), Mode 0

26.5-40 GHz

Spectrum							
Ref Level 97.00 d	BµV	BW 1 MHz BW 3 MHz Mode	Auto Sweep				
1Rm Max	00 0 0 0 0 1 0 5 0 1	BH CHILE HOUS	Adio Sweep				
90 dBµV			M1[1]		28.72 dBµV 36.90780 GHz		
80 dBµV							
70 dBµV							
60 dBµV							
50 dBµV							
40 dBµV							
30 dBµV				M1			
20 dBµV							
10 dBµV							
0 dBµV							
Start 26.5 GHz		5001 pts	Measurin		Stop 40.0 GHz		

Date: 2.JUN.2022 15:08:58

Measured Emission Frequency (GHz)	PSA Reading (dBµV)	Antenna Pol (H/V)	Antenna Factor (dB)	Cable Loss (dB)	Pre Amp Gain (dB)	Field Strength (dBµV/m at 1m)	Corrected Average Field Strength (dBµV/m at 3m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
37.32	28.75	V	39.294	9.2	36.799	40.445	30.905	-64.40	-61.3	-3.10

Channel 9 (7987.2 MHz), Mode 0

26.5-40 GHz

Ref Level 97.00 dBµV	RBW 1 MH	łz		('
	SWT 5 s 👄 VBW 3 MH	z Mode Auto Sweep		
90 dBµV		M1[1]		28.75 dBµV 37.31540 GHz
80 dBµV				
70 dBµV				
50 dBµV				
50 dBµV				
40 dBµV				
30 dBµV			M1	~~~~
20 dBµV				
LO dBµV				
) dBµV				
Start 26.5 GHz		5001 pts		Stop 40.0 GHz

Date: 2.JUN.2022 15:10:53

Additional Radiated Average Spurious Emissions with RBW of 1 kHz

Note: For Spurious Emissions testing, pre-scan was performed for all modes, and Mode 0 was selected to demonstrate compliance as the worst case configuration.

Note: For Spurious Emissions testing, pre-scan was performed for both Horizontal and Vertical Antenna Polarizations, and Vertical Polarization was selected to test for compliance as the worst case measurement configuration.

Note: In radiated measurement screenshots from 1164 MHz to 1240 MHz and 1559 MHz to 1610 MHz, shown emissions account for equipment factors to show corrected values compared to applicable limits.

Note: For practical reasons, a wider resolution bandwidth was used for measurement and to demonstrate compliance as worse case.

Note: According to ANSI C63.10 Section 10.3.9, measured field strength in $dB\mu V/m$ was converted to EIRP in dBm to compare with the limit. The equation below was used,

EIRP (dBm) = E (dB μ V/m)-95.3

Mode 0

Channel	Frequency Range (MHz)	Antenna Pol. (H/V)	Highest Emission Frequency (MHz)	Highest Emission (dBuV/m at 1 meter)	Corrected Value (dBuV/m at 3 meters)	EIRP (dBm)	Limit (dBm)	Margin (dB)
5	1164- 1240	V	1200	10.56	1.02	-94.28	-85.3	-8.98
5	1559- 1610	V	1584	13.47	3.93	-91.37	-85.3	-6.07
6	1164- 1240	V	1200	10.02	0.48	-94.82	-85.3	-9.52
0	1559- 1610	V	1584	14.73	5.19	-90.11	-85.3	-4.81
9	1164- 1240	V	1200	10.01	0.47	-94.83	-85.3	-9.53
9	1559- 1610	V	1584	15.54	6	-89.3	-85.3	-4

Agilent

og 10

d₿∕


d₿µ∿


*PAvg

1164 MHz-1240 MHz 1559 MHz-1610 MHz Peak Search Peak Search Agilent Mkr1 1.583 990 0 GH: 13.47 dBµV Soft Vasona: EMi Emission Software 91_dBµV #Atten 10 dB Mkr1 1.200 000 GH 10.56 dBµV EMiSoft Vasona: EMi Emission Software Ref 91_dBµV #Atten 10_dB Ref 91 dBµV #Avg _____ Ref 91 dBµV #Avg Next Peak Next Peak PASS LIMIT1 PASS LIMIT1 Log 10 dB/ Next Pk Right Next Pk Right Marker 1.200000000 GHz Marker 1.583990000 GHz Next Pk Left Next Pk Left 10.56 dBµV 13.47 dBµV ģ⊑ \$ ò iΒµ\ **Min Search Min Search** •PAvg Start 1.559 000 GHz #Res BW 30 kHz Stop 1.610 000 GHz #Sweep 5 s (5001 pts) Start 1.164 000 0 GHz Stop 1.240 000 0 GHz Res BW 6.2 kHz #VBW 20 kHz #Sweep 8 s (8192 pts) Pk-Pk Search #VBW 91 kHz Pk-Pk Search Marker Trace 1 (1) Marker Trace 1 (1) Amplitude 13.47 dBµV Type Freq X Axis 1.200 000 GHz Amplitude 10.56 dBµV Type Freq X Axis 1.583 990 0 GHz Mkr→CF Mkr→CF More More 1 of 2 1 of 2 File Operation Status, C:PICTURE.GIF file saved File Operation Status, C:PICTURE.GIF file saved


Channel 5

Channel 6







1559 MHz-1610 MHz



Channel 9

1164 MHz-1240 MHz





1559 MHz-1610 MHz

6 FCC §15.519(e), §15.521(e) & ISEDC RSS-220 §5.3.1(g) - Peak Fundamental Emission

6.1 Applicable Standards

According to FCC 15.519(e): There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, f_M . That limit is 0 dBm EIRP. It is acceptable to employ a different resolution bandwidth, and a correspondingly different peak emission limit, following the procedures described in 15.521.

According to FCC 15.521(e): The frequency at which the highest radiated emission occurs, f_M , must be contained within the UWB bandwidth.

According to ISEDC RSS-220 §5.3.1(g): The peak level of the transmissions shall not exceed the peak equivalent of the average limit contained within any 50 MHz bandwidth, as defined in section 4 of the Annex


According to ISEDC RSS-220 Annex 4(c): Peak measurements shall be made in addition to average measurements. Transmissions shall not exceed 0 dBm e.i.r.p. in any 50 MHz bandwidth when the average limit is -41.3 dBm/MHz.

According to FCC §15.521(g): When a peak measurement is required, it is acceptable to use a resolution bandwidth other than the 50 MHz specified in this subpart. This resolution bandwidth shall not be lower than 1 MHz or greater than 50 MHz, and the measurement shall be centered on the frequency at which the highest radiated emission occurs, f_M . If a resolution bandwidth other than 50 MHz is employed, the peak EIRP limit shall be 20 log (RBW/50) dBm where RBW is the resolution bandwidth in megahertz that is employed. This may be converted to a peak field strength level at 3 meters using E(dBuV/m) = P(dBm EIRP) + 95.2. If RBW is greater than 3 MHz, the application for certification filed with the Commission must contain a detailed description of the test procedure, calibration of the test setup, and the instrumentation employed in the testing.

6.2 Measurement Procedure

The measurements were based on ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices section 10.3: Radiated measurement procedure above 960MHz.

6.3 Test Setup Block Diagram



Ground Plane

Bacl No.	Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
655	Rhode & Schwarz	Spectrum Analyzer	FSQ26	200749	2022-02-07	2 years
-	Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
1192	ETS Lindgren	Horn Antenna	3117	00218973	2021-09-14	2 years
658	Agilent	Pre-Amplifier	8449B	3008A011 3	2022-05-05	1 year
	-	SMA cable	-	-	Each time ¹	N/A
1077	Insulated Wire Corp	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN- 3960-KPS	DC 1917	2022-03-03	1 year

6.4 Test Equipment List and Details

Note¹: cables included in the test set-up will be checked each time before testing.

Statement of Traceability: BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

6.5 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig and Deepak Mishra from 2022-05-09 and 2022-06-03 in 5m 3.

Channel Number	Channel Frequency (MHz)	Mode	PSA Reading (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Pre Amp Gain (dB)	Corrected Field Strength (dBµV/m at 3m)	Limit ¹ (dBµV/m at 3m)	Margin (dB)
		0	74.69	35.74	10.057	33.49	87.00	87.24	-0.24
5	6489.6	4	68.92	35.74	10.057	33.49	81.23	87.24	-6.01
		13	71.90	35.74	10.057	33.49	84.21	87.24	-3.03
		0	74.76	35.571	10.28	33.47	87.14	87.24	-0.10
6	6988.8	4	68.56	35.571	10.28	33.47	80.94	87.24	-6.30
		13	71.95	35.571	10.28	33.47	84.33	87.24	-2.91
		0	73.86	35.903	10.883	33.49	87.16	87.24	-0.08
9	7987.2	4	67.73	35.903	10.883	33.49	81.03	87.24	-6.21
		13	71.03	35.903	10.883	33.49	84.33	87.24	-2.91

6.6 Test Results


Note¹: Radiated Peak limit determined using a 20 MHz measurement BW. (i.e. $20*\log(20/50) = -7.96$ dB), then adding 95.2 dB for field strength at 3 meters as instructed to in FCC 15.521(g)

Channel Number	Channel Frequency (MHz)	Mode	f _M (MHz)	Range of UWB BW ² (MHz)	Result
		0	6890.2	6221.6-6765.6	Pass
5	6489.6	4	6600.4	6229.6-6791.6	Pass
		13	6614.8	6221.6-6787.6	Pass
		0	6997.0	6713.8-7258.8	Pass
6	6988.8	4	7058.8	6700.8-7281.8	Pass
		13	7050.0	6710.8-7275.8	Pass
		0	7995.4	7689.7-8264.7	Pass
9	7987.2	4	8128.5	7677.2-8288.2	Pass
		13	7861.8	7688.2-8273.2	Pass

Note²: please refer to Section 8.5 of this report for the UWB bandwidth measurement result.


Note: Only worst case test antenna polarization (Vertical) results recorded.


Please refer to the following plots.




Channel 5 (6489.6 MHz), Fundamental Peak Measurements

Mode 4












Channel 6 (6988.8MHz), Fundamental Peak Measurements









Mode 13



Channel 9 (7987.2 MHz), Fundamental Peak Measurements







Mode 13

7 FCC §15.503(d), §15.519(b) & ISEDC RSS-220 §5.1(a), RSS-Gen §6.7 -Emission Bandwidth

7.1 Applicable Standards

According to ECFR §15.503(a), For the purpose of this subpart, the UWB bandwidth is the frequency band bounded by the points that are 10 dB below the highest radiated emission, as based on the complete transmission system including the antenna.

According to ECFR §15.519(b) and ISEDC RSS-220 §5.1(a), the UWB bandwidth of a device operating under the provisions of this section must be contained between 3100 MHz and 10,600 MHz.


According to ECFR §15.503(b) and ISEDC RSS-220 §5.1(a), An intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

According to ISEDC RSS-Gen§6.7, The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

7.2 Measurement Procedure

The UWB bandwidth measurements were based on ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices section 10.1: Evaluation of -10dB bandwidth.

7.3 Test Setup Block Diagram



Ground Plane

Bacl No.	Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
655	Rhode & Schwarz	Spectrum Analyzer	FSQ26	200749	2022-02-07	2 years
-	Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
1192	ETS Lindgren	Horn Antenna	3117	00218973	2021-09-14	2 years
658	Agilent	Pre-Amplifier	8449B	3008A011 3	2022-05-05	1 year
	-	SMA cable	-	-	Each time ¹	N/A
1077	Insulated Wire Corp	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN- 3960-KPS	DC 1917	2022-03-03	1 year

7.4 Test Equipment List and Details

Note¹: cables included in the test set-up will be checked each time before testing.

Statement of Traceability: BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

7.5 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig and Deepak Mishra from 2022-05-09 and 2022-06-03 in 5m 3.


7.6 Test Results

10 dB Bandwidth

Channel	Frequency (MHz)	Mode	10 dB BW (MHz)	10 dB BW limit (MHz)	10 dB BW within 3100MHz- 10600MHz
		0	544	>500	Pass
5	6489.6	4	562	>500	Pass
		13	566	>500	Pass
		0	545	>500	Pass
6	6988.8	4	581	>500	Pass
		13	565	>500	Pass
		0	575	>500	Pass
9	7987.2	4	611	>500	Pass
		13	585	>500	Pass


Please refer to the following plots.


Report Number: R2203281-03




Channel 5 (6489.6 MHz), 10dB Bandwidth









Mode 13




Channel 6 (6988.8 MHz), 10dB Bandwidth

Mode 4







Mode 13



Channel 9 (7987.2 MHz), 10dB Bandwidth

Mode 4





Mode 13

8 FCC §15.519(a) (1) & ISEDC RSS-220 §5.3.1(b) - Cease Transmission


8.1 Applicable Standards

According to FCC §15.519(a)(1) and RSS-220 §5.3.1(b): A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgment of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting.

8.2 Measurement Procedure

A support UWB radio device was paired with the EUT for this testing. Transmission was monitored over a 20 second period. Both EUT and support equipment were switched on and paired for UWB ranging from the transmission off state. The support equipment was then powered off, and the transmission time from EUT was monitored and recorded. The first marker marks the time the support equipment was switched off, and the second marker marks the time the EUT stopped transmission.

8.3 Test Setup Block Diagram



Ground Plane

Bacl No.	Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
655	Rhode & Schwarz	Spectrum Analyzer	FSQ26	200749	2022-02-07	2 years
1192	ETS Lindgren	Horn Antenna	3117	00218973	2021-09-14	2 years
658	Agilent	Pre-Amplifier	8449B	3008A0113	2022-05-05	1 year
1077	Insulated Wire Corp	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN- 3960-KPS	DC 1917	2022-03-03	1 year
-	-	SMA cable	-	-	Each time ¹	N/A

8.4 Test Equipment List and Details

Note¹: cables included in the test set-up will be checked each time before testing.


Statement of Traceability: BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

8.5 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig on 2022-06-03 in 5m chamber 3.

8.6 Test Results



Note: The cease of transmission function operates the same way on all channels of this device. Therefore, only channel 6 was selected for testing.

9 Annex A (Normative) - Test Setup Photographs

Please refer to the attachment

10 Annex B (Normative) - EUT External Photographs

Please refer to the attachment

11 Annex C (Normative) - EUT Internal Photographs

Please refer to the attachment

12 Annex D (Normative) - A2LA Electrical Testing Certificate



Accredited Laboratory

A2LA has accredited

BAY AREA COMPLIANCE LABORATORIES CORP.

Sunnyvale, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets A2LA R222 - Specific Requirements EPA ENERGY STAR Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 10th day of March 2021.

Trace McInturff, Vice President, Accreditation Services For the Accreditation Council Certificate Number 3297.02 Valid to September 30, 2022

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

Please follow the web link below for a full ISO 17025 scope

https://www.a2la.org/scopepdf/3297-02.pdf

--- END OF REPORT ---