


FCC RADIO TEST REPORT

FCC ID : UDX-60076027
Equipment : LTE & Wi-Fi Router
Brand Name : CISCO
Model name : MX68CW-HW-NA
Applicant : Cisco Systems, Inc.
170 West Tasman Drive, San Jose,
CA 95134
Standard : FCC Part 15 Subpart E §15.407

The product was received on Mar. 16, 2018 and testing was started from Mar. 29, 2018 and completed on Aug. 02, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	11
3.2 Maximum Conducted Output Power Measurement	14
3.3 Power Spectral Density Measurement	15
3.4 Unwanted Emissions Measurement.....	18
3.5 AC Conducted Emission Measurement.....	24
3.6 Automatically Discontinue Transmission	26
3.7 Antenna Requirements.....	27
4 List of Measuring Equipment.....	29
5 Uncertainty of Evaluation.....	31
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR831635C	01	Initial issue of report	Sep. 05, 2018



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 1.13 dB at 5649.000 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 21.24 dB at 19.415 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Reviewed by: Joseph Lin

Report Producer: Fish Liu



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/ WCDMA/LTE, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac.

Product Specification subjective to this standard	
Antenna Type	WWAN: Main: Dipole Antenna Aux.: Dipole Antenna WLAN: Ant. 1: Dipole Antenna Ant. 2: Dipole Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH10-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0


TXBF Mode (Power Only)

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : RJ-45 (LAN) Link + RJ-45 (WAN) Link + USB Link + Adapter + POE + WLAN (5GHz) Link

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	ASUS	P2430U	FCC DoC	N/A	AC I/P : Unshielded, 1.2 m DC O/P : Shielded, 1.8 m
3.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	USB Flash Drive	Transcend	N/A	FCC DoC	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.



With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

<CDD Modes>


3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.



3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	4.32	5.84	5.84	8.12	0.00	2.12

Power Limit Reduction = $DG(\text{Power}) - 6\text{dBi}$, (min = 0)

PSD Limit Reduction = $DG(\text{PSD}) - 6\text{dBi}$, (min = 0)

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports beamforming for 802.11ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	4.32	5.84	8.12	8.12	2.12	2.12

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Mar. 06, 2018	Mar. 29, 2018~ Aug. 02, 2018	Mar. 05, 2019	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	Mar. 29, 2018~ Aug. 02, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz	Sep. 07, 2017	Mar. 29, 2018~ Aug. 02, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz ~ 30GHz	Nov. 13, 2017	Mar. 29, 2018~ Aug. 02, 2018	Nov. 12, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Mar. 29, 2018~ Aug. 02, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 23, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Jul. 23, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Jul. 23, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 23, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Jul. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Jul. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 19, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 18, 2018	Radiation (03CH10-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 17, 2018	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&0080 0N1D01N-06	35413&02	30MHz~1GHz	Dec. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Dec. 17, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 27, 2017	Apr. 12, 2018~ Jun. 06, 2018	Sep. 26, 2018	Radiation (03CH10-HY)
Hygrometer	TECPEL	DTM-303B	TP140320	N/A	Oct. 12, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 11, 2018	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Oct. 25, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 24, 2018	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JPA0010180 0-30-10P	1601180002	1GHz~18GHz	Jul. 31, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 30, 2018	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 31, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 30, 2018	Radiation (03CH10-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1~4m	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 22, 2018	Radiation (03CH10-HY)
Filter	Woken	WHKX8-587 2.5-6750-18 000-40ST	SN3	6.75G High Pass	Sep. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Sep. 17, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60ST	SN2	3 GHz Highpas s	Jul. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 18, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WLKS1200- 12SS	SN2	1.2G Low Pass	Jul. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 16, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4,M Y28655/4	9K-30M	Jan. 02, 2018	Apr. 12, 2018~ Jun. 06, 2018	Jan. 01, 2019	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	30M-1G	Nov. 14, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	1G-18G	Nov. 14, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40G	Oct. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 16, 2018	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	Apr. 12, 2018~ Jun. 06, 2018	Jan. 15, 2019	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 26, 2018	Radiation (03CH10-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.60
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.90
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Appendix A. Test Result of Conducted Test Items**<CDD Mode>**

Test Engineer:	Allen Lin/Shiming Liu	Temperature:	21~25	°C
Test Date:	2018/3/29~2018/8/2	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	18.05	17.45	34.15	31.80	16.25	15.90	0.5		Pass
11a	6Mbps	2	157	5785	18.20	17.70	33.80	32.60	16.30	16.30	0.5		Pass
11a	6Mbps	2	165	5825	19.65	17.85	39.70	34.35	16.25	16.30	0.5		Pass
HT20	MCS0	2	149	5745	18.70	18.45	35.50	29.15	16.20	15.95	0.5		Pass
HT20	MCS0	2	157	5785	18.65	18.45	32.95	25.05	17.15	17.55	0.5		Pass
HT20	MCS0	2	165	5825	18.90	18.60	36.40	28.75	17.50	17.50	0.5		Pass
HT40	MCS0	2	151	5755	36.90	36.60	63.16	51.26	35.10	35.10	0.5		Pass
HT40	MCS0	2	159	5795	37.00	36.70	74.54	65.20	35.10	35.10	0.5		Pass
VHT80	MCS0	2	155	5775	75.96	75.84	83.52	83.72	75.84	76.30	0.5		Pass

TEST RESULTS DATA
Average Power Table

Band IV															
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	149	5745	0.17	0.15	20.66	20.55	23.61	30.00		5.84		Pass	20.5
11a	6Mbps	2	157	5785	0.17	0.15	20.86	20.73	23.80	30.00		5.84		Pass	21
11a	6Mbps	2	165	5825	0.17	0.15	21.10	20.95	24.03	30.00		5.84		Pass	21
HT20	MCS0	2	149	5745	0.10	0.10	20.55	20.33	23.45	30.00		5.84		Pass	21
HT20	MCS0	2	157	5785	0.10	0.10	20.51	20.50	23.52	30.00		5.84		Pass	21
HT20	MCS0	2	165	5825	0.10	0.10	20.92	20.60	23.78	30.00		5.84		Pass	21
HT40	MCS0	2	151	5755	0.11	0.11	20.71	20.47	23.60	30.00		5.84		Pass	21
HT40	MCS0	2	159	5795	0.11	0.11	20.84	20.71	23.78	30.00		5.84		Pass	21
VHT20	MCS0	2	149	5745	0.10	0.10	20.54	20.32	23.44	30.00		5.84		Pass	21
VHT20	MCS0	2	157	5785	0.10	0.10	20.50	20.47	23.50	30.00		5.84		Pass	21
VHT20	MCS0	2	165	5825	0.10	0.10	20.90	20.55	23.74	30.00		5.84		Pass	21
VHT40	MCS0	2	151	5755	0.14	0.14	21.09	20.99	24.05	30.00		5.84		Pass	21
VHT40	MCS0	2	159	5795	0.14	0.14	20.79	20.70	23.76	30.00		5.84		Pass	21
VHT80	MCS0	2	155	5775	0.26	0.26	16.84	16.86	19.86	30.00		5.84		Pass	17.5

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.17	0.15	2.22	8.93	8.39	11.94	27.88	8.12	Pass			
11a	6Mbps	2	157	5785	0.17	0.15	2.22	8.66	8.31	11.67	27.88	8.12	Pass			
11a	6Mbps	2	165	5825	0.17	0.15	2.22	9.22	8.72	12.23	27.88	8.12	Pass			
HT20	MCS0	2	149	5745	0.10	0.10	2.22	8.19	8.13	11.20	27.88	8.12	Pass			
HT20	MCS0	2	157	5785	0.10	0.10	2.22	7.94	7.72	10.95	27.88	8.12	Pass			
HT20	MCS0	2	165	5825	0.10	0.10	2.22	8.44	7.93	11.45	27.88	8.12	Pass			
HT40	MCS0	2	151	5755	0.11	0.11	2.22	5.89	5.75	8.90	27.88	8.12	Pass			
HT40	MCS0	2	159	5795	0.11	0.11	2.22	5.74	5.32	8.75	27.88	8.12	Pass			
VHT80	MCS0	2	155	5775	0.26	0.26	2.22	-1.49	-1.93	1.52	27.88	8.12	Pass			

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

<TXBF Mode>

Test Engineer:	Allen Lin/Shiming Liu	Temperature:	21~25	°C
Test Date:	2018/3/29~2018/8/2	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

Band IV															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	149	5745	0.10	0.10	17.54	17.32	20.44	27.88		8.12		Pass	18
HT20	MCS0	2	157	5785	0.10	0.10	17.50	17.49	20.51	27.88		8.12		Pass	18
HT20	MCS0	2	165	5825	0.10	0.10	17.91	17.59	20.77	27.88		8.12		Pass	18
HT40	MCS0	2	151	5755	0.11	0.11	17.70	17.46	20.59	27.88		8.12		Pass	18
HT40	MCS0	2	159	5795	0.11	0.11	17.83	17.70	20.77	27.88		8.12		Pass	18
VHT20	MCS0	2	149	5745	0.10	0.10	17.53	17.31	20.43	27.88		8.12		Pass	18
VHT20	MCS0	2	157	5785	0.10	0.10	17.49	17.46	20.49	27.88		8.12		Pass	18
VHT20	MCS0	2	165	5825	0.10	0.10	17.89	17.54	20.73	27.88		8.12		Pass	18
VHT40	MCS0	2	151	5755	0.14	0.14	18.08	17.98	21.04	27.88		8.12		Pass	18
VHT40	MCS0	2	159	5795	0.14	0.14	17.78	17.69	20.75	27.88		8.12		Pass	18
VHT80	MCS0	2	155	5775	0.26	0.26	13.83	13.85	16.85	27.88		8.12		Pass	14.5




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Kai-Chun Chu	Temperature :	25~27°C
		Relative Humidity :	50~52%

EUT Information

Report NO : 831635
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	21.63	55.63	34.00	L1	OFF	19.5
0.156750	34.35	---	65.63	31.28	L1	OFF	19.5
0.246750	---	27.55	51.87	24.32	L1	OFF	19.5
0.246750	28.64	---	61.87	33.23	L1	OFF	19.5
0.368250	---	16.89	48.54	31.65	L1	OFF	19.5
0.368250	18.58	---	58.54	39.96	L1	OFF	19.5
0.501000	---	20.10	46.00	25.90	L1	OFF	19.5
0.501000	22.09	---	56.00	33.91	L1	OFF	19.5
1.680000	---	15.44	46.00	30.56	L1	OFF	19.6
1.680000	18.10	---	56.00	37.90	L1	OFF	19.6
19.695750	---	28.75	50.00	21.25	L1	OFF	19.8
19.695750	33.85	---	60.00	26.15	L1	OFF	19.8

EUT Information

Report NO : 831635
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163500	---	22.90	55.28	32.38	N	OFF	19.5
0.163500	33.00	---	65.28	32.28	N	OFF	19.5
0.233250	---	27.20	52.33	25.13	N	OFF	19.5
0.233250	28.57	---	62.33	33.76	N	OFF	19.5
0.368250	---	16.58	48.54	31.96	N	OFF	19.5
0.368250	18.42	---	58.54	40.12	N	OFF	19.5
0.505500	---	16.58	46.00	29.42	N	OFF	19.5
0.505500	19.00	---	56.00	37.00	N	OFF	19.5
1.637250	---	16.22	46.00	29.78	N	OFF	19.6
1.637250	18.70	---	56.00	37.30	N	OFF	19.6
19.414500	---	28.76	50.00	21.24	N	OFF	19.9
19.414500	33.80	---	60.00	26.20	N	OFF	19.9



Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee and JC Liang	Temperature :	18 ~ 22°C
		Relative Humidity :	48 ~ 52%

<CDD Mode>

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5646.4	59.42	-8.78	68.2	50.96	32.24	8.77	32.55	248	25	P	H
		5696.6	65.36	-37.33	102.69	56.75	32.29	8.89	32.57	248	25	P	H
		5717	77.29	-32.67	109.96	68.61	32.31	8.95	32.58	248	25	P	H
		5722.2	81.92	-33.9	115.82	73.17	32.32	9.01	32.58	248	25	P	H
	*	5745	118.18	-	-	109.36	32.34	9.07	32.59	248	25	P	H
	*	5745	110.38	-	-	101.56	32.34	9.07	32.59	248	25	A	H
													H
													H
		5642.4	64.59	-3.61	68.2	56.2	32.24	8.7	32.55	300	345	P	V
		5697.8	71.25	-32.33	103.58	62.64	32.29	8.89	32.57	300	345	P	V
		5716.6	84.27	-25.58	109.85	75.59	32.31	8.95	32.58	300	345	P	V
		5722.6	87.13	-29.6	116.73	78.38	32.32	9.01	32.58	300	345	P	V
	*	5745	122.95	-	-	114.13	32.34	9.07	32.59	300	345	P	V
	*	5745	115.24	-	-	106.42	32.34	9.07	32.59	300	345	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5645.8	50.27	-17.93	68.2	41.81	32.24	8.77	32.55	236	21	P	H
		5695.6	62.49	-39.47	101.96	53.88	32.29	8.89	32.57	236	21	P	H
		5719.6	52.96	-57.73	110.69	44.21	32.32	9.01	32.58	236	21	P	H
		5721.4	51.77	-62.22	113.99	43.02	32.32	9.01	32.58	236	21	P	H
	*	5785	116.66	-	-	107.69	32.38	9.2	32.61	236	21	P	H
	*	5785	109.8	-	-	100.83	32.38	9.2	32.61	236	21	A	H
		5850	52.31	-69.89	122.2	43.34	32.44	9.16	32.63	236	21	P	H
		5873.8	61.35	-44.19	105.54	52.38	32.48	9.13	32.64	236	21	P	H
		5877.8	63.79	-39.33	103.12	54.82	32.48	9.13	32.64	236	21	P	H
		5934	50.32	-17.88	68.2	41.43	32.53	9.01	32.65	236	21	P	H
													H
													H
		5601.2	53.41	-14.79	68.2	45.17	32.2	8.58	32.54	298	352	P	V
		5696.6	65.24	-37.45	102.69	56.63	32.29	8.89	32.57	298	352	P	V
		5711.4	54.9	-53.49	108.39	46.22	32.31	8.95	32.58	298	352	P	V
		5723	53.36	-64.28	117.64	44.61	32.32	9.01	32.58	298	352	P	V
	*	5785	120.26	-	-	111.29	32.38	9.2	32.61	298	352	P	V
	*	5785	112.41	-	-	103.44	32.38	9.2	32.61	298	352	A	V
		5853.2	53.4	-61.5	114.9	44.43	32.44	9.16	32.63	298	352	P	V
		5874.4	64.39	-40.98	105.37	55.42	32.48	9.13	32.64	298	352	P	V
		5879.2	64.38	-37.7	102.08	55.41	32.48	9.13	32.64	298	352	P	V
		5927	51.02	-17.18	68.2	42.1	32.53	9.04	32.65	298	352	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	117.82	-	-	108.78	32.43	9.23	32.62	241	22	P	H
	*	5825	110.11	-	-	101.07	32.43	9.23	32.62	241	22	A	H
		5851.4	74.89	-44.12	119.01	65.92	32.44	9.16	32.63	241	22	P	H
		5855.8	72.19	-38.39	110.58	63.2	32.46	9.16	32.63	241	22	P	H
		5917.8	61.44	-12.07	73.51	52.54	32.51	9.04	32.65	241	22	P	H
		5927.6	59.62	-8.58	68.2	50.7	32.53	9.04	32.65	241	22	P	H
													H
													H
	*	5825	120.51	-	-	111.47	32.43	9.23	32.62	305	352	P	V
	*	5825	112.06	-	-	103.02	32.43	9.23	32.62	305	352	A	V
		5852.4	76.36	-40.37	116.73	67.39	32.44	9.16	32.63	305	352	P	V
		5856.8	70.81	-39.49	110.3	61.82	32.46	9.16	32.63	305	352	P	V
		5924	63.03	-5.91	68.94	54.11	32.53	9.04	32.65	305	352	P	V
		5925.2	60.27	-7.93	68.2	51.35	32.53	9.04	32.65	305	352	P	V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	44.89	-29.11	74	58.55	39.81	12.74	66.21	100	0	P	H
		17235	45.85	-22.35	68.2	54.09	41.02	16.76	66.02	100	0	P	H
													H
													H
		11490	44.6	-29.4	74	58.26	39.81	12.74	66.21	100	0	P	V
		17235	45.37	-22.83	68.2	53.61	41.02	16.76	66.02	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	45.88	-28.12	74	54.71	39.69	13.08	61.6	100	0	P	H
		17355	48.71	-19.49	68.2	50.89	41.58	17.23	60.99	100	0	P	H
													H
													H
		11570	46.29	-27.71	74	55.12	39.69	13.08	61.6	100	0	P	V
		17355	49.86	-18.34	68.2	52.04	41.58	17.23	60.99	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	45.23	-28.77	74	54.1	39.58	13.15	61.6	100	0	P	H
		17475	48.8	-19.4	68.2	50.24	42.14	17.34	60.92	380	0	P	H
													H
													H
		11650	45.22	-28.78	74	54.09	39.58	13.15	61.6	100	0	P	V
		17475	48.55	-19.65	68.2	49.99	42.14	17.34	60.92	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5648	59.57	-8.63	68.2	51.11	32.24	8.77	32.55	217	18	P	H
		5699.4	65.56	-39.2	104.76	56.95	32.29	8.89	32.57	217	18	P	H
		5719	77.41	-33.11	110.52	68.66	32.32	9.01	32.58	217	18	P	H
		5724.4	82.33	-38.5	120.83	73.58	32.32	9.01	32.58	217	18	P	H
	*	5745	116.73	-	-	107.91	32.34	9.07	32.59	217	18	P	H
	*	5745	109.13	-	-	100.31	32.34	9.07	32.59	217	18	A	H
													H
													H
		5647.8	66.74	-1.46	68.2	58.28	32.24	8.77	32.55	297	352	P	V
		5699.8	70.43	-34.62	105.05	61.76	32.29	8.95	32.57	297	352	P	V
		5719.6	82.57	-28.12	110.69	73.82	32.32	9.01	32.58	297	352	P	V
		5722.2	87.88	-27.94	115.82	79.13	32.32	9.01	32.58	297	352	P	V
	*	5745	122.43	-	-	113.61	32.34	9.07	32.59	297	352	P	V
	*	5745	114.73	-	-	105.91	32.34	9.07	32.59	297	352	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5642.6	50.85	-17.35	68.2	42.46	32.24	8.7	32.55	235	21	P	H
		5696.8	60.75	-42.09	102.84	52.14	32.29	8.89	32.57	235	21	P	H
		5719.4	52.81	-57.82	110.63	44.06	32.32	9.01	32.58	235	21	P	H
		5722.2	51.58	-64.24	115.82	42.83	32.32	9.01	32.58	235	21	P	H
	*	5785	117.11	-	-	108.14	32.38	9.2	32.61	235	21	P	H
	*	5785	109.01	-	-	100.04	32.38	9.2	32.61	235	21	A	H
		5852.6	51.15	-65.12	116.27	42.18	32.44	9.16	32.63	235	21	P	H
		5873.6	60.56	-45.03	105.59	51.59	32.48	9.13	32.64	235	21	P	H
		5888.8	60.87	-34.09	94.96	51.91	32.5	9.1	32.64	235	21	P	H
		5946	50.42	-17.78	68.2	41.52	32.55	9.01	32.66	235	21	P	H
													H
													H
		5601.2	53.84	-14.36	68.2	45.6	32.2	8.58	32.54	304	339	P	V
		5696.6	64.9	-37.79	102.69	56.29	32.29	8.89	32.57	304	339	P	V
		5712.6	53.16	-55.57	108.73	44.48	32.31	8.95	32.58	304	339	P	V
		5724.8	55.52	-66.22	121.74	46.77	32.32	9.01	32.58	304	339	P	V
	*	5785	118.93	-	-	109.96	32.38	9.2	32.61	304	339	P	V
	*	5785	111.81	-	-	102.84	32.38	9.2	32.61	304	339	A	V
		5853	54.99	-60.37	115.36	46.02	32.44	9.16	32.63	304	339	P	V
		5874.8	66.2	-39.06	105.26	57.23	32.48	9.13	32.64	304	339	P	V
		5889	61.02	-33.79	94.81	52.06	32.5	9.1	32.64	304	339	P	V
		5932.4	51.62	-16.58	68.2	42.7	32.53	9.04	32.65	304	339	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	118.03	-	-	108.99	32.43	9.23	32.62	219	20	P	H
	*	5825	109.18	-	-	100.14	32.43	9.23	32.62	219	20	A	H
		5850	81.3	-40.9	122.2	72.33	32.44	9.16	32.63	219	20	P	H
		5855	68.69	-42.11	110.8	59.7	32.46	9.16	32.63	219	20	P	H
		5913.4	59.28	-17.48	76.76	50.35	32.51	9.07	32.65	219	20	P	H
		5927.4	58.29	-9.91	68.2	49.37	32.53	9.04	32.65	219	20	P	H
													H
													H
	*	5825	119.02	-	-	109.98	32.43	9.23	32.62	312	338	P	V
	*	5825	112.05	-	-	103.01	32.43	9.23	32.62	312	338	A	V
		5850.6	80.84	-39.99	120.83	71.87	32.44	9.16	32.63	312	338	P	V
		5857.8	74.1	-35.91	110.01	65.12	32.46	9.16	32.64	312	338	P	V
		5914.8	65.25	-10.47	75.72	56.32	32.51	9.07	32.65	312	338	P	V
		5928.6	58.7	-9.5	68.2	49.78	32.53	9.04	32.65	312	338	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preampl Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	45.62	-28.38	74	54.39	39.81	13.02	61.6	100	0	P	H
		17235	47.76	-20.44	68.2	50.68	41.02	17.12	61.06	100	0	P	H
													H
													H
		11490	45.53	-28.47	74	54.3	39.81	13.02	61.6	100	0	P	V
		17235	47.18	-21.02	68.2	50.1	41.02	17.12	61.06	100	0	P	V
													V
													V
802.11n HT20 CH 157 5785MHz		11570	45.51	-28.49	74	54.34	39.69	13.08	61.6	100	0	P	H
		17355	48.89	-19.31	68.2	51.07	41.58	17.23	60.99	100	0	P	H
													H
													H
		11570	45.04	-28.96	74	53.87	39.69	13.08	61.6	100	0	P	V
		17355	49.54	-18.66	68.2	51.72	41.58	17.23	60.99	100	0	P	V
													V
													V
802.11n HT20 CH 165 5825MHz		11650	44.04	-29.96	74	52.91	39.58	13.15	61.6	100	0	P	H
		17475	49.15	-19.05	68.2	50.59	42.14	17.34	60.92	100	0	P	H
													H
													H
		11650	45.13	-28.87	74	54	39.58	13.15	61.6	100	0	P	V
		17475	48.73	-19.47	68.2	50.17	42.14	17.34	60.92	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5648.6	62.07	-6.13	68.2	53.61	32.24	8.77	32.55	100	296	P	H
		5698	76.22	-27.51	103.73	67.61	32.29	8.89	32.57	100	296	P	H
		5719.8	82.36	-28.38	110.74	73.61	32.32	9.01	32.58	100	296	P	H
		5723	86.68	-30.96	117.64	77.93	32.32	9.01	32.58	100	296	P	H
	*	5755	114.43	-	-	105.52	32.36	9.14	32.59	100	296	P	H
	*	5755	106.07	-	-	97.16	32.36	9.14	32.59	100	296	A	H
		5854.8	61.61	-49.65	111.26	52.62	32.46	9.16	32.63	100	296	P	H
		5860.4	62.69	-46.6	109.29	53.71	32.46	9.16	32.64	100	296	P	H
		5876.4	57.31	-46.85	104.16	48.34	32.48	9.13	32.64	100	296	P	H
		5928.8	50.54	-17.66	68.2	41.62	32.53	9.04	32.65	100	296	P	H
													H
													H
		5649	67.07	-1.13	68.2	58.61	32.24	8.77	32.55	324	17	P	V
		5689	77.52	-19.57	97.09	68.91	32.29	8.89	32.57	324	17	P	V
		5718.8	89.46	-21	110.46	80.71	32.32	9.01	32.58	324	17	P	V
		5723.6	91.35	-27.66	119.01	82.6	32.32	9.01	32.58	324	17	P	V
	*	5755	118.08	-	-	109.17	32.36	9.14	32.59	324	17	P	V
	*	5755	110.5	-	-	101.59	32.36	9.14	32.59	324	17	A	V
		5850.2	66.45	-55.29	121.74	57.48	32.44	9.16	32.63	324	17	P	V
		5858.4	66.99	-42.86	109.85	58.01	32.46	9.16	32.64	324	17	P	V
		5884	59.92	-38.6	98.52	50.98	32.48	9.1	32.64	324	17	P	V
		5937.4	51.73	-16.47	68.2	42.85	32.53	9.01	32.66	324	17	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5646.6	51.38	-16.82	68.2	42.92	32.24	8.77	32.55	245	22	P	H
		5687.6	60.45	-35.6	96.05	51.84	32.29	8.89	32.57	245	22	P	H
		5703	60.9	-45.14	106.04	52.21	32.31	8.95	32.57	245	22	P	H
		5723	66.53	-51.11	117.64	57.78	32.32	9.01	32.58	245	22	P	H
	*	5795	116.42	-	-	107.38	32.39	9.26	32.61	245	22	P	H
	*	5795	107.92	-	-	98.88	32.39	9.26	32.61	245	22	A	H
		5853	69.38	-45.98	115.36	60.41	32.44	9.16	32.63	245	22	P	H
		5863.8	67.29	-41.04	108.33	58.34	32.46	9.13	32.64	245	22	P	H
		5882.6	62.72	-36.84	99.56	53.78	32.48	9.1	32.64	245	22	P	H
		5931	50.3	-17.9	68.2	41.38	32.53	9.04	32.65	245	22	P	H
													H
													H
		5605	52.55	-15.65	68.2	44.31	32.2	8.58	32.54	293	354	P	V
		5685.8	62.68	-32.04	94.72	54.07	32.29	8.89	32.57	293	354	P	V
		5719.8	66.63	-44.11	110.74	57.88	32.32	9.01	32.58	293	354	P	V
		5723.8	68.27	-51.19	119.46	59.52	32.32	9.01	32.58	293	354	P	V
	*	5795	118.02	-	-	108.98	32.39	9.26	32.61	293	354	P	V
	*	5795	110.49	-	-	101.45	32.39	9.26	32.61	293	354	A	V
		5850.4	68.07	-53.22	121.29	59.1	32.44	9.16	32.63	293	354	P	V
		5862.4	70.54	-38.19	108.73	61.59	32.46	9.13	32.64	293	354	P	V
		5881.2	65.73	-34.86	100.59	56.79	32.48	9.1	32.64	293	354	P	V
		5937.2	51.88	-16.32	68.2	43	32.53	9.01	32.66	293	354	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	45.62	-28.38	74	54.39	39.8	13.03	61.6	100	0	P	H
		17265	49.05	-19.15	68.2	51.76	41.18	17.15	61.04	100	0	P	H
													H
													H
		11510	47.09	-26.91	74	55.86	39.8	13.03	61.6	100	0	P	V
		17265	48.93	-19.27	68.2	51.64	41.18	17.15	61.04	100	0	P	V
													V
													V
802.11n HT40 CH 159 5795MHz		11590	45.96	-28.04	74	54.81	39.66	13.09	61.6	100	0	P	H
		17385	48.4	-19.8	68.2	50.37	41.74	17.26	60.97	100	0	P	H
													H
													H
		11590	45.53	-28.47	74	54.38	39.66	13.09	61.6	100	0	P	V
		17385	47.91	-20.29	68.2	49.88	41.74	17.26	60.97	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5646	63.28	-4.92	68.2	54.82	32.24	8.77	32.55	100	298	P	H
		5666.6	68.52	-12	80.52	59.98	32.27	8.83	32.56	100	298	P	H
		5702.6	68.04	-37.89	105.93	59.35	32.31	8.95	32.57	100	298	P	H
		5721.2	66.47	-47.07	113.54	57.72	32.32	9.01	32.58	100	298	P	H
	*	5775	106.87	-	-	97.89	32.38	9.2	32.6	100	298	P	H
	*	5775	98.89	-	-	89.91	32.38	9.2	32.6	100	298	A	H
		5852.2	66.36	-50.82	117.18	57.39	32.44	9.16	32.63	100	298	P	H
		5871	68.74	-37.58	106.32	59.77	32.48	9.13	32.64	100	298	P	H
		5876.8	67.01	-36.85	103.86	58.04	32.48	9.13	32.64	100	298	P	H
		5926.6	57.03	-11.17	68.2	48.11	32.53	9.04	32.65	100	298	P	H
													H
													H
		5643	66.08	-2.12	68.2	57.69	32.24	8.7	32.55	339	28	P	V
		5683.8	70.27	-22.98	93.25	61.66	32.29	8.89	32.57	339	28	P	V
		5718.2	69.18	-41.12	110.3	60.43	32.32	9.01	32.58	339	28	P	V
		5722.8	68.69	-48.49	117.18	59.94	32.32	9.01	32.58	339	28	P	V
	*	5775	111.42	-	-	102.44	32.38	9.2	32.6	339	28	P	V
	*	5775	104	-	-	95.02	32.38	9.2	32.6	339	28	A	V
		5852.2	69.6	-47.58	117.18	60.63	32.44	9.16	32.63	339	28	P	V
		5871.2	72.38	-33.88	106.26	63.41	32.48	9.13	32.64	339	28	P	V
		5881.4	70.81	-29.64	100.45	61.87	32.48	9.1	32.64	339	28	P	V
		5925	59.87	-8.33	68.2	50.95	32.53	9.04	32.65	339	28	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	45.38	-28.62	74	54.2	39.72	13.06	61.6	100	0	P	H
		17325	48.08	-20.12	68.2	50.47	41.42	17.2	61.01	100	0	P	H
													H
													H
		11550	44.99	-29.01	74	53.81	39.72	13.06	61.6	100	0	P	V
		17325	48.43	-19.77	68.2	50.82	41.42	17.2	61.01	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
5GHz 802.11n HT20 LF		30.54	21.32	-18.68	40	29.35	24.07	0.68	32.78			P	H	
		125.04	29.28	-14.22	43.5	42.84	17.71	1.42	32.69			P	H	
		282.18	27.63	-18.37	46	39.28	18.78	2.17	32.6			P	H	
		374.9	43.7	-2.3	46	52.94	20.93	2.43	32.6	100	4	QP	H	
		500.2	41.5	-4.5	46	47.43	23.86	2.85	32.64			P	H	
		699.7	38.64	-7.36	46	41.42	26.62	3.38	32.78			P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
		75.63	22.67	-17.33	40	41.3	12.94	1.16	32.73				P	V
		125.04	23.73	-19.77	43.5	37.29	17.71	1.42	32.69				P	V
		300	35.57	-10.43	46	46.81	19.13	2.22	32.59				P	V
		500.2	44.54	-1.46	46	50.47	23.86	2.85	32.64	100	341	QP	V	
		624.8	41.39	-4.61	46	44.98	26.01	3.21	32.81				P	V
		699.7	39.29	-6.71	46	42.07	26.62	3.38	32.78				P	V
														V
														V
														V
														V
														V
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission

Test Engineer :	Daniel Lee and JC Liang	Temperature :	18 ~ 22°C
		Relative Humidity :	48 ~ 52%



<CDD Mode>

Note symbol



-L	Low channel location
-R	High channel location









Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 831635





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(04)_15-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(04)_15-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635
Peak	 Site : 03CH10-HY Condition : PEAK_BE(04)_15-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635









Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL Detector : RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Project : 831635





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	Site : 03CH10-IHV Condition : PEAK_86(84)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Site : 03CH10-IHV Condition : PEAK(UNII)_3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank









WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635








WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635

Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 831635	 Site : 03CH10-HY Condition : PEAK(UBI) 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 831635
	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 831635	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank




Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635
Peak	 Site : 03CH10-IHV Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 831635	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 831635





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UWB) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UWB) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635

Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UWB) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : PEAK(UWB) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 831635

Emission below 1GHz
5GHz WIFI 802.11n HT20 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT20 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH10-HY Condition : QP 3m BT-LOG 6111D-LF HORIZONTAL Detector : Peak Project : 831635	 Site : 03CH10-HY Condition : QP 3m BT-LOG 6111D-LF VERTICAL Detector : Peak Project : 831635


Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1+2	802.11a for Ant. 1	96.27	2064	0.48	1kHz	0.17
1+2	802.11a for Ant. 2	96.63	2064	0.48	1kHz	0.15
1+2	5GHz 802.11n HT20 for Ant. 1	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11n HT20 for Ant. 2	97.64	4960	0.20	300Hz	0.10
1+2	5GHz 802.11n HT40 for Ant. 1	97.60	2440	0.41	1kHz	0.11
1+2	5GHz 802.11n HT40 for Ant. 2	97.60	2440	0.41	1kHz	0.11
1+2	5GHz 802.11ac VHT20 for Ant. 1	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11ac VHT20 for Ant. 2	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11ac VHT40 for Ant. 1	96.83	2440	0.41	1kHz	0.14
1+2	5GHz 802.11ac VHT40 for Ant. 2	96.81	2430	0.41	1kHz	0.14
1+2	5GHz 802.11ac VHT80 for Ant. 1	94.26	1150	0.87	1kHz	0.26
1+2	5GHz 802.11ac VHT80 for Ant. 2	94.26	1150	0.87	1kHz	0.26




MIMO <Ant. 1>

802.11a



Date: 29.MAR.2018 03:04:17


802.11n HT20



Date: 29.MAR.2018 05:09:40




802.11n HT40



Date: 29.MAR.2018 06:36:11


802.11ac VHT20



Date: 29.MAR.2018 06:26:09




802.11ac VHT40



Date: 29.MAR.2018 06:41:50

802.11ac VHT80




Date: 29.MAR.2018 07:52:23




MIMO <Ant. 2>

802.11a



Date: 29.MAR.2018 03:06:08


802.11n HT20



Date: 29.MAR.2018 05:10:18




802.11n HT40



Date: 29.MAR.2018 06:43:05


802.11ac VHT20



Date: 29.MAR.2018 06:28:21




802.11ac VHT40



Date: 29.MAR.2018 06:43:05

802.11ac VHT80



Date: 29.MAR.2018 07:52:59