



Honeywell Safety and Productivity Solutions


CK65L0N and IP30C

FCC 2.1091:2019

802.11, Bluetooth/Bluetooth Low Energy, 13.56 MHz NFC

900 MHz RFID, Bluetooth

Report # INMC1104.4



NVLAP Lab Code: 200630

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. This Report shall not be reproduced, except in full without written approval of the laboratory.

EAR-Controlled Data - This document contains technical data whose export and reexport/retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or re-export/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

More: <https://www.bis.doc.gov/index.php/forms-documents/regulations-docs/14-commerce-country-chart/fileT>

CERTIFICATE OF EVALUATION

Last Date of Evaluation: Monday, September 16, 2019
Honeywell Safety and Productivity Solutions
Model: CK65L0N and IP30C

RF Exposure Evaluation

Standards

Specification	Method
FCC 2.1091:2019	FCC 447498 D01 General RF Exposure Guidance v06

Results

Method Clause	Description	Applied	Results	Comments
7.2	Maximum Permissible Exposure	Yes	Pass	None

Deviations From Evaluation Standards

None

Approved By:



Donald Facteau, Process Architect

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information. As indicated in the Statement of Work sent with the quotation, Element's standard process is to always use the latest published version of the test methods even when earlier versions are cited in the test specification. Issuance of a purchase order was de facto acceptance of this approach. Otherwise, the client would have advised Element in writing of the specific version of the test methods they wanted applied to the subject testing

REVISION HISTORY



Revision Number		Description	Date (yyyy-mm-dd)	Page Number
00		None		

ACCREDITATIONS AND AUTHORIZATIONS



United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Accredited by A2LA to ISO / IEC 17065 as a product certifier. This allows Element to certify transmitters to FCC and IC specifications.

NVLAP - Each laboratory is accredited by NVLAP to ISO 17025

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB) and as a CAB for the acceptance of test data.

European Union

European Commission – Within Element, we have a EU Notified Body validated for the EMCD and RED Directives.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:

<https://www.nwemc.com/emc-testing-accreditations>

FACILITIES



California Labs OC01-17 41 Tesla Irvine, CA 92618 (949) 861-8918	Minnesota Labs MN01-10 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612)-638-5136	Oregon Labs EV01-12 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066	Texas Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255	Washington Labs NC01-05 19201 120 th Ave NE Bothell, WA 98011 (425)984-6600
NVLAP				
NVLAP Lab Code: 200676-0	NVLAP Lab Code: 200881-0	NVLAP Lab Code: 200630-0	NVLAP Lab Code:201049-0	NVLAP Lab Code: 200629-0
Innovation, Science and Economic Development Canada				
2834B-1, 2834B-3	2834E-1, 2834E-3	2834D-1	2834G-1	2834F-1
BSMI				
SL2-IN-E-1154R	SL2-IN-E-1152R	SL2-IN-E-1017	SL2-IN-E-1158R	SL2-IN-E-1153R
VCCI				
A-0029	A-0109	A-0108	A-0201	A-0110
Recognized Phase I CAB for ISED, ACMA, BSMI, IDA, KCC/RRR, MIC, MOC, NCC, OFCA				
US0158	US0175	US0017	US0191	US0157



RF Exposure Condition



The following RF Exposure conditions were used for the assessment documented in this report:	
Intended Use	Mobile (A SAR test exclusion assessment for portable use of the same radios is documented in Element report #INMC1104.6.)
Location on Body (if applicable)	NA
How is the Device Used	Information from the RFID module is communicated to the CK65L0N mobile computer via a Bluetooth radio. The CK65L0N mobile computer can communicate to the outside world by an 802.11 radio, a Bluetooth radio, or a Bluetooth Low Energy Radio.
Radios Contained in the Same Host Devices	<p>IP30C contains: 900 MHz RFID, FCC ID:EHA-IM11 Bluetooth, FCC ID:QOQWT12</p> <p>CK65L0N mobile computer (FCC ID:HD5-CK65L0N) contains: 802.11 (supports b/g/a/n/ac – referred to as 802.11 here) Bluetooth/Bluetooth Low Energy 13.56 MHz NFC (exempt from evaluation)</p>
Simultaneous Transmitting Radios	<p>CK65L0N 802.11, IP30C 900 MHz RFID, IP30C Bluetooth</p> <p>Or</p> <p>CK65L0N Bluetooth, IP30C Bluetooth, IP30C 900 MHz RFID,</p> <p>Or</p> <p>CK65L0N Bluetooth Low Energy, IP30C Bluetooth, IP30C 900 MHz RFID</p>
Body Worn Accessories	None
Environment	General Population/Uncontrolled Exposure

PRODUCT DESCRIPTION

Client and Equipment Under Evaluation Information

Company Name:	Honeywell Safety and Productivity Solutions
Address:	16201 25th Ave W
City, State, Zip:	Lynnwood, WA 98087
Evaluation Requested By:	Sean MacKellar
Model:	CK65L0N and IP30C
Date of Evaluation:	Monday, September 16, 2019

Information Provided by the Party Requesting the Evaluation

Functional Description of the Equipment:

The IP30C is a handheld RFID reader that attaches to the back of the Honeywell Model: CK65L0N mobile computer. The Intermec IM11 is a previously certified RFID module (FCC ID:EHA-IM11) that is installed in the Intermec IP30C handheld RFID reader. The IP30C also contains BlueGiga WT12 Bluetooth module (FCC ID:QOQWT12) used to communicate the data read by the IM11 to the Honeywell Model: CK65L0N mobile computer (FCC ID:HD5-CK65L0N). The CK65L0N mobile computer contains a 13.56 MHz NFC, a Bluetooth/Bluetooth Low Energy radio, and an 802.11 radio.

Objective:

To demonstrate compliance with FCC requirements for RF exposure for 2.1091 mobile/fixed devices

MAXIMUM PERMISSIBLE EXPOSURE (MPE)



OVERVIEW

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons. ANSI C95.1:2005 + Amd 1:2010 specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits. If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance. If the use of warning labels on a transmitter is not effective or desirable, the alternative of performing SAR evaluation with the device at its closest range to persons under normal operating conditions may be used. The field strength and power density limits adopted by the FCC are based on whole-body averaged exposure and the assumption of RF field levels relate most accurately to estimating whole-body averaged SAR. This means some local values of exposures exceeding the stated field strength and power density limits may not necessarily imply non-compliance if the spatial average of spatially averaged RF fields over the exposed portions of a person's body does not exceed the limits.

COMPLIANCE WITH FCC 2.1091

*"Mobile devices that operate in the Cellular Radiotelephone Service, the Personal Communications Services, the Satellite Communications Services, the General Wireless Communications Service, the Wireless Communications Service, the Maritime Services and the Specialized Mobile Radio Service authorized under subpart H of part 22 of this chapter, parts 24, 25, 26 and 27 of this chapter, part 80 of this chapter (ship earth stations devices only) and part 90 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more. Unlicensed personal communications service devices, unlicensed millimeter wave devices and unlicensed NII devices authorized under §§15.253, 15.255, and 15.257, and subparts D and E of part 15 of this chapter are also subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if their ERP is 3 watts or more or if they meet the definition of a portable device as specified in §2.1093(b) requiring evaluation under the provisions of that section. **All other mobile and unlicensed transmitting devices are categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in §§1.1307(c) and 1.1307(d) of this chapter. Applications for equipment authorization of mobile and unlicensed transmitting devices subject to routine environmental evaluation must contain a statement confirming compliance with the limits specified in paragraph (d) of this section as part of their application.**"*

The device will only be used with a separation distance between the antenna and the body of the user or nearby persons as shown in the table below and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b).

COMPLIANCE WITH FCC KDB 447498 D01 General RF Exposure Guidance v06

"KDB 447498 D01 General RF Exposure Guidance v06" provides the procedures, requirements, and authorization policies for mobile and portable devices.

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously are covered in section 7.1.

Devices containing multiple transmitters capable of simultaneous transmissions are covered in section 7.2.

MAXIMUM PERMISSIBLE EXPOSURE (MPE)



LIMITS

Limits for General Population /Uncontrolled Exposure: 47 CFR 1.1310

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30
1500 - 100000			1	30

f = frequency in MHz

* = Plane-wave equivalent power density

ASSESSMENT

The exposure level for the radio is evaluated at a 20 cm distance from the radio's transmitting antenna using the general equation:

$$S = \frac{P * G}{4 * \pi * R^2}$$

Where: S = power density (mW/cm²)

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

P*G = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is determined. This level is then compared to the applicable limit for the transmit frequency. If limits were not met at the 20 cm boundary the evaluation distance is increased until the limit is met as shown in the table below.

For co-located radios, the ratio of the calculated level to the limit is determined. The ratios for each co-located radio are summed. If the sum is less than or equal to one, then the device is excluded from testing and is deemed compliant.

The IP30C is an RFID scan handle that clips to the backside of the CK65L0N mobile computer as an optional accessory. Communication between the computer and the scan handle is via Bluetooth. There is no electrical connection between the two devices.

The IM11 UHF RFID radio module is contained within the IP30C hand scanner and is co-located with the CK65L0N mobile computer radios when the mobile computer is mounted in the IP30C scan handle. The duty cycle of the 900 MHz radio is limited to 50% in the software.

The IP30C RFID reader cannot operate while worn next to the body. The user is instructed to operate the reader from the hand, aimed toward remove tags, and pull the trigger to engage the transmitter while maintaining at least a 20cm separation from the RFID antenna and the head or torso.

MAXIMUM PERMISSIBLE EXPOSURE (MPE)



Intermec IP30C containing FCC ID: EHA-IM11 and FCC ID: QOQWT12 co-located with Intermec CK65L0N mobile computer FCC ID: HD5-CK65L0N

A SAR test exclusion assessment for portable use of the same radios is documented in Element report #INMC1104.6.

MPE estimates for Individual Devices (Conducted Measurements):

Radio	Transmit Frequency (MHz)	Measured Conducted Output Power (mW)	Duty Cycle	Highest Antenna Gain (dBi)	Minimum Antenna Cable Loss (dB)	Minimum Separation Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio
Bluetooth in IP30C	2480	2.2	1	0.5	0	20	0.00050	1.0	0.00050
900 MHz RFID in IP30C	902.75	938.2	0.5	5.2	0	20	0.3090	0.6	0.5135
802.11: 5745 - 5824 MHz in CK65L0N	5745	131	1	4.85	0	20	0.080	1.0	0.0796
802.11: 5500 - 5720 MHz in CK65L0N	5580	143	1	4.85	0	20	0.087	1.0	0.0869
802.11: 5260-5320 MHz in CK65L0N	5260	44	1	4.72	0	20	0.026	1.0	0.0260
802.11: 5180-5240 MHz in CK65L0N	5240	45	1	4.85	0	20	0.027	1.0	0.0273
802.11: 2412-2462 MHz in CK65L0N	2437	629	1	2.88	0	20	0.243	1.0	0.2429
Bluetooth in CK65L0N	2480	5.2	1	2.64	0	20	0.0019	1.0	0.0019
Bluetooth Low Energy in CK65L0N	2480	1.7	1	2.64	0	20	0.00062	1.0	0.00062

The information in the table above was obtained from:

From client supplied information for this application and the references provided in the table below.

Radio	Reference
Bluetooth in IP30C	SGS report# EF/2005/C0012
900 MHz RFID in IP30C	NWEMC report# ITRM0323
802.11 in CK65L0N	Bureau Veritas report# RF190111C05-4 and RF190111C05-2
Bluetooth in CK65L0N	Bureau Veritas report# RF190111C05
Bluetooth Low Energy in CK65L0N	Bureau Veritas report# RF190111C05-1

Worst Case Co-located Exposure Conditions:

The firmware for the Bluetooth, Bluetooth Low Energy, 802.11 radios in the CK65L0N mobile computer prevents simultaneous transmission of these radios (from FCC ID: HD5-CK65L0N grant documentation).

Radio	Transmit Frequency (MHz)	Power Density (mW/cm ²)	Ratio	FCC limit for Co-location
Bluetooth in IP30C	2480	0.0005	0.0005	
900 MHz RFID in IP30C	902.75	0.309	0.5135	
802.11 in CK65L0N	2437	0.243	0.2431	

MAXIMUM PERMISSIBLE EXPOSURE (MPE)



Sum of Ratios:	0.7570	1
----------------	--------	---

IP30C with CK65 – Separation Distance from Head/Body

