

## FCC 47 CFR PART 15 SUBPART E

# **TEST REPORT**

For

## WLAN 11a+b/g Access Point

Model: RBT-1002

## **Trade Name: ENTERASYS**

Issued to

ENTERASYS NETWORKS 50 MINUTEMAN ROAD, ANDOVER, Massachusetts, United States

Issued by

Compliance Certification Services Inc. No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, (338) Taiwan, R.O.C. TEL: 886-3-324-0332 FAX: 886-3-324-5235



*Note:* This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



# TABLE OF CONTENTS

1. TE	ST RESULT CERTIFICATION	
2. EU	T DESCRIPTION	4
3. TE	ST METHODOLOGY	5
3.1	EUT CONFIGURATION	5
3.2	EUT EXERCISE	
3.3	GENERAL TEST PROCEDURES	5
3.4	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	6
3.5	DESCRIPTION OF TEST MODES	
4. INS	STRUMENT CALIBRATION	7
4.1	MEASUREMENT EQUIPMENT USED	7
5. FA	CILITIES AND ACCREDITATIONS	
5.1	FACILITIES	
5.2	EQUIPMENT	
5.3	LABORATORY ACCREDITATIONS AND LISTING	
5.4	TABLE OF ACCREDITATIONS AND LISTINGS	9
6. SE	ГUP OF EQUIPMENT UNDER TEST	
6.1	SETUP CONFIGURATION OF EUT	
6.2	SUPPORT EQUIPMENT	
7. FC	C PART 15 REQUIREMENTS	
7.1	26 DB EMISSION BANDWITH	
7.2	PEAK POWER	
7.3	BAND EDGES MEASUREMENT	
7.4	PEAK POWER SPECTRAL DENSITY	
7.5	PEAK EXCURSION	
/.0 7 7	KADIATED UNDESIKABLE EMISSION.	
/./ 7.8	CONDUCTED UNDESIKABLE EMISSION	
79	TRANSMISSION IN ARSENCE OF DATA	
7 10	FREQUENCY STABILITY	42
,.10		
APPEN	NDIX I PHOTOGRAPHS OF TEST SETUP	
APPEN	NDIX II RADIO FREQUENCY EXPOSURE	



# **1. TEST RESULT CERTIFICATION**

Applicant:	ENTERASYS NETWORKS 50 MINUTEMAN ROAD, ANDOVER, Massachusetts, United States			
Equipment Under Test:	WLAN 11a+b/g Acc	ess Point		
Trade Name:	ENTERASYS			
Model:	RBT-1002			
Date of Test:	July 11 ~ August 17,	2005		
	APPLICABLE ST	TANDARDS		
STANDARD		TEST RESULT		
FCC 47 CFR Part	15 Subpart E	No non-compliance noted		

## We hereby certify that:

Compliance Certification Services Inc. tested the above equipment. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.407.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

parin. lim

Gavin Lim Section Manager Compliance Certification Services Inc.

Reviewed by:

ha Um

Amanda Wu Section Manager Compliance Certification Services Inc.



# 2. EUT DESCRIPTION

Product	WLAN 11a+b/g Access Point
Trade Name	ENTERASYS
Model Number	RBT-1002
Model Discrepancy	N/A
Power Supply	DELTA / ADP-15KB I/P: 100-240V, 0.5A, 50-60Hz O/P: 5.1V, 3.0A
Frequency Range	Base mode: 5.15 ~ 5.35 GHz
Transmit Power	Base mode: 14.06 dBm
Modulation Technique	OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Transmit Data Rate	54, 48, 36, 24, 18, 12, 9, 6 Mbps
Number of Channels	Base mode: 8 Channels
Antenna Specification	Trade name / Model name: Accton / EWP6021E-ZZ Antanna Type: dual-band one feeder antanna Antanna Gain: IEEE 802.11a: 5 dBi IEEE 802.11b/g: 2 dBi

## **Operation Frequency:**

UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII)					
CHANNEL	MHz				
1	5180				
2	5200				
3	5220				
4	5240				
5	5260				
6	5280				
7	5300				
8	5320				

## Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by

manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: <u>OXO-RBT1002</u> filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.



# **3. TEST METHODOLOGY**

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 Radiated testing was performed at an antenna to EUT distance 3 meters.

## **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed for RF field strength measurement to meet the Commissions requirement, and is operated in a manner intended to generate the maximum emission in a continuous normal application.

## 3.2 EUT EXERCISE

The EUT is operated in the engineering mode to fix the Tx frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

## **3.3 GENERAL TEST PROCEDURES**

## **Conducted Emissions**

The EUT is placed on the turntable, which is positioned at 0.8 m above the ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4, the conducted emission from the EUT is measured in the frequency range between 0.15 MHz and 30MHz, using the CISPR Quasi-Peak detector mode.

## **Radiated Emissions**

The EUT is placed on the turntable, which is 0.8 m above the ground plane. The turntable is then rotated for 360 degrees to determine the proper orientation for the maximum emission level. The EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission level. And, each emission is to be maximized by changing the horizontal and vertical polarization of the receiving antenna. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



## 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
$^{1}0.495 - 0.505$	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	$(^{2})$
13.36 - 13.41	322 - 335.4		

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

# 3.5 DESCRIPTION OF TEST MODES

The EUT (model: RBT-1002) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

#### Base mode:

Channel Low (5180MHz), Channel Mid (5260MHz) and Channel High (5320MHz) with 6Mbps data rate were chosen for full testing.



# 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

# 4.1 MEASUREMENT EQUIPMENT USED

## **Equipment Used for Emissions Measurement**

**Remark:** Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site						
Name of Equipment	Manufacturer	Model	Serial Number	<b>Calibration Due</b>		
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2006		

Open Area Test Site # 3					
Name of Equipment	Manufacturer	Model	Serial Number	<b>Calibration Due</b>	
EMI Test Receiver	R&S	ESVS20	838804/004	01/08/2006	
Spectrum Analyzer	R&S	FSP30	100112	09/23/2005	
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2006	
Pre-Amplifier	MITEC	AFS42-00102650	924206	N.C.R.	
Pre-Amplifier	MITEC	AMF-6F-260400	945377	N.C.R.	
Bilog Antenna	SCHWAZBECK	VULB9163	145	07/05/2006	
Horn Antenna	EMCO	3115	00022250	04/18/2006	
Horn Antenna	EMCO	3116	2487	12/08/2005	
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R	
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R	
Controller	EMCO	2090	9709-1256	N.C.R	
RF Switch	ANRITSU	MP59B	M53867	N.C.R	
Site NSA	C&C	N/A	N/A	09/06/2005	

**Remark:** The measurement uncertainty is less than +/- 2.16dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Powerline Conducted Emissions Test Site						
Name of Equipment	Manufacturer	Model	Serial Number	<b>Calibration Due</b>		
EMI TEST RECEIVER 9kHz-30MHz	ROHDE & SCHWARZ	ESHS30	828144/003	09/24/2005		
TWO-LINE V-NETWORK 9kHz-30MHz	SCHAFFNER	NNB41	03/10013	06/11/2006		
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	02/17/2006		
Test S/W LABVIEW (V 6.1)			EW (V 6.1)			

*Remark:* The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



# 5. FACILITIES AND ACCREDITATIONS

# **5.1 FACILITIES**

All measurement facilities used to collect the measurement data are located at

🛛 No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

# **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

# 5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200600-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (Registration no: 93105 and 90471).



# 5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP*	EN 55011, EN 55014-1, AS/NZS 1044, CNS 13783-1, EN 55022, CNS 13438, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, FCC OST/MP-5, AS/NZS CISPR 22, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	NVLAJ 200600-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	<b>FC</b> 93105, 90471
Japan	VCCI	4 3/10 meter Open Area Test Sites to perform conducted/radiated measurements	<b>VCCI</b> R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328-2, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	ELA 124a ELA 124b ELA 124c
Taiwan	CNLA	EN 300 328-1/2, EN 300 220-1/2/3, EN 300 440-1/2, EN 61000-3-2, EN 61000-3-3, 47 CFR FCC Part 15 Subpart C/D/E, EN 55013, CNS 13439, EN 55014-1, CNS 13783-1, EN 55022, CNS 13438, CISPR 22, AS/NZS 3548, EN 61000-4-2/3/4/5/6/8/11, ENV 50204, IEEE Std 1528, FCC OET Bulletin, 65+Supplement C, EN50360, EN50361, EN50371, RSS102	0 3 6 3 ILAC MRA
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	Canada IC 3991-3 IC 3991-4

\* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

\* Australia: MRA of NVLAP AS/NZS 4771 &AS/NZS 4268.



# 6. SETUP OF EQUIPMENT UNDER TEST6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

## 6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Notebook PC (remote)	IBM	2672(X31)	99PBTKB	FCC DoC	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

# 7. FCC PART 15 REQUIREMENTS

# 7.1 26 dB EMISSION BANDWITH

According to §15.303(c), for purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Compliance with the emissions limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

## **Test Configuration**

## **TEST PROCEDURE**

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 1%EBW, VBW = RBW, Span = 50MHz / 80MHz (Turbo Mode), and Sweep = auto.
  - Or Set the spectrum analyzer as RBW > 1%EBW, VBW > RBW, Span >26dB bandwidth (Base Mode) / >26dB bandwidth (Turbo Mode), and Sweep = auto.
- 4. Mark the peak frequency and –26dB (upper and lower) frequency.
- 5. Repeat until all the rest channels were investigated.

# TEST RESULTS

No non-compliance noted

## <u>Test Data</u>

Channel	Frequency (MHz)		Bandwidth (B) (MHz)
Low		5180	24.090
Mid	Base mode	5260	23.758
High		5320	24.224



#### **Test Plot**

## IEEE 802.11a Base mode

#### CH Low



Transmit Freq Error	6.390 kHz
x dB Bandwidth	24.090 MHz

## CH Mid



Transmit Freq Error	21.014 kHz
x dB Bandwidth	23.758 MHz



## CH High



Transmit Freq Error -28.755 kHz x dB Bandwidth 24.224 MHz



## 7.2 PEAK POWER

# LIMIT

According to §15.407(a),

- (1) For the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10log B, where B is the 26 dB emission bandwidth in MHz.
- (2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10log B, where B is the 26 dB emission bandwidth in MHz.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The peak power shall not exceed the limit as follow:

Frequency (MHz)		10 Log B (dB)	Limit 4 + 10 Log B or 11 + 10 Log B (dBm)	Power Limit (dBm)
	5180	13.818	17.818	17
Base mode	5260	13.758	24.758	24
	5320	13.842	24.842	24



## **Test Configuration**

The EUT was connected to a spectrum analyzer through a 50  $\Omega$  RF cable.



## TEST PROCEDURE

Set span to encompass the entire emission bandwidth (EBW) of the signal.

Set RBW = 1 MHz / Set VBW = 3 MHz.

Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to "free run". Trace average 100 traces in power averaging mode. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

## **TEST RESULTS**

No non-compliance noted

## <u>Test Data</u>

Channel	Frequency (MHz)		Output Power (dBm)	Limit (dBm)
1		5180	13.38	17
5	Base mode	5260	14.06	24
8		5320	13.53	24



#### **Test Plot**

## IEEE 802.11a Base mode

#### CH Low



## CH Mid





## **CH High**



## 13.53 dBm / 16.7600 MHz

-58.71 dBm/Hz



# 7.3 BAND EDGES MEASUREMENT

# LIMIT

According to \$15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

## **Test Configuration**



# TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

# TEST RESULTS

Refer to attach spectrum analyzer data chart.



#### Test Plot

## IEEE 802.11a Base mode / CH Low



## **Detector mode: Average**

## **Polarity: Vertical**



🔆 Agilent 10:54:05 Jul 5, 2005

#### **Detector mode: Peak**

#### 🔆 Agilent 10:57:59 Jul 5, 2005 Т Mkr1 5.150 0 GHz Ref 127 dBµ∀ Atten 10 dB 60.91 dBµ∀ #Peak Log 10 dB/ Offst 20 dB DI 74.0 dBµ∨ LgAv M1 S2 S3 FC Α ≈(f): FTun Swp Start 4.500 0 GHz Stop 5.190 0 GHz #Res BW 1 MHz #VBW 1 MHz #Sweep 100 ms (601 pts)

## **Detector mode: Average**

## **Polarity: Horizontal**

**Polarity: Horizontal** 

🔆 Agilent 10:57:36 Jul 5, 2005

⊤ Mkr1 5.150 0 GHz

Ref 127 dBµ∀ Atten 10 dB 49.48 dBµ∨ #Peak Log 10 dB/ Offst 20 dB DI 54.0 dBµ∨ LgAv W1 S2 S3 FC Α  $\approx$ (f): FTun 0 Swp Start 4.500 0 GHz Stop 5.190 0 GHz #Res BW 1 MHz #VBW 10 Hz Sweep 53.8 s (601 pts)

Rev. 00



## IEEE 802.11a Base mode / CH High

#### **Detector mode: Peak**



#### **Detector mode: Average**



**Polarity: Vertical** 



#### **Detector mode: Peak**

## **Polarity: Horizontal**



#### **Detector mode: Average**

**Polarity: Horizontal** 





# 7.4 PEAK POWER SPECTRAL DENSITY

# LIMIT

According to §15.407(a),

- (1) For the band 5.15-5.25 GHz, the peak power spectral density shall not exceed 4dBm in any 1MHz band.
- (2) For the band 5.25-5.35 GHz, the peak power spectral density shall not exceed 11dBm in any 1MHz band.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

## **Test Configuration**



## **TEST PROCEDURE**

- 1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2. Set the spectrum analyzer as RBW = 1MHz, VBW = 3MHz, Span = 50MHz, Sweep=Auto.
- 3. Record the max. reading.
- 4. Repeat the above procedure until the measurements for all frequencies are completed.

## TEST RESULTS

No non-compliance noted

## <u>Test Data</u>

Channel	Frequency (MHz)		PPSD (dBm)	Limit (dBm)	Margin (dB)	Result
Low		5180	2.983	4.0	-1.017	PASS
Mid	Base mode	5260	2.870	11.0	-8.13	PASS
High		5320	2.815	11.0	-8.185	PASS



## **Test Plot**

## IEEE 802.11a Base mode

#### CH Low



## 13.93 dBm / 16.7800 MHz

-58.32 dBm/Hz

## CH Mid



## 13.69 dBm /16.7200 MHz

-58.54 dBm/Hz



## CH High



## 13.18 dBm / 16.7600 MHz

## -59.07 dBm/Hz



# 7.5 PEAK EXCURSION

# **LIMIT**

According to §15.407(a)(6), the ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

## **Test Configuration**



# **TEST PROCEDURE**

The test is performed in accordance with <FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices> – Part 15, Subpart E, August 2002.

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to spectrum.
- 3. Trace A, Set RBW =1MHz, VBW = 3MHz, Span >26dB bandwidth (Base Mode) / >26dB bandwidth (Turbo Mode), Max. hold.
- 4. Trace B, Set RBW = 1MHz, VBW = 30kHz, Span >26dB bandwidth (Base Mode) / >26dB bandwidth (Turbo Mode), Max. hold.
- 5. Delta Mark trace A Maximum frequency and trace B same frequency.
- 6. Repeat the above procedure until measurements for all frequencies were complete.



# **TEST RESULTS**

No non-compliance noted

## <u>Test Data</u>

Channel	Frequen (MHz	су )	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low		5180	9.36	13.00	-3.64	PASS
M id	Base mode	5260	10.59	13.00	-2.41	PASS
High		5320	9.77	13.00	-3.23	PASS



## Test Plot

## IEEE 802.11a Base mode

#### CH Low



## CH Mid





#### **CH High**



19.73 dBm / 16.7600 MHz

-52.52 dBm/Hz



# 7.6 RADIATED UNDESIRABLE EMISSION

## **LIMIT**

According to 15.407(b),

- (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.

## **Test Configuration**

## **Below 1 GHz**









## **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.



## **TEST RESULTS**

## Below 1 GHz

<b>Operation Mode:</b>	Normal Link	Test Date:	August 16, 2005
Temperature:	31°C	Tested by:	Rex Lai
Humidity:	47% RH	<b>Polarity:</b>	Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
292.35	V	Peak	15.60	32.00	46.00	-14.00	16.40
319.82	V	Peak	16.10	34.30	46.00	-11.70	18.20
480.80	V	Peak	19.70	35.30	46.00	-10.70	15.60
491.13	V	Peak	20.50	28.70	46.00	-17.30	8.20
769.00	V	Peak	25.70	36.00	46.00	-10.00	10.30
879.81	V	Peak	23.50	33.30	46.00	-12.70	9.80
285.12	Н	Peak	15.10	32.30	46.00	-13.70	17.20
294.15	Н	Peak	15.70	29.30	46.00	-16.70	13.60
320.00	Н	Peak	16.10	29.50	46.00	-16.50	13.40
486.67	Н	Peak	20.20	31.00	46.00	-15.00	10.80
769.00	Н	Peak	25.70	35.30	46.00	-10.70	9.60
885.00	Н	Peak	23.40	30.70	46.00	-15.30	7.30

- 1. Measuring frequencies from 30 MHz to the 1GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/Quasi-peak detector mode.
- 3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 4. The IF bandwidth of SPA between 30MHz and 1GHz was 100 kHz.



## Above 1 GHz

<b>Operation Mode:</b>	Tx / IEEE 802.11a Base mode / CH Low	Test Date:	August 16, 2005
Temperature:	31°C	Tested by:	Rex Lai
Humidity:	50% RH	Polarity:	Ver. / Hor.

Erog	Ant.	Peak	AV	Ant. / CL	Actu	al Fs	Peak	AV	Morgin	
(MHz)	Pol H/V	Reading (dBuV)	Reading (dBuV)	CF (dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	(dB)	Remark
10360	V	43.26		8.29	51.55		74.00	54.00	-2.45	Peak
N/A										
10360	Н	42.99		8.29	51.28		74.00	54.00	-2.72	Peak
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 5. Spectrum setting:
  - *a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.*
  - *b.* AV Setting 1GH z to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



<b>Operation Mode:</b>	Tx / IEEE 802.11a Base mode / CH Mid	Test Date:	August 16, 2005
Temperature:	31°C	Tested by:	Rex Lai
Humidity:	50% RH	Polarity:	Ver. / Hor.

Erog	Ant.	Peak	AV	Ant. / CL	Actu	al Fs	Peak AV		AV	
(MHz)	Pol H/V	Reading (dBuV)	Reading (dBuV)	CF (dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	(dB)	Remark
10520.00	V	50.10	37.21	8.73	58.83	45.94	74.00	54.00	-8.06	Average
N/A										
10520.00	Н	42.16		8.73	50.89		74.00	54.00	-3.11	Peak
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 5. Spectrum setting:
  - *a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.*
  - *b.* AV Setting 1GH z to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



<b>Operation Mode:</b>	Tx / IEEE 802.11a Base mode / CH High	Test Date:	August 16, 2005
Temperature:	31°C	Tested by:	Rex Lai
Humidity:	50% RH	Polarity:	Ver. / Hor.

Frog	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak	AV	Morgin	
(MHz)					Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	(dB)	Remark
10640.00	V	48.51	36.30	9.15	57.66	45.45	74.00	54.00	-8.55	Average
N/A										
10640.00	Н	43.25	33.12	9.15	52.40	42.27	74.00	54.00	-11.73	Average
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 5. Spectrum setting:
  - *a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.*
  - *b.* AV Setting 1GH z to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



# 7.7 CONDUCTED UNDESIRABLE EMISSION

# LIMIT

According to 15.407(b),

- (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.

## **Test Configuration**



# **TEST PROCEDURE**

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 1 MHz. The video bandwidth is set to 1 MHz. Peak detector measurements are compared to the average EIRP limit, adjusted for the maximum antenna gain. If necessary, additional average detection measurements are made.

Measurements are made over the 30 MHz to 40 GHz range with the transmitter set to the lowest, middle, and highest channels.

# **TEST RESULTS**

No non-compliance noted



## **Test Plot**

## IEEE 802.11a Base mode

## CH Low

## **30MHz ~ 40GHz**



## CH Mid

#### **30MHz ~ 40GHz**





## CH High

## $30 MHz \sim 40 GHz$





# 7.8 POWERLINE CONDUCTED EMISSIONS

## **LIMIT**

According to \$15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBµV)				
requency Range (WIIIZ)	Quasi-peak	Average			
0.15 to 0.50	66 to 56*	56 to 46*			
0.50 to 5	56	46			
5 to 30	60	50			

\* Decreases with the logarithm of the frequency.

## **TEST CONFIGURATION**

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

## TEST PROCEDURE

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.



## TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

## <u>Test Data</u>

<b>Operation Mode:</b>	Normal Link	Test Date:	August 17, 2005
Temperature:	25°C	Tested by:	Bruce Chen
Humidity:	55% RH		

Freq. (MHz)	QP Reading	AV Reading	Corr. factor	QP Result	AV Result	QP Limit	AV Limit	QP Margin	AV Margin	Note
0.170	45.940	40.320	0.160	46.100	40.480	64.960	54.960	-18.860	-14.480	L1
0.346	30.350	28.550	0.100	30.450	28.650	59.058	49.058	-28.608	-20.408	L1
0.698	25.460	18.530	0.100	25.560	18.630	56.000	46.000	-30.440	-27.370	L1
0.859	31.110	24.450	0.100	31.210	24.550	56.000	46.000	-24.790	-21.450	L1
1.040	35.220	28.390	0.100	35.320	28.490	56.000	46.000	-20.680	-17.510	L1
27.497	24.070	20.350	1.300	25.370	21.650	60.000	50.000	-34.630	-28.350	L1
0.169	15.640	6.130	0.162	15.802	6.292	65.009	55.009	-49.207	-48.717	L2
0.338	12.170	11.590	0.100	12.270	11.690	59.252	49.252	-46.982	-37.562	L2
0.687	9.470	8.320	0.100	9.570	8.420	56.000	46.000	-46.430	-37.580	L2
0.859	11.180	1.100	0.100	11.280	1.200	56.000	46.000	-44.720	-44.800	L2
1.023	9.250	5.750	0.100	9.350	5.850	56.000	46.000	-46.650	-40.150	L2
27.497	25.150	21.500	1.300	26.450	22.800	60.000	50.000	-33.550	-27.200	L2

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
- 3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
- *4. L1* = *Line One (Live Line)* / *L2* = *Line Two (Neutral Line)*



## **Test Plots**





## Conducted emissions (Line 2)





# 7.9TRANSMISSION IN ABSENCE OF DATA

# **LIMIT**

According to §15.319(f), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

## **TEST RESULTS**

No non-compliance noted

**Remark:** For the details, please refer to the theory of the operation.

## 7.10 FREQUENCY STABILITY

# **LIMIT**

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

## **TEST RESULTS**

Please refer to the user's manual for further details.

**Remark:** An examination of the band-edge plots shows that the emission will stay within the authorized band over the entire temperature range.