



TEST REPORT

Application No.: GZCR2109021139AT
Applicant: PAX Technology Limited
Address of Applicant: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong Kong, China
Manufacturer: PAX Computer Technology(Shenzhen) Co., Ltd.
Address of Manufacturer: 4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

Equipment Under Test (EUT):

EUT Name: Mobile Payment Cell Phone
Model No.: M50
Trade Mark: PAX
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-09-16
Date of Test: 2021-09-17 to 2021-10-12
Date of Issue: 2021-10-18

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198 Kaizhu Road, Solentech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
Guangzhou Branch Testing & Inspection EMC Laboratory. 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-10-18		Original

Authorized for issue by				
				
		Curry Wu/Project Engineer		
				
		Ricky Liu/Reviewer		

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

Remark: This report is only valid with SZEM201201302804, by comparison with previous report, this report just changed as below:

1. The middle frame changed from rounded corners to right angles.
2. Power key and volume key position changed.
3. The material of battery cover changed from plastic to glass.

Considering the difference above, Radiated Emissions which fall in the restricted bands & Radiated Spurious Emissions were re-tested.

For other test data, please refer to previous report.

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units.....	5
4.3 Measurement Uncertainty	5
4.4 Test Location	6
4.5 Test Facility.....	6
4.6 Deviation from Standards.....	7
4.7 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Matter Test Results.....	10
6.1 Radiated Emissions which fall in the restricted bands	10
6.1.1 E.U.T. Operation	10
6.1.2 Test Mode Description	10
6.1.3 Test Setup Diagram	11
6.1.4 Measurement Procedure and Data.....	11
6.2 Radiated Spurious Emissions (Below 1GHz)	28
6.2.1 E.U.T. Operation.....	28
6.2.2 Test Mode Description	28
6.2.3 Test Setup Diagram	29
6.2.4 Measurement Procedure and Data.....	30
6.3 Radiated Spurious Emissions (Above 1GHz).....	33
6.3.1 E.U.T. Operation.....	33
6.3.2 Test Mode Description	33
6.3.3 Test Setup Diagram	34
6.3.4 Measurement Procedure and Data.....	35
7 Test Setup Photo	60
8 EUT Constructional Details (EUT Photos).....	61

4 General Information

4.1 Details of E.U.T.

Power supply:	DC3.85V by li-ion battery(3020mAh) Recharged by power adapter Adapter M/N: SW-0983 Adapter input: AC100-240V, 50/60Hz, 0.5A Adapter output: DC5V/2A
Cable(s):	USB type C cable: 1m shielded cable without ferrite core
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	1dBi declared by applicant
Firmware Version:	15.1.01
Hardware Version:	M50
Testing Software:	Type in *##3646633##* in the dial display to enter engineering mode
SN	2250000695
Power Setting:	16dBm for 802.11b, 15dBm for 802.11g, 14dBm for 802.11n mode, can not be changed by user.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.06\text{dB}$ (3m); $\pm 4.46\text{dB}$ (10m)
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27

Radiated Spurious Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Chamber cable	HangTianXing	N/A	EMC0542	2020-09-09	2022-09-08
Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-02-22	2022-02-22
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2019-12-27	2021-12-26
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2021-05-26	2022-05-25

Radiated Spurious Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2021-07-05	2022-07-05
DMM	Fluke	73	EMC0007	2021-07-05	2022-07-05



6 Radio Spectrum Matter Test Results

6.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C Humidity: 60 % RH Atmospheric Pressure: 1003 mbar

6.1.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Pre-scan	09	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.
Final test	10	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.1.3 Test Setup Diagram




6.1.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 10; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2362.770	47.53	27.27	3.42	37.60	40.62	54.00	-13.38	HORIZONTAL	Average
2	2362.770	58.48	27.27	3.42	37.60	51.57	74.00	-22.43	HORIZONTAL	Peak
3	2390.000	46.72	27.33	3.48	37.59	39.94	54.00	-14.06	HORIZONTAL	Average
4	2390.000	56.36	27.33	3.48	37.59	49.58	74.00	-24.42	HORIZONTAL	Peak
5 *	2412.000	101.55	27.38	3.47	37.59	94.81	54.00	40.81	HORIZONTAL	Average
6 *	2412.000	104.98	27.38	3.47	37.59	98.24	74.00	24.24	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2371.641	47.23	27.30	3.45	37.60	40.38	54.00	-13.62	VERTICAL	Average
2	2371.641	57.23	27.30	3.45	37.60	50.38	74.00	-23.62	VERTICAL	Peak
3	2390.000	46.71	27.33	3.48	37.59	39.93	54.00	-14.07	VERTICAL	Average
4	2390.000	55.12	27.33	3.48	37.59	48.34	74.00	-25.66	VERTICAL	Peak
5 *	2412.000	95.41	27.38	3.47	37.59	88.67	54.00	34.67	VERTICAL	Average
6 *	2412.000	98.21	27.38	3.47	37.59	91.47	74.00	17.47	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



race: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	101.14	27.45	3.50	37.58	94.51	54.00	40.51	HORIZONTAL	Average
2 *	2462.000	104.66	27.45	3.50	37.58	98.03	74.00	24.03	HORIZONTAL	Peak
3	2483.500	46.94	27.48	3.53	37.57	40.38	54.00	-13.62	HORIZONTAL	Average
4	2483.500	56.97	27.48	3.53	37.57	50.41	74.00	-23.59	HORIZONTAL	Peak
5	2486.551	47.21	27.48	3.53	37.57	40.65	54.00	-13.35	HORIZONTAL	Average
6	2486.601	59.41	27.48	3.53	37.57	52.85	74.00	-21.15	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	95.18	27.45	3.50	37.58	88.55	54.00	34.55	VERTICAL	Average
2 *	2462.000	97.79	27.45	3.50	37.58	91.16	74.00	17.16	VERTICAL	Peak
3	2483.500	46.93	27.48	3.53	37.57	40.37	54.00	-13.63	VERTICAL	Average
4	2483.500	55.26	27.48	3.53	37.57	48.70	74.00	-25.30	VERTICAL	Peak
5	2488.209	56.76	27.48	3.53	37.56	50.21	74.00	-23.79	VERTICAL	Peak
6	2490.472	47.18	27.49	3.47	37.56	40.58	54.00	-13.42	VERTICAL	Average

Test Mode: 10; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2315.271	48.41	27.15	3.32	37.62	41.26	54.00	-12.74	HORIZONTAL	Average
2	2315.271	59.18	27.15	3.32	37.62	52.03	74.00	-21.97	HORIZONTAL	Peak
3	2390.000	47.71	27.33	3.48	37.59	40.93	54.00	-13.07	HORIZONTAL	Average
4	2390.000	56.85	27.33	3.48	37.59	50.07	74.00	-23.93	HORIZONTAL	Peak
5 *	2412.000	95.65	27.38	3.47	37.59	88.91	54.00	34.91	HORIZONTAL	Average
6 *	2412.000	106.66	27.38	3.47	37.59	99.92	74.00	25.92	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2343.227	48.10	27.24	3.38	37.61	41.11	54.00	-12.89	VERTICAL	Average
2	2343.227	57.33	27.24	3.38	37.61	50.34	74.00	-23.66	VERTICAL	Peak
3	2390.000	47.28	27.33	3.48	37.59	40.50	54.00	-13.50	VERTICAL	Average
4	2390.000	54.74	27.33	3.48	37.59	47.96	74.00	-26.04	VERTICAL	Peak
5 *	2412.000	90.46	27.38	3.47	37.59	83.72	54.00	29.72	VERTICAL	Average
6 *	2412.000	99.25	27.38	3.47	37.59	92.51	74.00	18.51	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	97.00	27.45	3.50	37.58	90.37	54.00	36.37	HORIZONTAL	Average
2 *	2462.000	106.57	27.45	3.50	37.58	99.94	74.00	25.94	HORIZONTAL	Peak
3	2483.500	48.76	27.48	3.53	37.57	42.20	54.00	-11.80	HORIZONTAL	Average
4	2483.500	61.00	27.48	3.53	37.57	54.44	74.00	-19.56	HORIZONTAL	Peak
5	2483.940	48.59	27.48	3.53	37.57	42.03	54.00	-11.97	HORIZONTAL	Average
6	2484.041	61.03	27.48	3.53	37.57	54.47	74.00	-19.53	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	89.28	27.45	3.50	37.58	82.65	54.00	28.65	VERTICAL	Average
2 *	2462.000	97.81	27.45	3.50	37.58	91.18	74.00	17.18	VERTICAL	Peak
3	2483.500	47.62	27.48	3.53	37.57	41.06	54.00	-12.94	VERTICAL	Average
4	2483.500	54.66	27.48	3.53	37.57	48.10	74.00	-25.90	VERTICAL	Peak
5	2483.890	47.41	27.48	3.53	37.57	40.85	54.00	-13.15	VERTICAL	Average
6	2483.890	57.72	27.48	3.53	37.57	51.16	74.00	-22.84	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.484	58.22	27.33	3.48	37.59	51.44	74.00	-22.56	HORIZONTAL Peak
2	2389.968	47.45	27.33	3.48	37.59	40.67	54.00	-13.33	HORIZONTAL Average
3	2390.000	47.45	27.33	3.48	37.59	40.67	54.00	-13.33	HORIZONTAL Average
4	2390.000	57.87	27.33	3.48	37.59	51.09	74.00	-22.91	HORIZONTAL Peak
5 *	2412.000	95.74	27.38	3.47	37.59	89.00	54.00	35.00	HORIZONTAL Average
6 *	2412.000	105.40	27.38	3.47	37.59	98.66	74.00	24.66	HORIZONTAL Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2354.409	47.35	27.25	3.40	37.61	40.39	54.00	-13.61	VERTICAL	Average
2	2354.409	57.18	27.25	3.40	37.61	50.22	74.00	-23.78	VERTICAL	Peak
3	2390.000	46.89	27.33	3.48	37.59	40.11	54.00	-13.89	VERTICAL	Average
4	2390.000	54.38	27.33	3.48	37.59	47.60	74.00	-26.40	VERTICAL	Peak
5 *	2412.000	89.69	27.38	3.47	37.59	82.95	54.00	28.95	VERTICAL	Average
6 *	2412.000	98.64	27.38	3.47	37.59	91.90	74.00	17.90	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	95.63	27.45	3.50	37.58	89.00	54.00	35.00	HORIZONTAL	Average
2 *	2462.000	105.65	27.45	3.50	37.58	99.02	74.00	25.02	HORIZONTAL	Peak
3	2483.500	49.45	27.48	3.53	37.57	42.89	54.00	-11.11	HORIZONTAL	Average
4	2483.500	59.46	27.48	3.53	37.57	52.90	74.00	-21.10	HORIZONTAL	Peak
5	2483.790	49.10	27.48	3.53	37.57	42.54	54.00	-11.46	HORIZONTAL	Average
6	2484.041	63.46	27.48	3.53	37.57	56.90	74.00	-17.10	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	87.84	27.45	3.50	37.58	81.21	54.00	27.21	VERTICAL	Average
2 *	2462.000	96.85	27.45	3.50	37.58	90.22	74.00	16.22	VERTICAL	Peak
3	2483.500	47.25	27.48	3.53	37.57	40.69	54.00	-13.31	VERTICAL	Average
4	2483.500	55.84	27.48	3.53	37.57	49.28	74.00	-24.72	VERTICAL	Peak
5	2497.476	47.32	27.50	3.40	37.56	40.66	54.00	-13.34	VERTICAL	Average
6	2497.476	56.66	27.50	3.40	37.56	50.00	74.00	-24.00	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



race: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.677	58.45	27.33	3.48	37.59	51.67	74.00	-22.33	HORIZONTAL	Peak
2	2389.827	48.37	27.33	3.48	37.59	41.59	54.00	-12.41	HORIZONTAL	Average
3	2390.000	48.48	27.33	3.48	37.59	41.70	54.00	-12.30	HORIZONTAL	Average
4	2390.000	56.25	27.33	3.48	37.59	49.47	74.00	-24.53	HORIZONTAL	Peak
5 *	2422.000	94.19	27.39	3.45	37.58	87.45	54.00	33.45	HORIZONTAL	Average
6 *	2422.000	101.42	27.39	3.45	37.58	94.68	74.00	20.68	HORIZONTAL	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions of Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory.


中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2361.876	47.19	27.27	3.42	37.61	40.27	54.00	-13.73	VERTICAL	Average
2	2361.876	56.56	27.27	3.42	37.61	49.64	74.00	-24.36	VERTICAL	Peak
3	2390.000	46.92	27.33	3.48	37.59	40.14	54.00	-13.86	VERTICAL	Average
4	2390.000	54.94	27.33	3.48	37.59	48.16	74.00	-25.84	VERTICAL	Peak
5 *	2422.000	87.44	27.39	3.45	37.58	80.70	54.00	26.70	VERTICAL	Average
6 *	2422.000	95.45	27.39	3.45	37.58	88.71	74.00	14.71	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



race: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2452.000	92.05	27.43	3.40	37.58	85.30	54.00	31.30	HORIZONTAL	Average
2 *	2452.000	102.31	27.43	3.40	37.58	95.56	74.00	21.56	HORIZONTAL	Peak
3	2483.500	52.76	27.48	3.53	37.57	46.20	54.00	-7.80	HORIZONTAL	Average
4	2483.500	65.00	27.48	3.53	37.57	58.44	74.00	-15.56	HORIZONTAL	Peak
5	2490.717	52.53	27.49	3.47	37.56	45.93	54.00	-8.07	HORIZONTAL	Average
6	2490.717	66.52	27.49	3.47	37.56	59.92	74.00	-14.08	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2452.000	85.36	27.43	3.40	37.58	78.61	54.00	24.61	VERTICAL	Average
2 *	2452.000	94.31	27.43	3.40	37.58	87.56	74.00	13.56	VERTICAL	Peak
3	2483.500	48.32	27.48	3.53	37.57	41.76	54.00	-12.24	VERTICAL	Average
4	2483.500	56.53	27.48	3.53	37.57	49.97	74.00	-24.03	VERTICAL	Peak
5	2484.217	48.35	27.48	3.53	37.57	41.79	54.00	-12.21	VERTICAL	Average
6	2485.205	58.50	27.48	3.53	37.57	51.94	74.00	-22.06	VERTICAL	Peak

6.2 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C

Humidity: 60 % RH

Atmospheric Pressure: 1003 mbar

6.2.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Pre-scan 09 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.


Final test 10 Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.2.3 Test Setup Diagram



30MHz-1GHz

6.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1) Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

3) Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 10; Polarity: Horizontal



Test Mode: 10; Polarity: Vertical



6.3 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C

Humidity: 60 % RH

Atmospheric Pressure: 1003 mbar

6.3.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Pre-scan 09 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.


Final test 10 Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.3.3 Test Setup Diagram



6.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 10; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1648.778	49.54	25.63	2.80	37.93	40.04	74.00	-33.96	HORIZONTAL	Peak
2	4456.315	48.51	30.75	4.88	36.81	47.33	74.00	-26.67	HORIZONTAL	Peak
3	4824.000	47.74	31.45	5.42	36.83	47.78	74.00	-26.22	HORIZONTAL	Peak
4	5967.033	49.45	32.37	6.10	36.90	51.02	74.00	-22.98	HORIZONTAL	Peak
5	7236.000	46.51	35.70	6.03	37.39	50.85	74.00	-23.15	HORIZONTAL	Peak
6	9648.000	44.48	38.40	7.06	37.42	52.52	74.00	-21.48	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	48.09	25.66	2.80	37.91	38.64	74.00	-35.36	VERTICAL	Peak
2	4098.010	49.78	29.94	4.60	36.80	47.52	74.00	-26.48	VERTICAL	Peak
3	4824.000	48.20	31.45	5.42	36.83	48.24	74.00	-25.76	VERTICAL	Peak
4	6602.265	47.98	34.16	5.84	37.04	50.94	74.00	-23.06	VERTICAL	Peak
5	7236.000	46.26	35.70	6.03	37.39	50.60	74.00	-23.40	VERTICAL	Peak
6	9648.000	43.69	38.40	7.06	37.42	51.73	74.00	-22.27	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	48.93	25.65	2.80	37.91	39.47	74.00	-34.53	HORIZONTAL	Peak
2	4379.699	48.99	30.64	4.69	36.81	47.51	74.00	-26.49	HORIZONTAL	Peak
3	4874.000	46.63	31.54	5.50	36.84	46.83	74.00	-27.17	HORIZONTAL	Peak
4	6285.695	48.20	33.37	5.98	36.95	50.60	74.00	-23.40	HORIZONTAL	Peak
5	7311.000	47.46	35.93	6.11	37.42	52.08	74.00	-21.92	HORIZONTAL	Peak
6	9748.000	44.38	38.50	7.02	37.41	52.49	74.00	-21.51	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1503.119	48.30	25.50	2.80	38.10	38.50	74.00	-35.50	VERTICAL	Peak
2	4254.921	49.14	30.34	4.62	36.81	47.29	74.00	-26.71	VERTICAL	Peak
3	4874.000	46.80	31.54	5.50	36.84	47.00	74.00	-27.00	VERTICAL	Peak
4	6717.762	48.06	34.44	5.83	37.09	51.24	74.00	-22.76	VERTICAL	Peak
5	7311.000	47.62	35.93	6.11	37.42	52.24	74.00	-21.76	VERTICAL	Peak
6	9748.000	43.00	38.50	7.02	37.41	51.11	74.00	-22.89	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	49.56	25.72	2.80	37.89	40.19	74.00	-33.81	HORIZONTAL	Peak
2	4430.628	49.41	30.72	4.78	36.81	48.10	74.00	-25.90	HORIZONTAL	Peak
3	4924.000	45.80	31.62	5.60	36.84	46.18	74.00	-27.82	HORIZONTAL	Peak
4	6177.627	48.77	32.89	6.09	36.93	50.82	74.00	-23.18	HORIZONTAL	Peak
5	7386.000	46.78	36.17	6.19	37.45	51.69	74.00	-22.31	HORIZONTAL	Peak
6	9848.000	43.68	38.58	6.99	37.41	51.84	74.00	-22.16	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1529.414	48.45	25.52	2.80	38.07	38.70	74.00	-35.30	VERTICAL	Peak
2	4181.768	49.28	30.12	4.60	36.80	47.20	74.00	-26.80	VERTICAL	Peak
3	4924.000	45.57	31.62	5.60	36.84	45.95	74.00	-28.05	VERTICAL	Peak
4	5984.305	49.21	32.39	6.15	36.90	50.85	74.00	-23.15	VERTICAL	Peak
5	7386.000	46.26	36.17	6.19	37.45	51.17	74.00	-22.83	VERTICAL	Peak
6	9848.000	43.04	38.58	6.99	37.41	51.20	74.00	-22.80	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1687.347	48.72	25.69	2.80	37.91	39.30	74.00	-34.70	HORIZONTAL	Peak
2	4469.214	49.36	30.77	4.93	36.81	48.25	74.00	-25.75	HORIZONTAL	Peak
3	4824.000	48.04	31.45	5.42	36.83	48.08	74.00	-25.92	HORIZONTAL	Peak
4	6001.626	49.57	32.40	6.20	36.90	51.27	74.00	-22.73	HORIZONTAL	Peak
5	7236.000	46.99	35.70	6.03	37.39	51.33	74.00	-22.67	HORIZONTAL	Peak
6	9648.000	43.74	38.40	7.06	37.42	51.78	74.00	-22.22	HORIZONTAL	Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1687.347	49.53	25.69	2.80	37.91	40.11	74.00	-33.89	VERTICAL	Peak
2	4379.699	49.06	30.64	4.69	36.81	47.58	74.00	-26.42	VERTICAL	Peak
3	4824.000	47.08	31.45	5.42	36.83	47.12	74.00	-26.88	VERTICAL	Peak
4	6432.732	48.02	33.83	5.88	36.99	50.74	74.00	-23.26	VERTICAL	Peak
5	7236.000	46.66	35.70	6.03	37.39	51.00	74.00	-23.00	VERTICAL	Peak
6	9648.000	43.27	38.40	7.06	37.42	51.31	74.00	-22.69	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1583.392	48.13	25.56	2.80	38.00	38.49	74.00	-35.51	HORIZONTAL Peak
2	4482.150	48.50	30.78	4.99	36.81	47.46	74.00	-26.54	HORIZONTAL Peak
3	4874.000	46.32	31.54	5.50	36.84	46.52	74.00	-27.48	HORIZONTAL Peak
4	5599.412	49.34	31.89	6.30	36.89	50.64	74.00	-23.36	HORIZONTAL Peak
5	7311.000	47.40	35.93	6.11	37.42	52.02	74.00	-21.98	HORIZONTAL Peak
6	9748.000	43.39	38.50	7.02	37.41	51.50	74.00	-22.50	HORIZONTAL Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	48.12	25.57	2.80	37.98	38.51	74.00	-35.49	VERTICAL	Peak
2	4417.841	48.95	30.70	4.74	36.81	47.58	74.00	-26.42	VERTICAL	Peak
3	4874.000	47.36	31.54	5.50	36.84	47.56	74.00	-26.44	VERTICAL	Peak
4	6451.353	48.36	33.88	5.87	37.00	51.11	74.00	-22.89	VERTICAL	Peak
5	7311.000	47.28	35.93	6.11	37.42	51.90	74.00	-22.10	VERTICAL	Peak
6	9748.000	43.84	38.50	7.02	37.41	51.95	74.00	-22.05	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1682.477	49.09	25.68	2.80	37.91	39.66	74.00	-34.34	HORIZONTAL	Peak
2	4417.841	49.67	30.70	4.74	36.81	48.30	74.00	-25.70	HORIZONTAL	Peak
3	4924.000	46.29	31.62	5.60	36.84	46.67	74.00	-27.33	HORIZONTAL	Peak
4	6995.172	47.36	35.00	5.81	37.25	50.92	74.00	-23.08	HORIZONTAL	Peak
5	7386.000	47.63	36.17	6.19	37.45	52.54	74.00	-21.46	HORIZONTAL	Peak
6	9848.000	43.09	38.58	6.99	37.41	51.25	74.00	-22.75	HORIZONTAL	Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1667.951	48.45	25.66	2.80	37.91	39.00	74.00	-35.00	VERTICAL Peak
2	4169.698	49.30	30.09	4.60	36.80	47.19	74.00	-26.81	VERTICAL Peak
3	4924.000	45.86	31.62	5.60	36.84	46.24	74.00	-27.76	VERTICAL Peak
4	6974.982	47.34	34.97	5.81	37.23	50.89	74.00	-23.11	VERTICAL Peak
5	7386.000	48.00	36.17	6.19	37.45	52.91	74.00	-21.09	VERTICAL Peak
6	9848.000	43.76	38.58	6.99	37.41	51.92	74.00	-22.08	VERTICAL Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	48.35	25.72	2.80	37.89	38.98	74.00	-35.02	HORIZONTAL	Peak
2	4417.841	49.56	30.70	4.74	36.81	48.19	74.00	-25.81	HORIZONTAL	Peak
3	4824.000	48.43	31.45	5.42	36.83	48.47	74.00	-25.53	HORIZONTAL	Peak
4	6340.436	48.27	33.57	5.94	36.97	50.81	74.00	-23.19	HORIZONTAL	Peak
5	7236.000	46.22	35.70	6.03	37.39	50.56	74.00	-23.44	HORIZONTAL	Peak
6	9648.000	43.95	38.40	7.06	37.42	51.99	74.00	-22.01	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1606.441	49.23	25.59	2.80	37.98	39.64	74.00	-34.36	VERTICAL	Peak
2	4015.929	50.35	29.82	4.60	36.80	47.97	74.00	-26.03	VERTICAL	Peak
3	4824.000	47.99	31.45	5.42	36.83	48.03	74.00	-25.97	VERTICAL	Peak
4	6914.763	47.18	34.89	5.81	37.19	50.69	74.00	-23.31	VERTICAL	Peak
5	7236.000	46.64	35.70	6.03	37.39	50.98	74.00	-23.02	VERTICAL	Peak
6	9648.000	43.18	38.40	7.06	37.42	51.22	74.00	-22.78	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1667.951	48.03	25.66	2.80	37.91	38.58	74.00	-35.42	HORIZONTAL Peak
2	4086.182	50.29	29.92	4.60	36.80	48.01	74.00	-25.99	HORIZONTAL Peak
3	4874.000	47.38	31.54	5.50	36.84	47.58	74.00	-26.42	HORIZONTAL Peak
4	6602.265	47.55	34.16	5.84	37.04	50.51	74.00	-23.49	HORIZONTAL Peak
5	7311.000	47.15	35.93	6.11	37.42	51.77	74.00	-22.23	HORIZONTAL Peak
6	9748.000	43.75	38.50	7.02	37.41	51.86	74.00	-22.14	HORIZONTAL Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1697.129	48.62	25.71	2.80	37.89	39.24	74.00	-34.76	VERTICAL	Peak
2	4291.977	49.44	30.45	4.64	36.81	47.72	74.00	-26.28	VERTICAL	Peak
3	4874.000	48.07	31.54	5.50	36.84	48.27	74.00	-25.73	VERTICAL	Peak
4	6874.906	47.10	34.82	5.82	37.16	50.58	74.00	-23.42	VERTICAL	Peak
5	7311.000	46.97	35.93	6.11	37.42	51.59	74.00	-22.41	VERTICAL	Peak
6	9748.000	43.56	38.50	7.02	37.41	51.67	74.00	-22.33	VERTICAL	Peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1648.778	48.44	25.63	2.80	37.93	38.94	74.00	-35.06	HORIZONTAL	Peak
2	4443.453	49.44	30.73	4.83	36.81	48.19	74.00	-25.81	HORIZONTAL	Peak
3	4924.000	46.80	31.62	5.60	36.84	47.18	74.00	-26.82	HORIZONTAL	Peak
4	6470.026	47.88	33.92	5.86	37.00	50.66	74.00	-23.34	HORIZONTAL	Peak
5	7386.000	47.61	36.17	6.19	37.45	52.52	74.00	-21.48	HORIZONTAL	Peak
6	9848.000	44.23	38.58	6.99	37.41	52.39	74.00	-21.61	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	48.92	25.72	2.80	37.89	39.55	74.00	-34.45	VERTICAL	Peak
2	4193.872	49.35	30.15	4.60	36.81	47.29	74.00	-26.71	VERTICAL	Peak
3	4924.000	47.36	31.62	5.60	36.84	47.74	74.00	-26.26	VERTICAL	Peak
4	6303.890	48.71	33.44	5.97	36.96	51.16	74.00	-22.84	VERTICAL	Peak
5	7386.000	46.37	36.17	6.19	37.45	51.28	74.00	-22.72	VERTICAL	Peak
6	9848.000	43.67	38.58	6.99	37.41	51.83	74.00	-22.17	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1687.347	50.17	25.69	2.80	37.91	40.75	74.00	-33.25	HORIZONTAL	Peak
2	4443.453	49.24	30.73	4.83	36.81	47.99	74.00	-26.01	HORIZONTAL	Peak
3	4844.000	47.22	31.50	5.45	36.84	47.33	74.00	-26.67	HORIZONTAL	Peak
4	6776.265	48.05	34.61	5.82	37.11	51.37	74.00	-22.63	HORIZONTAL	Peak
5	7266.000	47.26	35.78	6.06	37.41	51.69	74.00	-22.31	HORIZONTAL	Peak
6	9688.000	43.93	38.44	7.04	37.42	51.99	74.00	-22.01	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	48.00	25.57	2.80	37.98	38.39	74.00	-35.61	VERTICAL	Peak
2	3969.767	49.86	29.77	4.60	36.81	47.42	74.00	-26.58	VERTICAL	Peak
3	4844.000	47.44	31.50	5.45	36.84	47.55	74.00	-26.45	VERTICAL	Peak
4	6894.806	47.33	34.85	5.81	37.18	50.81	74.00	-23.19	VERTICAL	Peak
5	7266.000	46.94	35.78	6.06	37.41	51.37	74.00	-22.63	VERTICAL	Peak
6	9688.000	43.30	38.44	7.04	37.42	51.36	74.00	-22.64	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1692.231	48.51	25.70	2.80	37.89	39.12	74.00	-34.88	HORIZONTAL	Peak
2	4242.641	49.24	30.30	4.62	36.81	47.35	74.00	-26.65	HORIZONTAL	Peak
3	4874.000	48.90	31.54	5.50	36.84	49.10	74.00	-24.90	HORIZONTAL	Peak
4	6737.207	47.06	34.50	5.82	37.09	50.29	74.00	-23.71	HORIZONTAL	Peak
5	7311.000	47.00	35.93	6.11	37.42	51.62	74.00	-22.38	HORIZONTAL	Peak
6	9748.000	43.38	38.50	7.02	37.41	51.49	74.00	-22.51	HORIZONTAL	Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	48.34	25.66	2.80	37.91	38.89	74.00	-35.11	VERTICAL	Peak
2	4242.641	49.42	30.30	4.62	36.81	47.53	74.00	-26.47	VERTICAL	Peak
3	4874.000	46.21	31.54	5.50	36.84	46.41	74.00	-27.59	VERTICAL	Peak
4	6621.375	47.75	34.20	5.83	37.05	50.73	74.00	-23.27	VERTICAL	Peak
5	7311.000	47.56	35.93	6.11	37.42	52.18	74.00	-21.82	VERTICAL	Peak
6	9748.000	43.72	38.50	7.02	37.41	51.83	74.00	-22.17	VERTICAL	Peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1682.477	47.93	25.68	2.80	37.91	38.50	74.00	-35.50	HORIZONTAL Peak
2	4417.841	48.41	30.70	4.74	36.81	47.04	74.00	-26.96	HORIZONTAL Peak
3	4904.000	46.19	31.58	5.55	36.84	46.48	74.00	-27.52	HORIZONTAL Peak
4	6894.806	47.29	34.85	5.81	37.18	50.77	74.00	-23.23	HORIZONTAL Peak
5	7356.000	47.47	36.06	6.15	37.44	52.24	74.00	-21.76	HORIZONTAL Peak
6	9808.000	43.11	38.56	7.00	37.41	51.26	74.00	-22.74	HORIZONTAL Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	48.86	25.65	2.80	37.91	39.40	74.00	-34.60	VERTICAL	Peak
2	4392.376	48.29	30.66	4.70	36.81	46.84	74.00	-27.16	VERTICAL	Peak
3	4904.000	47.09	31.58	5.55	36.84	47.38	74.00	-26.62	VERTICAL	Peak
4	6053.894	49.00	32.52	6.17	36.91	50.78	74.00	-23.22	VERTICAL	Peak
5	7356.000	47.71	36.06	6.15	37.44	52.48	74.00	-21.52	VERTICAL	Peak
6	9808.000	43.39	38.56	7.00	37.41	51.54	74.00	-22.46	VERTICAL	Peak

7 Test Setup Photo

Refer to Appendix - Setup Photos-BTWIFI for GZCR2109021139AT

8 EUT Constructional Details (EUT Photos)

Refer to Appendix - External Photos & Internal Photos for GZCR2109021139AT

- End of the Report -