

Diese technische Unterlage ist ausschliesslich unser Eigentum. Ohne unsere vorherige Zustimmung darf sie weder vervielfältigt noch Dritten zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch fuer den Fall der Patentierung oder Gebrauchsmustereintragung, -Aenderungen von Massen oder Abweichungen von freigegebenen Mustern nur mit unserer Zustimmung. Robert Bosch (Malaysia) Sdn Bhd

Bearbeitungsort:
Zweitoriginal in:

8649 039 170

FD, HW, SW
Printing sample only!!

Production week
Production year
(refer table)

Hardware(refer table)
Software (refer table)

KC Mark

FD: WWYY
HW: YY/WW
SW: 0000
ZGS: 001
Power Supply: 24V
Max Current: <3A
Bosch-No. 7 620 002 039
MB-No. A 001 446 21 62
Model : TCC NGA Mid MY19
Radio with Bluetooth

R-R-RBR-TCCNGAMidMY19

CE EAC UK CA TP Br Mercedes-Benz

CMIIT ID: 2019DJ12465
IC: 25847-TCCNGAMID
FCC ID: 2AUXS-TCCNGAMID

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause un-desired operation.

Robert Bosch GmbH
Business Unit CVO
Robert-Bosch-Platz 1
70839 GERLINGEN, GERMANY


55 mm

105 mm


Bosch symbol : acc. to N41A B04/2
and Supplier Address.

Machine readable code : Code 39
(BOSCH Product no.)

United Kingdom Logo



Ukraine Logo



Belarus Logo



China Logo



CMIIT ID: 2019DJ12465



FCC ID: 2AUXS-TCCNGAMID



IC: 25847-TCCNGAMID



Production week Production year	SW	HW
WWYY	0000	YY/WW

WWYY: WW = Week, YY = Year
YY/WW: YY = Year of hardware change
WW = Calendar week of hardware change
0000 - software version taken from SPL document

Part has to correspond with Bosch standard N2580-1.

Dimension reference lines and reference lines not printed


Front:
“Sans Condensed Regular/Bold” is to be download at
[http:// design.bosch.com](http://design.bosch.com) --> Basiselemente --> Schritten

Design:
Background: White
Fonts & symbols: Black

Back side: permanently glueing
Labels glued on Silicon paper
Glue: strong adhered glue on acryl base
The sticker shall not peel off from the surface (electrolytic zinc coated steel) at temperature range from +85 °C to -40 °C

Sticker must fulfill IEC/EN 62368-1 F.3.10
Part qualification: BPV 8 600 HM0 029

Part weight tolerance +/-10%. (For reference only)



PCB-Transfer-File :																			
Projekt-Library : M:\ENG\ENG_Projects\Product_Artwork_Design\Corel_Files\PS\Truck_2010_Red_safety																			
Measures without indication of tolerance acc. to														CAD Drawing		ID			
3	3E10049732	31.05.2021	OPL	6				9				12			Replaces:				
2	3E1004679131	16.02.2021	OPL	5				8				11							
1	3E1003168001	07.02.2020	OPL	4	3E10063054	14.04.2022	OPL	7				10			Replaced by:				
Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name				
Valid for production								Dwn. 08.10.2019 OPL				Part name/Part title Top Cover Sticker							
Material:								First Use 7620 002 039								Ckd. FSO1PG1			
																Ntc. Dpt. CM-CI1/ENG-Pg			
Raw part: 8613 921 261												Drawing-Nr./Ref.no. 8649 039 170				Scale 1:1			
								Weight: 730.00mg				No. of sheets 01 This includes:				Sheet no. 01 A3			