


RF Exposure Evaluation Report

FCC ID : 2AVDR-MISSION2
Equipment : Dive Computer
Brand Name : ATMOS
Model Name : MISSION2
Applicant : ATMOS CO., LTD.
16F-7, No. 258, Liancheng Rd., Zhonghe Dist.,
NEW TAIPEI CITY, 23553, Taiwan
Manufacturer : ATMOS CO., LTD.
16F-7, No. 258, Liancheng Rd., Zhonghe Dist.,
NEW TAIPEI CITY, 23553, Taiwan
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Mar. 07, 2022, and testing was started from Mar. 25, 2022 and completed on May 20, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB 447498 D04 Interim General RF Exposure Guidance v01 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

1. General Description.....	4
1.1. EUT General Information	4
1.2. Testing Location Information	4
2. RF Exposure Evaluation	5
2.1. Applicable Standard	5
2.2. SAR evaluation	5

Photographs of EUT V01

1. General Description

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.2. Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)		
	TEL: 886-3-327-3456		FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)		
	TEL: 886-3-318-0787		FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01,
Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	Option	TL EIRP (dBm)
2.4G;BT-LE	0.50	-0.80	-0.30	0.50	0.20	0.5	B	6.546

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01 exclusion thresholds is $0.20 < 6.546$, RF exposure evaluation is not required.
- 10g SAR test exemption is applied base on 10g SAR test exemption which is considered by applying a factor of 2.5 to the 1g SAR-based exemption thresholds.

————THE END————