

## TEST REPORT

**Report No.: 23030430HKG-001**

VTech Telecommunications Ltd.

Application For Original Grant of 47 CFR Part 15 Certification

Single New of RSS-210 Issue 10 Amendment 1 Certification

Breathing Sensor Tag

**FCC ID: EW780-3000-00**

**IC: 1135B-80300000**

**Prepared and Checked by:**

**Approved by:**

Signed on File

Wong Cheuk Ho, Herbert  
Lead Engineer

Wong Kwok Yeung, Kenneth  
Assistant Supervisor  
Date: March 30, 2023

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

## TEST REPORT

### GENERAL INFORMATION

|                                    |  |
|------------------------------------|--|
| <b>Grantee:</b>                    | VTech Telecommunications Ltd.  |
| <b>Grantee Address:</b>            | 23/F., Tai Ping Industrial Centre, Block 1,<br>57 Ting Kok Road, Tai Po,<br>Hong Kong.   |
| <b>Manufacturer:</b>               | VTech (Dongguan) Telecommunications Limited  |
| <b>Manufacturer Address:</b>       | VTech Science Park, Xia Ling Bei Management Zone,<br>Liaobu, Dongguan, Guangdong, China.   |
| <b>FCC Specification Standard:</b> | FCC Part 15, October 1, 2021 Edition   |
| <b>FCC ID:</b>                     | EW780-3000-00  |
| <b>FCC Model(s):</b>               | VC2810   |
| <b>IC Specification Standard:</b>  | RSS-210 Issue 10 Amendment 1, April 2020<br>RSS-Gen Issue 5 Amendment 2, February 2021   |
| <b>IC:</b>                         | 1135B-80300000   |
| <b>HVIN:</b>                       | 35-202055BU  |
| <b>PMN:</b>                        | VC2810   |
| <b>VTech Model(s):</b>             | VC2810   |
| <b>Type of EUT:</b>                | Transceiver  |
| <b>Description of EUT:</b>         | Breathing Sensor Tag   |
| <b>Brand Name:</b>                 | vtech  |
| <b>Sample Receipt Date:</b>        | March 13, 2023   |
| <b>Date of Test:</b>               | March 13, 2023 to March 30, 2023   |
| <b>Report Date:</b>                | March 30, 2023   |
| <b>Environmental Conditions:</b>   | Temperature: +10 to 40°C<br>Relative Humidity: 10 to 90%   |
| <b>Conclusion:</b>                 | Test was conducted by client submitted sample.<br>The submitted sample as received complied with the<br>47 CFR Part 15 / RSS-210 Issue 10 Amendment 1 Certification. |

## TEST REPORT

### SUMMARY OF TEST RESULT

| Test Items                                 | FCC Part 15 Section | RSS-210 / RSS-Gen <sup>#</sup> | Results  |
|--|---------------------|--------------------------------|----------|
| Transmitter Power Line Conducted Emissions | 15.207              | 8.8 <sup>#</sup>               | Complied |
| Radiated Emission                          | 15.249, 15.209      | B.10 / 8.9 <sup>#</sup>        | Complied |
| Radiated Emission on the Bandedge          |                     |                                | Complied |
| Radiated Emission in Restricted Bands      | 15.205              | 8.10 <sup>#</sup>              | Complied |

For Canada, all technical data can be referred to Annex B – Report cover sheet.

For electronic filing, the Annex B – Report cover sheet is saved with filename: Annex B.pdf.

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2021 Edition

RSS-210 Issue 10 Amendment 1, April 2020

RSS-Gen Issue 5 Amendment 2, February 2021

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

## TEST REPORT

### TABLE OF CONTENTS

|             |   |           |
|-------------|---|-----------|
| <b>1.0</b>  | <b>GENERAL DESCRIPTION.....</b>                   | <b>5</b>  |
| 1.1         | Product Description .....                         | 5         |
| 1.2         | Related Submittal(s) Grants.....                  | 5         |
| 1.3         | Test Methodology .....                            | 5         |
| 1.4         | Test Facility.....                                | 5         |
| <b>2.0</b>  | <b>SYSTEM TEST CONFIGURATION.....</b>             | <b>6</b>  |
| 2.1         | Justification .....                               | 6         |
| 2.2         | EUT Exercising Software.....                      | 6         |
| 2.3         | Special Accessories.....                          | 6         |
| 2.4         | Measurement Uncertainty.....                      | 6         |
| 2.5         | Support Equipment List and Description .....      | 6         |
| <b>3.0</b>  | <b>EMISSION RESULTS .....</b>                     | <b>7</b>  |
| 3.1         | Field Strength Calculation .....                  | 7         |
| 3.2         | Radiated Emission Configuration Photograph.....   | 8         |
| 3.3         | Radiated Emission Data .....                      | 8         |
| 3.4         | Conducted Emission Configuration Photograph ..... | 8         |
| 3.5         | Conducted Emission Data .....                     | 8         |
| <b>4.0</b>  | <b>EQUIPMENT PHOTOGRAPHS.....</b>                 | <b>23</b> |
| <b>5.0</b>  | <b>PRODUCT LABELLING.....</b>                     | <b>23</b> |
| <b>6.0</b>  | <b>TECHNICAL SPECIFICATIONS .....</b>             | <b>23</b> |
| <b>7.0</b>  | <b>INSTRUCTION MANUAL .....</b>                   | <b>23</b> |
| <b>8.0</b>  | <b>MISCELLANEOUS INFORMATION .....</b>            | <b>24</b> |
| 8.1         | Radiated Emission on the Bandedge .....           | 24        |
| 8.2         | Discussion of Pulse Desensitization .....         | 33        |
| 8.3         | Calculation of Average Factor .....               | 33        |
| 8.4         | Emissions Test Procedures.....                    | 34        |
| 8.5         | Occupied Bandwidth .....                          | 37        |
| <b>9.0</b>  | <b>CONFIDENTIALITY REQUEST.....</b>               | <b>41</b> |
| <b>10.0</b> | <b>EQUIPMENT LIST .....</b>                       | <b>41</b> |

## TEST REPORT

### 1.0 GENERAL DESCRIPTION

#### 1.1 Product Description

The Equipment Under Test (EUT), is a Breathing Sensor Tag with Bluetooth BLE feature. The EUT operates in a frequency range between 2402MHz and 2480MHz. The EUT is powered 3.7VDC internal rechargeable Li-ion battery and/or USB port (5VDC).

Antenna Type: Internal, Integral, wire antenna

Peak Antenna Gain: 0dBi

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

#### 1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC Designation No. "HK0005" and IC No. 2042H, CABID is "HKAP01".

## TEST REPORT

### 2.0 SYSTEM TEST CONFIGURATION

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

The EUT exercise program (if any) used during radiated testing was designed to exercise the various system components in a manner similar to a typical use.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044. For these excepted or not mentioned standards, CI 4.2.2 of ILAC-G8:09/2019 decision rules will be reference and guard band will be equal to our measurement uncertainty with 95% confidence level ( $k=2$ ). In case, the measured value is within guard band region, undetermined decision will be used.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

#### 2.5 Support Equipment List and Description

| Description                                      | Remark                |
|--|-----------------------|
| HP Notebook Computer (Adaptor Model: HSTNN-CA15) | Provided by Intertek  |
| 1 x LAN cable with length of 2.0 meter long      | Provided by Intertek  |
| 1 x USB cable with length of 0.4 meter long      | Provided by Applicant |

## TEST REPORT

### 3.0 EMISSION RESULTS

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

|    |   |   |
|----|---|---|
| FS | = | Field Strength in dBμV/m                            |
| RA | = | Receiver Amplitude (including preamplifier) in dBμV |
| AF | = | Antenna Factor in dB                                |
| CF | = | Cable Attenuation Factor in dB                      |
| AG | = | Amplifier Gain in dB                                |
| AV | = | Average Factor in dB                                |

In the following table(s), the reading shown on the data table reflects the preamplifier gain.

An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

|    |   |                          |
|----|---|--------------------------|
| FS | = | Field Strength in dBμV/m |
| RR | = | RA - AG - AV in dBμV     |
| LF | = | CF + AF in dB            |

Assume a receiver reading of 52.0 dBμV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29.0 dB and average factor of 5.0 dB are subtracted, giving a field strength of 27.0 dBμV/m. This value in dBμV/m was converted to its corresponding level in μV/m.

|    |   |                          |                |
|----|---|--------------------------|----------------|
| RA | = | 52.0 dBμV/m              |                |
| AF | = | 7.4 dB                   | RR = 18.0 dBμV |
| CF | = | 1.6 dB                   | LF = 9.0 dB    |
| AG | = | 29.0 dB                  |                |
| AV | = | 5.0 dB                   |                |
| FS | = | RR + LF                  |                |
| FS | = | 18.0 + 9.0 = 27.0 dBμV/m |                |

Level in μV/m = Common Antilogarithm [(27.0 dBμV/m)/20] = 22.4 μV/m

## TEST REPORT

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 7206.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 3.6 dB

### 3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.150 MHz

For electronic filing, the worst-case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.


Judgment: Pass by 27.2 dB



## TEST REPORT

### CONDUCTED EMISSION

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Bluetooth Operating and Charging



| EDIT PEAK LIST (Final Measurement Results) |           |            |                |  |
|--|-----------|------------|----------------|--|
| Trace1:                                    | CF15MQP   |            |                |  |
| Trace2:                                    | CF15MAV   |            |                |  |
| Trace3:                                    | ---       |            |                |  |
| TRACE                                      | FREQUENCY | LEVEL dBμV | DELTA LIMIT dB |  |
| 1 Quasi Peak                               | 150 kHz   | 38.84 L1   | -27.15         |  |

Note: Measurement Uncertainty is  $\pm 4.2$  dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 125K)

Table 1

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Lowest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2402.000        | 80.4           | 33                | 29.4                | 76.8                         | 94.0                         | -17.2       |
| V            | 4804.000        | 36.9           | 33                | 34.9                | 38.8                         | 54.0                         | -15.2       |
| V            | 7206.000        | 45.2           | 33                | 37.9                | 50.1                         | 54.0                         | -3.9        |
| H            | 9608.000        | 33.1           | 33                | 40.4                | 40.5                         | 54.0                         | -13.5       |
| V            | 12010.000       | 31.3           | 33                | 40.5                | 38.8                         | 54.0                         | -15.2       |
| V            | 14412.000       | 38.6           | 33                | 40.0                | 45.6                         | 54.0                         | -8.4        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2402.000        | 90.1           | 33                | 29.4                | 86.5                      | 114.0                     | -27.5       |
| V            | 4804.000        | 43.9           | 33                | 34.9                | 45.8                      | 74.0                      | -28.2       |
| V            | 7206.000        | 60.9           | 33                | 37.9                | 65.8                      | 74.0                      | -8.2        |
| H            | 9608.000        | 43.1           | 33                | 40.4                | 50.5                      | 74.0                      | -23.5       |
| V            | 12010.000       | 45.0           | 33                | 40.5                | 52.5                      | 74.0                      | -21.5       |
| V            | 14412.000       | 57.8           | 33                | 40.0                | 64.8                      | 74.0                      | -9.2        |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 125K)

Table 2

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Middle Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2440.000        | 80.2           | 33                | 29.4                | 76.6                         | 94.0                         | -17.4       |
| V            | 4880.000        | 36.9           | 33                | 34.9                | 38.8                         | 54.0                         | -15.2       |
| V            | 7320.000        | 43.9           | 33                | 37.9                | 48.8                         | 54.0                         | -5.2        |
| H            | 9760.000        | 31.4           | 33                | 40.4                | 38.8                         | 54.0                         | -15.2       |
| V            | 12200.000       | 33.0           | 33                | 40.5                | 40.5                         | 54.0                         | -13.5       |
| V            | 14640.000       | 40.4           | 33                | 38.4                | 45.8                         | 54.0                         | -8.2        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2440.000        | 90.0           | 33                | 29.4                | 86.4                      | 114.0                     | -27.6       |
| V            | 4880.000        | 46.9           | 33                | 34.9                | 48.8                      | 74.0                      | -25.2       |
| V            | 7320.000        | 55.3           | 33                | 37.9                | 60.2                      | 74.0                      | -13.8       |
| H            | 9760.000        | 39.4           | 33                | 40.4                | 46.8                      | 74.0                      | -27.2       |
| V            | 12200.000       | 48.7           | 33                | 40.5                | 56.2                      | 74.0                      | -17.8       |
| V            | 14640.000       | 53.4           | 33                | 38.4                | 58.8                      | 74.0                      | -15.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 125K)

Table 3

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Highest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2480.000        | 79.4           | 33                | 29.4                | 75.8                         | 94.0                         | -18.2       |
| V            | 4960.000        | 37.3           | 33                | 34.9                | 39.2                         | 54.0                         | -14.8       |
| V            | 7440.000        | 44.6           | 33                | 37.9                | 49.5                         | 54.0                         | -4.5        |
| H            | 9920.000        | 41.1           | 33                | 40.4                | 48.5                         | 54.0                         | -5.5        |
| V            | 12400.000       | 39.7           | 33                | 40.5                | 47.2                         | 54.0                         | -6.8        |
| V            | 14880.000       | 41.4           | 33                | 38.4                | 46.8                         | 54.0                         | -7.2        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2480.000        | 89.8           | 33                | 29.4                | 86.2                      | 114.0                     | -27.8       |
| V            | 4960.000        | 42.9           | 33                | 34.9                | 44.8                      | 74.0                      | -29.2       |
| V            | 7440.000        | 55.6           | 33                | 37.9                | 60.5                      | 74.0                      | -13.5       |
| H            | 9920.000        | 49.1           | 33                | 40.4                | 56.5                      | 74.0                      | -17.5       |
| V            | 12400.000       | 51.0           | 33                | 40.5                | 58.5                      | 74.0                      | -15.5       |
| V            | 14880.000       | 55.6           | 33                | 38.4                | 61.0                      | 74.0                      | -13.0       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 500K)

Table 4

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Lowest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2402.000        | 79.4           | 33                | 29.4                | 75.8                         | 94.0                         | -18.2       |
| V            | 4804.000        | 34.9           | 33                | 34.9                | 36.8                         | 54.0                         | -17.2       |
| V            | 7206.000        | 43.9           | 33                | 37.9                | 48.8                         | 54.0                         | -5.2        |
| H            | 9608.000        | 30.8           | 33                | 40.4                | 38.2                         | 54.0                         | -15.8       |
| V            | 12010.000       | 29.3           | 33                | 40.5                | 36.8                         | 54.0                         | -17.2       |
| V            | 14412.000       | 35.2           | 33                | 40.0                | 42.2                         | 54.0                         | -11.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2402.000        | 89.4           | 33                | 29.4                | 85.8                      | 114.0                     | -28.2       |
| V            | 4804.000        | 43.3           | 33                | 34.9                | 45.2                      | 74.0                      | -28.8       |
| V            | 7206.000        | 60.5           | 33                | 37.9                | 65.4                      | 74.0                      | -8.6        |
| H            | 9608.000        | 42.1           | 33                | 40.4                | 49.5                      | 74.0                      | -24.5       |
| V            | 12010.000       | 47.0           | 33                | 40.5                | 54.5                      | 74.0                      | -19.5       |
| V            | 14412.000       | 55.8           | 33                | 40.0                | 62.8                      | 74.0                      | -11.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 500K)

Table 5

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Middle Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2440.000        | 79.1           | 33                | 29.4                | 75.5                         | 94.0                         | -18.5       |
| V            | 4880.000        | 34.6           | 33                | 34.9                | 36.5                         | 54.0                         | -17.5       |
| V            | 7320.000        | 44.9           | 33                | 37.9                | 49.8                         | 54.0                         | -4.2        |
| H            | 9760.000        | 31.2           | 33                | 40.4                | 38.6                         | 54.0                         | -15.4       |
| V            | 12200.000       | 31.3           | 33                | 40.5                | 38.8                         | 54.0                         | -15.2       |
| V            | 14640.000       | 39.8           | 33                | 38.4                | 45.2                         | 54.0                         | -8.8        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2440.000        | 89.1           | 33                | 29.4                | 85.5                      | 114.0                     | -28.5       |
| V            | 4880.000        | 43.9           | 33                | 34.9                | 45.8                      | 74.0                      | -28.2       |
| V            | 7320.000        | 55.6           | 33                | 37.9                | 60.5                      | 74.0                      | -13.5       |
| H            | 9760.000        | 41.4           | 33                | 40.4                | 48.8                      | 74.0                      | -25.2       |
| V            | 12200.000       | 48.1           | 33                | 40.5                | 55.6                      | 74.0                      | -18.4       |
| V            | 14640.000       | 54.8           | 33                | 38.4                | 60.2                      | 74.0                      | -13.8       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 500K)

Table 6

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Highest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2480.000        | 78.8           | 33                | 29.4                | 75.2                         | 94.0                         | -18.8       |
| V            | 4960.000        | 36.9           | 33                | 34.9                | 38.8                         | 54.0                         | -15.2       |
| V            | 7440.000        | 43.9           | 33                | 37.9                | 48.8                         | 54.0                         | -5.2        |
| H            | 9920.000        | 40.8           | 33                | 40.4                | 48.2                         | 54.0                         | -5.8        |
| V            | 12400.000       | 38.7           | 33                | 40.5                | 46.2                         | 54.0                         | -7.8        |
| V            | 14880.000       | 41.0           | 33                | 38.4                | 46.4                         | 54.0                         | -7.6        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2480.000        | 88.4           | 33                | 29.4                | 84.8                      | 114.0                     | -29.2       |
| V            | 4960.000        | 42.6           | 33                | 34.9                | 44.5                      | 74.0                      | -29.5       |
| V            | 7440.000        | 55.3           | 33                | 37.9                | 60.2                      | 74.0                      | -13.8       |
| H            | 9920.000        | 48.1           | 33                | 40.4                | 55.5                      | 74.0                      | -18.5       |
| V            | 12400.000       | 51.3           | 33                | 40.5                | 58.8                      | 74.0                      | -15.2       |
| V            | 14880.000       | 55.0           | 33                | 38.4                | 60.4                      | 74.0                      | -13.6       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 1M)

Table 7

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Lowest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2402.000        | 81.0           | 33                | 29.4                | 77.4                         | 94.0                         | -16.6       |
| V            | 4804.000        | 36.6           | 33                | 34.9                | 38.5                         | 54.0                         | -15.5       |
| V            | 7206.000        | 45.5           | 33                | 37.9                | 50.4                         | 54.0                         | -3.6        |
| H            | 9608.000        | 29.8           | 33                | 40.4                | 37.2                         | 54.0                         | -16.8       |
| V            | 12010.000       | 30.7           | 33                | 40.5                | 38.2                         | 54.0                         | -15.8       |
| V            | 14412.000       | 34.2           | 33                | 40.0                | 41.2                         | 54.0                         | -12.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2402.000        | 90.8           | 33                | 29.4                | 87.2                      | 114.0                     | -26.8       |
| V            | 4804.000        | 42.3           | 33                | 34.9                | 44.2                      | 74.0                      | -29.8       |
| V            | 7206.000        | 52.3           | 33                | 37.9                | 57.2                      | 74.0                      | -16.8       |
| H            | 9608.000        | 41.4           | 33                | 40.4                | 48.8                      | 74.0                      | -25.2       |
| V            | 12010.000       | 45.7           | 33                | 40.5                | 53.2                      | 74.0                      | -20.8       |
| V            | 14412.000       | 53.8           | 33                | 40.0                | 60.8                      | 74.0                      | -13.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.



## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 1M)

Table 8

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Middle Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2440.000        | 81.2           | 33                | 29.4                | 77.6                         | 94.0                         | -16.4       |
| V            | 4880.000        | 34.5           | 33                | 34.9                | 36.4                         | 54.0                         | -17.6       |
| V            | 7320.000        | 44.3           | 33                | 37.9                | 49.2                         | 54.0                         | -4.8        |
| H            | 9760.000        | 30.1           | 33                | 40.4                | 37.5                         | 54.0                         | -16.5       |
| V            | 12200.000       | 31.0           | 33                | 40.5                | 38.5                         | 54.0                         | -15.5       |
| V            | 14640.000       | 37.2           | 33                | 38.4                | 42.6                         | 54.0                         | -11.4       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2440.000        | 91.4           | 33                | 29.4                | 87.8                      | 114.0                     | -26.2       |
| V            | 4880.000        | 39.9           | 33                | 34.9                | 41.8                      | 74.0                      | -32.2       |
| V            | 7320.000        | 51.9           | 33                | 37.9                | 56.8                      | 74.0                      | -17.2       |
| H            | 9760.000        | 41.1           | 33                | 40.4                | 48.5                      | 74.0                      | -25.5       |
| V            | 12200.000       | 47.1           | 33                | 40.5                | 54.6                      | 74.0                      | -19.4       |
| V            | 14640.000       | 53.4           | 33                | 38.4                | 58.8                      | 74.0                      | -15.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 1M)

Table 9

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Highest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2480.000        | 81.4           | 33                | 29.4                | 77.8                         | 94.0                         | -16.2       |
| V            | 4960.000        | 34.9           | 33                | 34.9                | 36.8                         | 54.0                         | -17.2       |
| V            | 7440.000        | 41.7           | 33                | 37.9                | 46.6                         | 54.0                         | -7.4        |
| H            | 9920.000        | 32.8           | 33                | 40.4                | 40.2                         | 54.0                         | -13.8       |
| V            | 12400.000       | 34.7           | 33                | 40.5                | 42.2                         | 54.0                         | -11.8       |
| V            | 14880.000       | 39.1           | 33                | 38.4                | 44.5                         | 54.0                         | -9.5        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2480.000        | 91.8           | 33                | 29.4                | 88.2                      | 114.0                     | -25.8       |
| V            | 4960.000        | 41.6           | 33                | 34.9                | 43.5                      | 74.0                      | -30.5       |
| V            | 7440.000        | 51.9           | 33                | 37.9                | 56.8                      | 74.0                      | -17.2       |
| H            | 9920.000        | 42.2           | 33                | 40.4                | 49.6                      | 74.0                      | -24.4       |
| V            | 12400.000       | 50.3           | 33                | 40.5                | 57.8                      | 74.0                      | -16.2       |
| V            | 14880.000       | 54.4           | 33                | 38.4                | 59.8                      | 74.0                      | -14.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 2M)

Table 10

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Lowest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2402.000        | 79.8           | 33                | 29.4                | 76.2                         | 94.0                         | -17.8       |
| V            | 4804.000        | 33.9           | 33                | 34.9                | 35.8                         | 54.0                         | -18.2       |
| V            | 7206.000        | 43.3           | 33                | 37.9                | 48.2                         | 54.0                         | -5.8        |
| H            | 9608.000        | 29.8           | 33                | 40.4                | 37.2                         | 54.0                         | -16.8       |
| V            | 12010.000       | 30.7           | 33                | 40.5                | 38.2                         | 54.0                         | -15.8       |
| V            | 14412.000       | 34.2           | 33                | 40.0                | 41.2                         | 54.0                         | -12.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2402.000        | 90.1           | 33                | 29.4                | 86.5                      | 114.0                     | -27.5       |
| V            | 4804.000        | 41.5           | 33                | 34.9                | 43.4                      | 74.0                      | -30.6       |
| V            | 7206.000        | 53.5           | 33                | 37.9                | 58.4                      | 74.0                      | -15.6       |
| H            | 9608.000        | 41.4           | 33                | 40.4                | 48.8                      | 74.0                      | -25.2       |
| V            | 12010.000       | 45.9           | 33                | 40.5                | 53.4                      | 74.0                      | -20.6       |
| V            | 14412.000       | 52.4           | 33                | 40.0                | 59.4                      | 74.0                      | -14.6       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 2M)

Table 11

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Middle Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2440.000        | 80.2           | 33                | 29.4                | 76.6                         | 94.0                         | -17.4       |
| V            | 4880.000        | 30.3           | 33                | 34.9                | 32.2                         | 54.0                         | -21.8       |
| V            | 7320.000        | 45.3           | 33                | 37.9                | 50.2                         | 54.0                         | -3.8        |
| H            | 9760.000        | 30.0           | 33                | 40.4                | 37.4                         | 54.0                         | -16.6       |
| V            | 12200.000       | 31.1           | 33                | 40.5                | 38.6                         | 54.0                         | -15.4       |
| V            | 14640.000       | 36.1           | 33                | 38.4                | 41.5                         | 54.0                         | -12.5       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2440.000        | 91.0           | 33                | 29.4                | 87.4                      | 114.0                     | -26.6       |
| V            | 4880.000        | 40.3           | 33                | 34.9                | 42.2                      | 74.0                      | -31.8       |
| V            | 7320.000        | 53.3           | 33                | 37.9                | 58.2                      | 74.0                      | -15.8       |
| H            | 9760.000        | 42.0           | 33                | 40.4                | 49.4                      | 74.0                      | -24.6       |
| V            | 12200.000       | 47.1           | 33                | 40.5                | 54.6                      | 74.0                      | -19.4       |
| V            | 14640.000       | 51.4           | 33                | 38.4                | 56.8                      | 74.0                      | -17.2       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE 2M)

Table 12

Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement

Highest Channel

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Average (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|------------------------------|------------------------------|-------------|
| H            | 2480.000        | 80.4           | 33                | 29.4                | 76.8                         | 94.0                         | -17.2       |
| V            | 4960.000        | 33.6           | 33                | 34.9                | 35.5                         | 54.0                         | -18.5       |
| V            | 7440.000        | 41.9           | 33                | 37.9                | 46.8                         | 54.0                         | -7.2        |
| H            | 9920.000        | 30.8           | 33                | 40.4                | 38.2                         | 54.0                         | -15.8       |
| V            | 12400.000       | 32.3           | 33                | 40.5                | 39.8                         | 54.0                         | -14.2       |
| V            | 14880.000       | 39.8           | 33                | 38.4                | 45.2                         | 54.0                         | -8.8        |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|---------------------------|---------------------------|-------------|
| H            | 2480.000        | 91.2           | 33                | 29.4                | 87.6                      | 114.0                     | -26.4       |
| V            | 4960.000        | 41.9           | 33                | 34.9                | 43.8                      | 74.0                      | -30.2       |
| V            | 7440.000        | 52.3           | 33                | 37.9                | 57.2                      | 74.0                      | -16.8       |
| H            | 9920.000        | 41.4           | 33                | 40.4                | 48.8                      | 74.0                      | -25.2       |
| V            | 12400.000       | 48.3           | 33                | 40.5                | 55.8                      | 74.0                      | -18.2       |
| V            | 14880.000       | 54.0           | 33                | 38.4                | 59.4                      | 74.0                      | -14.6       |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: VC2810  
Date of Test: March 22, 2023  
Worst-Case Operating Mode: Charging

Table 13

Pursuant to FCC Part 15 Section 15.209 / RSS-GEN 8.9 Requirement

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-amp (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|--------------|---------------------|--------------------|----------------------|-------------|
| V            | 30.002          | 18.5           | 16           | 10.0                | 12.5               | 40.0                 | -27.5       |
| H            | 127.972         | 16.5           | 16           | 14.0                | 14.5               | 43.5                 | -29.0       |
| H            | 159.982         | 28.2           | 16           | 16.0                | 28.2               | 43.5                 | -15.3       |
| H            | 191.994         | 30.4           | 16           | 16.0                | 30.4               | 43.5                 | -13.1       |
| H            | 224.005         | 20.8           | 16           | 18.0                | 22.8               | 46.0                 | -23.2       |
| H            | 339.915         | 14.4           | 16           | 24.0                | 22.4               | 46.0                 | -23.6       |
| H            | 415.938         | 17.4           | 16           | 25.0                | 26.4               | 46.0                 | -19.6       |

- Notes:
1. Quasi-Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.
  5. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
  6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## **TEST REPORT**

### **4.0 EQUIPMENT PHOTOGRAPHS**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### **5.0 PRODUCT LABELLING**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### **6.0 TECHNICAL SPECIFICATIONS**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### **7.0 INSTRUCTION MANUAL**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

## TEST REPORT

### 8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

#### 8.1 Radiated Emission on the Bandedge



From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209 / RSS-Gen 8.9, whichever is the lesser attenuation, which meet the requirement of Part 15.249(d) / RSS-210 B.10.





## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 125K)





## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 500K)





## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 1M)



## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 2M)



## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 125K)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 86.5 \text{ dB}\mu\text{V/m} - 45.8 \text{ dB} \\ &= 40.7 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 76.8 \text{ dB}\mu\text{V/m} - 45.8 \text{ dB} \\ &= 31.0 \text{ dB}\mu\text{V/m} \end{aligned}$$

Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 86.2 \text{ dB}\mu\text{V/m} - 49.1 \text{ dB} \\ &= 37.1 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 75.8 \text{ dB}\mu\text{V/m} - 49.1 \text{ dB} \\ &= 26.7 \text{ dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dBμV/m (Peak Limit) and 54 dBμV/m (Average Limit).

## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 500K)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 85.8 \text{ dB}\mu\text{V/m} - 50.2 \text{ dB} \\ &= 35.6 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 75.8 \text{ dB}\mu\text{V/m} - 50.2 \text{ dB} \\ &= 25.6 \text{ dB}\mu\text{V/m} \end{aligned}$$

Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 84.8 \text{ dB}\mu\text{V/m} - 50.9 \text{ dB} \\ &= 33.9 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 75.2 \text{ dB}\mu\text{V/m} - 50.9 \text{ dB} \\ &= 24.3 \text{ dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dBμV/m (Peak Limit) and 54 dBμV/m (Average Limit).

## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 1M)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 87.2 \text{ dB}\mu\text{V/m} - 50.3 \text{ dB} \\ &= 36.9 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 77.4 \text{ dB}\mu\text{V/m} - 50.3 \text{ dB} \\ &= 27.1 \text{ dB}\mu\text{V/m} \end{aligned}$$

Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 88.2 \text{ dB}\mu\text{V/m} - 53.0 \text{ dB} \\ &= 35.2 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 77.8 \text{ dB}\mu\text{V/m} - 53.0 \text{ dB} \\ &= 24.8 \text{ dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dBμV/m (Peak Limit) and 54 dBμV/m (Average Limit).

## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE 2M)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 86.5 \text{ dB}\mu\text{V/m} - 32.1 \text{ dB} \\ &= 54.4 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 76.2 \text{ dB}\mu\text{V/m} - 32.1 \text{ dB} \\ &= 44.1 \text{ dB}\mu\text{V/m} \end{aligned}$$

Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 87.6 \text{ dB}\mu\text{V/m} - 50.7 \text{ dB} \\ &= 36.9 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 76.8 \text{ dB}\mu\text{V/m} - 50.7 \text{ dB} \\ &= 26.1 \text{ dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dBμV/m (Peak Limit) and 54 dBμV/m (Average Limit).



## TEST REPORT

### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately  $625\mu s$  for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 3MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

## TEST REPORT

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


## TEST REPORT

### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


## TEST REPORT

### 8.4.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 8.4.3 Conducted Emission Test Setup




## TEST REPORT

### 8.5 Occupied Bandwidth

Occupied Bandwidth Results: (Bluetooth 4.0 BLE 125K)

| Bluetooth (MHz)      | Occupied Bandwidth (kHz) |
|----------------------|--------------------------|
| Low Channel: 2402    | 1080                     |
| Middle Channel: 2442 | 1062                     |
| High Channel: 2480   | 1092                     |

The worst case is shown as below:




## TEST REPORT

### 8.5 Occupied Bandwidth

Occupied Bandwidth Results: (Bluetooth 4.0 BLE 500K)

| Bluetooth (MHz)      | Occupied Bandwidth (kHz) |
|----------------------|--------------------------|
| Low Channel: 2402    | 1044                     |
| Middle Channel: 2442 | 1062                     |
| High Channel: 2480   | 1044                     |

The worst case is shown as below:




## TEST REPORT

### 8.5 Occupied Bandwidth

Occupied Bandwidth Results: (Bluetooth 4.0 BLE 1M)

| Bluetooth (MHz)      | Occupied Bandwidth (kHz) |
|----------------------|--------------------------|
| Low Channel: 2402    | 1056                     |
| Middle Channel: 2442 | 1062                     |
| High Channel: 2480   | 1068                     |

The worst case is shown as below:




## TEST REPORT

### 8.5 Occupied Bandwidth

Occupied Bandwidth Results: (Bluetooth 4.0 BLE 2M)

| Bluetooth (MHz)      | Occupied Bandwidth (kHz) |
|----------------------|--------------------------|
| Low Channel: 2402    | 2070                     |
| Middle Channel: 2442 | 2070                     |
| High Channel: 2480   | 2090                     |

The worst case is shown as below:





## TEST REPORT

### 9 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

### 10 EQUIPMENT LIST

#### 1) Radiated Emissions Test

| Equipment            | Signal and Spectrum Analyzer (10Hz to 40GHz) | Biconical Antenna (30MHz to 300MHz) | EMI Test Receiver 7GHz |
|----------------------|--|-------------------------------------|------------------------|
| Registration No.     | EW-3016                                      | EW-3242                             | EW-3481                |
| Manufacturer         | ROHDESCHWARZ                                 | EMCO                                | ROHDESCHWARZ           |
| Model No.            | FSV40  | 3110C                               | ESR7                   |
| Calibration Date     | January 29, 2022                             | May 26, 2021                        | December 21, 2021      |
| Calibration Due Date | April 29, 2023                               | May 26, 2023                        | June 21, 2023          |

| Equipment            | Log Periodic Antenna | Double Ridged Guide Antenna | Active Loop H-field (9kHz to 30MHz) |
|----------------------|----------------------|-----------------------------|-------------------------------------|
| Registration No.     | EW-3243              | EW-1133                     | EW-3302                             |
| Manufacturer         | EMCO                 | EMCO                        | EMCO                                |
| Model No.            | 3148B                | 3115                        | 6502                                |
| Calibration Date     | June 03, 2021        | May 26, 2021                | September 08, 2022                  |
| Calibration Due Date | March 30, 2023       | May 26, 2023                | September 08, 2023                  |

| Equipment            | RF Preamplifier (9kHz to 6000MHz) | 2.4GHz Notch Filter | 14m Double Shield RF Cable (9kHz - 6GHz) |
|----------------------|-----------------------------------|---------------------|--|
| Registration No.     | EW-3006b                          | EW-3435             | EW-2376                                  |
| Manufacturer         | SCHWARZBECK                       | MICROWAVE           | RADIALL                                  |
| Model No.            | BBV9718                           | N0324413            | n m/br56/bnc m 14m                       |
| Calibration Date     | February 15, 2022                 | June 16, 2022       | January 26, 2022                         |
| Calibration Due Date | May 15, 2023                      | June 16, 2023       | April 26, 2023                           |

| Equipment            | RF Cable 14m (1GHz to 26.5GHz) | 14m Double Shield RF Cable (20MHz to 6GHz) | Pyramidal Horn Antenna |
|----------------------|--------------------------------|--|------------------------|
| Registration No.     | EW-2781                        | EW-2074                                    | EW-0905                |
| Manufacturer         | GREATBILLION                   | RADIALL                                    | EMCO                   |
| Model No.            | SMA m/SHF5MPU /SMA m ra14m,26G | N(m)-RG142-BNC(m) L=14M                    | 3160-09                |
| Calibration Date     | November 24, 2021              | December 10, 2021                          | July 20, 2021          |
| Calibration Due Date | April 24, 2023                 | June 10, 2023                              | May 20, 2023           |

## TEST REPORT

### 2) Conducted Emissions Test

| Equipment            | RF Cable 80cm (RG142)<br>(9kHz to 30MHz) | EMI Test Receiver<br>7GHz | Artificial Mains<br>Network |
|----------------------|--|---------------------------|-----------------------------|
| Registration No.     | EW-2451                                  | EW-3481                   | EW-2501                     |
| Manufacturer         | RADIALL                                  | ROHDESCHWARZ              | ROHDESCHWARZ                |
| Model No.            | bnc m st / 142 / bnc m st<br>80cm        | ESR7                      | ENV-216                     |
| Calibration Date     | May 06, 2022                             | December 21, 2021         | November 09, 2021           |
| Calibration Due Date | May 06, 2023                             | June 21, 2023             | May 09, 2023                |

### 3) Bandedge Measurement

| Equipment            | EMI Test Receiver 7GHz | 5m RF Cable (40GHz) |
|----------------------|------------------------|---------------------|
| Registration No.     | EW-3481                | EW-2701             |
| Manufacturer         | ROHDESCHWARZ           | RADIALL             |
| Model No.            | ESR7                   | Sma m-m 5m 40G      |
| Calibration Date     | December 21, 2021      | November 24, 2021   |
| Calibration Due Date | June 21, 2023          | May 24, 2023        |

### 4) OBW Measurement

| Equipment            | EMI Test Receiver 7GHz | 5m RF Cable (40GHz) |
|----------------------|------------------------|---------------------|
| Registration No.     | EW-3481                | EW-2701             |
| Manufacturer         | ROHDESCHWARZ           | RADIALL             |
| Model No.            | ESR7                   | Sma m-m 5m 40G      |
| Calibration Date     | December 21, 2021      | November 24, 2021   |
| Calibration Due Date | June 21, 2023          | May 24, 2023        |

### 5) Control Software for Radiated Emission

| Software Information |              |
|----------------------|--------------|
| Software Name        | EMC32        |
| Manufacturer         | ROHDESCHWARZ |
| Software version     | 10.50.40     |

**END OF TEST REPORT**