



Test Report

FCC ID: 2AUTE-MT800

Date of issue: Oct. 22, 2019

Report number: MTi19091603-9E1

Sample description: A4 Mobile Printer

Model(s): MT800, MT808, MT818, MT866, MT888, MPT8C, M81C,
MTU81C, MTU82C, MTU83C, MTU84C, MTU85C, MTX81C,
MTX82C, MTX83C, MTX84C, MTX85C

Applicant: Xiamen Hanin Electronic Technology Co., Ltd.

Address: Room 305A, Angye Building, Pioneering Park, Torch High-tech,
Zone, Xiamen

Date of test: Oct. 10, 2019 to Oct. 22, 2019

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>



Table of Contents

1. GENERAL INFORMATION.....	5
1.1. DESCRIPTION OF EUT	5
1.2. OPERATION CHANNEL LIST	5
1.3. TEST CHANNEL LIST	6
1.4. ANCILLARY EQUIPMENT LIST	6
1.5. DESCRIPTION OF SUPPORT UNITS	6
2. SUMMARY OF TEST RESULTS.....	7
3. TEST FACILITIES AND ACCREDITATIONS	8
3.1. TEST LABORATORY	8
3.2. ENVIRONMENTAL CONDITIONS	8
3.3. MEASUREMENT UNCERTAINTY	8
3.4. TEST SOFTWARE	8
4. EQUIPMENT LIST.....	9
5. TEST RESULT	10
5.1. ANTENNA REQUIREMENT	10
5.1.1 Standard Requirement	10
5.1.2 EUT Antenna	10
5.2. PEAK OUTPUT POWER TEST	11
5.2.1 Limit	11
5.2.2 Test setup	11
5.2.3 Test Procedure	11
5.2.4 EUT Operation Condition	11
5.2.5 Test Results.....	11
5.3. CONDUCTED EMISSION	14
5.3.1 Limits.....	14
5.3.2 Test Setup	14
5.3.3 Test Procedure	15
5.3.4 Test Results.....	15
5.4. RADIATED SPURIOUS EMISSION.....	20
5.4.1 Limits.....	20
5.4.2 Test Setup	21
5.4.3 Test Procedure	22
5.4.4 Test Results.....	23
5.4.4.1 Band edge-radiated	27
5.4.4.2 Spurious Emission in Restricted Band 3260MHz-18000MHz	28
5.5. POWER SPECTRAL DENSITY TEST	29
5.5.1 Limit	29
5.5.2 Test Procedure	29
5.5.3 Test Setup	29
5.5.4 EUT Operation Conditions.....	29
5.5.5 Test Results.....	30
5.6. 6DB BANDWIDTH	32
5.6.1 Limit	32
5.6.2 Test Procedure	32
5.6.3 Test Setup	32
5.6.4 EUT Operation Conditions.....	32
5.6.5 Test Result	32
5.7. DUTY CYCLE	35
5.7.1 Conformance Limit	35
5.7.2 Measuring Instruments	35
5.7.3 Test Setup	35



5.7.4	<i>Test Procedure</i>	35
5.7.5	<i>Test Results</i>	36
5.8	CONDUCTED BAND EDGE.....	38
5.8.1	<i>Limits</i>	38
5.8.2	<i>Test Setup</i>	38
5.8.3	<i>Test Procedure</i>	38
5.8.4	<i>EUT Operation Conditions</i>	38
5.8.5	<i>Test Result</i>	38
5.9	SPURIOUS RF CONDUCTED EMISSIONS	40
5.9.1	<i>Conformance Limit</i>	40
5.9.2	<i>Measuring Instruments</i>	40
5.9.3	<i>Test Setup</i>	40
5.9.4	<i>Test Procedure</i>	40
5.9.5	<i>Test Results</i>	40
	PHOTOGRAPHS OF THE TEST SETUP	43
	PHOTOGRAPHS OF THE EUT.....	45



PRODUCT INFORMATION

Applicant's name:	Xiamen Hanin Electronic Technology Co., Ltd.
Address:	Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen
Manufacture's name:	Xiamen Hanin Electronic Technology Co., Ltd.
Address:	Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen
Product name:	A4 Mobile Printer
Trademark:	HPRT
Model name:	MT800, MT808, MT818, MT866, MT888, MPT8C, M81C, MTU81C, MTU82C, MTU83C, MTU84C, MTU85C, MTX81C, MTX82C, MTX83C, MTX84C, MTX85C
Standards:	FCC Part 15.247
Test procedure:	ANSI C63.10:2013 KDB 558074 D01 DTS Meas Guidance v05r02

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Demi Mu

Oct. 22, 2019

Reviewed by:

Blue Zheng

Oct. 22, 2019

Approved by:

Smith Chen

Oct. 22, 2019



1. General Information

1.1. Description of EUT

Product name:	A4 Mobile Printer
Model name:	MT800
Serial model:	MT808, MT818, MT866, MT888, MPT8C, M81C, MTU81C, MTU82C, MTU83C, MTU84C, MTU85C, MTX81C, MTX82C, MTX83C, MTX84C, MTX85C
Difference in series models:	All the model are the same circuit and RF module, except the model No..
Operation frequency:	2402-2480MHz
Modulation type:	GFSK
Bit Rate of transmitter:	1 Mbps
Antenna type:	PCB Antenna
Antenna gain:	1dBi
Max. output power:	-3.22dBm
Hardware version:	MPT8C-MB
Software version:	MT800_MB3_V1
Power supply:	DC 7.4V from Battery or DC 5V from adapter
Adapter information:	N/A
Battery:	DC 7.4V 2000mAh

1.2. Operation channel list

Channel No.	Frequency (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



1.3. Test channel list

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	19	2440
High	39	2480

1.4. Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
Adapter	EQ-24BCN	/	Huizhou Dongyang Yienbi Electronics Co., Ltd.	/

1.5. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
/	/	/	/	/	
/	/	/	/	/	

Note:

- (1)The support equipment was authorized by Declaration of Confirmation.
- (2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2. Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	



3. Test Facilities and Accreditations

3.1. Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2. Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1G)	±4.68dB
5	All emissions, radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3.4. Test software

Software Name	Manufacturer	Model	Version
Bluetooth and WiFi Test System	Shenzhen JS tonscrend co., ltd	JS1120-3	2.5.77.0418



4. Equipment list

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI7	100314	2019/10/09	2020/10/08
MTI-E006	TRILOG Broadband Antenna	schwarbeck	VULB 9163	9163-872	2019/10/15	2020/10/14
MTI-E014	amplifier	Hewlett-Packard	8447D	3113A061 50	2019/10/09	2020/10/08
MTI-E036	Single path vehicle AMN(LISN)	Schwarzbeck	NNBM 8124	01175	2019/10/09	2020/10/08
MTI-E038	Low noise active vertical monopole antenna	Schwarzbeck	VAMP 9243	#565	2019/10/16	2020/10/15
MTI-E039	Biconical antenna	Schwarzbeck	BBA 9106	#164	2019/10/15	2020/10/14
MTI-E041	MXG Vector Signal Generator	Agilent	N5182A	MY49060 455	2019/04/16	2020/04/15
MTI-E042	ESG Series Analog signal generator	Agilent	E4421B	GB40051 240	2019/05/21	2020/05/20
MTI-E044	Thermometer clock humidity monitor	-	HTC-1	/	2019/04/17	2020/04/16
MTI-E062	Log Periodic Antenna	Schwarzbeck	VUSLP 9111B	#312	2018/04/11	2020/04/10
MTI-E063	Log Periodic Dipole Array Antenna	ETS-LIND GREN	3148B	00224524	2018/04/11	2020/04/10
MTI-E065	Amplifier	EMtrace	RP06A	00117	2019/04/29	2020/04/28
MTI-E071	PXA Signal Analyzer	Agilent	N9030A	MY51350 296	2018/10/25	2019/10/24
MTI-E076	EMI Test Receiver	Rohde&schwarz	ESIB26	100273	2019/04/16	2020/04/15
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A019 57	2019/04/16	2020/04/15
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027 695	2019/04/16	2020/04/15
MTI-E093	Artificial mains network	3ctest	LISN J50	ES391180 5	2019/04/16	2020/04/15
MTI-E096	Power amplifier	Space-Dtronics	EWLNA0118G -P40	1852001	2019/04/29	2020/04/28
MTI-E097	Current Probe	SOLAR ELECTRONICS CO.	9207-1	220095-1	2019/04/17	2020/04/16
MTI-E098	Loop Sensor	SOLAR ELECTRONICS CO.	7334-1	220095-2	2019/04/21	2020/04/20
MTI-E081	EPM Series Power Meter	Agilent	E4419B	MY50000 438	2019/04/16	2021/04/15
Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).						



5. Test Result

5.1. Antenna requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna

The EUT antenna is PCB antenna (1dBi). It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.



5.2. Peak Output Power Test

5.2.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.2.2 Test setup



5.2.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.2.4 EUT Operation Condition

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.2.5 Test Results



EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1012 hPa	Test Voltage:	DC 7.4V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		


Test Channel	Frequency	Maximum Conducted Output Power(PK)	Limit
	(MHz)	(dBm)	dBm
CH00	2402	-3.22	30
CH19	2440	-4.13	30
CH39	2480	-4.24	30




2402MHz



2440MHz



2480MHz





5.3. Conducted emission

5.3.1 Limits


FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note

(1)The tighter limit applies at the band edges.

(2)The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.3.2 Test Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes



5.3.3 Test Procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.


For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.3.4 Test Results



Test data

EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Over Detector
1	*	0.1539	42.22	9.73	51.95	65.79	-13.84	QP
2		0.1539	22.67	9.73	32.40	55.79	-23.39	AVG
3		0.2180	36.49	9.73	46.22	62.89	-16.67	QP
4		0.2180	21.39	9.73	31.12	52.89	-21.77	AVG
5		0.5540	25.45	9.89	35.34	56.00	-20.66	QP
6		0.5540	13.56	9.89	23.45	46.00	-22.55	AVG
7		2.0660	26.18	9.97	36.15	56.00	-19.85	QP
8		2.0660	10.27	9.97	20.24	46.00	-25.76	AVG
9		4.7020	28.30	10.04	38.34	56.00	-17.66	QP
10		4.7020	14.81	10.04	24.85	46.00	-21.15	AVG
11		9.8620	32.10	10.29	42.39	60.00	-17.61	QP
12		9.8620	18.55	10.29	28.84	50.00	-21.16	AVG




EUT:	A4 Mobile Printer	Model Name:	MT800					
Pressure:	1010hPa	Phase:	N					
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	Charging+TX					
80.0 dBuV								
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	dB Over Detector	Over
1	*	0.1819	41.56	9.73	51.29	64.40	-13.11	QP
2		0.1819	23.93	9.73	33.66	54.40	-20.74	AVG
3		0.2540	32.39	9.73	42.12	61.63	-19.51	QP
4		0.2540	17.11	9.73	26.84	51.63	-24.79	AVG
5		0.5700	25.85	9.89	35.74	56.00	-20.26	QP
6		0.5700	13.35	9.89	23.24	46.00	-22.76	AVG
7		2.0900	28.78	9.97	38.75	56.00	-17.25	QP
8		2.0900	13.27	9.97	23.24	46.00	-22.76	AVG
9		4.9460	30.29	10.05	40.34	56.00	-15.66	QP
10		4.9460	15.11	10.05	25.16	46.00	-20.84	AVG
11		13.8740	35.92	10.22	46.14	60.00	-13.86	QP
12		13.8740	23.81	10.22	34.03	50.00	-15.97	AVG



EUT:	A4 Mobile Printer	Model Name:	MT800					
Pressure:	1010hPa	Phase:	L					
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	Charging+TX					
80.0 dBuV								
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV	Limit dBuV	Over dB	Over Detector
1	0.1700	35.11	9.73	44.84	64.96	-20.12	QP	
2	0.1700	17.25	9.73	26.98	54.96	-27.98	AVG	
3	0.5658	31.91	9.89	41.80	56.00	-14.20	QP	
4	0.5658	11.51	9.89	21.40	46.00	-24.60	AVG	
5	1.2660	29.77	9.96	39.73	56.00	-16.27	QP	
6	1.2660	15.49	9.96	25.45	46.00	-20.55	AVG	
7	2.4300	29.95	9.98	39.93	56.00	-16.07	QP	
8	2.4300	17.19	9.98	27.17	46.00	-18.83	AVG	
9	5.0819	35.24	10.05	45.29	60.00	-14.71	QP	
10	5.0819	18.65	10.05	28.70	50.00	-21.30	AVG	
11 *	9.0379	36.48	10.24	46.72	60.00	-13.28	QP	
12	9.0379	21.68	10.24	31.92	50.00	-18.08	AVG	



EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Over Detector
1		0.1660	35.61	9.73	45.34	65.16	-19.82	QP
2		0.1660	15.87	9.73	25.60	55.16	-29.56	AVG
3		0.3339	30.26	9.78	40.04	59.35	-19.31	QP
4		0.3339	15.34	9.78	25.12	49.35	-24.23	AVG
5 *		1.3660	29.76	9.96	39.72	56.00	-16.28	QP
6		1.3660	17.12	9.96	27.08	46.00	-18.92	AVG
7		3.9860	27.31	10.03	37.34	56.00	-18.66	QP
8		3.9860	16.83	10.03	26.86	46.00	-19.14	AVG
9		14.4420	32.20	10.20	42.40	60.00	-17.60	QP
10		14.4420	23.29	10.20	33.49	50.00	-16.51	AVG
11		23.3300	23.84	10.19	34.03	60.00	-25.97	QP
12		23.3300	17.55	10.19	27.74	50.00	-22.26	AVG



5.4. Radiated spurious emission

5.4.1 Limits

Frequency (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP




5.4.2 Test Setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz





5.4.3 Test Procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter shield area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] = $10 \times \lg(100 [\text{kHz}]/\text{narrower RBW} [\text{kHz}])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



5.4.4 Test Results

Below 30MHz

EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1010 hPa	Test Voltage:	DC 5V from adapter
Test Mode:	Charging+TX	Polarization::	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:


For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


Between 30MHz – 1GHz:

Note: The high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is CH39.





EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1010 hPa	Phase:	V
Test Mode:	Charging+TX	Test Voltage:	DC 5V from adapter



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	Detector
1	*	59.6492	37.09	-8.13	28.96	40.00	-11.04	QP
2		88.3421	31.17	-10.15	21.02	43.50	-22.48	QP
3		166.0680	40.96	-9.80	31.16	43.50	-12.34	QP
4		252.0627	27.57	-5.74	21.83	46.00	-24.17	QP
5		378.5842	34.49	-3.91	30.58	46.00	-15.42	QP
6		558.7300	31.17	-1.19	29.98	46.00	-16.02	QP
7		739.6603	31.95	1.17	33.12	46.00	-12.88	QP



1G-25GHz

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(3) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark	Comment
--------------------	-------------------------------	-----------------------	---------------------------	--------------------------	-------------------------------------	--------------------------	----------------	--------	---------

Low Channel (2402 MHz)-Above 1G

4804.338	63.09	4.36	32.92	45.53	54.84	74.00	-19.16	Pk	Vertical
4804.338	41.72	4.36	32.92	45.53	33.47	54.00	-20.53	AV	Vertical
7206.107	60.55	5.02	37.63	45.56	57.64	74.00	-16.36	Pk	Vertical
7206.107	41.56	5.02	37.63	45.56	38.65	54.00	-15.35	AV	Vertical
4804.169	64.54	4.36	32.92	45.53	56.29	74.00	-17.71	Pk	Horizontal
4804.169	42.82	4.36	32.92	45.53	34.57	54.00	-19.43	AV	Horizontal
7206.214	61.43	5.02	37.63	45.56	58.52	74.00	-15.48	Pk	Horizontal
7206.214	40.85	5.02	37.63	45.56	37.94	54.00	-16.06	AV	Horizontal

Mid Channel (2440 MHz)-Above 1G

4880.473	64.19	4.41	33.01	45.76	55.85	74.00	-18.15	Pk	Vertical
4880.473	42.69	4.41	33.01	45.76	34.35	54.00	-19.65	AV	Vertical
7320.265	64.30	5.02	37.68	45.59	61.41	74.00	-12.59	Pk	Vertical
7320.265	40.91	5.02	37.68	45.59	38.02	54.00	-15.98	AV	Vertical
4880.366	62.96	4.41	33.01	45.76	54.62	74.00	-19.38	Pk	Horizontal
4880.366	40.15	4.41	33.01	45.76	31.81	54.00	-22.19	AV	Horizontal
7320.234	60.06	5.02	37.68	45.59	57.17	74.00	-16.83	Pk	Horizontal
7320.234	43.78	5.02	37.68	45.59	40.89	54.00	-13.11	AV	Horizontal

High Channel (2480 MHz)- Above 1G

4960.482	63.62	4.50	33.26	46.07	55.31	74.00	-18.69	Pk	Vertical
4960.482	42.10	4.50	33.26	46.07	33.79	54.00	-20.21	AV	Vertical
7440.131	63.70	5.02	37.78	45.77	60.73	74.00	-13.27	Pk	Vertical
7440.131	49.71	5.02	37.78	45.77	46.74	54.00	-7.26	AV	Vertical
4960.326	64.33	4.50	33.26	46.07	56.02	74.00	-17.98	Pk	Horizontal
4960.326	44.36	4.50	33.26	46.07	36.05	54.00	-17.95	AV	Horizontal
7440.199	65.23	5.02	37.78	45.77	62.26	74.00	-11.74	Pk	Horizontal
7440.199	45.37	5.02	37.78	45.77	42.40	54.00	-11.60	AV	Horizontal



5.4.4.1 Band edge-radiated

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(3) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
GFSK									
2310.00	63.01	2.40	27.70	40.40	52.71	74	-21.29	Pk	Horizontal
2310.00	43.83	2.40	27.70	40.40	33.53	54	-20.47	AV	Horizontal
2310.00	61.87	2.40	27.70	40.40	51.57	74	-22.43	Pk	Vertical
2310.00	42.26	2.40	27.70	40.40	31.96	54	-22.04	AV	Vertical
2390.00	64.67	2.44	28.30	40.10	55.31	74	-18.69	Pk	Vertical
2390.00	44.08	2.44	28.30	40.10	34.72	54	-19.28	AV	Vertical
2390.00	63.24	2.44	28.30	40.10	53.88	74	-20.12	Pk	Horizontal
2390.00	41.73	2.44	28.30	40.10	32.37	54	-21.63	AV	Horizontal
2483.50	63.17	2.48	28.70	39.80	54.55	74	-19.45	Pk	Vertical
2483.50	43.75	2.48	28.70	39.80	35.13	54	-18.87	AV	Vertical
2483.50	65.60	2.48	28.70	39.80	56.98	74	-17.02	Pk	Horizontal
2483.50	44.17	2.48	28.70	39.80	35.55	54	-18.45	AV	Horizontal



5.4.4.2 Spurious Emission in Restricted Band 3260MHz-18000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
3260	61.37	3.27	30.02	38.05	56.61	74	-17.39	Pk	Vertical
3260	40.95	3.27	30.02	38.05	36.19	54	-17.81	AV	Vertical
3260	64.40	3.27	30.02	38.05	59.64	74	-14.36	Pk	Horizontal
3260	43.01	3.27	30.02	38.05	38.25	54	-15.75	AV	Horizontal
3332	63.77	3.31	30.00	37.91	59.17	74	-14.83	Pk	Vertical
3332	42.33	3.31	30.00	37.91	37.73	54	-16.27	AV	Vertical
3332	64.04	3.31	30.00	37.91	59.44	74	-14.56	Pk	Horizontal
3332	42.01	3.31	30.00	37.91	37.41	54	-16.59	AV	Horizontal
17797	43.56	8.63	44.23	39.60	56.82	74	-17.18	Pk	Vertical
17797	30.50	8.63	44.23	39.60	43.76	54	-10.24	AV	Vertical
17788	43.35	8.63	44.23	39.60	56.61	74	-17.39	Pk	Horizontal
17788	30.73	8.63	44.23	39.60	43.99	54	-10.01	AV	Horizontal



5.5 Power spectral density test

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.5.2 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW \geq 3 kHz.
4. Set the VBW \geq 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test Setup



5.5.4 EUT Operation Conditions


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.





5.5.5 Test Results

EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1015 hPa	Test Voltage:	DC 7.4V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-20.762	8	PASS
2440 MHz	-21.648	8	PASS
2480 MHz	-21.705	8	PASS





5.6 6dB bandwidth

5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	>= 500kHz (6dB bandwidth)	2400-2483.5

5.6.2 Test Procedure

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Test Setup



5.6.4 EUT Operation Conditions

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.6.5 Test Result

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>


E-mail: mti@51mti.com

Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China



EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1012 hPa	Test Voltage:	DC 7.4V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	515.7	500	Pass
Middle	2440	532.2	500	Pass
High	2480	532.4	500	Pass





5.7 Duty Cycle


5.7.1 Conformance Limit

No limit requirement.

5.7.2 Measuring Instruments

The Measuring equipment is listed in the section 4 of this test report.

5.7.3 Test Setup



5.7.4 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz (the largest available value)

VBW = 8MHz (\geq RBW)

Number of points in Sweep > 100

Detector function = peak

Trace = Clear write


Measure Ttotal and Ton


Calculate Duty Cycle = Ton / Ttotal



5.7.5 Test Results

EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1012 hPa	Test Voltage:	DC 7.4V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		







5.8 Conducted band edge

5.8.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2 Test Setup



5.8.3 Test Procedure

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

5.8.4 EUT Operation Conditions


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.8.5 Test Result




EUT:	A4 Mobile Printer	Model Name:	MT800
Pressure:	1012 hPa	Test Voltage:	DC 7.4V from battery
Test Mode:	TX Mode /CH00, CH39		

BLE: Band Edge, Left Side



BLE: Band Edge, Right Side





5.9 Spurious RF Conducted Emissions

5.9.1 Conformance Limit

Below -20dB of the highest emission level in operating band.

5.9.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

5.9.3 Test Setup


Please refer to Section 6.1 of this test report.


5.9.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.9.5 Test Results

Remark: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.








Photographs of the Test Setup

Radiated emission





Conducted emission





Photographs of the EUT

See the APPENDIX 1: EUT PHOTO in the report No.: MTi19091603-9E1-1.

----END OF REPORT----