



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

CERTIFICATION TEST REPORT

For

WIFI+BT Module

MODEL NUMBER: DCT2UM1111

FCC ID:2AC23-DCT2U

IC:12290A-DCT2U

REPORT NUMBER: 4790191813.2-1

ISSUE DATE: March 7, 2022

Prepared for

**Hui Zhou Gaoshengda Technology Co.,LTD
NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	3/7/2022	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d)	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test for AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass
<p>Note:</p> <p>1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.</p>			



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM PEAK OUTPUT POWER	9
5.4. TEST CHANNEL CONFIGURATION	9
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	10
5.7. WORST-CASE CONFIGURATIONS	10
5.8. DESCRIPTION OF TEST SETUP	11
6. MEASURING INSTRUMENT AND SOFTWARE USED	12
7. ANTENNA PORT TEST RESULTS	14
7.1. ON TIME AND DUTY CYCLE	14
7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	15
7.3. CONDUCTED OUTPUT POWER	17
7.4. POWER SPECTRAL DENSITY	18
7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS	20
8. RADIATED TEST RESULTS	22
8.1. RESTRICTED BANDEDGE	28
8.1.1. LE 1M MODE - FPC ANTENNA	28
8.1.2. LE 2M MODE - FPC ANTENNA	31
8.1.3. LE 1M MODE - PIFA ANTENNA	34
8.1.4. LE 2M MODE - PIFA ANTENNA	38
8.1.5. LE 1M MODE - PCB ANTENNA	41
8.1.6. LE 2M MODE - PCB ANTENNA	44
8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)	46
8.2.1. LE 1M MODE- FPC ANTENNA	46
8.2.2. LE 1M MODE- PIFA ANTENNA	52
8.2.1. LE 1M MODE- PCB ANTENNA	58
8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)	64



8.3.1.	LE 1M MODE- FPC ANTENNA	64
8.3.2.	LE 2M MODE- FPC ANTENNA	70
8.3.3.	LE 1M MODE- PIFA ANTENNA.....	76
8.3.4.	LE 2M MODE- PIFA ANTENNA.....	82
8.3.1.	LE 1M MODE- PCB ANTENNA	88
8.3.2.	LE 2M MODE- PCB ANTENNA	94
8.4.	<i>SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)</i>	100
8.4.1.	LE 2M MODE- PCB ANTENNA	100
8.5.	<i>SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)</i>	102
8.5.1.	LE 2M MODE- PCB ANTENNA	102
8.6.	<i>SPURIOUS EMISSIONS BELOW 30 MHz</i>	104
8.6.1.	LE 2M MODE- PCB ANTENNA	104
9.	AC POWER LINE CONDUCTED EMISSIONS	107
9.1.	LE 2M MODE- FPC ANTENNA.....	108
10.	ANTENNA REQUIREMENTS	110
11.	Appendix.....	111
11.1.	<i>Appendix A: DTS Bandwidth</i>	111
11.1.1.	Test Result.....	111
11.1.2.	Test Graphs	112
11.2.	<i>Appendix B: Occupied Channel Bandwidth</i>	114
11.2.1.	Test Result.....	114
11.2.2.	Test Graphs	115
11.3.	<i>Appendix C: Maximum conducted output power</i>	117
11.3.1.	Test Result.....	117
11.4.	<i>Appendix D: Maximum power spectral density</i>	118
11.4.1.	Test Result.....	118
11.4.2.	Test Graphs	119
11.5.	<i>Appendix E: Band edge measurements</i>	121
11.5.1.	Test Result.....	121
11.5.2.	Test Graphs	122
11.6.	<i>Appendix F: Conducted Spurious Emission</i>	124
11.6.1.	Test Result.....	124
11.6.2.	Test Graphs	125
11.7.	<i>Appendix G: Duty Cycle</i>	131
11.7.1.	Test Result.....	131
11.7.2.	Test Graphs	132



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
Address: NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China

Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
Address: NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China

EUT Information

EUT Name: WIFI+BT Module
Model: DCT2UM1111
Brand: GSD
Sample Received Date: December 30, 2021
Sample Status: Normal
Sample ID: 4540907
Date of Tested: December 30, 2021 ~ March 6, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Kebo Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	WIFI+BT Module	
Model Name	DCT2UM1111	
Product Description	Operation Frequency	2402 MHz ~ 2480 MHz
	Modulation Type	Data Rate
	GFSK	1Mbps
	GFSK	2Mbps
Rated Input	DC 5 V	

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

5.3. MAXIMUM PEAK OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
LE 1M	2402 ~ 2480	0-39[40]	8.19	11.19
LE 2M	2402 ~ 2480	0-39[40]	8.39	11.39

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		WCN_Combo_Tool		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	default	default	default
GFSK(2Mbps)	1	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PCB	3

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	FPC	2.77

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PIFA	2.88

The EUT have three kinds of antennas, they are PCB antenna, FPC antenna, and PIFA antenna.

Test Mode	Transmit and Receive Mode	Description
GFSK(1Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.
GFSK(2Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.
Note: The value of the antenna gain was declared by customer.		

5.7. WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BLE	DTS	GFSK(1Mbps)	1Mbit/s
BLE	DTS	GFSK(2Mbps)	2Mbit/s

Note:

The EUT have three kinds of antennas, they are PCB antenna, FPC antenna, and PIFA antenna. For the conducted testing, only the maximum antenna gain data are recorded in this report. For the radiated testing, three kinds of antenna gain data are recorded in this report.

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	T430	/
2	UART	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	N/A	N/A	1	N/A


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



Note: AC adapter only use for AC POWER LINE CONDUCTED EMISSIONS testing.



6. MEASURING INSTRUMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.23,2021	Mar.22,2022
Vector Signal Generator	R&S	SMBV100A	261637	Oct.30, 2021	Oct.29, 2022
Signal Generator	R&S	SMB100A	178553	Oct.30, 2021	Oct.29, 2022
Signal Analyzer	R&S	FSV40	101118	Oct.30, 2021	Oct.29, 2022
Software					
Description	Manufacturer		Name		Version
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32		10.60.10
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.30, 2021	Oct.29, 2022
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.29, 2021	Sep.28, 2022
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.30, 2021	Oct.29, 2022
DC power supply	Keysight	E3642A	MY55159130	Oct.30, 2021	Oct.29, 2022
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2022
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	



Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.30, 2021	Oct.29, 2022
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.30, 2021	Oct.29, 2022
EMI Measurement Receiver	R&S	ESR26	101377	Oct.30, 2021	Oct.29, 2022
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.30, 2021	Oct.29, 2022
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.31, 2021	Oct.30, 2022
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.31, 2021	Oct.30, 2022
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13,2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.31, 2021	Oct.30, 2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Oct.31, 2021	Oct.30, 2022
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.31, 2021	Oct.30, 2022
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1



7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	46 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to appendix G.

7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



**TEST ENVIRONMENT**

Temperature	24.5 °C	Relative Humidity	46 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to appendix A & B.



7.3. CONDUCTED OUTPUT POWER


LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conducted Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).
Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	46 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to appendix C.

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	46 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V



RESULTS

Please refer to appendix D.



7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.



TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	46 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to appendix E & F.



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.028	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5490	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	22.3 °C	Relative Humidity	65 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS




8.1. RESTRICTED BANDEDGE

8.1.1. LE 1M MODE - FPC ANTENNA

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	15.87	32.66	48.53	74.00	-25.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	24.38	33.10	57.48	74.00	-16.52	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	5.37	33.10	38.47	54.00	-15.53	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

8.1.2. LE 2M MODE - FPC ANTENNA

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	15.21	32.66	47.87	74.00	-26.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	24.19	33.10	57.29	74.00	-16.71	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	10.78	33.10	43.88	54.00	-10.12	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

8.1.3. LE 1M MODE - PIFA ANTENNA

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	14.05	32.66	46.71	74.00	-27.29	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	16.72	32.66	49.38	74.00	-24.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.32	33.10	54.42	74.00	-19.58	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	5.18	33.10	38.28	54.00	-15.72	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.



8.1.4. LE 2M MODE - PIFA ANTENNA


RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	16.28	32.66	48.94	74.00	-25.06	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.26	33.10	55.36	74.00	-18.64	peak
2	2484.820	22.67	33.10	55.77	74.00	-18.23	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	10.48	33.10	43.58	54.00	-10.42	AVG
2	2484.820	6.08	33.10	39.18	54.00	-14.82	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

8.1.5. LE 1M MODE - PCB ANTENNA


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	14.98	32.66	47.64	74.00	-26.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	14.22	32.66	46.88	74.00	-27.12	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGHT CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.34	33.10	51.44	74.00	-22.56	peak
2	2483.740	18.83	33.10	51.93	74.00	-22.07	peak


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

8.1.6. LE 2M MODE - PCB ANTENNA


RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.71	32.66	46.37	74.00	-27.63	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGHT CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.86	33.10	51.96	74.00	-22.04	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. LE 1M MODE- FPC ANTENNA

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1119.000	50.02	-14.26	35.76	74.00	-38.24	peak
2	1590.000	45.60	-11.90	33.70	74.00	-40.30	peak
3	1920.000	55.22	-10.81	44.41	74.00	-29.59	peak
4	2151.000	46.77	-10.01	36.76	74.00	-37.24	peak
5	2402.000	54.04	-8.94	45.10	/	/	Fundamental
6	2669.000	45.29	-8.26	37.03	74.00	-36.97	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1220.000	48.27	-13.64	34.63	74.00	-39.37	peak
2	1732.000	45.16	-11.01	34.15	74.00	-39.85	peak
3	1920.000	50.97	-10.81	40.16	74.00	-33.84	peak
4	2150.000	46.67	-10.02	36.65	74.00	-37.35	peak
5	2402.000	54.02	-8.94	45.08	/	/	Fundamental
6	2795.000	44.25	-7.69	36.56	74.00	-37.44	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1205.000	49.31	-13.69	35.62	74.00	-38.38	peak
2	1586.000	45.34	-11.92	33.42	74.00	-40.58	peak
3	1920.000	55.32	-10.81	44.51	74.00	-29.49	peak
4	2150.000	46.08	-10.02	36.06	74.00	-37.94	peak
5	2440.000	53.23	-8.86	44.37	/	/	Fundamental
6	2688.000	44.72	-8.17	36.55	74.00	-37.45	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1138.000	49.95	-14.13	35.82	74.00	-38.18	peak
2	1589.000	45.59	-11.91	33.68	74.00	-40.32	peak
3	1920.000	50.77	-10.81	39.96	74.00	-34.04	peak
4	2158.000	46.30	-9.97	36.33	74.00	-37.67	peak
5	2440.000	60.49	-8.86	51.63	/	/	Fundamental
6	2582.000	45.14	-8.59	36.55	74.00	-37.45	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1055.000	50.48	-14.69	35.79	74.00	-38.21	peak
2	1206.000	48.68	-13.69	34.99	74.00	-39.01	peak
3	1664.000	45.57	-11.45	34.12	74.00	-39.88	peak
4	1920.000	54.88	-10.81	44.07	74.00	-29.93	peak
5	2157.000	46.61	-9.98	36.63	74.00	-37.37	peak
6	2480.000	54.61	-8.76	45.85	/	/	Fundamental

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1138.000	48.91	-14.13	34.78	74.00	-39.22	peak
2	1745.000	45.39	-10.93	34.46	74.00	-39.54	peak
3	1920.000	50.66	-10.81	39.85	74.00	-34.15	peak
4	2154.000	47.72	-10.00	37.72	74.00	-36.28	peak
5	2480.000	57.90	-8.76	49.14	/	/	Fundamental
6	2789.000	43.82	-7.72	36.10	74.00	-37.90	peak


Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels had been tested, but only the worst data was recorded in the report.

8.2.2. LE 1M MODE- PIFA ANTENNA

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1056.000	49.33	-14.68	34.65	74.00	-39.35	peak
2	1195.000	49.02	-13.75	35.27	74.00	-38.73	peak
3	1591.000	45.41	-11.90	33.51	74.00	-40.49	peak
4	1920.000	55.26	-10.81	44.45	74.00	-29.55	peak
5	2151.000	46.30	-10.01	36.29	74.00	-37.71	peak
6	2402.000	54.84	-8.94	45.90	/	/	Fundamental

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1190.000	47.87	-13.77	34.10	74.00	-39.90	peak
2	1920.000	52.82	-10.81	42.01	74.00	-31.99	peak
3	2152.000	47.01	-10.00	37.01	74.00	-36.99	peak
4	2402.000	56.16	-8.94	47.22	/	/	Fundamental
5	2562.000	46.29	-8.63	37.66	74.00	-36.34	peak
6	2646.000	46.03	-8.37	37.66	74.00	-36.34	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1222.000	49.13	-13.64	35.49	74.00	-38.51	peak
2	1636.000	45.74	-11.62	34.12	74.00	-39.88	peak
3	1920.000	54.94	-10.81	44.13	74.00	-29.87	peak
4	2157.000	46.32	-9.98	36.34	74.00	-37.66	peak
5	2440.000	53.60	-8.85	44.75	/	/	Fundamental
6	2673.000	44.97	-8.24	36.73	74.00	-37.27	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1222.000	49.55	-13.64	35.91	74.00	-38.09	peak
2	1593.000	46.06	-11.89	34.17	74.00	-39.83	peak
3	1920.000	55.37	-10.81	44.56	74.00	-29.44	peak
4	2158.000	45.81	-9.97	35.84	74.00	-38.16	peak
5	2480.000	52.86	-8.76	44.10	/	/	Fundamental
6	2725.000	44.28	-8.01	36.27	74.00	-37.73	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes, channels and antenna had been tested, but only the worst data was recorded in the report.

8.2.1. LE 1M MODE- PCB ANTENNA

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	49.81	-13.71	36.10	74.00	-37.90	peak
2	1440.000	47.50	-12.79	34.71	74.00	-39.29	peak
3	1920.000	53.47	-10.81	42.66	74.00	-31.34	peak
4	2158.000	47.01	-9.97	37.04	74.00	-36.96	peak
5	2402.000	46.58	-8.94	37.64	/	/	Fundamental
6	2840.000	43.71	-7.56	36.15	74.00	-37.85	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1198.000	49.89	-13.73	36.16	74.00	-37.84	peak
2	1436.000	47.01	-12.83	34.18	74.00	-39.82	peak
3	1920.000	55.40	-10.81	44.59	74.00	-29.41	peak
4	2156.000	46.05	-9.98	36.07	74.00	-37.93	peak
5	2402.000	48.20	-8.94	39.26	/	/	Fundamental
6	2792.000	44.01	-7.71	36.30	74.00	-37.70	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1006.000	49.75	-15.02	34.73	74.00	-39.27	peak
2	1198.000	49.33	-13.73	35.60	74.00	-38.40	peak
3	1438.000	47.17	-12.81	34.36	74.00	-39.64	peak
4	1920.000	53.59	-10.81	42.78	74.00	-31.22	peak
5	2158.000	47.05	-9.97	37.08	74.00	-36.92	peak
6	2440.000	46.51	-8.86	37.65	/	/	Fundamental

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	49.85	-13.71	36.14	74.00	-37.86	peak
2	1438.000	47.61	-12.81	34.80	74.00	-39.20	peak
3	1806.000	45.47	-10.60	34.87	74.00	-39.13	peak
4	1920.000	55.32	-10.81	44.51	74.00	-29.49	peak
5	2158.000	46.48	-9.97	36.51	74.00	-37.49	peak
6	2440.000	48.87	-8.86	40.01	/	/	Fundamental

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1196.000	49.36	-13.73	35.63	74.00	-38.37	peak
2	1436.000	48.45	-12.83	35.62	74.00	-38.38	peak
3	1920.000	53.41	-10.81	42.60	74.00	-31.40	peak
4	2158.000	47.16	-9.97	37.19	74.00	-36.81	peak
5	2480.000	46.27	-8.76	37.51	/	/	Fundamental
6	2728.000	44.25	-7.99	36.26	74.00	-37.74	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1194.000	49.99	-13.75	36.24	74.00	-37.76	peak
2	1436.000	47.33	-12.83	34.50	74.00	-39.50	peak
3	1726.000	45.87	-11.05	34.82	74.00	-39.18	peak
4	1920.000	55.44	-10.81	44.63	74.00	-29.37	peak
5	2480.000	50.09	-8.76	41.33	/	/	Fundamental
6	2564.000	45.31	-8.62	36.69	74.00	-37.31	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes, channels and antenna had been tested, but only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. LE 1M MODE- FPC ANTENNA


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	39.55	4.89	44.44	74.00	-29.56	peak
2	9585.000	37.27	10.60	47.87	74.00	-26.13	peak
3	11370.000	37.29	15.46	52.75	74.00	-21.25	peak
4	11842.500	35.87	17.00	52.87	74.00	-21.13	peak
5	13627.500	32.38	20.57	52.95	74.00	-21.05	peak
6	17100.000	31.29	20.82	52.11	74.00	-21.89	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5677.500	40.53	1.27	41.80	74.00	-32.20	peak
2	8265.000	38.37	7.65	46.02	74.00	-27.98	peak
3	9585.000	37.37	10.60	47.97	74.00	-26.03	peak
4	12690.000	35.77	17.21	52.98	74.00	-21.02	peak
5	14385.000	32.98	19.66	52.64	74.00	-21.36	peak
6	17940.000	27.84	24.89	52.73	74.00	-21.27	peak


Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5857.500	39.28	2.22	41.50	74.00	-32.50	peak
2	6510.000	38.54	4.89	43.43	74.00	-30.57	peak
3	9405.000	37.19	10.33	47.52	74.00	-26.48	peak
4	11355.000	37.07	15.27	52.34	74.00	-21.66	peak
5	13635.000	32.44	20.61	53.05	74.00	-20.95	peak
6	17377.500	30.77	21.47	52.24	74.00	-21.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5670.000	40.31	1.27	41.58	74.00	-32.42	peak
2	7815.000	38.46	7.10	45.56	74.00	-28.44	peak
3	9367.500	37.83	10.12	47.95	74.00	-26.05	peak
4	11685.000	35.78	16.76	52.54	74.00	-21.46	peak
5	13920.000	32.10	21.24	53.34	74.00	-20.66	peak
6	17940.000	27.67	24.89	52.56	74.00	-21.44	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5917.500	39.51	2.52	42.03	74.00	-31.97	peak
2	6510.000	38.60	4.89	43.49	74.00	-30.51	peak
3	9592.500	36.91	10.63	47.54	74.00	-26.46	peak
4	11707.500	35.70	16.87	52.57	74.00	-21.43	peak
5	13530.000	32.59	20.39	52.98	74.00	-21.02	peak
6	17640.000	30.36	23.08	53.44	74.00	-20.56	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5857.500	39.90	2.22	42.12	74.00	-31.88	peak
2	8122.500	38.11	7.89	46.00	74.00	-28.00	peak
3	9367.500	37.47	10.12	47.59	74.00	-26.41	peak
4	12750.000	35.39	17.42	52.81	74.00	-21.19	peak
5	13920.000	30.75	21.24	51.99	74.00	-22.01	peak
6	16882.500	31.87	20.03	51.90	74.00	-22.10	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.2. LE 2M MODE- FPC ANTENNA


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	41.58	-0.77	40.81	74.00	-33.19	peak
2	6510.000	38.16	4.89	43.05	74.00	-30.95	peak
3	8977.500	37.22	9.71	46.93	74.00	-27.07	peak
4	11947.500	35.48	17.28	52.76	74.00	-21.24	peak
5	13605.000	32.53	20.42	52.95	74.00	-21.05	peak
6	17242.500	30.95	21.45	52.40	74.00	-21.60	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	41.69	-0.77	40.92	74.00	-33.08	peak
2	7890.000	39.33	6.67	46.00	74.00	-28.00	peak
3	9135.000	38.34	9.13	47.47	74.00	-26.53	peak
4	11677.500	35.89	16.71	52.60	74.00	-21.40	peak
5	14475.000	33.81	19.04	52.85	74.00	-21.15	peak
6	17865.000	27.79	24.59	52.38	74.00	-21.62	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4582.500	42.47	-1.26	41.21	74.00	-32.79	peak
2	6510.000	38.43	4.89	43.32	74.00	-30.68	peak
3	9352.500	37.41	10.01	47.42	74.00	-26.58	peak
4	11805.000	36.05	16.87	52.92	74.00	-21.08	peak
5	14820.000	33.57	18.30	51.87	74.00	-22.13	peak
6	17385.000	30.85	21.43	52.28	74.00	-21.72	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	42.00	-0.77	41.23	74.00	-32.77	peak
2	7717.500	39.20	6.50	45.70	74.00	-28.30	peak
3	8985.000	37.70	9.86	47.56	74.00	-26.44	peak
4	11685.000	35.82	16.76	52.58	74.00	-21.42	peak
5	14070.000	31.71	21.01	52.72	74.00	-21.28	peak
6	17910.000	27.39	24.70	52.09	74.00	-21.91	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5872.500	39.40	2.36	41.76	74.00	-32.24	peak
2	8152.500	38.23	7.82	46.05	74.00	-27.95	peak
3	9435.000	37.62	10.23	47.85	74.00	-26.15	peak
4	11797.500	36.02	16.86	52.88	74.00	-21.12	peak
5	13987.500	31.74	21.42	53.16	74.00	-20.84	peak
6	17947.500	28.39	24.95	53.34	74.00	-20.66	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5917.500	38.93	2.52	41.45	74.00	-32.55	peak
2	7875.000	38.92	6.75	45.67	74.00	-28.33	peak
3	9390.000	37.12	10.27	47.39	74.00	-26.61	peak
4	11812.500	35.73	16.89	52.62	74.00	-21.38	peak
5	14062.500	32.31	21.07	53.38	74.00	-20.62	peak
6	16905.000	32.14	20.19	52.33	74.00	-21.67	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.3. LE 1M MODE- PIFA ANTENNA


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	42.91	-0.33	42.58	74.00	-31.42	peak
2	8220.000	38.50	7.67	46.17	74.00	-27.83	peak
3	9570.000	36.87	10.49	47.36	74.00	-26.64	peak
4	11670.000	36.45	16.66	53.11	74.00	-20.89	peak
5	13605.000	32.75	20.42	53.17	74.00	-20.83	peak
6	17940.000	29.13	24.89	54.02	74.00	-19.98	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	44.03	-0.33	43.70	74.00	-30.30	peak
2	8242.500	37.95	7.67	45.62	74.00	-28.38	peak
3	9247.500	38.14	9.34	47.48	74.00	-26.52	peak
4	11730.000	35.65	16.86	52.51	74.00	-21.49	peak
5	13957.500	31.82	21.35	53.17	74.00	-20.83	peak
6	16822.500	33.35	19.46	52.81	74.00	-21.19	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	37.57	4.89	42.46	74.00	-31.54	peak
2	7710.000	38.78	6.44	45.22	74.00	-28.78	peak
3	9397.500	36.90	10.33	47.23	74.00	-26.77	peak
4	11827.500	35.43	16.95	52.38	74.00	-21.62	peak
5	13942.500	31.76	21.30	53.06	74.00	-20.94	peak
6	17992.500	27.17	25.23	52.40	74.00	-21.60	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.88	-0.52	42.36	74.00	-31.64	peak
2	8242.500	38.45	7.67	46.12	74.00	-27.88	peak
3	9367.500	37.15	10.12	47.27	74.00	-26.73	peak
4	11820.000	36.45	16.92	53.37	74.00	-20.63	peak
5	13612.500	33.12	20.47	53.59	74.00	-20.41	peak
6	17775.000	27.89	24.31	52.20	74.00	-21.80	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	41.83	-0.49	41.34	74.00	-32.66	peak
2	6510.000	38.31	4.89	43.20	74.00	-30.80	peak
3	9030.000	37.23	9.87	47.10	74.00	-26.90	peak
4	11940.000	34.98	17.27	52.25	74.00	-21.75	peak
5	13470.000	32.94	20.24	53.18	74.00	-20.82	peak
6	17580.000	30.14	22.48	52.62	74.00	-21.38	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5880.000	38.73	2.43	41.16	74.00	-32.84	peak
2	6510.000	38.03	4.89	42.92	74.00	-31.08	peak
3	8977.500	37.26	9.71	46.97	74.00	-27.03	peak
4	12375.000	35.54	17.53	53.07	74.00	-20.93	peak
5	13537.500	32.74	20.39	53.13	74.00	-20.87	peak
6	17940.000	27.97	24.89	52.86	74.00	-21.14	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.4. LE 2M MODE- PIFA ANTENNA


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	42.66	-0.33	42.33	74.00	-31.67	peak
2	6510.000	38.76	4.89	43.65	74.00	-30.35	peak
3	9345.000	38.24	9.96	48.20	74.00	-25.80	peak
4	11805.000	35.74	16.87	52.61	74.00	-21.39	peak
5	13920.000	31.92	21.24	53.16	74.00	-20.84	peak
6	17587.500	29.63	22.54	52.17	74.00	-21.83	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.21	-0.33	42.88	74.00	-31.12	peak
2	6510.000	38.87	4.89	43.76	74.00	-30.24	peak
3	9022.500	37.47	9.94	47.41	74.00	-26.59	peak
4	11820.000	35.92	16.92	52.84	74.00	-21.16	peak
5	13972.500	31.04	21.38	52.42	74.00	-21.58	peak
6	18000.000	26.96	25.28	52.24	74.00	-21.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	37.44	4.89	42.33	74.00	-31.67	peak
2	7882.500	38.83	6.72	45.55	74.00	-28.45	peak
3	9585.000	36.88	10.60	47.48	74.00	-26.52	peak
4	11722.500	35.74	16.87	52.61	74.00	-21.39	peak
5	13620.000	32.84	20.51	53.35	74.00	-20.65	peak
6	17932.500	27.35	24.84	52.19	74.00	-21.81	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.49	-0.52	41.97	74.00	-32.03	peak
2	6510.000	38.60	4.89	43.49	74.00	-30.51	peak
3	9352.500	37.49	10.01	47.50	74.00	-26.50	peak
4	11947.500	34.56	17.28	51.84	74.00	-22.16	peak
5	14077.500	32.18	20.97	53.15	74.00	-20.85	peak
6	16890.000	32.32	20.10	52.42	74.00	-21.58	peak


Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5857.500	39.29	2.22	41.51	74.00	-32.49	peak
2	8160.000	38.29	7.80	46.09	74.00	-27.91	peak
3	9322.500	37.94	9.81	47.75	74.00	-26.25	peak
4	12412.500	35.12	17.44	52.56	74.00	-21.44	peak
5	14490.000	33.93	18.95	52.88	74.00	-21.12	peak
6	17940.000	27.76	24.89	52.65	74.00	-21.35	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5520.000	40.00	1.55	41.55	74.00	-32.45	peak
2	6510.000	38.74	4.89	43.63	74.00	-30.37	peak
3	9345.000	37.32	9.96	47.28	74.00	-26.72	peak
4	11707.500	35.89	16.87	52.76	74.00	-21.24	peak
5	12630.000	35.62	17.27	52.89	74.00	-21.11	peak
6	17992.500	26.62	25.23	51.85	74.00	-22.15	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.1. LE 1M MODE- PCB ANTENNA


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5925.000	39.29	2.48	41.77	74.00	-32.23	peak
2	6510.000	40.19	4.89	45.08	74.00	-28.92	peak
3	8985.000	36.82	9.86	46.68	74.00	-27.32	peak
4	11715.000	35.64	16.87	52.51	74.00	-21.49	peak
5	13590.000	33.26	20.39	53.65	74.00	-20.35	peak
6	17685.000	29.11	23.53	52.64	74.00	-21.36	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5880.000	39.65	2.43	42.08	74.00	-31.92	peak
2	6510.000	38.09	4.89	42.98	74.00	-31.02	peak
3	8970.000	37.47	9.55	47.02	74.00	-26.98	peak
4	11820.000	35.84	16.92	52.76	74.00	-21.24	peak
5	13980.000	31.19	21.41	52.60	74.00	-21.40	peak
6	17640.000	28.87	23.08	51.95	74.00	-22.05	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4575.000	42.27	-1.30	40.97	74.00	-33.03	peak
2	6510.000	39.91	4.89	44.80	74.00	-29.20	peak
3	8115.000	37.88	7.92	45.80	74.00	-28.20	peak
4	12375.000	34.20	17.53	51.73	74.00	-22.27	peak
5	13950.000	31.68	21.33	53.01	74.00	-20.99	peak
6	17370.000	30.72	21.52	52.24	74.00	-21.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.500	40.50	0.68	41.18	74.00	-32.82	peak
2	8287.500	37.45	6.97	44.42	74.00	-29.58	peak
3	9412.500	37.56	9.71	47.27	74.00	-26.73	peak
4	11782.500	35.83	17.11	52.94	74.00	-21.06	peak
5	13635.000	32.52	19.86	52.38	74.00	-21.62	peak
6	18000.000	28.94	23.68	52.62	74.00	-21.38	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	41.57	-1.33	40.24	74.00	-33.76	peak
2	6510.000	40.24	3.17	43.41	74.00	-30.59	peak
3	9195.000	38.52	8.45	46.97	74.00	-27.03	peak
4	11827.500	35.40	17.20	52.60	74.00	-21.40	peak
5	13590.000	32.82	19.70	52.52	74.00	-21.48	peak
6	17295.000	32.17	20.18	52.35	74.00	-21.65	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	41.68	-1.72	39.96	74.00	-34.04	peak
2	8220.000	37.64	7.17	44.81	74.00	-29.19	peak
3	8970.000	37.56	9.17	46.73	74.00	-27.27	peak
4	11700.000	36.60	16.58	53.18	74.00	-20.82	peak
5	13807.500	32.15	20.51	52.66	74.00	-21.34	peak
6	17940.000	28.56	23.54	52.10	74.00	-21.90	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


8.3.2. LE 2M MODE- PCB ANTENNA

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	41.24	-1.13	40.11	74.00	-33.89	peak
2	6510.000	38.09	3.17	41.26	74.00	-32.74	peak
3	8985.000	37.26	9.34	46.60	74.00	-27.40	peak
4	11820.000	35.87	17.21	53.08	74.00	-20.92	peak
5	14475.000	34.48	18.50	52.98	74.00	-21.02	peak
6	17850.000	28.96	23.32	52.28	74.00	-21.72	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	41.24	-1.13	40.11	74.00	-33.89	peak
2	6510.000	38.09	3.17	41.26	74.00	-32.74	peak
3	8985.000	37.26	9.34	46.60	74.00	-27.40	peak
4	11820.000	35.87	17.21	53.08	74.00	-20.92	peak
5	14475.000	34.48	18.50	52.98	74.00	-21.02	peak
6	17850.000	28.96	23.32	52.28	74.00	-21.72	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4680.000	41.69	-1.65	40.04	74.00	-33.96	peak
2	6510.000	42.16	3.17	45.33	74.00	-28.67	peak
3	7725.000	39.32	5.84	45.16	74.00	-28.84	peak
4	11805.000	35.50	17.21	52.71	74.00	-21.29	peak
5	13950.000	32.17	20.61	52.78	74.00	-21.22	peak
6	17490.000	31.11	20.47	51.58	74.00	-22.42	peak


Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5670.000	39.50	0.68	40.18	74.00	-33.82	peak
2	6510.000	38.23	3.17	41.40	74.00	-32.60	peak
3	9435.000	37.95	9.78	47.73	74.00	-26.27	peak
4	11820.000	35.52	17.21	52.73	74.00	-21.27	peak
5	13605.000	32.67	19.74	52.41	74.00	-21.59	peak
6	17700.000	29.63	22.15	51.78	74.00	-22.22	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5655.000	39.12	0.69	39.81	74.00	-34.19	peak
2	6510.000	41.88	3.17	45.05	74.00	-28.95	peak
3	9060.000	37.43	9.20	46.63	74.00	-27.37	peak
4	11835.000	35.43	17.20	52.63	74.00	-21.37	peak
5	14070.000	32.26	20.29	52.55	74.00	-21.45	peak
6	17940.000	29.02	23.54	52.56	74.00	-21.44	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	38.70	3.17	41.87	74.00	-32.13	peak
2	7890.000	38.96	5.75	44.71	74.00	-29.29	peak
3	8955.000	37.50	8.99	46.49	74.00	-27.51	peak
4	11835.000	34.92	17.20	52.12	74.00	-21.88	peak
5	13665.000	32.40	19.97	52.37	74.00	-21.63	peak
6	17235.000	31.10	20.17	51.27	74.00	-22.73	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

8.4.1. LE 2M MODE- PCB ANTENNA

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18416.000	50.23	-5.35	44.88	74.00	-29.12	peak
2	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
3	20312.000	51.02	-5.56	45.46	74.00	-28.54	peak
4	21248.000	49.79	-4.77	45.02	74.00	-28.98	peak
5	23064.000	48.49	-3.42	45.07	74.00	-28.93	peak
6	25072.000	46.67	-1.97	44.70	74.00	-29.30	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18152.000	51.26	-5.48	45.78	74.00	-28.22	peak
2	18712.000	51.40	-5.40	46.00	74.00	-28.00	peak
3	20176.000	52.21	-5.56	46.65	74.00	-27.35	peak
4	22976.000	48.26	-3.46	44.80	74.00	-29.20	peak
5	24720.000	46.72	-2.33	44.39	74.00	-29.61	peak
6	25312.000	45.70	-1.70	44.00	74.00	-30.00	peak


Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. LE 2M MODE- PCB ANTENNA

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	50.3700	47.08	-20.76	26.32	40.00	-13.68	QP
2	108.5700	48.42	-20.53	27.89	43.50	-15.61	QP
3	154.1600	48.21	-18.06	30.15	43.50	-13.35	QP
4	239.5200	49.91	-19.16	30.75	46.00	-15.25	QP
5	307.4200	38.97	-15.13	23.84	46.00	-22.16	QP
6	480.0800	52.32	-11.79	40.53	46.00	-5.47	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	50.3700	57.61	-20.76	36.85	40.00	-3.15	QP
2	108.5700	58.23	-20.53	37.70	43.50	-5.80	QP
3	154.1600	52.54	-18.06	34.48	43.50	-9.02	QP
4	239.5200	57.65	-19.16	38.49	46.00	-7.51	QP
5	480.0800	50.47	-11.79	38.68	46.00	-7.32	QP
6	663.4099	35.30	-8.66	26.64	46.00	-19.36	QP

- Note: 1. Result Level = Read Level + Correct Factor.
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. LE 2M MODE- PCB ANTENNA

SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	75.72	-101.40	-25.68	47.6	-77.18	-3.90	-73.28	peak
2	0.0131	71.97	-101.38	-29.41	45.25	-80.91	-6.25	-74.66	peak
3	0.0181	69.85	-101.36	-31.51	42.45	-83.01	-9.05	-73.96	peak
4	0.0279	66.67	-101.38	-34.71	38.69	-86.21	-12.81	-73.40	peak
5	0.0636	61.81	-101.54	-39.73	31.53	-91.23	-19.97	-71.26	peak
6	0.0767	60.09	-101.61	-41.52	29.91	-93.02	-21.59	-71.43	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1554	76.27	-101.65	-25.38	23.77	-76.88	-27.73	-49.15	peak
2	0.1733	72.42	-101.67	-29.25	22.83	-80.75	-28.67	-52.08	peak
3	0.2197	66.77	-101.75	-34.98	20.76	-86.48	-30.74	-55.74	peak
4	0.2605	63.64	-101.81	-38.17	19.28	-89.67	-32.22	-57.45	peak
5	0.3431	61.17	-101.90	-40.73	16.89	-92.23	-34.61	-57.62	peak
6	0.4102	59.98	-101.97	-41.99	15.34	-93.49	-36.16	-57.33	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.6298	64.17	-62.09	2.08	31.62	-49.42	-19.88	-29.54	peak
2	0.7737	63.91	-62.13	1.78	29.83	-49.72	-21.67	-28.05	peak
3	1.6149	57.62	-62.00	-4.38	23.44	-55.88	-28.06	-27.82	peak
4	6.8936	53.09	-61.22	-8.13	29.54	-59.63	-21.96	-37.67	peak
5	11.8513	52.06	-60.88	-8.82	29.54	-60.32	-21.96	-38.36	peak
6	22.1503	51.70	-60.67	-8.97	29.54	-60.47	-21.96	-38.51	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


TEST ENVIRONMENT

Temperature	22.3 °C	Relative Humidity	65 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

RESULTS

9.1. LE 2M MODE- FPC ANTENNA

LINE L RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1635	36.09	9.52	45.61	65.28	-19.67	QP
2	0.1635	25.13	9.52	34.65	55.28	-20.63	AVG
3	0.6351	12.90	9.50	22.40	56.00	-33.60	QP
4	0.6351	4.33	9.50	13.83	46.00	-32.17	AVG
5	1.0011	9.73	9.51	19.24	56.00	-36.76	QP
6	1.0011	5.09	9.51	14.60	46.00	-31.40	AVG
7	1.8554	11.91	9.61	21.52	56.00	-34.48	QP
8	1.8554	7.43	9.61	17.04	46.00	-28.96	AVG
9	4.4471	13.01	9.52	22.53	56.00	-33.47	QP
10	4.4471	8.74	9.52	18.26	46.00	-27.74	AVG
11	20.0047	17.37	9.74	27.11	60.00	-32.89	QP
12	20.0047	12.57	9.74	22.31	50.00	-27.69	AVG


Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

LINE N RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1556	38.05	9.50	47.55	65.70	-18.15	QP
2	0.1556	27.54	9.50	37.04	55.70	-18.66	AVG
3	0.6986	13.59	9.50	23.09	56.00	-32.91	QP
4	0.6986	7.80	9.50	17.30	46.00	-28.70	AVG
5	1.1204	10.82	9.52	20.34	56.00	-35.66	QP
6	1.1204	5.86	9.52	15.38	46.00	-30.62	AVG
7	1.5248	12.42	9.57	21.99	56.00	-34.01	QP
8	1.5248	7.33	9.57	16.90	46.00	-29.10	AVG
9	2.2237	11.67	9.63	21.30	56.00	-34.70	QP
10	2.2237	7.46	9.63	17.09	46.00	-28.91	AVG
11	20.0000	19.26	9.74	29.00	60.00	-31.00	QP
12	20.0000	14.54	9.74	24.28	50.00	-25.72	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies




11. Appendix


11.1. Appendix A: DTS Bandwidth

11.1.1. Test Result


Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.69	2401.64	2402.33	0.5	PASS
		2440	0.68	2439.65	2440.33	0.5	PASS
		2480	0.68	2479.65	2480.33	0.5	PASS
BLE_2M	Ant1	2402	1.15	2401.42	2402.57	0.5	PASS
		2440	1.15	2439.42	2440.57	0.5	PASS
		2480	1.16	2479.40	2480.57	0.5	PASS

11.1.2. Test Graphs






BLE 2M Ant1_2402



BLE 2M Ant1_2440



BLE 2M Ant1_2480





11.2. Appendix B: Occupied Channel Bandwidth

11.2.1. Test Result


Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant1	2402	1.039	2401.477	2402.515	PASS
		2440	1.039	2439.477	2440.515	PASS
		2480	1.039	2479.477	2480.515	PASS
BLE_2M	Ant1	2402	2.062	2400.969	2403.031	PASS
		2440	2.062	2438.969	2441.031	PASS
		2480	2.062	2478.969	2481.031	PASS

11.2.2. Test Graphs






BLE 2M Ant1_2402



BLE 2M Ant1_2440



BLE 2M Ant1_2480



11.3. Appendix C: Maximum conducted output power

11.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	8.14	≤30	PASS
		2440	8.19	≤30	PASS
		2480	8.03	≤30	PASS
BLE_2M	Ant1	2402	8.30	≤30	PASS
		2440	8.39	≤30	PASS
		2480	8.30	≤30	PASS





11.4. Appendix D: Maximum power spectral density

11.4.1. Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-7.07	≤8.00	PASS
		2440	-7.01	≤8.00	PASS
		2480	-7.19	≤8.00	PASS
BLE_2M	Ant1	2402	-10.56	≤8.00	PASS
		2440	-10.54	≤8.00	PASS
		2480	-10.59	≤8.00	PASS

11.4.2. Test Graphs






BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480





11.5. Appendix E: Band edge measurements

11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	7.46	-45.09	≤-12.54	PASS
		High	2480	7.37	-43.63	≤-12.63	PASS
BLE_2M	Ant1	Low	2402	6.75	-25.02	≤-13.25	PASS
		High	2480	7.47	-44.2	≤-12.53	PASS

11.5.2. Test Graphs







11.6. Appendix F: Conducted Spurious Emission

11.6.1. Test Result


Test Mode	Antenna	Channel	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	7.53	---	PASS
			30~1000	-54	≤ -12.47	PASS
			1000~26500	-48.2	≤ -12.47	PASS
		2440	Reference	7.60	---	PASS
			30~1000	-53.82	≤ -12.4	PASS
			1000~26500	-49.3	≤ -12.4	PASS
		2480	Reference	7.43	---	PASS
			30~1000	-54.79	≤ -12.57	PASS
			1000~26500	-49.31	≤ -12.57	PASS
BLE_2M	Ant1	2402	Reference	7.41	---	PASS
			30~1000	-53.95	≤ -12.59	PASS
			1000~26500	-49.49	≤ -12.59	PASS
		2440	Reference	7.64	---	PASS
			30~1000	-53.8	≤ -12.36	PASS
			1000~26500	-48.91	≤ -12.36	PASS
		2480	Reference	7.46	---	PASS
			30~1000	-54.15	≤ -12.54	PASS
			1000~26500	-49.38	≤ -12.54	PASS

11.6.2. Test Graphs






BLE_1M_Ant1_2440_0~Reference



BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




Date: 15.FEB.2022 13:23:19

BLE_1M_Ant1_2480_0~Reference




Date: 15.FEB.2022 13:23:25

BLE_1M_Ant1_2480_30~1000




Date: 15.FEB.2022 13:23:47

BLE_1M_Ant1_2480_1000~26500




Date: 15.FEB.2022 13:24:49

BLE_2M_Ant1_2402_0-Reference




Date: 15.FEB.2022 13:24:55

BLE_2M_Ant1_2402_30~1000




Date: 15.FEB.2022 13:25:16

BLE_2M_Ant1_2402_1000~26500




Date: 15.FEB.2022 13:26:23

BLE_2M_Ant1_2440_0-Reference




Date: 15.FEB.2022 13:26:30

BLE_2M_Ant1_2440_30~1000




Date: 15.FEB.2022 13:26:51


BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant1_2480_0-Reference



BLE_2M_Ant1_2480_30~1000



BLE_2M_Ant1_2480_1000~26500



11.7. Appendix G: Duty Cycle

11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.37	0.61	0.6066	60.66	2.17	2.70	3
BLE_2M	1.06	1.85	0.5730	57.30	2.42	0.94	1

Note:


Duty Cycle Correction Factor= $10\log(1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

11.7.2. Test Graphs



END OF REPORT