

APPENDIX C PLOTS OF THE SAR MEASUREMENTS

Plots of the measured SAR distributions inside the phantom are given in this Appendix for all tested configurations.



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz 3G EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 02-09-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1907.6$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 39.9$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 02-09-20/Channel 9538 Test/Area Scan (101x151x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.565 W/kg**Back 0mm Spacing 02-09-20/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 17.915 V/m; **Power Drift = 0.09 dB****Averaged SAR: SAR(1g) = 0.497 W/kg; SAR(10g) = 0.256 W/kg**

Maximum value of SAR (interpolated) = 0.857 W/kg



0 dB = 0.565 W/kg = -2.48 dBW/kg

SAR Measurement Plot 1



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz 3G EN.da52:4

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 02-09-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1907.6$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 39.9$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 02-09-20/Channel 9538 Test/Area Scan (101x71x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 3.080 W/kg**Left 0mm Spacing 02-09-20/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 37.137 V/m; **Power Drift = -0.07 dB****Averaged SAR: SAR(1g) = 2.610 W/kg; SAR(10g) = 1.370 W/kg**

Maximum value of SAR (interpolated) = 4.580 W/kg



SAR Measurement Plot 2



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz 3G EN.da52:6

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 02-09-20**Communication System: 0 - System Check; Communication System Band: 1950 MHz; Frequency: 1950 MHz,
Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00Medium Parameters used: $f=1950$ MHz; $\sigma = 1.46$ S/m; $\epsilon_r = 39.8$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.05,5.05,5.05); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 02-09-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 13.300 W/kg

System Check 02-09-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 94.672 V/m; **Power Drift = 0.06 dB****Averaged SAR: SAR(1g) = 10.500 W/kg; SAR(10g) = 5.510 W/kg**

Maximum value of SAR (interpolated) = 17.600 W/kg



SAR Measurement Plot 3



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz 3G EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 31-08-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 4 1735 MHz; Frequency: 1712 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1712.5$ MHz; $\sigma = 1.33$ S/m; $\epsilon_r = 38.7$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 31-08-20/Channel 1312 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.750 W/kg**Back 0mm Spacing 31-08-20/Channel 1312 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.927 V/m; **Power Drift = -0.08 dB****Averaged SAR: SAR(1g) = 0.688 W/kg; SAR(10g) = 0.392 W/kg**

Maximum value of SAR (interpolated) = 1.070 W/kg



SAR Measurement Plot 4



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz 3G EN.da52:4

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 31-08-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 4 1735 MHz; Frequency: 1735 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1735.5$ MHz; $\sigma = 1.34$ S/m; $\epsilon_r = 38.7$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 31-08-20/Channel 1427 Test/Area Scan (101x71x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 2.050 W/kg**Left 0mm Spacing 31-08-20/Channel 1427 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 26.654 V/m; **Power Drift = -0.11 dB****Averaged SAR: SAR(1g) = 1.790 W/kg; SAR(10g) = 0.987 W/kg**

Maximum value of SAR (interpolated) = 3.010 W/kg



SAR Measurement Plot 5



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz 3G EN.da52:6

DUT Name: Dipole 1800 MHz, Type: DV1800V2, Serial: 242**Configuration: System Check 31-08-20**

Communication System: 0 - System Check; Communication System Band: 1800 MHz; Frequency: 1800 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1800$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.4$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 31-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 11.400 W/kg

System Check 31-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 90.099 V/m; **Power Drift = 0.03 dB****Averaged SAR: SAR(1g) = 9.290 W/kg; SAR(10g) = 5.050 W/kg**

Maximum value of SAR (interpolated) = 15.200 W/kg



SAR Measurement Plot 6



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz 3G EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 18-08-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 5 850 MHz; Frequency: 836.6 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=836.6$ MHz; $\sigma = 0.88$ S/m; $\epsilon_r = 40.6$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 18-08-20/Channel 4183 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.283 W/kg**Back 0mm Spacing 18-08-20/Channel 4183 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.256 V/m; **Power Drift = 0.02 dB****Averaged SAR: SAR(1g) = 0.260 W/kg; SAR(10g) = 0.176 W/kg**

Maximum value of SAR (interpolated) = 0.380 W/kg



SAR Measurement Plot 7



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz 3G EN.da52:4

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 18-08-20**

Communication System: 0 - WCDMA - UMTS; Communication System Band: Band 5 850 MHz; Frequency: 836.6 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=836.6$ MHz; $\sigma = 0.88$ S/m; $\epsilon_r = 40.6$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 18-08-20/Channel 4183 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 1.730 W/kg**Left 0mm Spacing 18-08-20/Channel 4183 Test/Zoom Scan (26x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 35.161 V/m; **Power Drift = 0.03 dB****Averaged SAR: SAR(1g) = 1.600 W/kg; SAR(10g) = 0.914 W/kg**

Maximum value of SAR (interpolated) = 2.750 W/kg



SAR Measurement Plot 8



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz 3G EN.da52:6

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 18-08-20**Communication System: 0 - System Check; Communication System Band: 900 MHz; Frequency: 900.0 MHz;
Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00Medium Parameters used: $f=900$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 39.8$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 18-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm;

Maximum value of SAR (interpolated) = 2.880 W/kg

System Check 18-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 57.657 V/m; **Power Drift = 0.06 dB****Averaged SAR: SAR(1g) = 2.680 W/kg; SAR(10g) = 1.740 W/kg**

Maximum value of SAR (interpolated) = 3.840 W/kg



SAR Measurement Plot 9



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz LTE EN.da52:1

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 50 RB 01-09-20**

Communication System: 0 - LTE FDD 20MHz QPSK (50RB High); Communication System Band: Bnad 2 E-UTRA 1900; Frequency: 1900 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1900$ MHz; $\sigma = 1.42$ S/m; $\epsilon_r = 39.2$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 50 RB 01-09-20/Channel 19100 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.302 W/kg

Back 0mm Spacing 50 RB 01-09-20/Channel 19100 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.793 V/m; **Power Drift = 0.01 dB**

Averaged SAR: SAR(1g) = 0.262 W/kg; SAR(10g) = 0.139 W/kg

Maximum value of SAR (interpolated) = 0.445 W/kg



SAR Measurement Plot 10



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz LTE EN.da52:9

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 50 RB 01-09-20**

Communication System: 0 - LTE FDD 20MHz QPSK (50RB High); Communication System Band: Bnad 2 E-UTRA 1900; Frequency: 1900 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1900$ MHz; $\sigma = 1.42$ S/m; $\epsilon_r = 39.2$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 50 RB 01-09-20/Channel 19100 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 2.720 W/kg

Left 0mm Spacing 50 RB 01-09-20/Channel 19100 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 33.908 V/m; **Power Drift = 0.02 dB**

Averaged SAR: SAR(1g) = 2.290 W/kg; SAR(10g) = 1.150 W/kg

Maximum value of SAR (interpolated) = 4.240 W/kg



SAR Measurement Plot 11



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1900 MHz LTE EN.da52:12

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 01-09-20**

Communication System: 0 - System Check; Communication System Band: 1950 MHz; Frequency: 1950 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=1950$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 39.1$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.05,5.05,5.05); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 01-09-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 13.500 W/kg

System Check 01-09-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 96.166 V/m; **Power Drift = -0.02 dB****Averaged SAR: SAR(1g) = 10.500 W/kg; SAR(10g) = 5.540 W/kg**

Maximum value of SAR (interpolated) = 17.900 W/kg



SAR Measurement Plot 12



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 1 RB 27-08-20**

Communication System: 0 - LTE FDD 20MHz QPSK (1RB Low); Communication System Band: Band 4 E-UTRA 1700; Frequency: 1720 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1720$ MHz; $\sigma = 1.33$ S/m; $\epsilon_r = 39.2$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 1 RB 27-08-20/Channel 20050 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.624 W/kg

Back 0mm Spacing 1 RB 27-08-20/Channel 20050 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.140 V/m; **Power Drift = 0.09 dB**

Averaged SAR: SAR(1g) = 0.540 W/kg; SAR(10g) = 0.311 W/kg

Maximum value of SAR (interpolated) = 0.830 W/kg



SAR Measurement Plot 13



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:8

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 1 RB 27-08-20**

Communication System: 0 - LTE FDD 20MHz QPSK (1RB Mid); Communication System Band: Band 4 E-UTRA 1700; Frequency: 1733 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1732.5$ MHz; $\sigma = 1.34$ S/m; $\epsilon_r = 39.1$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 1 RB 27-08-20/Channel 20175 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 1.790 W/kg

Left 0mm Spacing 1 RB 27-08-20/Channel 20175 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 26.398 V/m; **Power Drift = 0.03 dB**

Averaged SAR: SAR(1g) = 1.520 W/kg; SAR(10g) = 0.803 W/kg

Maximum value of SAR (interpolated) = 2.540 W/kg



SAR Measurement Plot 14



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:12

DUT Name: Dipole 1800 MHz, Type: DV1800V2, Serial: 242**Configuration: System Check 27-08-20**Communication System: 0 - System Check; Communication System Band: 1800 MHz; Frequency: 1800 MHz,
Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00Medium Parameters used: $f=1800$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 38.9$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 27-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 12.100 W/kg

System Check 27-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 95.046 V/m; **Power Drift = -0.00 dB****Averaged SAR: SAR(1g) = 9.540 W/kg; SAR(10g) = 5.170 W/kg**

Maximum value of SAR (interpolated) = 15.600 W/kg



SAR Measurement Plot 15



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz LTE EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 1 RB 17-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (1RB Mid); Communication System Band: Band 5 E-UTRA 835; Frequency: 836.5 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=836.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.8$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 1 RB 17-08-20/Channel 20525 Test/Area Scan (101x151x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.256 W/kg

Back 0mm Spacing 1 RB 17-08-20/Channel 20525 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 14.971 V/m; **Power Drift = -0.09 dB**

Averaged SAR: SAR(1g) = 0.235 W/kg; SAR(10g) = 0.161 W/kg

Maximum value of SAR (interpolated) = 0.333 W/kg



SAR Measurement Plot 16



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz LTE EN.da52:8

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 1 RB 17-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (1RB Mid); Communication System Band: Band 5 E-UTRA 835; Frequency: 836.5 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=836.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.8$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 1 RB 17-08-20/Channel 20525 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 1.420 W/kg

Left 0mm Spacing 1 RB 17-08-20/Channel 20525 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 37.897 V/m; **Power Drift = 0.06 dB**

Averaged SAR: SAR(1g) = 1.270 W/kg; SAR(10g) = 0.723 W/kg

Maximum value of SAR (interpolated) = 2.250 W/kg



SAR Measurement Plot 17



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 850 MHz LTE EN.da52:12

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 17-08-20**Communication System: 0 - System Check; Communication System Band: 900 MHz; Frequency: 900.0 MHz,
Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00Medium Parameters used: $f=900$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 40.1$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.09,6.09,6.09); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 17-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm;

Maximum value of SAR (interpolated) = 2.830 W/kg

System Check 17-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 57.864 V/m; **Power Drift = 0.00 dB****Averaged SAR: SAR(1g) = 2.640 W/kg; SAR(10g) = 1.720 W/kg**

Maximum value of SAR (interpolated) = 3.770 W/kg



SAR Measurement Plot 18



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:0

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 1 RB 11-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (1RB Mid); Communication System Band: Band 12 E-UTRA 700; Frequency: 711.0 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=711$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.4$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 1 RB 11-08-20/Channel 23130 Test/Area Scan (101x151x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.086 W/kg**Back 0mm Spacing 1 RB 11-08-20/Channel 23130 Test/Zoom Scan (36x31x36)/Cube 0:** Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 9.774 V/m; **Power Drift = 0.17 dB****Averaged SAR: SAR(1g) = 0.088 W/kg; SAR(10g) = 0.062 W/kg**

Maximum value of SAR (interpolated) = 0.124 W/kg



SAR Measurement Plot 19



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:9

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 25 RB 11-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (25RB Mid); Communication System Band: Bnad 12 E-UTRA 700; Frequency: 711.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=711$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.4$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 25 RB 11-08-20/Channel 23130 Test/Area Scan (101x71x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.357 W/kg

Left 0mm Spacing 25 RB 11-08-20/Channel 23130 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 17.672 V/m; **Power Drift = 0.06 dB**

Averaged SAR: SAR(1g) = 0.330 W/kg; SAR(10g) = 0.198 W/kg

Maximum value of SAR (interpolated) = 0.540 W/kg



SAR Measurement Plot 20



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:12

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 11-08-20**

Communication System: 0 - CW (0); Communication System Band: 750 MHz; Frequency: 750.0 MHz,

Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=750$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 39.9$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 11-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 2.450 W/kg

System Check 11-08-20/Channel 1 Test/Zoom Scan (31x36x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 54.407 V/m; **Power Drift = -0.05 dB****Averaged SAR: SAR(1g) = 2.280 W/kg; SAR(10g) = 1.500 W/kg**

Maximum value of SAR (interpolated) = 3.230 W/kg



SAR Measurement Plot 21



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:1

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 25 RB 12-08-20**

Communication System: 0 - LTE FDD 5MHz QPSK (25RB Mid); Communication System Band: Band 13 E-UTRA 700; Frequency: 784.5 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=784.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.1$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 25 RB 12-08-20/Channel 23255 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.157 W/kg

Back 0mm Spacing 25 RB 12-08-20/Channel 23255 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.619 V/m; **Power Drift = 0.06 dB**

Averaged SAR: SAR(1g) = 0.149 W/kg; SAR(10g) = 0.101 W/kg

Maximum value of SAR (interpolated) = 0.199 W/kg



SAR Measurement Plot 22



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:9

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 25 RB 12-08-20**

Communication System: 0 - LTE FDD 5MHz QPSK (25RB Mid); Communication System Band: Band 13 E-UTRA 700; Frequency: 784.5 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=784.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.1$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 25 RB 12-08-20/Channel 23255 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.776 W/kg**Left 0mm Spacing 25 RB 12-08-20/Channel 23255 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 25.606 V/m; **Power Drift = -0.00 dB****Averaged SAR: SAR(1g) = 0.679 W/kg; SAR(10g) = 0.393 W/kg**

Maximum value of SAR (interpolated) = 1.160 W/kg



SAR Measurement Plot 23



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:12

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 12-08-20**

Communication System: 0 - CW (0); Communication System Band: 750 MHz; Frequency: 750.0 MHz,

Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=750$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 40.0$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 12-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 2.260 W/kg

System Check 12-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 52.626 V/m; **Power Drift = 0.11 dB****Averaged SAR: SAR(1g) = 2.120 W/kg; SAR(10g) = 1.400 W/kg**

Maximum value of SAR (interpolated) = 3.010 W/kg



SAR Measurement Plot 24



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:1

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 25 RB 13-08-20**

Communication System: 0 - LTE FDD 5MHz QPSK (25RB Mid); Communication System Band: Band 14 E-UTRA 700; Frequency: 790.5 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=790.5$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 40.1$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 25 RB 13-08-20/Channel 23305 Test/Area Scan (101x151x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.158 W/kg

Back 0mm Spacing 25 RB 13-08-20/Channel 23305 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 12.952 V/m; **Power Drift = -0.00 dB**

Averaged SAR: SAR(1g) = 0.157 W/kg; SAR(10g) = 0.108 W/kg

Maximum value of SAR (interpolated) = 0.214 W/kg



SAR Measurement Plot 25



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:8

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 1 RB 13-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (1RB Mid); Communication System Band: Band 14 E-UTRA 700; Frequency: 793.0 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=793$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 40.1$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 1 RB 13-08-20/Channel 23330 Test/Area Scan (101x71x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 1.360 W/kg**Left 0mm Spacing 1 RB 13-08-20/Channel 23330 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 33.456 V/m; **Power Drift = -0.03 dB****Averaged SAR: SAR(1g) = 1.180 W/kg; SAR(10g) = 0.677 W/kg**

Maximum value of SAR (interpolated) = 2.030 W/kg



SAR Measurement Plot 26



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:12

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 13-08-20**

Communication System: 0 - CW (0); Communication System Band: 750 MHz; Frequency: 750.0 MHz,

Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=750$ MHz; $\sigma = 0.88$ S/m; $\epsilon_r = 40.3$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 13-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 2.330 W/kg

System Check 13-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 53.856 V/m; **Power Drift = 0.03 dB****Averaged SAR: SAR(1g) = 2.160 W/kg; SAR(10g) = 1.430 W/kg**

Maximum value of SAR (interpolated) = 3.060 W/kg



SAR Measurement Plot 27



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:1

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 25 RB 14-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (25RB High); Communication System Band: Band 17 E-UTRA 710; Frequency: 709.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=709$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 25 RB 14-08-20/Channel 23780 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.082 W/kg

Back 0mm Spacing 25 RB 14-08-20/Channel 23780 Test/Zoom Scan (26x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.381 V/m; **Power Drift = -0.01 dB**

Averaged SAR: SAR(1g) = 0.075 W/kg; SAR(10g) = 0.052 W/kg

Maximum value of SAR (interpolated) = 0.106 W/kg



SAR Measurement Plot 28



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:11

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 1 RB 14-08-20**

Communication System: 0 - LTE FDD 10MHz QPSK (1RB Mid); Communication System Band: Band 17 E-UTRA 710; Frequency: 710.0 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=710$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 40.6$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))


Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101

DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 1 RB 14-08-20/Channel 23790 Test/Area Scan (101x71x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 0.473 W/kg**Left 0mm Spacing 1 RB 14-08-20/Channel 23790 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 20.218 V/m; **Power Drift = 0.03 dB****Averaged SAR: SAR(1g) = 0.428 W/kg; SAR(10g) = 0.259 W/kg**

Maximum value of SAR (interpolated) = 0.692 W/kg



SAR Measurement Plot 29



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 700 MHz LTE EN.da52:17

DUT Name: Dipole 750 MHz, Type: D750V3, Serial: D750V3 - SN:1051**Configuration: System Check 17-08-20**

Communication System: 0 - CW (0); Communication System Band: 750 MHz; Frequency: 750.0 MHz,

Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=750$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 39.9$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (6.49,6.49,6.49); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 17-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 2.390 W/kg

System Check 17-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 53.476 V/m; **Power Drift = 0.06 dB****Averaged SAR: SAR(1g) = 2.220 W/kg; SAR(10g) = 1.470 W/kg**

Maximum value of SAR (interpolated) = 3.140 W/kg



SAR Measurement Plot 30



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:1

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Back 0mm Spacing 50 RB 26-08-20**

Communication System: 0 - LTE FDD 20MHz QPSK (50RB Low); Communication System Band: Bnad 66 E-UTRA 700; Frequency: 1720 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1720$ MHz; $\sigma = 1.31$ S/m; $\epsilon_r = 39.1$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Back 0mm Spacing 50 RB 26-08-20/Channel 132072 Test/Area Scan (101x151x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.364 W/kg

Back 0mm Spacing 50 RB 26-08-20/Channel 132072 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.087 V/m; **Power Drift = 0.02 dB**

Averaged SAR: SAR(1g) = 0.328 W/kg; SAR(10g) = 0.186 W/kg

Maximum value of SAR (interpolated) = 0.512 W/kg



SAR Measurement Plot 31



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:8

DUT Name: Mentis 3G-LTE Transmitter, Type: W510, Serial: IMEI:015250000176440**Configuration: Left 0mm Spacing 1 RB 26-08-20**

Communication System: 0 - LTE FDD 20MHz QPSK (1RB High); Communication System Band: Bnad 66 E-UTRA 1700; Frequency: 1745 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=1745$ MHz; $\sigma = 1.32$ S/m; $\epsilon_r = 39.0$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 6/12/2019
Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101
DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

Left 0mm Spacing 1 RB 26-08-20/Channel 132322 Test/Area Scan (101x71x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 2.200 W/kg

Left 0mm Spacing 1 RB 26-08-20/Channel 132322 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 34.598 V/m; **Power Drift = -0.09 dB**

Averaged SAR: SAR(1g) = 1.710 W/kg; SAR(10g) = 0.905 W/kg

Maximum value of SAR (interpolated) = 2.920 W/kg



SAR Measurement Plot 32



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.

Test Lab: EMCTech

Test File: M2006031 Walker Tx 1700 MHz LTE EN.da52:12

DUT Name: Dipole 1800 MHz, Type: DV1800V2, Serial: 242**Configuration: System Check 26-08-20**Communication System: 0 - System Check; Communication System Band: 1800 MHz; Frequency: 1800 MHz,
Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00Medium Parameters used: $f=1800$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 38.7$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (5.16,5.16,5.16); Calibrated: 9/12/2019;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 6/12/2019

Phantom: ELI 4.0 (5deg probe tilt); Type: QDOVA001BA; Serial: 1101


DASY52 52.10.1(1476); SEMCAD X Version 14.6.11 (7437)

System Check 26-08-20/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;

Maximum value of SAR (interpolated) = 11.800 W/kg

System Check 26-08-20/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 95.140 V/m; **Power Drift = -0.10 dB****Averaged SAR: SAR(1g) = 9.290 W/kg; SAR(10g) = 5.020 W/kg**

Maximum value of SAR (interpolated) = 15.200 W/kg



SAR Measurement Plot 33



Accredited for compliance with ISO/IEC 17025 – Testing.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.



Accredited for compliance with ISO/IEC 17025 – Testing.
 NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance this document must only be reproduced in full.