

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Band	Frequency (MHz)	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict	
WIFI	2437MHz ANT 1	18.17	65.61	2.05	0.0209	1.0	PASS	
2.4G	2422MHz MIMO	17.99	62.95	5.05	0.0401	1.0		
Internal Antenna								
WCDMA Band II	826.40-846.60	26	398.11	1.93	0.1235	0.45		
WCDMA Band V	1852.40-1907.60	23.39	218.27	0.78	0.0520	0.26		
LTE band 2	1850-1910	23.48	222.84	1.93	0.0691	1.0		
LTE band 4	1710-1755	24.26	266.69	2.63	0.0972	1.0		
LTE band 5	824-849	23.63	230.67	0.78	0.0504	0.55		
LTE band 7	2500-2570	23.68	233.35	3.28	0.0988	1.0		
External Antenna								
WCDMA Band II	826.40-846.60	26	398.11	0.23	0.0835	0.45	PASS	
WCDMA Band V	1852.40-1907.60	23.39	218.27	-1.03	0.0343	0.26		
LTE band 2	1850-1910	23.48	222.84	0.23	0.0467	1.0		
LTE band 4	1710-1755	24.26	266.69	1.58	0.0763	1.0		
LTE band 5	824-849	23.63	230.67	-1.03	0.0362	0.55		
LTE band 7	2500-2570	23.68	233.35	2.61	0.0847	1.0		

The maximum simultaneously transmitting were as below

Internal Antenna:

DTS+WCDMA: 0.315<1

DTS+LTE: 0.14<1

External Antenna:

DTS+WCDMA: 0.206<1

DTS+LTE: 0.11<1

The max power density is less than MPE exempt limit, so it is compliance.