



FCC ID: 2ARUDACTV200BT

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances  $\leq 50\text{mm}$ , the SAR test exclusion threshold is determined according to the following

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$

$\times [\sqrt{f(\text{GHz})}] \leq 3.0$

### 1. SAR test exclusion threshold

**Frequency: 2 480 MHz (min. separation distances = 5 mm)**

SAR test exclusion thresholds (5 mm) =  $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

| Test mode | Max. Tune-up Tolerance (mW) | SAR Test Exclusion Thresholds (5mm) (mW) |
|-----------|-----------------------------|--|
| BT        | 2.0                         | 9.525                                    |

Calculation value:  $2.0 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.630$

So, Calculation value  $\leq 3.0$

Remark:

-For BT Max. conducted power is 2.0 (mW) closet 2.0(mW), so 2.0 (mW) was calculated.

-When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of 5 mm is applied to determine

SAR test exclusion.

### 2. Conclusion: No SAR is required.