



FCC RADIO TEST REPORT

Equipment : VR Headset
Brand Name : META PLATFORMS TECHNOLOGIES, LLC
Model Name : S3A
Applicant : Meta Platforms Technologies, LLC.
1 Hacker Way, Menlo Park, CA 94025, USA
Manufacturer : Meta Platforms Technologies, LLC.
1 Hacker Way, Menlo Park, CA 94025, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 02, 2023 and testing was performed from May 09, 2023 to Jun. 15, 2023. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 EUT Operation Test Setup	10
2.5 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements	21
4 List of Measuring Equipment	22
5 Uncertainty of Evaluation.....	23
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR261607-06H	01	Initial issue of report	Jun. 30, 2023

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	6.82 dB under the limit at 2484.080 MHz
3.6	15.207	AC Conducted Emission	Pass	17.38 dB under the limit at 0.164 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Lea Yu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs	Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11ax and nRF.
Sample 1	Main-A
Sample 2	Main-B
Sample 3	Main-C
Sample 4	Main-D
Antenna Type	WLAN: <Ant. 0>: Dipole Antenna <Ant. 1>: Dipole Antenna Bluetooth: Dipole Antenna nRF: Dipole Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.20

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH20-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
nRF	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	-	-
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Mode 1: nRF Tx CH00_2402 MHz_2Mbps Mode 2: nRF Tx CH19_2440 MHz_2Mbps Mode 3: nRF Tx CH38_2478 MHz_2Mbps
Radiated Test Cases	Mode 1: nRF Tx CH00_2402 MHz_2Mbps Mode 2: nRF Tx CH19_2440 MHz_2Mbps Mode 3: nRF Tx CH38_2478 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + NRF Link with controller + USB Cable (Charging from Adapter) for Sample 1 Mode 2: WLAN (2.4GHz) Link + Bluetooth Link + NRF Link with controller + USB Cable (Charging from Adapter) for Sample 2 Mode 3: WLAN (2.4GHz) Link + Bluetooth Link + NRF Link with controller + USB Cable (Charging from Adapter) for Sample 3 Mode 4: WLAN (2.4GHz) Link + Bluetooth Link + NRF Link with controller + USB Cable (Charging from Adapter) for Sample 4
Remark: 1. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. For Radiated Test Cases, the tests were performed with Battery 2, USB Cable 2 and Sample 1.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<SRD-nRF Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	P79G	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	DELL	Latitude5310	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Sony	SBH20	PY7-RD0010	N/A	N/A
5.	Handheld controller	META PLATFORMS TECHNOLOGIES, LLC	S2Y	2AGOZ-S2Y	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “CMD Version1.0.40” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density Plots (100kHz)

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (3kHz)

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20MHz~8.4GHz	Apr. 25, 2023	May 09, 2023~ Jun. 15, 2023	Apr. 24, 2024	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	May 09, 2023~ Jun. 15, 2023	Sep. 19, 2023	Radiation (03CH20-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	May 09, 2023~ Jun. 15, 2023	N/A	Radiation (03CH20-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	May 09, 2023~ Jun. 15, 2023	N/A	Radiation (03CH20-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	May 09, 2023~ Jun. 15, 2023	N/A	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 28, 2022	May 09, 2023~ Jun. 15, 2023	Jun. 27, 2023	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 22, 2022	May 09, 2023~ Jun. 15, 2023	Dec. 21, 2023	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00802 N1D01N-06	55606 & 08	30MHz~1GHz	Oct. 22, 2022	May 09, 2023~ Jun. 15, 2023	Oct. 21, 2023	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 04, 2022	May 09, 2023~ Jun. 15, 2023	Nov. 03, 2023	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA9170	00994	18GHz-40GHz	Nov. 04, 2022	May 09, 2023~ Jun. 15, 2023	Nov. 03, 2023	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Jan. 02, 2023	May 09, 2023~ Jun. 15, 2023	Jan. 01, 2024	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45S E	980792	N/A	Nov. 14, 2022	May 09, 2023~ Jun. 15, 2023	Nov. 13, 2023	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,804 015/2,804027 /2	N/A	Jan. 18, 2023	May 09, 2023~ Jun. 15, 2023	Jan. 17, 2024	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303B	TP200728	N/A	Mar. 28, 2023	May 09, 2023~ Jun. 15, 2023	Mar. 27, 2024	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	May 09, 2023~ Jun. 15, 2023	N/A	Radiation (03CH20-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jun. 02, 2023	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 02, 2023	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 01, 2022	Jun. 02, 2023	Oct. 31, 2023	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 15, 2023	Jun. 02, 2023	Mar. 14, 2024	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 05, 2023	Jun. 02, 2023	Mar. 04, 2024	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 13, 2023	Jun. 02, 2023	Mar. 12, 2024	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 06, 2022	Jun. 02, 2023	Oct. 05, 2023	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 17, 2022	May 10, 2023~ Jun. 05, 2023	Nov. 16, 2023	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO 12 (NO:113)	10MHz~6GHz	Dec. 13, 2022	May 10, 2023~ Jun. 05, 2023	Dec. 12, 2023	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101905	10Hz - 40GHz(amp)	Aug. 03, 2022	May 10, 2023~ Jun. 05, 2023	Aug. 02, 2023	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.46 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.80 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.40 dB
---	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Benny Ku	Temperature:	21~25	°C
Test Date:	2023/5/10~2023/6/5	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
nRF	2Mbps	1	0	2402	1.998	0.560	0.50	Pass
nRF	2Mbps	1	19	2440	1.998	0.560	0.50	Pass
nRF	2Mbps	1	38	2478	1.998	0.568	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
nRF	2Mbps	1	0	2402	5.70	30.00	2.20	7.90	36.00	Pass
nRF	2Mbps	1	19	2440	5.70	30.00	2.20	7.90	36.00	Pass
nRF	2Mbps	1	38	2478	5.70	30.00	2.20	7.90	36.00	Pass

TEST RESULTS DATA
Peak Power Density


Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
nRF	2Mbps	1	0	2402	5.61	-9.55	2.20	8.00	Pass
nRF	2Mbps	1	19	2440	5.86	-9.24	2.20	8.00	Pass
nRF	2Mbps	1	38	2478	5.77	-9.39	2.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.


6dB Bandwidth

<2Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19




6 dB Bandwidth Plot on Channel 39






**99% Occupied Bandwidth**

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00**99% Occupied Plot Bandwidth on Channel 19****99% Occupied Bandwidth Plot on Channel 39**

**Power Spectral Density (dBm/3kHz)**

<2Mbps>

Power Density (dBm/3kHz) Plot Channel 00**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**


Band Edge and Spurious Emission






<2Mbps> Channel 19

100kHz PSD reference Level Plot




Low Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2Mbps> Channel 39


100kHz PSD reference Level Plot




Low Channel Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	23.5~25.1℃
		Relative Humidity :	52.3~68.9%

EUT Information

Report NO : 261607-06
Test Mode : Mode 3
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163500	---	30.29	55.28	24.99	L1	OFF	19.9
0.163500	47.90	---	65.28	17.38	L1	OFF	19.9
0.188340	---	27.07	54.11	27.04	L1	OFF	19.9
0.188340	44.52	---	64.11	19.59	L1	OFF	19.9
0.222000	---	24.70	52.74	28.04	L1	OFF	20.0
0.222000	40.84	---	62.74	21.90	L1	OFF	20.0
0.368250	---	25.38	48.54	23.16	L1	OFF	20.0
0.368250	40.36	---	58.54	18.18	L1	OFF	20.0
0.478500	---	21.46	46.37	24.91	L1	OFF	20.0
0.478500	38.20	---	56.37	18.17	L1	OFF	20.0
0.506040	---	25.41	46.00	20.59	L1	OFF	20.0
0.506040	37.93	---	56.00	18.07	L1	OFF	20.0
0.641130	---	22.93	46.00	23.07	L1	OFF	20.0
0.641130	36.35	---	56.00	19.65	L1	OFF	20.0
1.125060	---	24.12	46.00	21.88	L1	OFF	20.0
1.125060	34.81	---	56.00	21.19	L1	OFF	20.0
2.811390	---	25.62	46.00	20.38	L1	OFF	20.0
2.811390	34.29	---	56.00	21.71	L1	OFF	20.0

EUT Information

Report NO : 261607-06
Test Mode : Mode 3
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.151755	---	30.53	55.90	25.37	N	OFF	20.0
0.151755	44.96	---	65.90	20.94	N	OFF	20.0
0.156750	---	29.64	55.63	25.99	N	OFF	20.0
0.156750	45.43	---	65.63	20.20	N	OFF	20.0
0.192750	---	24.78	53.92	29.14	N	OFF	20.0
0.192750	40.84	---	63.92	23.08	N	OFF	20.0
0.206970	---	24.42	53.33	28.91	N	OFF	20.0
0.206970	40.51	---	63.33	22.82	N	OFF	20.0
0.361140	---	24.55	48.70	24.15	N	OFF	20.0
0.361140	38.56	---	58.70	20.14	N	OFF	20.0
0.481650	---	20.33	46.31	25.98	N	OFF	20.0
0.481650	38.05	---	56.31	18.26	N	OFF	20.0
0.514860	---	24.56	46.00	21.44	N	OFF	20.0
0.514860	35.82	---	56.00	20.18	N	OFF	20.0
0.629250	---	22.80	46.00	23.20	N	OFF	20.0
0.629250	35.13	---	56.00	20.87	N	OFF	20.0
2.806350	---	26.22	46.00	19.78	N	OFF	20.0
2.806350	34.96	---	56.00	21.04	N	OFF	20.0
21.619140	---	26.52	50.00	23.48	N	OFF	20.2

21.619140	33.73	---	60.00	26.27	N	OFF	20.2
-----------	-------	-----	-------	-------	---	-----	------



Appendix C. Radiated Spurious Emission

Test Engineer :	John Chuang, JC Liang and Howard Huang	Temperature :	18.2~22.4°C
		Relative Humidity :	66.8~69.1%



2.4GHz 2400~2483.5MHz

NRF (Band Edge @ 3m)

NRF	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	TanRF	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
NRF CH 00 2402MHz		2389.38	51.02	-22.98	74	41.07	27.38	18.63	36.06	111	344	P	H
		2370.06	45.27	-8.73	54	35.39	27.34	18.59	36.05	111	344	A	H
	*	2402	105.81	-	-	95.81	27.41	18.65	36.06	111	344	P	H
	*	2402	105.26	-	-	95.26	27.41	18.65	36.06	111	344	A	H
													H
													H
		2361.03	49.9	-24.1	74	40.06	27.32	18.57	36.05	207	32	P	V
		2381.925	41.87	-12.13	54	31.95	27.36	18.61	36.05	207	32	A	V
	*	2402	97.27	-	-	87.27	27.41	18.65	36.06	207	32	P	V
	*	2402	96.61	-	-	86.61	27.41	18.65	36.06	207	32	A	V
													V
													V
NRF CH 19 2440MHz		2312.38	50.89	-23.11	74	41.14	27.3	18.48	36.03	110	345	P	H
		2312.1	46.16	-7.84	54	36.41	27.3	18.48	36.03	110	345	A	H
	*	2440	105.45	-	-	95.23	27.56	18.73	36.07	110	345	P	H
	*	2440	104.91	-	-	94.69	27.56	18.73	36.07	110	345	A	H
		2486.98	50.68	-23.32	74	40.2	27.75	18.82	36.09	110	345	P	H
		2487.05	43.68	-10.32	54	33.2	27.75	18.82	36.09	110	345	A	H
		2347.1	49.81	-24.19	74	40	27.3	18.55	36.04	206	41	P	V
		2336.04	42.22	-11.78	54	32.43	27.3	18.53	36.04	206	41	A	V
	*	2440	98.01	-	-	87.79	27.56	18.73	36.07	206	41	P	V
	*	2440	97.45	-	-	87.23	27.56	18.73	36.07	206	41	A	V
		2488.52	50.35	-23.65	74	39.86	27.75	18.83	36.09	206	41	P	V
		2498.18	42.65	-11.35	54	32.1	27.79	18.85	36.09	206	41	A	V



NRF	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	TanRF Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
NRF CH 38 2478MHz	*	2478	105.16	-	-	94.72	27.71	18.81	36.08	111	343	P	H
	*	2478	104.57	-	-	94.13	27.71	18.81	36.08	111	343	A	H
		2484.2	54.63	-19.37	74	44.16	27.74	18.82	36.09	111	343	P	H
		2484.08	47.18	-6.82	54	36.71	27.74	18.82	36.09	111	343	A	H
													H
													H
	*	2478	98.8	-	-	88.36	27.71	18.81	36.08	198	36	P	V
	*	2478	98.27	-	-	87.83	27.71	18.81	36.08	198	36	A	V
		2486.24	51.32	-22.68	74	40.85	27.74	18.82	36.09	198	36	P	V
		2484.44	43.54	-10.46	54	33.07	27.74	18.82	36.09	198	36	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

NRF (Harmonic @ 3m)

NRF	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	TanRF Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
NRF CH 00 2402MHz		4804	43.42	-30.58	74	35.41	32.32	12.89	37.2	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		4804	43.91	-30.09	74	35.9	32.32	12.89	37.2	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



NRF	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	TanRF Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
NRF CH 19 2440MHz		4880	43.6	-30.4	74	35.09	32.66	13.11	37.26	-	-	P	H
		7320	47.89	-26.11	74	33.35	36.82	15.89	38.17	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		4880	43.52	-30.48	74	35.01	32.66	13.11	37.26	-	-	P	V
		7320	49.68	-24.32	74	35.14	36.82	15.89	38.17	100	31	P	V
		7320	39.29	-14.71	54	24.75	36.82	15.89	38.17	100	31	A	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



NRF	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	TanRF Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
NRF CH 38 2478MHz		4956	43.54	-30.46	74	34.62	32.92	13.33	37.33	-	-	P	H
		7434	47.95	-26.05	74	33.76	36.43	16.01	38.25	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		4956	43.45	-30.55	74	34.53	32.92	13.33	37.33	-	-	P	V
		7434	47.38	-26.62	74	33.19	36.43	16.01	38.25	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												
		3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											

Emission above 18GHz

2.4GHz NRF (SHF)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	TanRF	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz NRF SHF		24937	42.11	-31.89	74	35.81	39.67	19.77	53.14	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
2.4GHz NRF SHF		24874	42.52	-31.48	74	36.31	39.65	19.74	53.18	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.												

Emission below 1GHz

2.4GHz NRF (LF)

NRF	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	TanRF	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz NRF LF		88.2	26.79	-16.71	43.5	46.19	14.45	1.84	35.69	-	-	P	H
		158.04	31.72	-11.78	43.5	48.16	16.73	2.41	35.58	-	-	P	H
		258.92	30.82	-15.18	46	43.22	19.96	3.02	35.38	-	-	P	H
		299.66	30.25	-15.75	46	42.95	19.33	3.25	35.28	-	-	P	H
		744.89	32.31	-13.69	46	33.3	27.94	4.98	33.91	-	-	P	H
		952.47	34.93	-11.07	46	31.53	30.85	5.67	33.12	-	-	P	H
													H
													H
													H
													H
													H
													H
		47.46	27.37	-12.63	40	46.21	15.52	1.38	35.74	-	-	P	V
		143.49	23.76	-19.74	43.5	39.35	17.7	2.31	35.6	-	-	P	V
		203.63	26.31	-17.19	43.5	43.91	15.2	2.67	35.47	-	-	P	V
		499.48	29.44	-16.56	46	36.08	24	4.14	34.78	-	-	P	V
		589.69	31.85	-14.15	46	36.08	25.72	4.53	34.48	-	-	P	V
		959.26	35.61	-10.39	46	31.9	31.12	5.69	33.1	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												
	3. The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical

A calculation example for radiated spurious emission is shown as below:

NRF	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	TanRF	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
NRF CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Path Loss(dB) = CanRF loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Margin(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Margin(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Margin(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	John Chuang, JC Liang and Howard Huang	Temperature :	18.2~22.4°C
		Relative Humidity :	66.8~69.1%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz

NRF (Band Edge @ 3m)

NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH20-HV Condition : PEAK_BE_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HV Condition : PEAK_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg.	 Site : 03CH20-HV Condition : AVG_BE_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	 Site : 03CH20-HV Condition : AVG_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto







NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	 Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto





NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg.	Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto







NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank
Avg.	Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	Left blank

NRF		2.4GHz 2400~2483.5MHz Band Edge @ 3m	
		NRF CH19 2440MHz - L	
		Vertical	Fundamental
Peak		 Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	Avg.	 Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto



NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH19 2440MHz - R	
	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH38 2478MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg.	 Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto



NRF	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	NRF CH38 2478MHz	
	Vertical	Fundamental
Peak	Site : 03CH20-HY Condition : PEAK_BE_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg.	Site : 03CH20-HY Condition : AVG_BE_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto	Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto







2.4GHz 2400~2483.5MHz

NRF (Harmonic @ 3m)

NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 9120D_02360_ZZ1104 HORIZONTAL	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 9120D_02360_ZZ1104 VERTICAL



NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH00 2402MHz	
	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 HORIZONTAL :	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 VERTICAL :
17.7G ~18G Avg	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 HORIZONTAL :	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 VERTICAL :



NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 HORIZONTAL :	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 VERTICAL :







NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH19 2440MHz	
	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for 14.47G. The plot shows a flat line at approximately 45 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-05-16. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for 14.47G. The plot shows a flat line at approximately 45 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-05-16. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 VERTICAL
17.7G ~18G Avg	Level (dBuV/m) vs Frequency (MHz) plot for 17.7G. The plot shows a flat line at approximately 45 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-05-16. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for 17.7G. The plot shows a flat line at approximately 45 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-05-16. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_221104 VERTICAL



NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH38 2478MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 HORIZONTAL :	Level (dBuV/m) Date: 2023-05-16 Site : 03CH20-HY Condition : PEAK_74 3m 91200_02360_221104 VERTICAL :





NRF	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	NRF CH38 2478MHz	
	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 HORIZONTAL :	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 VERTICAL :
17.7G ~18G Avg	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 HORIZONTAL :	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_221104 VERTICAL :




Emission above 18GHz

2.4GHz NRF (SHF @ 1m)

NRF	2.4GHz 2400~2483.5MHz	
	NRF SHF	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2023-05-24  Site : 03CH20-HY Condition : PEAK_74 1m SHF_00994_221104 HORIZONTAL :	Level (dBuV/m) Date: 2023-05-24  Site : 03CH20-HY Condition : PEAK_74 1m SHF_00994_221104 VERTICAL :

Emission below 1GHz

2.4GHz NRF (LF)

NRF	2.4GHz 2400~2483.5MHz	
	NRF LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH20-HY Condition : QP 3m LF_55606608_221022 HORIZONTAL	 Site : 03CH20-HY Condition : QP 3m LF_55606608_221022 VERTICAL



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
nRF	47.16	106	9.40	10kHz

