

Shenzhen CTL Testing Technology Co., Ltd. Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

FCC PART	15 SUBPART C TEST R	EPORT
Report Reference No	CTL1906131022-WF	
Compiled by	Happy Cuo	Happy Gus
(position+printed name+signature):	(File administrators)	inging Guo
Name of the organization performing		
the tests	Nice Nong	NICP NON9
( position+printed name+signature):	(Test Engineer)	inee wong
Approved by	Ivan Xie	Tim Nie
( position+printed name+signature):	(Manager)	Man ( 1010
Applicant's name	Shenzhen Powerqi Technology (	Co., Ltd.
Address	2nd Floor, A4 Building, Block A, Fa Longgang District, Shenzhen, Chin	ngxing Science & Tech. Park, a
Testing Laboratory Name	Shenzhen CTL Testing Technolo	gy Co., Ltd.
Address	Floor 1-A, Baisha Technology Park Nanshan, Shenzhen 518055 China	, No. 3011, Shahexi Road,
Test specification:		
Standard	FCC Part 15C	
Master TRF	Dated 2011-01	
Test item description	15W Fast Wireless Charger	
FCC ID	2AFP2-FC16C	
Trade Mark	POWERQI	
Model/Type reference:	FC16C	
Transmit Frequency	115~205KHz	
Antenna type	Loop antenna	
Date of receipt of test item:	Jun. 20, 2019	
Date of sampling:	Jun. 20, 2019	
Date of Test Date:	Jun. 20, 2019–Jul. 02, 2019	
Data of Issue:	Jul. 09, 2019	
Result	Pass	
Shenzhen CTL Testing Technology	Co., Ltd. All rights reserved.	

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.



### V1.0

Page 2 of 22

# **TEST REPORT**

Test Report No. :	CTL1906131022-WF	Jul. 09, 2019
		Date of issue

Equipment under Test	:	15W Fast Wireless Charger
Type / Model(s)	÷	FC16C
Applicant	2:	Shenzhen Powerqi Technology Co., Ltd.
Address	1	2nd Floor, A4 Building, Block A, Fangxing Science & Tech. Park, Longgang District, Shenzhen, China
Manufacturer	:	Shenzhen Powerqi Technology Co., Ltd.
Address	:	2nd Floor, A4 Building, Block A, Fangxing Science & Tech. Park, Longgang District, Shenzhen, China

Test Result	
according to the standards on	Positive
page 4:	P

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.



V1	.0 Page 3	6 of 22	Report No.:CTL1906131022-WF
	Co	ontents	
	FCC PART 15 SUBPART C TEST REPOR	хтт.	
<u>1.</u>	TEST STANDARDS	<u></u>	
<u>2.</u>	<u>SUMMARY</u>	<u></u>	
• •			
2.1.	General Remarks		5
2.2.	Short description of the Equipment und	er Test (FUT	) 5
2.4.	EUT operation mode		, 5
2.5.	EUT configuration		5
2.6.	Related Submittal(s) / Grant (s)		5
2.7.	Modifications		5
Summ	ary of Test Results		6
			_
<u>3.</u>	TEST ENVIRONMENT	<u></u>	<u>7</u>
3.1.	Address of the test laboratory		$\frac{1}{7}$
3.3	Environmental conditions		17
3.4.	Statement of the measurement uncertai	ntv	ż
3.5.	Equipments Used during the Test		8
4.	TEST CONDITIONS AND RES	ULTS	
4.1.	AC Power Conducted Emission		9
4.2.	Radiated Emission		12
4.3.	20dB Bandwidth/99% Bandwidth		17
5.	TEST SETUP PHOTOS OF TH	E EUT	

# 6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT ...... 19



# 1. <u>TEST STANDARDS</u>

The tests were performed according to following standards:

FCC Rules Part 15.207,15.209, 15.215(c)

ANSI C63.10-2013









# V1.0

# 2. <u>Summary</u>

# 2.1. General Remarks

Date of receipt of test sample	:	Jun. 20, 2019
Testing commenced on	:	Jun. 20, 2019
	6	
Testing concluded on	:	Jul. 02, 2019

# 2.2. Equipment Under Test

# Power supply system utilised

Power supply voltage	:	0	120V / 60 Hz	0	115V / 60Hz
		0	12 V DC	0	24 V DC
			Other (specified in blank bel	ow)	

DC 5V from USB

# 2.3. Short description of the Equipment under Test (EUT)

A Wireless Charging Pad work frequency range 115-205 KHz. For more details, refer to the user's manual of the EUT. Serial number: Prototype

# 2.4. EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting mode for testing.

# 2.5. EUT configuration

# The following peripheral devices and interface cables were connected during the measurement:

 $\, \bigcirc \,$  - supplied by the manufacturer

supplied by the lab

0	USB Cable	Manufacturer:	Shenzhen Powerqi Technology Co., Ltd.
		Length.:	1.8m
•	Notebook PC	Manufacturer:	DELL
		Model:	PP18L
•	Mobile phone	Manufacturer:	Apple
		Model:	iphone 8 Plus

# 2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AFP2-FC16C** fileing to comply with FCC Part 15, Subpart C Rules.

# 2.7. Modifications

No modifications were implemented to meet testing criteria.

# Summary of Test Results

The EUT is night light with wireless charger, The test summary of the EUT listed as below:

	Test Standards	Test Result
Electric Field Radiated Emissions	FCC Part 15 C (Section15.209)	PASS
20dB Bandwidth/99% Bandwidth	FCC Part 15 C (Section15.215(c))	PASS
Conducted Emissions	FCC Part 15 C (Section15.207)	PASS

Remark: The measurement uncertainty is not included in the test result.







#### V1.0

# 3. TEST ENVIRONMENT

### 3.1. Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd. Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

# 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

# CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

### A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### IC Registration No.: 9518B

### CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9518B on Jan. 22, 2019.

# FCC-Registration No.: 399832

# **Designation No.: CN1216**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

# 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

# 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested

may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

# 3.5. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2019/05/24	2020/05/23
LISN	R&S	ESH2-Z5	860014/010	2019/05/24	2020/05/23
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2019/05/24	2020/05/23
EMI Test Receiver	R&S	ESCI	1166.5950.03	2019/05/24	2020/05/23
Spectrum Analyzer	Agilent	E4407B	MY41440676	2019/05/24	2020/05/23
Spectrum Analyzer	Agilent	N9020	US46220290	2019/05/24	2020/05/23
Controller	EM Electronics	EM 1000	060859	2019/05/24	2020/05/23
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2019/05/24	2020/05/23
Active Loop Antenna	Da Ze	ZN30900A	/	2019/05/24	2020/05/23
Amplifier	Agilent	8449B	3008A02306	2019/05/24	2020/05/23
Amplifier	Agilent	8447D	2944A10176	2019/05/24	2020/05/23
Temperature/Humidi ty Meter	Gangxing	CTH-608	02	2019/05/24	2020/05/23
High-Pass Filter	micro-tranics	HPM50108	G174	2019/05/24	2020/05/23
High-Pass Filter	micro-tranics	HPM50111	G142	2019/05/24	2020/05/23
Coaxial Cables	HUBER+SUHNE R	SUCOFLEX 104PEA-10M	10m	2019/05/24	2020/05/23
Coaxial Cables	HUBER+SUHNE R	SUCOFLEX 104PEA-3M	3m	2019/05/24	2020/05/23
Coaxial Cables	HUBER+SUHNE R	SUCOFLEX 104PEA-3M	3m	2019/05/24	2020/05/23
RF Cable	Megalon	RF-A303	N/A	2019/05/24	2020/05/23

The calibration interval was one year

# 4. TEST CONDITIONS AND RESULTS

# 4.1. AC Power Conducted Emission

### **TEST CONFIGURATION**



### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC5V power from USB port of PC, PC received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a

# receiver bandwidth of 9kHz.

### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

<b>Francis</b>	Maximum RF Line Voltage (dBµV)						
(MHz)	CLAS	S A	CLASS B				
	Q.P.	Ave.	Q.P.	Ave.			
0.15 - 0.50	79	66	66-56*	56-46*			
0.50 - 5.00	73	60	56	46			
5.00 - 30.0	73	60	60	50			

\* Decreasing linearly with the logarithm of the frequency

# TEST RESULTS



### MEASUREMENT RESULT: "CTL190621614\_fin"

2019-6-21 (	)9:59??						
Frequency MHz	γ Level z dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154000 0.166000 0.190000 0.410000 0.474000	52.40   44.20   44.60   26.60   35.20	11.2 11.2 11.2 11.2 11.2 11.2	66 65 64 58 56	13.4 21.0 19.4 31.0 21.2	QP QP QP QP QP	L1 L1 L1 L1 L1	GND GND GND GND GND
29.984000	38.00	11.7	60	22.0	QP	L1	GND

#### MEASUREMENT RESULT: "CTL190621614 fin2"

2019-6-21 09: Frequency MHz	59?? Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
28.934000	31.40	11.7	50	18.6	AV	L1	GND
29.198000	34.50	11.7	50	15.5	AV	L1	GND
29.462000	35.00	11.7	50	15.0	AV	L1	GND
29.726000	32.80	11.7	50	17.2	AV	L1	GND
29.852000	34.20	11.7	50	15.8	AV	L1	GND
29.984000	37.00	11.7	50	13.0	AV	L1	GND



#### Page 11 of 22

#### SCAN TABLE: "Voltage (9K-30M)FIN" Short Description: 150K-30M Voltage



#### MEASUREMENT RESULT: "CTL190621613\_fin"

2019-6-21 09:	55??						
Frequency	Level	Transd	Limit	Margin	Detector	Line	ΡE
MHz	dBµV	dB	dBµV	dB			
0.178000	45.20	11.2	65	19.4	QP	Ν	GND
0.182000	44.30	11.2	64	20.1	QP	Ν	GND
0.186000	42.50	11.2	64	21.7	QΡ	Ν	GND
20.216000	36.30	11.5	60	23.7	QP	Ν	GND
20.384000	37.60	11.5	60	22.4	QP	Ν	GND
20.642000	36.10	11.5	60	23.9	QP	Ν	GND

MEASUREMENT RESULT: "CTL190621613\_fin2"

2019-6-21 09 Frequency MHz	9:55?? Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
17.708000 28.928000 29.186000 29.450000 29.708000 29.966000	21.80 12.80 12.70 12.70 12.70 12.00	11.3 11.7 11.7 11.7 11.7 11.7 11.7	50 50 50 50 50 50	28.2 37.2 37.3 37.3 37.3 37.3 38.0	AV AV AV AV AV AV	N N N N N	GND GND GND GND GND GND

# 4.2. Radiated Emission

### **TEST CONFIGURATION**

Radiated Emission Test Set-Up Frequency range 9KHz – 30MHz



Frequency range 30MHz – 1000MHz



### TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- 3 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4 Repeat above procedures until all frequency measurements have been completed.

#### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

### FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency	FS	RA	AF	CL	AG	Transd
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dB)	(dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

Transd=AF +CL-AG

#### RADIATION LIMIT

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

#### 9k~30MHz:

Frequency Range (MHz)	E-field Strength Limit @ 30m (mV/m)	E-field Strength Limit @ 3m (dBµV/m)
0.009-0.490	2400/F(kHz)	129-94
0.490-1.705	24000/F(kHz)	74-63
1.705-30	30	70

Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

Extrapolation(dB) =  $40\log_{10}$  (Measurement Distance/Specification Distance)

Note:

(1) The tighter limit shall apply at the edge between two frequency bands.

(2) dBuV/m = 20\*log(uV/m)

# 30M~1GHz:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

Note:

(1) The tighter limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.

### TEST RESULTS

### WORST-CASE RADIATED EMISSION BELOW 30 MHz

Frequency	Reading	Polar	Antenna Factor	Cable Loss	Emission Levels	Limits at 3m	Detector Mode
(MHz)	(dBµV/m)	Loop	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	
0.134(F)	47.95	Loop	23.64	0.01	71.60	105.06	PK
0.134(F)	44.13	Loop	23.64	0.01	67.78	85.06	AV
0.110	33.87	Loop	23.55	0.01	57.43	106.78	PK
0.110	30.62	Loop	23.55	0.01	54.18	86.78	AV
0.495	34.79	Loop	25.07	-0.17	59.69	73.71	QP
1.167	34.95	Loop	27.12	-0.25	61.82	66.26	QP
2.133	33.91	Loop	23.91	-0.24	57.58	69.54	QP

Remark: 1. Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

- 2. The test limit distance is 3m limit.
- 3. PK means Peak Value, QP means Quasi Peak Value, AV means Average Value.
- 4. F means Fundamental Frequency.





#### Page 15 of 22

#### Radiated Emission Test Data 30-1000MHz:





#### MEASUREMENT RESULT: "CTL190620507\_red"

2019-6-20 9:4	47								
Frequency	Level	Transd	Limit	Margin	Det.	Height	Azimuth	Polarization	
MHz	dB礦/m	dB	dB礦/m	dB		cm	deg		
0.05 000000	26.00	15 6	10.0						
365.620000	36.20	15.6	46.0	9.8		0.0	0.00	HORIZONTAL	
433.520000	33.60	17.1	46.0	12.4		0.0	0.00	HORIZONTAL	
499.480000	37.60	18.2	46.0	8.4		0.0	0.00	HORIZONTAL	
565.440000	34.50	19.4	46.0	11.5		0.0	0.00	HORIZONTAL	
633.340000	33.50	20.7	46.0	12.5		0.0	0.00	HORIZONTAL	
864.200000	34.70	23.3	46.0	11.3		0.0	0.00	HORIZONTAL	







#### MEASUREMENT RESULT: "CTL190620505\_red"

2019-6-20 9:4	15							
Frequency MHz	Level dB礦/m	Transd dB	Limit dB礦/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
39.700000	32.90	14.8	40.0	7.1		0.0	0.00	VERTICAL
78.500000	26.80	10.3	40.0	13.2		0.0	0.00	VERTICAL
152.220000	34.60	15.2	43.5	8.9		0.0	0.00	VERTICAL
165.800000	31.00	14.7	43.5	12.5		0.0	0.00	VERTICAL
499.480000	31.30	18.2	46.0	14.7		0.0	0.00	VERTICAL
631.400000	36.40	20.7	46.0	9.6		0.0	0.00	VERTICAL



# 4.3. 20dB Bandwidth/99% Bandwidth

### TEST CONFIGURATION

EUT	SPECTRUM ANALYZER

### TEST PROCEDURE

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 10Hz RBW and 30Hz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### <u>LIMIT</u>

The 20dB bandwidth shall be less than 80% of the permitted frequency band.

### TEST RESULTS



TX: 134 KHz

Result: 2.745kHz







# 5. Test Setup Photos of the EUT

























# 6. External and Internal Photos of the EUT











#### Page 21 of 22

#### Internal photos







Loop Antenna





2

V1.0

### Page 22 of 22





CL







