







11.6. APPENDIX F: FREQUENCY STABILITY

11.6.1. Test Result

Frequency Error vs. Voltage									
802.11a:5200MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
TN	VL	5199.9790	-4.03	5200.0036	0.69	5199.9809	-3.67	5199.9851	-2.87
TN	VN	5200.0181	3.49	5200.0045	0.86	5200.0171	3.29	5199.9809	-3.67
TN	VH	5199.9850	-2.88	5199.9837	-3.13	5200.0026	0.50	5200.0004	0.09
Frequency Error vs. Temperature									
802.11a:5200MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
40	VN	5199.9999	-0.03	5200.0167	3.21	5199.9904	-1.85	5199.9910	-1.73
30	VN	5200.0199	3.82	5200.0163	3.14	5199.9865	-2.60	5199.9969	-0.60
20	VN	5199.9804	-3.78	5199.9804	-3.77	5199.9969	-0.59	5199.9977	-0.45
10	VN	5200.0036	0.69	5199.9917	-1.59	5199.9802	-3.80	5199.9759	-4.63
0	VN	5200.0088	1.69	5200.0169	3.25	5199.9993	-0.13	5200.0121	2.32

Note:

1. All antennas, test modes and test channels have been tested, only the worst data record in the report.
2. For the detail Test Conditions, please refer to section 7.5 TEST ENVIRONMENT.

Frequency Error vs. Voltage									
802.11a:5825MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
TN	VL	5824.9937	-1.09	5825.0209	3.58	5824.9880	-2.06	5825.0187	3.21
TN	VN	5825.0170	2.92	5824.9750	-4.29	5824.9825	-3.01	5825.0193	3.32
TN	VH	5824.9939	-1.06	5824.9847	-2.63	5825.0080	1.37	5825.0010	0.17
Frequency Error vs. Temperature									
802.11a:5825MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
40	VN	5824.9804	-3.36	5824.9873	-2.18	5825.0207	3.56	5825.0170	2.93
30	VN	5825.0234	4.02	5824.9963	-0.64	5825.0082	1.41	5825.0225	3.87
20	VN	5824.9871	-2.21	5825.0042	0.72	5824.9914	-1.48	5825.0010	0.18
10	VN	5824.9866	-2.30	5824.9891	-1.86	5824.9803	-3.38	5825.0208	3.58
0	VN	5824.9788	-3.65	5824.9813	-3.20	5825.0057	0.98	5825.0152	2.60

Note:

1. All antennas, test modes and test channels have been tested, only the worst data record in the report.
2. For the detail Test Conditions, please refer to section 7.5 TEST ENVIRONMENT.

11.7. APPENDIX G: DUTY CYCLE

11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11A-CDD	1.40	1.45	0.9655	96.55	0.15	0.71	1
11AX20MIMO	1.02	1.08	0.9444	94.44	0.25	0.98	2
11AX40MIMO	0.54	0.59	0.9153	91.53	0.38	1.85	2
11AX80MIMO	0.28	0.34	0.8235	82.35	0.84	3.57	4

Note:


Duty Cycle Correction Factor= $10\log(1/x)$.


Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

11.7.2. Test Graphs





END OF REPORT