

EMI TEST REPORT

FCC CERTIFICATION / ISED

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632
United States

Date of Receipt: May 09, 2018**Date of Issue:** May 24, 2018**Test Report No.** HCT-EM-1805-FI008**FCC ID
IC****ZNFX510WM
2703C-X510WM**

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
ICES-003 Issue 6 Class B / ANSI C63.4-2014
EUT Type: Multi-band GSM/WCMDA/LTE Phone with BT and WiFi
Model Name: LM-X510WM
Additional Model Name: LMX510WM, X510WM
TA Information: Model Name: MCS-H06WD, Manufacturer: DONGDO
Date of Test: May 15, 2018 – May 23, 2018

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Wook Yi
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



REVISION HISTORY

The revision history for this document is shown in table.

Report No.	Issue Date	Description
HCT-EM-1805-FI008	May 24, 2018	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s)	4
1.3 Test Facility	5
1.4 Calibration of Measuring Instrument	5
1.5 Tested System Details	6
1.6 Cable Description	6
1.7 Noise Suppression Parts on Cable. (I/O Cable)	6
2. MEASUREMENT UNCERTAINTY	7
3. DESCRIPTION OF TEST	8
3.1 Measurement of Conducted Emission.....	8
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	11
4.1 Conducted Emission Test	11
4.2 Radiated Emission Test	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
5.1 Conducted Emission Test	12
5.2 Radiated Emission Test	19
6. LIST OF TEST EQUIPMENT.....	21
7. CONCLUSION.....	22
8. APPENDIX A. TEST SETUP PHOTOGRAPHS	23



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFX510WM
IC	2703C-X510WM
Model	LM-X510WM
Additional Model	LMX510WM, X510WM
EUT Type	Multi-band GSM/WCDMA/LTE Phone with BT and WiFi
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 2 496 MHz to 2 570 MHz (LTE B7) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 704 MHz to 716 MHz (LTE B17) 1 710 MHz to 1 780 MHz (LTE B66) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 2 516 MHz to 2 690 MHz (LTE B7) 729 MHz to 746 MHz (LTE B12) 746 MHz to 756 MHz (LTE B13) 734 MHz to 746 MHz (LTE B17) 2 110 MHz to 2 200 MHz (LTE B66) 2 402 MHz to 2 480 MHz (Bluetooth)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	
Filing the EMI Measurement Facility (3 m Semi Anechoic Chamber and Shielded Room)	IC 5944A-4
Filing the EMI Measurement Facility (10 m Semi-Anechoic Chamber)	IC 5944A-2

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer	FCC ID/ IC/ DoC
EUT	LM-X510WM	-	LG	ZNFX510WM 2703C-X510WM
Data cable	EAD63769721	-	Ningbo Broad	-
Earphone	EAB64468444	-	CRESYN	-
Travel adaptor	MCS-H06WD	-	DONGDO	-
Micro SD card	SAMSUNG EVO+ microSDXC CLASS10 UHS-I (256 GB)	-	SAMSUNG	-

1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P)1.0
	Earphone	N/A	Y	(D)1.2

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB ($k = 2$)
3 m Radiated Emissions (30 MHz to 1 GHz)	5.20 dB ($k = 2$)
3 m Radiated Emissions (1 GHz to 18 GHz)	5.24 dB ($k = 2$)
3 m Radiated Emissions (18 GHz to 40 GHz)	5.40 dB ($k = 2$)



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Non-Conductive Table
Power Line: 120 VAC



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

Operation Mode: ☒ Camera (Front) & MP3 mode
☒ Camera (Rear) & FM Radio mode
☒ Idle mode

NOTE. *The worst-case emissions are reported.*

4. 2 Radiated Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

Operation Mode: ☒ Camera (Front) & MP3 mode
☒ Camera (Rear) & FM Radio mode
☒ Idle mode

NOTE. *The worst-case emissions are reported.*



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Operation Mode	Camera (Front) & MP3 mode
Kind of Test Site	Shielded Room
Temperature	23.0 °C
Relative Humidity	47.2 %
Test Date	May 17, 2018

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.524000	37.5	9.000	L1	9.7	18.5	56.0
0.530000	43.3	9.000	L1	9.7	12.7	56.0
0.536000	44.1	9.000	L1	9.7	11.9	56.0
0.540000	42.8	9.000	L1	9.7	13.2	56.0
0.574000	38.0	9.000	L1	9.7	18.0	56.0
0.578000	38.2	9.000	L1	9.7	17.8	56.0
1.104000	38.6	9.000	L1	9.8	17.4	56.0
1.116000	39.4	9.000	L1	9.8	16.6	56.0
1.124000	39.6	9.000	L1	9.8	16.4	56.0
1.128000	39.4	9.000	L1	9.8	16.6	56.0
1.138000	39.9	9.000	L1	9.8	16.1	56.0
1.148000	40.0	9.000	L1	9.8	16.0	56.0
12.474000	37.1	9.000	L1	10.2	22.9	60.0
12.952000	34.9	9.000	L1	10.2	25.1	60.0
13.156000	35.0	9.000	L1	10.2	25.0	60.0
13.540000	36.7	9.000	L1	10.2	23.3	60.0
13.762000	35.8	9.000	L1	10.2	24.2	60.0
14.028000	35.7	9.000	L1	10.2	24.3	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.438000	28.4	9.000	L1	9.7	18.7	47.1
0.444000	28.7	9.000	L1	9.7	18.3	47.0
0.532000	36.8	9.000	L1	9.7	9.2	46.0
0.536000	38.0	9.000	L1	9.7	8.0	46.0
0.570000	27.7	9.000	L1	9.7	18.3	46.0
0.580000	31.3	9.000	L1	9.7	14.7	46.0
1.074000	31.9	9.000	L1	9.8	14.1	46.0
1.106000	32.3	9.000	L1	9.8	13.7	46.0
1.116000	32.8	9.000	L1	9.8	13.2	46.0
1.124000	33.0	9.000	L1	9.8	13.0	46.0
1.138000	32.9	9.000	L1	9.8	13.1	46.0
1.150000	32.6	9.000	L1	9.8	13.4	46.0
12.474000	25.1	9.000	L1	10.2	24.9	50.0
12.574000	25.7	9.000	L1	10.2	24.3	50.0
12.952000	24.7	9.000	L1	10.2	25.3	50.0
13.156000	25.5	9.000	L1	10.2	24.5	50.0
13.540000	25.5	9.000	L1	10.2	24.5	50.0
14.028000	25.4	9.000	L1	10.2	24.6	50.0



Figure 2: Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.424000	34.8	9.000	N	9.7	22.5	57.4
0.456000	36.3	9.000	N	9.7	20.5	56.8
0.530000	38.5	9.000	N	9.7	17.5	56.0
0.538000	40.3	9.000	N	9.7	15.7	56.0
0.542000	39.1	9.000	N	9.7	16.9	56.0
0.546000	35.7	9.000	N	9.7	20.3	56.0
1.070000	37.9	9.000	N	9.8	18.1	56.0
1.078000	38.3	9.000	N	9.8	17.7	56.0
1.090000	38.6	9.000	N	9.8	17.4	56.0
1.122000	39.5	9.000	N	9.8	16.5	56.0
1.144000	39.6	9.000	N	9.8	16.4	56.0
1.148000	40.0	9.000	N	9.8	16.0	56.0
10.116000	28.4	9.000	N	10.3	31.6	60.0
13.632000	30.7	9.000	N	10.4	29.3	60.0
13.674000	29.5	9.000	N	10.4	30.5	60.0
14.164000	30.0	9.000	N	10.4	30.0	60.0
14.260000	31.4	9.000	N	10.4	28.6	60.0
14.266000	31.5	9.000	N	10.4	28.5	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.424000	26.8	9.000	N	9.7	20.6	47.4
0.434000	28.5	9.000	N	9.7	18.7	47.2
0.456000	27.1	9.000	N	9.7	19.7	46.8
0.464000	27.1	9.000	N	9.7	19.6	46.6
0.534000	33.0	9.000	N	9.7	13.0	46.0
0.538000	33.3	9.000	N	9.7	12.7	46.0
1.078000	31.8	9.000	N	9.8	14.2	46.0
1.090000	32.2	9.000	N	9.8	13.8	46.0
1.116000	32.8	9.000	N	9.8	13.2	46.0
1.122000	32.6	9.000	N	9.8	13.4	46.0
1.130000	32.4	9.000	N	9.8	13.6	46.0
1.148000	32.4	9.000	N	9.8	13.6	46.0
10.116000	20.7	9.000	N	10.3	29.3	50.0
12.522000	20.6	9.000	N	10.4	29.4	50.0
12.662000	21.2	9.000	N	10.4	28.8	50.0
13.632000	21.4	9.000	N	10.4	28.6	50.0
14.164000	20.0	9.000	N	10.4	30.0	50.0
14.266000	22.7	9.000	N	10.4	27.3	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operation Mode	Camera (Front) & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.3/ 22.3 °C
Relative Humidity	39.8/ 43.9 %
Test Date	May 15 / May 16, 2018

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
31.026400	27.9	100.0	V	30.0	18.8	12.1	40.0
86.892000	23.6	191.7	H	113.0	14.8	16.4	40.0
169.818400	25.0	99.8	V	265.0	19.5	18.5	43.5
188.032000	25.8	118.8	H	153.0	18.0	17.7	43.5
210.299200	18.1	116.8	V	237.0	17.2	25.4	43.5
944.764800	31.6	99.8	H	138.0	31.6	14.4	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2 690 MHz
Tested Frequency Range	1 GHz to 18 GHz
Worst Case of Operation Mode	Camera (Front) & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.9 °C
Relative Humidity	44.8 %
Test Date	May 23, 2018

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
2456.650000	33.1	276.5	V	37.0	-24.6	40.9	74.0
4628.925000	36.3	350.1	V	353.0	-19.3	37.7	74.0
6273.675000	38.8	150.0	V	81.0	-15.7	35.2	74.0
7558.195000	42.2	248.7	H	145.0	-12.1	31.8	74.0
8780.510000	42.6	99.7	H	0.0	-11.6	31.4	74.0
9861.435000	43.3	99.8	V	112.0	-10.0	30.7	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
2456.650000	20.0	276.5	V	37.0	-24.6	34.0	54.0
4628.925000	23.4	350.1	V	353.0	-19.3	30.6	54.0
6273.675000	25.9	150.0	V	81.0	-15.7	28.1	54.0
7558.195000	29.5	248.7	H	145.0	-12.1	24.5	54.0
8780.510000	29.9	99.7	H	0.0	-11.6	24.2	54.0
9861.435000	30.2	99.8	V	112.0	-10.0	23.8	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	CAL Date
<u>Conducted Emission</u>					
☐ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.20.2017
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.27.2017
☐ LISN	Rohde & Schwarz	ENV216	100073	1 year	07.18.2017
☒ LISN	Rohde & Schwarz	ENV216	102245	1 year	12.20.2017
☒ Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
☒ Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	04.06.2017
☐ Antenna master	HD GmbH	MA240	240/520	N/A	-
☐ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	-	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	-	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
☒ Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	-	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	-	N/A	-
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
☒ Low Noise Amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.06.2018
☐ Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.20.2017
☐ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	2 year	12.05.2017
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Multi-band GSM/WCMDA/LTE Phone with BT and WiFi, Model: LM-X510WM** complies with §15.107 and §15.109 of the FCC rules and ICES-003 Issue 6 of the IC rules.



8. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Appendix A