

APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-“).

This device is enabled with Qualcomm® Smart Transmit Gen2 with pre-defined antenna groups (AG0 and AG1). Simultaneous transmission analysis is performed per antenna groups. Below analysis demonstrates the mutually exclusive operation of AG0 and AG1, and the compliance between each antenna group with non-Smart Transmit Radios. For this model, WWAN/WLAN/BT Radios are managed under Smart Transmit. Non-Smart Transmit Radios include NFC/UWB.

When operating in the same antenna group, the compliance under dynamic transmission condition, including all supported simultaneous transmission scenarios, should be assessed and demonstrated in the Part 2 Report during algorithm validation. Therefore, no further simultaneous analysis is needed within an antenna group.

E.3 Antenna Groups

The 2nd generation of Smart Transmit (GEN2) operates based on pre-defined antenna groups (AG). Sub6/ WLAN/BT Tx antennas in the device are grouped based on spatial variation of RF exposure distributions, where the RF exposure of one AG is mutually exclusive from other AG. This is accomplished by demonstrating either of below conditions for all exposure scenarios:

- a) Sum of SAR of one antenna from each of the sub6 AGs and the RF exposure from radios outside Smart Transmit is less than regulatory limits. This condition must be demonstrated for all antenna combinations of sub6 AGs.

(or)

- b) Every antenna from each sub6 AG meets SPLSR criteria (Section 4.3.2(c) in FCC KDB 447498 D04) with every antenna from another sub6 AG. These criteria must be demonstrated for all antenna combinations for each pair of AGs.

This device supports two AGs: AG0 and AG1, with AG0 having 4 antennas (0, 1, 2, 3) and AG1 having 5 antennas (6, 7, 9, 10, 11). The conditions are verified through the following criteria:

- i) Sum of SAR: Demonstrate that the sum of *max.norm.exp.AG0* and *max.norm.exp.AG1* and the reported normalized SAR values from radios outside Smart Transmit (denoted as *reported.norm.exp.ER*) should be less than the regulatory limit for each supported DSI following the below procedure:

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 1 of 7

1. Obtain the worst-case *adjusted SAR* for each antenna group, i.e., maximum *reported SAR* at EFS $P_{limit} + \text{unc}$ (or max of $\{P_{max} + \text{unc}, \text{EFS } P_{limit}\}$ when $\text{EFS } P_{limit} > P_{max}$) out of all supported technologies, frequency bands and antennas in AG0 and AG1, then normalized to the regulatory limit to get the maximum normalized SAR for each antenna group, denoted as *max.norm.exp.AG0* and *max.norm.exp.AG1*
2. For external radios outside of Smart Transmit (NFC/UWB): Obtain the worst-case RF exposure for each external radio normalized to regulatory limit to get the normalized SAR for each external radio, denoted as *reported.norm.exp.NFC* and *reported.norm.exp.UWB*
3. Demonstrate that the sum of these RF exposures meets: $\{max.norm.exp.AG0 + max.norm.exp.AG1 + \text{normalized NFC SAR} + \text{normalized UWB SAR}\} \leq 1$.

ii) SPLSR or composite exposure distribution criteria: when TER sum of an antenna pair is over the limit for a DSI/exposure position, SPLSR or composite exposure distribution can be done to demonstrate simultaneous transmission compliance.

1. SPLSR analysis for sub6 antenna pairs: For each antenna, obtain the highest *adjusted SAR* at EFS $P_{limit} + \text{unc}$ (or max of $\{P_{max} + \text{unc}, \text{EFS } P_{limit}\}$ when $\text{EFS } P_{limit} > P_{max}$) out of all supported technologies for each frequency band. Using these values, demonstrate for a given DSI that every antenna from one AG meets SPLSR criteria with every antenna in another AG for all frequency bands. This criterion must be demonstrated for all antenna pair combinations irrespective of supported simultaneous transmission scenarios as given below for each DSI. As it can be seen, these include all combinations of antenna groups, antennas, and frequency bands.
 - If SPLSR criteria evaluation and analysis is needed to determine compliance for a certain DSI configuration, SPLSR is performed by taking the highest reported SAR for each of the supported technologies and bands per antenna, along with the peak SAR locations. Per Qualcomm guidance, only Y-axis coordinates are recorded in the analysis for calculation simplicity (assumes all 0mm of separation on the x-axis). Peak locations are documented in the Highest Report SAR and Hotspot Location Section below for each DSI configuration. For bottom AG0, Y_max coordinates represents the worst-case hotspot location that is closest to the top AG1. Similarly, for top AG1, Y_min coordinate represents the worst-case hotspot location that is closest to the bottom AG0
 - The following formula is used to calculate the SPLSR between AG0 and AG1 for each exposure configuration:

$$SPLSR = \frac{(Max\ SAR\ AG0 + Max\ SAR\ AG1)^{1.5}}{|Y_{max} - Y_{min}|}$$

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 2 of 7

E.4 Head (DSI = 1) SAR Antenna Group Analysis

Table E-1
DSI=1 Held-to-ear AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Head SAR	Configuration	0	1	2	3	Max
	Right Cheek	0.208	0.207	0.071	0.010	0.208
	Right Tilt	0.159	0.121	0.022	0.005	0.159
	Left Cheek	0.208	0.093	0.044	0.009	0.208
	Left Tilt	0.153	0.137	0.023	0.002	0.153

Table E-2
DSI=1 Held-to-ear AG1 Highest Adjusted SAR

AG1 Ratio to Limit							
Head SAR	Configuration	6	7	9	10	11	Max
	Right Cheek	0.456	0.523	0.551	0.549	0.551	0.551
	Right Tilt	0.350	0.661	0.250	0.054	0.250	0.661
	Left Cheek	0.624	0.345	0.282	0.694	0.316	0.694
	Left Tilt	0.535	0.417	0.118	0.096	0.085	0.535

Table E-3
DSI=1 Held-to-ear AG Verification

Head SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Right Cheek	0.208	0.551	0.759
	Right Tilt	0.159	0.661	0.820
	Left Cheek	0.208	0.694	0.902
	Left Tilt	0.153	0.535	0.688

Notes:

1. For all combinations where the TER sum of AG0+AG1 is less than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 3 of 7

E.5 Body-worn (DSI = 0) SAR Antenna Group Analysis

Table E-4
DSI=0 Body-worn AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Bodyworn SAR	Configuration	0	1	2	3	Max
	Back	0.463	0.390	0.151	0.464	0.464

Table E-5
DSI=0 Body-worn AG1 Highest Adjusted SAR

AG1 Ratio to Limit							
Bodyworn SAR	Configuration	6	7	9	10	11	Max
	Back	0.468	0.529	0.369	0.134	0.305	0.529

Table E-6
DSI=0 Body-worn AG Verification

Bodyworn SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.464	0.529	0.993

Notes:

1. For all combinations where the TER sum of AG0+AG1 is less than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 4 of 7

E.6 Hotspot (DSI = 0) SAR Antenna Group Analysis

Table E-7
DSI=0 Hotspot AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Hotspot SAR	Configuration	0	1	2	3	Max
	Back	0.463	0.390	0.151	0.464	0.464
	Front	0.278	0.264	0.079	0.016	0.278
	Top	-	-	-	-	-
	Bottom	0.674	0.549	0.038	0.088	0.674
	Right	0.324	0.417	0.291	-	0.417
	Left	0.211	-	-	0.026	0.211

Table E-8
DSI=0 Hotspot AG1 Highest Adjusted SAR

AG1 Ratio to Limit							
Hotspot SAR	Configuration	6	7	9	10	11	Max
	Back	0.435	0.529	0.339	0.134	0.305	0.529
	Front	0.584	0.260	0.273	0.081	0.273	0.584
	Top	0.611	0.636	0.122	0.001	0.076	0.636
	Bottom	-	-	-	-	-	-
	Right	0.423	-	0.108	-	0.108	0.423
	Left	0.372	0.104	0.513	0.060	0.513	0.513

Table E-9
DSI=0 Hotspot AG Verification

Hotspot SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.464	0.529	0.993
	Front	0.278	0.584	0.862
	Top	-	0.636	0.636
	Bottom	0.674	-	0.674
	Right	0.417	0.423	0.840
	Left	0.211	0.513	0.724

Notes:

1. For all combinations where the TER sum of AG0+AG1 is less than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 5 of 7

E.7 Phablet (DSI = 0) SAR Antenna Group Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

Table E-10
DSI=0 Phablet AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Phablet SAR	Configuration	0	1	2	3	Max
	Back	-	-	-	-	-
	Front	-	-	-	-	-
	Top	-	-	-	-	-
	Bottom	-	-	-	-	-
	Right	-	-	-	-	-
	Left	-	-	-	-	-

Table E-11
DSI=0 Phablet AG1 Highest Adjusted SAR

AG1 Ratio to Limit							
Phablet SAR	Configuration	6	7	9	10	11	Max
	Back	0.373	-	0.394	-	0.394	0.394
	Front	0.171	-	0.541	-	0.541	0.541
	Top	0.086	-	0.092	-	0.011	0.092
	Bottom	-	-	-	-	-	-
	Right	0.060	-	0.188	-	0.188	0.188
	Left	0.707	-	0.707	-	0.010	0.707

Table E-12
Simultaneous Transmission Scenarios of NFC/UWB (Phablet)

	Configuration	NFC	UWB
		Ratio to Limit	Ratio to Limit
Phablet SAR	Back	0.003	0.001
	Front	0.000	0.001
	Top	0.000	0.001
	Bottom	-	-
	Right	-	-
	Left	0.000	0.000

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 6 of 7

Table E-13
DSI=0 Phablet AG Verification

	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	NFC Ratio to Limit	UWB Ratio to Limit	AG0 + AG1 + NFC + UWB Ratio to Limit
Phablet SAR	Back	-	0.394	0.003	0.001	0.398
	Front	-	0.541	0.000	0.001	0.542
	Top	-	0.092	0.000	0.001	0.093
	Bottom	-	-	-	-	-
	Right	-	0.188	-	-	0.188
	Left	-	0.707	0.000	0.000	0.707

Notes:

1. For all combinations where the TER sum of AG0+AG1 +UWB+NFC is less than 1, there's no further analysis required for compliance demonstration.

E.8 Conclusion

The above numerical summed SAR results for all the combinations of antenna groups are sufficient to show that AG0 is mutually exclusive from AG1 and that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID A3LSMS928B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 7 of 7