# FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### **Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Report No.: RSZ201210001-00A

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	$*(180/f^2)$	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz

#### Result

### **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.247 Page 9 of 23

<sup>\* =</sup> Plane-wave equivalent power density

Frequency (MHz)	Antenna Gain		Maximum Tune Up Conducted Power		Evaluation Distance	Power Density	MPE Limit
	(dBi)	(numeric)	(dBm)	(mW)	(cm)	$(mW/cm^2)$	(mW/cm <sup>2</sup> )
2402-2480	3.05	2.02	6.5	4.47	20	0.002	1
5150-5250	4.42	2.77	12.0	15.85	20	0.009	1
5725-5850	4.42	2.77	12.5	17.78	20	0.010	1

Report No.: RSZ201210001-00A

## Note:

- 1) To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.
- 2) Bluetooth and 5GHz Wi-Fi can transmit simultaneously for this device.
- 3) Simultaneous transmitting consideration:

The ratio=MPE<sub>DSS</sub>/limit+MPE<sub>NII</sub>/limit= $0.002+0.010=0.012 \le 1.0$ , so simultaneous exposure is not required.

**Result: Pass** 

FCC Part 15.247 Page 10 of 23