M. Flom Associates, Inc. - Global Compliance Center 3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176 www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: May 16, 2000

Federal Communications Commission Via: Electronic Filing

| Attention: | Authorization & Evaluation Division |
|---|---|
| Applicant: Equipment: FCC ID: FCC Rules: | Kenwood Communications Corporation TK-760HG-1 and TK-762HG-1 ALH29373210 22, 74, 90, 90.201 and 47 CFR 1.1307, Environmental Assessment |

Gentlemen:

The attached R.F. EXPOSURE report is being sent to INDUSTRY CANADA and is being '**copied**' here for your information that this unit is in compliance.

Sincerely yours,

Morton Flom, P. Eng.

M. Flom Associates, Inc. - Global Compliance Center 3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176 www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date:

May 16, 2000

INDUSTRY CANADA Certification & Engineering Bureau 3701 Carling Avenue, Bldg. 94 P.O. Box 11490, Station "H" Ottawa, Ontario, Canada K2H 8S2

Attention: Certification Section

| Applicant: | Kenwood Communications Corporation |
|----------------|---|
| Equipment: | Kenwood TK-760HG-1 and TK-762HG-1 |
| Specification: | RSS-102, Issue 1 (Provisional) Sept. 25, 1999 |
| | [R.F. Exposure (Calculated Results)] |

Gentlemen:

On behalf of the Applicant, the RF Exposure Evaluation testing to meet the requirements of Health Canada's Safety Code 6 has been successfully completed. Copies of the report have been sent to the Applicant/Manufacturer.

For your files, attached is a copy of the Declaration of Compliance included with the report.

Should you need any further information, kindly contact the writer who is authorized to act as agent.

M. Flom Associates, Inc. per:

Morton Flom, P. Eng.

enclosure(s) cc: Applicant MF/cvr

MFA p0040012, d0050032



ENVIRONMENTAL ASSESSMENT

for

MODEL: Kenwood TK-760HG-1 and TK-762HG-1

VHF FM Mobile Transceiver

to

INDUSTRY CANADA

GUIDE: RSS-102, Issue 1 (Provisional) September 25, 1999 Health Canada's Safety Code 6

DATE OF REPORT: May 16, 2000

ON THE BEHALF OF THE APPLICANT:

Kenwood Communications Corporation

AT THE REQUEST OF:

P.O. 40470

Kenwood Communications Corporation P.O. Box 22745 Long Beach, CA 90801-5745

Attention of: Joel E. Berger, Research & Development JBerger@kenwoodusa.com (310) 761-4409; FAX: -8246

CANADIAN MAINTENANCE FACILITY:

Kenwood Electronics Canada Inc.

M. Ower P. Eng

Morton Flom, P. Eng.

SUPERVISED BY:

PAGE NO. 1 of 3. Required information per ISO/IEC Guide 25-1990, paragraph 13.2: a) <u>TEST REPORT</u> b) Laboratory: M. Flom Associates, Inc. (FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107 (Canada: IC 2044) Chandler, AZ 85225 c) Report Number: d0050032

d) Client: Kenwood Communications Corporation P.O. Box 22745 Long Beach, CA 90801-5745

- e) Identification: Kenwood TK-760HG-1 and TK-762HG-1 Description: VHF FM Mobile Transceiver
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: May 16, 2000 EUT Received: April 20, 2000
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- 1) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by:

M. Thur P. Eng

Morton Flom, P. Eng.

- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40° C (50° to 104° F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10° to 90° relative humidity.

M. Flom Associates, Inc. - Global Compliance Center 3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176 www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

PAGE NO. 2 of 3. RSS-102 Declaration of Compliance

Subject: Health Canada Safety Code 6

For: R.F. Exposure Evaluation

The product/device shown below has been evaluated by M. Flom Associates, Inc. to Industry Canada RSS-102 and has complied with the R.F. Exposure limits for humans.

The Applicant/Manufacturer has been notified and supplied with a copy of the ETR for their files.

This device complies with Industry Canada specification RSS-102.

MODELS: Kenwood TK-760HG-1 and TK-762HG-1 SERIAL NUMBER: 18180 TYPE: VHF Mobile Transceiver

DUTY CYCLE: per specs/manual

MINIMUM SEPARATION DISTANCE: 25 mm

AGENT FOR APPLICANT: M. Flom Associates, Inc

11: Ower P. Eng

Morton Flom, P. Eng.

DATE: May 16, 2000

| PAGE NO. | 3 of 3. |
|--|---|
| Name of test: | Environmental Assessment |
| EUT Description: Power, Conducted [W] Test Frequency, MHz Ant. Gain[dBi] | = 50 = 174 |
| Rated Probe: | Narda 8761D Probe = 10 $\mu\text{W}/\text{cm}^2$ to 20 mW/cm^2 |
| | 0.3-1.234 MHz: 1.34-300 MHz: 30-300 MHz: 300-1500 MHz 1500-100,000 MHz: Limit [mW/cm ²] = 100 Limit [mW/cm ²] = (180/f ²) Limit [mW/cm ²] = 0.2 Limit [mW/cm ²] = f/1500 Limit [mW/cm ²] = 1.0 |
| Power[W EIRP] Limit [mW/cm ²] Limit [W/m ²] Theoretical safe distance: | 1/2 |

TESTIMONIAL AND STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

- THAT the application was prepared either by, or under the direct supervision of, the undersigned.
- 2. THAT the technical data supplied with the application was taken under my direction and supervision.
- THAT the data was obtained on representative units, randomly selected.
- 4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

1: Thuck P. Eng

Morton Flom, P. Eng.

CERTIFYING ENGINEER: