COMPLIANCE Certification Services

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

1366 BORDEAUX DRIVE, SUNNYVALE, CA 94089
PHONE: (408) 752-8166 FAX: (408) 752-8168

Project #:	00E8905
Report #:	8905D2
Date& Time:	8/28/2000
Test Engr:	BILL HUANG

Company:	NUTEK CORPORATION
EUT Description:	DROOE3C (Alarm Tx / 302MHz)
Test Configuration :	EUT ONLY
Type of Test:	FCC 15.231(b)/FCC 15.209
Mode of Operation:	NORMAL MODE

(•) D-Site ( ) E-Site 6 Worst Descendin

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Dist dB	Level (dBuV/m)	Limit FCC_B	Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter	Mark (P/Q/A)
1208	**51.38**	**39.565**	**25.2**	**2.7**	**43.32**	**-9.5**	**14.66**	**54.0**	**-39.35**	**1mV**	**90**	**2.0**	**A**
1510	**50.44**	**38.625**	**25.2**	**3.0**	**43.16**	**-9.5**	**14.17**	**54.0**	**-39.84**	**1mV**	**90**	**1.3**	**A**
1208	**50.42**	**38.605**	**25.2**	**2.7**	**43.32**	**-9.5**	**13.70**	**54.0**	**-40.31**	**1mH**	**270**	**1.0**	**A**
1510	**48.54**	**36.725**	**25.2**	**3.0**	**43.16**	**-9.5**	**12.27**	**54.0**	**-41.74**	**1mH**	**270**	**1.0**	**A**

* No other emission were found within 20dB under the limits upto 3.02 GHz.

Total data #:4 P(Peak): RBW=VBW=1MHz Distance = 20log(1/3)= -9.5dB
V.2d A(Average): Pk Reading - 11.815dB(For FCC 15.231(b))