



FCC PART 15 TEST REPORT No.I21Z70040-IOT06

for

Samsung Electronics Co., Ltd.

Tablet PC

SM-T220

With

FCC ID: ZCASMT220

Hardware Version: REV1.0

Software Version: T220.001

Issued Date: 2021-03-10

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I21Z70040-IOT06	Rev.0	1st edition	2021-03-01
I21Z70040-IOT06	Rev.1	Add the information of attenuator on page 12. Add the test result of channel 144 142 138.	2021-03-10

CONTENTS

CONTENTS	3
1. TEST LATORATORY.....	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATE	5
1.5. SIGNATURE	6
2. CLIENT INFORMATION.....	7
2.1 APPLICANT INFORMATION	7
2.2 MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARYEQUIPMENT(AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
3.4. GENERAL DESCRIPTION.....	9
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	10
4. REFERENCE DOCUMENTS	10
4.1. DOCUMENTS SUPPLIED BY APPLICANT	10
4.2. REFERENCE DOCUMENTS FOR TESTING.....	10
5. LABORATORY ENVIRONMENT.....	10
6. SUMMARY OF TEST RESULTS	11
6.1. SUMMARY OF TEST RESULTS.....	11
6.2. STATEMENTS.....	11
6.3. TEST CONDITIONS	11
7. TEST EQUIPMENTS UTILIZED	12
8. MEASUREMENT UNCERTAINTY	13
8.1 TRANSMITTER OUTPUT POWER	13
8.2 PEAK POWER SPECTRAL DENSITY	13
8.3 OCCUPIED CHANNEL BANDWIDTH	13
8.4 BAND EDGES COMPLIANCE	13
8.5 SPURIOUS EMISSIONS	13
8.6 AC POWER-LINE CONDUCTED EMISSION	13
ANNEX A: EUT PARAMETERS.....	13
ANNEX B: MEASUREMENT RESULTS.....	14
B.1. MEASUREMENT METHOD	14

B.2. MAXIMUM OUTPUT POWER.....	15
B.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	18
B.4. OCCUPIED 26DB BANDWIDTH(CONDUCTED).....	19
B.5. BAND EDGES COMPLIANCE	37
B.5.1 BAND EDGES - RADIATED	37
B.6. TRANSMITTER SPURIOUS EMISSION.....	50
B.7. AC POWERLINE CONDUCTED EMISSION (150kHz- 30MHz).....	91
B.8. 99% OCCUPIED BANDWIDTH	94
B.9. POWER CONTROL	99
ANNEX C: ACCREDITATION CERTIFICATE	100

1. TEST LATORATORY

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

1.4. Project date


Testing Start Date: 2020-12-31

Testing End Date: 2021-03-10

1.5. Signature



Xie Xiuzhen
(Prepared this test report)



Zheng Wei
(Reviewed this test report)



Hu Xiaoyu
(Approved this test report)

2. CLIENT INFORMATION

2.1 Applicant Information

Company Name: Samsung Electronics Co., Ltd.
Address: 19 Chapin Rd., Building D Pine Brook, NJ 07058
Contact: Jenni Chun
Email: j1.chun@samsung.com
Telephone: +1-201-937-4203
Fax: /

2.2 Manufacturer Information

Company Name: Samsung Electronics Co., Ltd.
Address: Samsung R5, Maetan dong 129, Samsung ro
Youngtong gu, Suwon city 443 742, Korea
Contact: Sunghoon Cho
Email: ggobi.cho@samsung.com
Telephone: +82-10-2722-4159
Fax: /

3. EQUIPMENT UNDER TEST (EUT) AND

ANCILLARY EQUIPMENT (AE)

3.1. About EUT

Description	Tablet PC
Model name	SM-T220
FCC ID	ZCASMT220
WLAN Frequency Band	ISM Bands: -5150MHz~5250MHz -5250MHz~5350MHz -5470MHz~5725MHz
Type of modulation	OFDM
Antenna Gain	-1.1dBi
Voltage	4.0V

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
UT08a	2170040UT08a	REV1.0	T220.001
UT01a	2170040UT01a	REV1.0	T220.001

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Charger1	/
AE2	Charger2	/
AE3	Charger3	/
AE4	Charger4	/
AE5	Charger5	/
AE6	Charger6	/
AE7	USB cable	/
AE8	Headset1	/
AE9	Headset2	/
AE10	battery	/

AE1

Model	EP-TA50JWE
Manufacturer	RFTECH Co., Ltd.
Length of cable	/

AE2

Model	EP-TA50JWE
Manufacturer	HAEM Co., Ltd.
Length of cable	/

AE3

Model	EP-TA200
Manufacturer	DongYang E&P Inc.
Length of cable	/
AE4	
Model	EP-TA200
Manufacturer	HAEM Co., Ltd.
Length of cable	/
AE5	
Model	EP-TA200
Manufacturer	SoluM Co.,Ltd
Length of cable	/
AE6	
Model	EP-TA200
Manufacturer	RFTECH Co., Ltd.
Length of cable	/
AE7	
Model	EP-DT725BWE
Manufacturer	Samsung Electronics Co., Ltd.
Length of cable	/
AE8	
Model	EHS61ASFWE
Manufacturer	ALMUS
Length of cable	/
AE9	
Model	EHS61ASFWE
Manufacturer	Cresyn
Length of cable	/
AE10	
Type	Secondary Li-ion Battery
SN	HQ-3565S
Manufacturer	SCUD (Fujian) Electronics CO.,LTD

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of Tablet PC with integrated antenna and inbuilt battery. It has Bluetooth (EDR)function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2018
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	BR
Peak Power Spectral Density	15.407	/	BR
Occupied 26dB Bandwidth	15.403	/	BR
Band edge compliance (Radiated)	15.209	/	P
Transmitter spurious emissions (Radiated)	15.407	/	P
AC Powerline Conducted Emission (150kHz- 30MHz)	15.407	/	P
99% Occupied bandwidth	/	/	BR
Transmit Power Control	15.407	/	NA

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
BR	Re-use test data from basic model report.
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

The Equipment Under Test (EUT) model SM-T220 (FCC ID: ZCASMT220) is a variant product of SM-T225 (FCC ID: ZCASMT225), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements were performed on this device, all the test results are derived from test report No.I20Z60378-IOT04, except the result of radiated.

For detail differences between two models please refer the Declaration of Changes document.

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26℃
Voltage	4.0V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-06
2	LISN	ENV216	101200	Rohde & Schwarz	1 year	2021-05-19
3	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2022-02-23
4	Shielding Room	S81	/	ETS-Lindgren	/	/
5	Attenuator	10dB	/	Rosenberger	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2022-02-23
2	BiLog Antenna	VULB9163	9163-1223	Schwarzbeck	1 year	2021-03-18
3	Antenna	3115	00167250	ETS-Lindgren	1 year	2021-05-14
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2021-08-05

8. Measurement Uncertainty

8.1 Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2 Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3 Occupied Channel Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4 Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5 Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.16
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.44
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.28

8.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08,k=2

ANNEX A: EUT parameters


Disclaimer: the antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX B: MEASUREMENT RESULTS

B.1. Measurement Method

B.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




B.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

B.2. Maximum output Power

Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm
	5250MHz~5350MHz	24dBm or $11+10\log B$
	5470MHz~5725MHz	24dBm or $11+10\log B$

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-2 is made according to KDB 789033

Note:

For straddle channel 20MHz Bandwidth 5720MHz, Conducted Output Power Limit:

$802.11a = 11 + 10 \cdot \log(B) = 22.83$, $B = 20.45/2 + 5 = 15.225\text{MHz}$,

$802.11n\text{-HT}20 = 11 + 10 \cdot \log(B) = 22.89$, $B = 20.93/2 + 5 = 15.465\text{MHz}$,

$802.11ac\text{-VHT}20 = 11 + 10 \cdot \log(B) = 22.88$, $B = 20.80/2 + 5 = 15.40\text{MHz}$,

For straddle channel 40/80MHz Bandwidth, conducted output power limit=24 dBm

$802.11n\text{-HT}40$: $B = 40.70/2 + 15 = \text{MHz}$,

$802.11ac\text{-VHT}40$: $B = 40.64/2 + 15 = 35.32\text{MHz}$,

$802.11ac\text{-VHT}80$: $B = 81.60/2 + 35 = 75.80\text{MHz}$,

Measurement Results:

802.11a mode

Mode	Frequency	Test Result (dBm)							
		Data Rate (Mbps)							
		6	9	12	18	24	36	48	54
802.11a	5180MHz	13.23	/	/	/	/	/	/	/
	5200MHz	13.40	/	/	/	/	/	/	/
	5240MHz	13.53	/	/	/	/	/	/	/
	5260MHz	14.11	14.10	13.85	13.86	13.86	13.86	13.36	13.37
	5280MHz	13.91	/	/	/	/	/	/	/
	5320MHz	13.72	/	/	/	/	/	/	/
	5500MHz	13.34	/	/	/	/	/	/	/
	5580MHz	14.37	/	/	/	/	/	/	/
	5700MHz	14.61	/	/	/	/	/	/	/
	5720MHz	14.72	/	/	/	/	/	/	/

The data rate 6Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT20)	5180MHz	12.81	/	/	/	/	/	/	/
	5200MHz	13.11	/	/	/	/	/	/	/
	5240MHz	13.30	/	/	/	/	/	/	/
	5260MHz	13.49	13.46	13.20	13.21	12.69	12.71	12.72	12.72
	5280MHz	13.40	/	/	/	/	/	/	/
	5320MHz	13.23	/	/	/	/	/	/	/
	5500MHz	13.11	/	/	/	/	/	/	/
	5580MHz	13.80	/	/	/	/	/	/	/
	5700MHz	13.95	/	/	/	/	/	/	/
	5720MHz	14.04	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT20 mode

Mode	Frequency	Test Result (dBm)								
		Data Rate								
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac (HT20)	5180MHz	13.31	/	/	/	/	/	/	/	/
	5200MHz	13.61	/	/	/	/	/	/	/	/
	5240MHz	13.76	/	/	/	/	/	/	/	/
	5260MHz	13.92	13.81	13.80	13.80	13.80	13.30	13.30	13.31	13.28
	5280MHz	13.88	/	/	/	/	/	/	/	/
	5320MHz	13.70	/	/	/	/	/	/	/	/
	5500MHz	13.25	/	/	/	/	/	/	/	/
	5580MHz	14.37	/	/	/	/	/	/	/	/
	5700MHz	14.64	/	/	/	/	/	/	/	/
	5720MHz	14.68	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT40)	5190MHz	13.22	/	/	/	/	/	/	/
	5230MHz	13.59	/	/	/	/	/	/	/
	5270MHz	13.89	13.68	13.70	13.69	13.70	13.71	12.69	12.70
	5310MHz	13.37	/	/	/	/	/	/	/

	5510MHz	13.38	/	/	/	/	/	/	/
	5550MHz	13.42	/	/	/	/	/	/	/
	5670MHz	14.01	/	/	/	/	/	/	/
	5710MHz	14.38	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT40 mode

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT40)	5190MHz	13.43	/	/	/	/	/	/	/	/	/
	5230MHz	13.64	/	/	/	/	/	/	/	/	/
	5270MHz	13.98	13.88	13.87	13.86	13.88	13.89	13.40	13.38	12.84	12.85
	5310MHz	13.87	/	/	/	/	/	/	/	/	/
	5510MHz	13.41	/	/	/	/	/	/	/	/	/
	5550MHz	13.74	/	/	/	/	/	/	/	/	/
	5670MHz	14.36	/	/	/	/	/	/	/	/	/
	5710MHz	14.54	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT80 mode

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT80)	5210MHz	13.11	/	/	/	/	/	/	/	/	/
	5290MHz	13.37	13.20	13.20	13.19	13.21	13.22	12.72	12.70	11.70	11.69
	5530MHz	12.86	/	/	/	/	/	/	/	/	/
	5610MHz	13.76	/	/	/	/	/	/	/	/	/
	5690MHz	13.82	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

The duty cycle of all mode are 100%.

The spot check result of average output power is 13.85dBm (802.11ac-HT20 MCS0 ch144)

B.3. Peak Power Spectral Density (conducted)

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11
	5250MHz~5350MHz	11
	5470MHz~5725MHz	11

The output power measurement method Section F is made according to KDB 789033

Measurement Results:

Mode	Frequency	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	1.78	P
	5200 MHz	1.57	P
	5240 MHz	1.37	P
	5260 MHz	2.17	P
	5280 MHz	1.93	P
	5320 MHz	1.91	P
	5500 MHz	2.23	P
	5580 MHz	2.61	P
	5700 MHz	2.19	P
	5720 MHz	1.92	P
802.11ac HT20	5180 MHz	1.12	P
	5200 MHz	1.22	P
	5240 MHz	1.28	P
	5260 MHz	1.81	P
	5280 MHz	1.86	P
	5320 MHz	2.09	P
	5500 MHz	1.70	P
	5580 MHz	2.54	P
	5700 MHz	1.86	P
	5720 MHz	0.81	P
802.11ac HT40	5190 MHz	0.06	P
	5230 MHz	-0.08	P
	5270 MHz	0.35	P
	5310 MHz	0.61	P
	5510 MHz	0.45	P
	5550 MHz	0.55	P
	5670 MHz	0.84	P
	5710 MHz	-1.97	P
802.11ac HT80	5210 MHz	-5.12	P
	5290 MHz	-4.83	P
	5530 MHz	-4.27	P

	5610 MHz	-4.21	P
	5690 MHz	-5.77	P

Conclusion: PASS

B.4. Occupied 26dB Bandwidth(conducted)

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Frequency	Occupied 26dB Bandwidth (MHz)		conclusion
802.11a	5180 MHz	Fig.1	20.70	P
	5200 MHz	Fig.2	20.70	P
	5240 MHz	Fig.3	20.50	P
	5260 MHz	Fig.4	20.50	P
	5280 MHz	Fig.5	20.70	P
	5320 MHz	Fig.6	20.65	P
	5500 MHz	Fig.7	20.65	P
	5580 MHz	Fig.8	20.60	P
	5700 MHz	Fig.9	20.65	P
	5720 MHz	Fig.10	20.45	P

802.11ac HT20	5180 MHz	Fig.11	20.90	P
	5200 MHz	Fig.12	20.95	P
	5240 MHz	Fig.13	20.90	P
	5260 MHz	Fig.14	20.75	P
	5280 MHz	Fig.15	20.85	P
	5320 MHz	Fig.16	20.85	P
	5500 MHz	Fig.17	20.90	P
	5580 MHz	Fig.18	20.90	P
	5700 MHz	Fig.19	20.90	P
	5720 MHz	Fig.20	20.80	P

802.11ac HT40	5190 MHz	Fig.21	41.04	P
	5230 MHz	Fig.22	40.80	P
	5270 MHz	Fig.23	40.72	P
	5310 MHz	Fig.24	41.12	P
	5510 MHz	Fig.25	40.96	P
	5550 MHz	Fig.26	41.20	P
	5670 MHz	Fig.27	41.12	P
	5710 MHz	Fig.28	40.64	P

802.11ac HT80	5210 MHz	Fig.29	81.60	P
	5290 MHz	Fig.30	81.44	P
	5530 MHz	Fig.31	81.76	P
	5610 MHz	Fig.32	81.60	P
	5690 MHz	Fig.33	81.60	P

Conclusion: PASS

Test graphs as below:




Fig.1 Occupied 26dB Bandwidth (802.11a, 5180MHz)




Fig.2 Occupied 26dB Bandwidth (802.11a, 5200MHz)




Fig.3 Occupied 26dB Bandwidth (802.11a, 5240MHz)




Fig.4 Occupied 26dB Bandwidth (802.11a, 5260MHz)




Fig.5 Occupied 26dB Bandwidth (802.11a, 5280MHz)




Fig.6 Occupied 26dB Bandwidth (802.11a, 5320MHz)




Fig.7 Occupied 26dB Bandwidth (802.11a, 5500MHz)




Fig.8 Occupied 26dB Bandwidth (802.11a, 5580MHz)




Fig.9 Occupied 26dB Bandwidth (802.11a, 5700MHz)




Fig.10 Occupied 26dB Bandwidth (802.11a, 5720MHz)




Fig.11 Occupied 26dB Bandwidth (802.11ac-HT20, 5180MHz)




Fig.12 Occupied 26dB Bandwidth (802.11ac-HT20, 5200MHz)




Fig.13 Occupied 26dB Bandwidth (802.11ac-HT20, 5240MHz)




Fig.14 Occupied 26dB Bandwidth (802.11ac-HT20, 5260MHz)




Fig.15 Occupied 26dB Bandwidth (802.11ac-HT20, 5280MHz)




Fig.16 Occupied 26dB Bandwidth (802.11ac-HT20, 5320MHz)




Fig.17 Occupied 26dB Bandwidth (802. 11ac-HT20, 5500MHz)




Fig.18 Occupied 26dB Bandwidth (802. 11ac-HT20, 5580MHz)




Fig.19 Occupied 26dB Bandwidth (802. 11ac-HT20, 5700MHz)




Fig.20 Occupied 26dB Bandwidth (802. 11ac-HT20, 5720MHz)




Fig.21 Occupied 26dB Bandwidth (802.11ac-HT40, 5190MHz)




Fig.22 Occupied 26dB Bandwidth (802.11ac-HT40, 5230MHz)




Fig.23 Occupied 26dB Bandwidth (802.11ac-HT40, 5270MHz)




Fig.24 Occupied 26dB Bandwidth (802.11ac-HT40, 5310MHz)




Fig.25 Occupied 26dB Bandwidth (802.11ac-HT40, 5510MHz)




Fig.26 Occupied 26dB Bandwidth (802. 11ac-HT40, 5550MHz)




Fig.27 Occupied 26dB Bandwidth (802. 11ac-HT40, 5670MHz)




Fig.28 Occupied 26dB Bandwidth (802. 11ac-HT40, 5710MHz)




Fig.29 Occupied 26dB Bandwidth (802. 11ac-HT80, 5210MHz)




Fig.30 Occupied 26dB Bandwidth (802. 11ac-HT80, 5290MHz)




Fig.31 Occupied 26dB Bandwidth (802. 11ac-HT80, 5530MHz)




Fig.32 Occupied 26dB Bandwidth (802. 11ac-HT80, 5610MHz)




Fig.33 Occupied 26dB Bandwidth (802. 11ac-HT80, 5690MHz)

B.5. Band Edges Compliance

B.5.1 Band Edges - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)	Measurement distance(m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The measurement is made according to ANSI C63.10-2013 and KDB 789033

Measurement Result:

Mode	Channel	Test Results	Conclusion
802.11a	5180 MHz	Fig.34	P
	5320 MHz	Fig.35	P
	5500 MHz	Fig.36	P
	5700 MHz	Fig.37	P
802.11n HT20	5180 MHz	Fig.38	P
	5320 MHz	Fig.39	P
	5500 MHz	Fig.40	P
	5700 MHz	Fig.41	P
802.11ac HT20	5180 MHz	Fig.42	P
	5320 MHz	Fig.43	P
	5500 MHz	Fig.44	P
	5700 MHz	Fig.45	P
02.11n HT40	5190 MHz	Fig.46	P
	5310 MHz	Fig.47	P
	5510 MHz	Fig.48	P
	5670 MHz	Fig.49	P
802.11ac HT40	5190 MHz	Fig.50	P
	5310 MHz	Fig.51	P
	5510 MHz	Fig.52	P
	5670 MHz	Fig.53	P
802.11ac HT80	5210MHz	Fig.54	P
	5290MHz	Fig.55	P
	5530MHz	Fig.56	P

Conclusion: PASS

Test graphs as below:




Fig.34 Band Edges (802.11a, 5180MHz)




Fig.35 Band Edges (802.11a, 5320MHz)




Fig.36 Band Edges (802.11a, 5500MHz)




Fig.37 Band Edges (802.11a, 5700MHz)




Fig.38 Band Edges (802.11n-HT20, 5180MHz)




Fig.39 Band Edges (802.11n-HT20, 5320MHz)




Fig.40 Band Edges (802.11n-HT20, 5500MHz)




Fig.41 Band Edges (802.11n-HT20, 5700MHz)

Full Spectrum




Fig.42 Band Edges (802.11n-HT40, 5190MHz)

Full Spectrum




Fig.43 Band Edges (802.11n-HT40, 5310MHz)

Full Spectrum




Fig.44 Band Edges (802.11n-HT40, 5510MHz)

Full Spectrum




Fig.45 Band Edges (802.11n-HT40, 5670MHz)




Fig.46 Band Edges (802.11ac-HT20, 5180MHz)




Fig.47 Band Edges (802.11ac-HT20, 5320MHz)




Fig.48 Band Edges (802.11ac-HT20, 5500MHz)




Fig.49 Band Edges (802.11ac-HT20, 5700MHz)




Fig.50 Band Edges (802.11ac-HT40, 5190MHz)




Fig.51 Band Edges (802.11ac-HT40, 5310MHz)




Fig.52 Band Edges (802.11ac-HT40, 5510MHz)




Fig.53 Band Edges (802.11ac-HT40, 5670MHz)




Fig.54 Band Edges (802.11ac-HT80, 5210MHz)




Fig.55 Band Edges (802.11ac-HT80, 5290MHz)




Fig.56 Band Edges (802.11ac-HT80, 5530MHz)

B.6. Transmitter Spurious Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)	Measurement distance(m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The measurement is made according to ANSI C63.10-2013 and KDB 789033

Measurement Results:

802.11a mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11a	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n - HT20	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	38(5190MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	46(5230MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	54(5270MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	62(5310MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	102(5510MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	118(5590MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	134(5670MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	142(5710MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac - HT20	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P