

Report No. : FR832801D



FCC RADIO TEST REPORT

FCC ID	: B32E280BTWF
Equipment	: Point of Sales Terminal
Brand Name	: Verifone
Model Name	: e280
Applicant	: Verifone, Inc.
	1400 West Stanford Ranch Road, Suite 100, 150 & 200, Rocklin CA 95765 USA
Manufacturer	: Inventec Applicanes (Pudong) Corp.
Standard	: FCC Part 15 Subpart C §15.225

The product was received on Mar. 28, 2018 and testing was started from Apr. 28, 2018 and completed on May 29, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERTIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsar

Approved by: Jones Tsai SPORTON INTERTIONAL INC. EMC & Wireless Communications Laboratory No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History	y of this test report	3
Summ	ary of Test Result	4
1. Gen	eral Description	5
1.1	Product Feature of Equipment Under Test	5
1.2	Modification of EUT	5
1.3	Testing Location	6
1.4	Applicable Standards	6
2. Test	t Configuration of Equipment Under Test	7
2.1	Descriptions of Test Mode	7
2.2	Table for Supporting Units	7
2.3	EUT Operation Test Setup	7
3. Test	t Results	
3.1	AC Power Line Conducted Emissions Measurement	
3.2	20dB and 99% OBW Spectrum Bandwidth Measurement	
3.3	Frequency Stability Measurement	
3.4	Field Strength of Fundamental Emissions and Mask Measurement	
3.5	Radiated Emissions Measurement	
3.6	Antenna Requirements	
4. List	of Measuring Equipment	
	ertainty of Evaluation	
Appen	dix A. Test Results of Conducted Emission Test	
Appen	dix B. Test Results of Conducted Test Items	
B1.	Test Result of 20dB Spectrum Bandwidth	
	Test Result of Frequency Stability	
Appen	idix C. Test Results of Radiated Test Items	
~ ~ ~		

- C1. Test Result of Field Strength of Fundamental Emissions
- C2. Results of Radiated Emissions (9 kHz~30MHz)
- C3. Results of Radiated Emissions (30MHz~1GHz)

Appendix D. Setup Photographs



History of this test report

Report No.	Version	Description	Issued Date
FR832801D	01	Initial issue of report	Jun. 12, 2018



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	Under limit 7.32 dB at 27.121MHz
2.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
3.2	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 79.20 dBµV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	Under limit 3.66 dB at 213.060MHz
3.6	15.203	Antenna Requirements	Pass	-

Reviewed by: Joseph Lin Report Producer: Maggie Chiang



1. General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and RFID.

Product Specification subjective to this standard		
Antenna Type	WLAN: Stamping Antenna Bluetooth: Stamping Antenna RFID: Loop Antenna	

Specification of Accessory				
	Brand Name	Verifone		
	Manufacturer	Phihong		
AC Adapter	Model Name	PSAA05A-050QL6V		
AC Adapter	Power Rating	Input:100-240Vac, 50-60Hz 0.2A		
		Output: 5V/1A		
	Power Cord	N/A		
Potton	Brand Name	Verifone		
Battery	Model Name	BPK087-700		
USB Cable	Brand Name	Verifone		
	Model Name	N/A		

1.2 Modification of EUT

No modifications are made to the EUT during all test items.



1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.				
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978				
Test Site No.	Sporton Site No.				
Test Site NO.	TH03-HY	CO05-HY	03CH07-HY		
Test Engineer	Louis Chung Shareef Yu and Jesse Wang Shareef Yu and Jesse Wang				
Temperature	22~24°C 25~27 23~25				
Relative Humidity	53~55% 50~52 51~53				

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- ANSI C63.10-2013

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items			
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions		
20dB Spectrum Bandwidth	Frequency Stability		
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz		

Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.

	Test Cases					
AC	Mode 1: Bluetooth Idle + WLAN (2.4GHz) Idle + MSR + Smart Card + LED +					
Conducted	Buzzer + RFID On + USB Cable (Charging from Adapter)					
Emission						

2.2 Table for Supporting Units

ltem	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	iPhone	Apple	A1387	BCG-E2430A	N/A	N/A
3.	MSR Card	N/A	N/A	N/A	N/A	N/A
4.	Smart Card	N/A	N/A	N/A	N/A	N/A

2.3 EUT Operation Test Setup

The RF test items, utility "Tera Tern" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission	Conducted Limit (dBµV)		
(MHz)	Quasi-Peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.

3.1.2 Measuring Instruments


See list of measuring equipment of this test report.

3.1.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.56MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.



3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 3. Measured the spectrum width with power higher than 20dB below carrier.
- 4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.



3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ±100ppm.
- 6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225				
Description	Compliance with th	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Free of Emission (MUT)	Field Strength	Field Strength	Field Strength	Field Strength	
Freq. of Emission (MHz)	(µV/m) at 30m	(dBµV/m) at 30m	(dBµV/m) at 10m	(dBµV/m) at 3m	
1.705~13.110	30	29.5	48.58	69.5	
13.110~13.410	106	40.5	59.58	80.5	
13.410~13.553	334	50.5	69.58	90.5	
13.553~13.567	15848	84.0	103.08	124.0	
13.567~13.710	334	50.5	69.58	90.5	
13.710~14.010	106	40.5	59.58	80.5	
14.010~30.000	30	29.5	48.58	69.5	

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.




3.4.3 Test Procedures

- Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- 4. For Fundamental emissions, use the receiver to measure QP reading.
- 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 6. Compliance with the spectrum mask is tested with RBW set to 9kHz. Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies	Field Strength	Measurement Distance
(MHz)	(μV/m)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures

- Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.




3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Mar. 21, 2018	May 07, 2018	Mar. 20, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	May 07, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30° ℃ ~70°℃	Dec. 06, 2017	May 07, 2018	Dec. 05, 2019	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 28, 2018~ May 18, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Apr. 28, 2018~ May 18, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Apr. 28, 2018~ May 18, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 28, 2018~ May 18, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Apr. 28, 2018~ May 18, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Apr. 28, 2018~ May 18, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Dec. 18, 2017	May 29, 2018	Dec. 17, 2018	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	May 29, 2018	Nov. 09, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4, MY28655/4	9KHz~30MHz	Jan. 02, 2018	May 29, 2018	Jan. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	30MHz~1GHz	Feb. 27, 2018	May 29, 2018	Feb. 26, 2019	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	May 29, 2018	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	May 29, 2018	N/A	Radiation (03CH07-HY)
Amplifier	SONOMA	310N	187231	9kHz~1GHz	Jan. 08, 2018	May 29, 2018	Jan. 07, 2019	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	May 29, 2018	Jan. 15, 2019	Radiation (03CH07-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	May 29, 2018	N/A	Radiation (03CH07-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.7
of 95% (U = 2Uc(y))	2.1

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	24
of 95% (U = 2Uc(y))	5.4

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.7
--	-----



Appendix A. Test Results of Conducted Emission Test


Toot Engineer	t Engineer : Shareef Yu and Kai-Chun Chu	Temperature :	25~27 ℃
Test Engineer .		Relative Humidity :	50~52%

Report NO : Test Mode : Test Voltage : Phase : 832801 Mode 1 120Vac/60Hz Line Original Mode



Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.152250		26.91	55.88	28.97	L1	OFF	19.5
0.152250	38.09		65.88	27.79	L1	OFF	19.5
0.233250		31.12	52.33	21.21	L1	OFF	19.5
0.233250	32.77		62.33	29.56	L1	OFF	19.5
0.368250		27.18	48.54	21.36	L1	OFF	19.5
0.368250	28.96		58.54	29.58	L1	OFF	19.5
0.642750		23.18	46.00	22.82	L1	OFF	19.5
0.642750	28.26		56.00	27.74	L1	OFF	19.5
1.792500		22.68	46.00	23.32	L1	OFF	19.6
1.792500	24.44		56.00	31.56	L1	OFF	19.6
7.107000		24.68	50.00	25.32	L1	OFF	19.6
7.107000	26.54		60.00	33.46	L1	OFF	19.6
13.560000		71.94	50.00	-21.94	L1	OFF	19.7
13.560000	78.65		60.00	-18.65	L1	OFF	19.7
27.120750		42.38	50.00	7.62	L1	OFF	19.8
27.120750	52.68		60.00	7.32	L1	OFF	19.8

Report NO : Test Mode : Test Voltage : Phase : 832801 Mode 1 120Vac/60Hz Neutral Original Mode




FullSpectrum

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.152250		27.74	55.88	28.14	Ν	OFF	19.5
0.152250	44.33		65.88	21.55	Ν	OFF	19.5
0.233250		31.96	52.33	20.37	Ν	OFF	19.5
0.233250	33.83		62.33	28.50	Ν	OFF	19.5
0.368250		28.99	48.54	19.55	Ν	OFF	19.5
0.368250	30.58		58.54	27.96	Ν	OFF	19.5
0.640500		22.88	46.00	23.12	Ν	OFF	19.5
0.640500	26.04		56.00	29.96	Ν	OFF	19.5
1.945500		22.74	46.00	23.26	Ν	OFF	19.6
1.945500	24.52		56.00	31.48	Ν	OFF	19.6
5.538750		24.64	50.00	25.36	Ν	OFF	19.6
5.538750	26.61		60.00	33.39	Ν	OFF	19.6
13.560000		69.93	50.00	-19.93	Ν	OFF	19.8
13.560000	71.73		60.00	-11.73	Ν	OFF	19.8
27.118500		31.40	50.00	18.60	Ν	OFF	20.0
27.118500	47.44		60.00	12.56	Ν	OFF	20.0

Report NO : Test Mode : Test Voltage : Phase :


832801 Mode 1 120Vac/60Hz Line Terminal



Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
13.560000		36.37	50.00	13.63	L1	OFF	19.7
13.560000	42.48		60.00	17.52	L1	OFF	19.7

Report NO : Test Mode : Test Voltage : Phase :


832801 Mode 1 120Vac/60Hz Neutral Terminal



Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
13.560000		39.80	50.00	10.20	Ν	OFF	19.8
13.560000	45.52		60.00	14.48	Ν	OFF	19.8



Appendix B. Test Results of Conducted Test Items



B1. Test Result of 20dB Spectrum Bandwidth

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability


B3. Voltage vs. F	requency Stability	Tempera	ture vs. Frequ	ency Stability
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
120	13.559980	-20	0	13.559980
102	13.559980		2	13.560000
138	13.559970		5	13.560000
			10	13.560020
		-10	0	13.560050
			2	13.560060
			5	13.560040
			10	13.560060
		0	0	13.560060
			2	13.560060
			5	13.560060
			10	13.560060
		10	0	13.560050
			2	13.560040
			5	13.560050
			10	13.560040
		20	0	13.559980
			2	13.559980
			5	13.559970
			10	13.559980
		30	0	13.560000
			2	13.559980
			5	13.559980
			10	13.559980
		40	0	13.559980
			2	13.559980
			5	13.559980
			10	13.559980



Voltage vs. Frequ	ency Stability	Temperature vs. Frequency Stability				
	Measurement	Temperature (°C)	Time	Measurement		
Voltage (Vac)	Frequency (MHz)	Temperature (C)		Frequency (MHz)		
		50	0	13.559980		
			2	13.559980		
			5	13.559980		
			10	13.559970		
Max.Deviation (MHz)	-0.000030	Max.Deviation (MHz)		0.000060		
Max.Deviation (ppm)	-2.2124	Max.Deviati	4.4248			
Limit	FS < ±100 ppm	Limi	FS < ±100 ppm			
Test Result	PASS	Test Re	PASS			



Appendix C. Test Results of Radiated Test Items



C1. Test Result of Field Strength of Fundamental Emissions

Test Mode	NFC Tx			Polariz	ation :	H	Horizontal				
	Lovel (dPu)//	m)						Date: 2018-	.05.29		
	40 Level (dBuV/										
12											
10											
	4.3										
83	2.9			7							
	1.4						1	5.209 LIMIT	LINE		
	0.0			8							
	7.1						9		10		
	5.7										
14	4.3										
:	2.9						_				
	8.6										
-20 <mark>0.009 6.007 12.005 18.004 24.002 30 Frequency (MHz)</mark>									30		
Frequency	Level	Over	Limit	Read	Antenna	Cable	Ant	Table	Remark		
		Limit	Line	Level	Factor	Loss		Pos			
(MHz)	(dBµV/m)		(dBµV/m)	(dBµV)	(dB)	(dB)	(cm)	(deg)	_		
0.01017	52.71	-74.75	127.46	31.65	20.63	0.43	-	-	Average		
0.06051	51.28	-60.69	111.97	30.75	20.1	0.43	-	-	Average		
0.0926	52.07	-56.2	108.27	31.55	20.09	0.43	-	-	QP		
0.12804	52.37	-53.09	105.46	31.87	20.07	0.43	-	-	Average		
0.15	53.03	-51.05	104.08	32.54	20.06	0.43	-	-	Average		
0.51253	48.07	-25.34	73.41	27.65	19.99	0.43	-	-	QP		
13.56	78.91	9.41	69.5	58.57	19.91	0.43	-	-	QP		
13.696	54.45	-15.05	69.5	34.11	19.91	0.43	100	0	QP		
22.669	36.53	-32.97	69.5	14.9	20.43	1.2	-	-	QP		
29.62	36.75	-32.75	69.5	15.53	20.02	1.2	-	-	QP		


C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)



Test Mode :	NFC	NFC Tx			Polarization :			Vertical				
140 Level (dBuV/m) Date: 2018-05-29												
128												
117												
105	5.7									_		
94	I.3									_		
	2.9			7				45.200				
).0							15.20) LIMIT LI			
	3.6 6			8								
	7.1						9		10			
25	5.7									_		
	1.3									_		
	3.6											
	20 _{0.009}	6.007		2.005	18.00		24	.002		30		
	0.009	0.007			cy (MHz)	4	24	.002		50		
Frequency	Level	Over	Limit	Read	Antenna	Cab	le A	nt Ta	ble	Remark		
		Limit	Line	Level	Factor	Los	-		os			
(MHz)	(dBµV/m)		(dBµV/m)	(dBµV)	(dB)	(dB		m) (d	eg)			
0.009	53.2	-75.32	128.52	32.14	20.63	0.4	3.	-	- /	Average		
0.06015	51.5	-60.52	112.02	30.97	20.1	0.4	3.	-	- /	Average		
0.09208	51.43	-56.89	108.32	30.91	20.09	0.4	3.	-	-	QP		
0.12364	51.22	-54.54	105.76	30.72	20.07	0.4	3 ·	-	- /	Average		
0.15272	51.65	-52.28	103.93	31.16	20.06	0.4	3.	-	- /	Average		
0.62518	42.73	-28.95	71.68	22.32	19.98	0.4	3 ·	-	-	QP		
13.56	76.33	6.83	69.5	55.99	19.91	0.4	3.	-	-	QP		
13.6	47.42	-22.08	69.5	27.08	19.91	0.4	3 10	00	0	QP		
22.588	36.5	-33	69.5	14.88	20.42	1.2	<u>2</u> .	-	-	QP		
27.12	36.98	-32.52	69.5	15.4	20.38	1.2	<u>2</u> .	-	-	QP		


Note:

- 1. 13.56 MHz is fundamental signal which can be ignored.
- 2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- 4. Limit line = specific limits $(dB\mu V)$ + distance extrapolation factor.



C3. Results of Radiated Spurious Emissions (30MHz~1GHz)





Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor= Level.