



Date: Oct. 22, 2015

This is to justify, and certify that the transmitter output power (BT/BT4.0/802.11a/b/g/n) (please see the pages 2~4) are dropped in order to enhance the holistic performance while installing to the platform, Model: N15P1, platform: Tablet Computer, host owner: Acer Incorporated. Power at the originally tested default channel is set lower with professional installation under per-chain condition so as to counter the measurable influence on spurious emission near the restricted band of the frequency (\$15.205).

Applicant: HON HAI Precision Ind. Co., Ltd.

FCC IDENTIFIER: MCLT77H462

The Product Name of Radio Equipment: 802.11abgn+BT4.0 module

Platform: Tablet Computer

The owner of the platform: Acer Incorporated.

A handwritten signature in black ink that reads 'Rio Chen'.

HON HAI Precision Ind. Co., Ltd.

Name: Mr Rio Chen

Title: Compliance Manager

Email: rio.chen@foxconn.com

Date: March 3, 2015

802.11abgn+BT4.0 module

Model T77H462

FCC/IC approved power levels

Power Levels tuned for T77H462 approvals testing

FCC				
Center Freq (MHz)	11b	11g	HT20	HT20 MIMO MCS8
1 2412	15	9.5	8.75	11.75
2 2417	15	9.5	8.75	11.75
3 2422	15	9.5	8.75	11.75
4 2427	15	9.5	8.75	11.75
5 2432	15	9.5	8.75	11.75
6 2437	15	9.5	8.75	11.75
7 2442	15	9.5	8.75	11.75
8 2447	15	9.5	8.75	11.75
9 2452	15	9.5	8.75	11.75
10 2457	15	9.5	8.75	11.75
11 2462	15	9.5	8.75	11.75

FCC			
Center Freq (MHz)	11a	HT20	HT20 MIMO MCS8
36 5180	12.5	13.5	16.5
40 5200	12.5	13.5	16.5
44 5220	12.5	13.5	16.5
48 5240	12.5	13.5	16.5
52 5260	12.5	13.5	16.5
56 5280	12.5	13.5	16.5
60 5300	12.5	13.5	16.5
64 5320	12.5	13.5	16.5

100	5500	12	11.5	14.5
104	5520	12	11.5	14.5
108	5540	12	11.5	14.5
112	5560	12	11.5	14.5
116	5580	12	11.5	14.5
132	5660	12	11.5	14.5
136	5680	12	11.5	14.5
140	5700	12	11.5	14.5
149	5745	12.5	11.5	14.5
153	5765	12.5	11.5	14.5
157	5785	12.5	11.5	14.5
161	5805	12.5	11.5	14.5
165	5825	12.5	11.5	14.5

	FCC		
	Center Freq (MHz)	HT40	HT40 MIMO MCS8
38	5190	11	14
46	5230	11	14
54	5270	11	14
62	5310	11	14
102	5510	8	11
110	5550	8	11
134	5670	8	11
151	5755	9.5	12.5
159	5795	9.5	12.5

The power table Includes tune-up tolerance (+/- 2dBm)

BT

<i>FCC</i>	<i>by Spectrum</i>		<i>unit: dBm</i>
GFSK	2402	2441	2480
Peak	3.17	4.05	4.00
π4DQPSK	2402	2441	2480
Peak	2.34	3.16	3.04
8DPSK	2402	2441	2480
Peak	2.75	3.55	3.45

BT4.0

<i>FCC</i>	<i>by Power meter</i>		<i>unit: dBm</i>
BT4.0	2402	2442	2480
Peak	3.95	4.68	4.63
Average	1.60	2.35	2.33