



Test Report

For:
Visteon Corporation

Brand:
Visteon

Marketing Name:
Battery Pack Control Module

Model Name:
BPCMFx

Product Description:
Battery Pack Control Module

FCC ID: NT8-BPCMFx
IC: 3043A-BPCMFx

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)
RSS-247 Issue 3 (DTS) & RSS-Gen Issue 5

REPORT #: EMC_VISTE_002_23001_FCC15247_DTS_BPCMFx_Rev2

DATE: 2024-06-13



A2LA Accredited

IC recognized #
3462B
CABID: US0187

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT.....	3
2	ADMINISTRATIVE DATA	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER.....	4
3	EQUIPMENT UNDER TEST (EUT).....	5
3.1	EUT SPECIFICATIONS	5
3.2	RADIO SPECIFICATIONS	6
3.3	EUT SAMPLE DETAILS	7
3.4	ACCESSORY EQUIPMENT (AE) DETAILS.....	7
3.5	TEST SAMPLE CONFIGURATION	7
3.6	MODE OF OPERATION.....	7
3.7	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	7
4	SUBJECT OF INVESTIGATION	8
4.1	TEST PROCEDURES AND STANDARDS APPLIED	8
5	MEASUREMENT RESULTS SUMMARY	8
6	MEASUREMENT UNCERTAINTY.....	9
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	9
6.2	DATES OF TESTING:	9
6.3	DECISION RULE:.....	9
7	MEASUREMENT PROCEDURES.....	10
7.1	RADIATED MEASUREMENT.....	10
7.2	POWER LINE CONDUCTED MEASUREMENT PROCEDURE	12
7.3	RF CONDUCTED MEASUREMENT PROCEDURE	12
8	TEST RESULT DATA	13
8.1	EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH	13
8.2	MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	16
8.3	POWER SPECTRAL DENSITY	18
8.4	DUTY CYCLE.....	20
8.5	NON-RESTRICTED BAND EDGE COMPLIANCE AND CONDUCTED SPURIOUS EMISSIONS	21
8.6	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BAND EDGE	24
9	TEST SETUP PHOTOS	44
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	44
11	REVISION HISTORY	45

1 **Assessment**

The following device was evaluated against the applicable criteria specified in

- FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and
- ISED Canada standard RSS-247 Issue 3.

No deviations were ascertained.

Company	Description	Model #
Visteon Corporation	Battery Pack Control Module	BPCMFX

Responsible for the Report:

2024-06-13	Compliance	Guangcheng Huang (Senior EMC Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section3.
CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 **Administrative Data**

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Ghanma, Issa
Project Manager:	Baskaran, Akanksha

2.2 Identification of the Client

Client's Name:	Visteon Corporation
Street Address:	One Village Center Drive
City/Zip Code	Van Buren Township, MI/48111
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	Same as Client
City/Zip Code	Same as Client
Country	Same as Client

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	BPCMFX
Marketing Name:	Battery Pack Control Module
HW Version :	VPRE1F-12A650-MA
SW Version :	SWE201-28418-000F01
FCC ID :	NT8-BPCMFX
IC :	3043A-BPCMFX
FWIN:	N/A
HVIN:	BPCMFX
PMN:	Battery Pack Control Module
Product Description:	Battery Pack Control Module
Power Supply / Rated operating Voltage Range:	Min. 8 V, Nom 13.5 V, Max. 16 V powered by the vehicle battery power system
Operating Temperature Range	-40°C to +85°C
Sample Revision	Production
EUT Dimensions	12.4 cm X 40.86 cm X 0+ 3.47 cm
Note: All information provided by the client.	

3.2 Radio Specifications

Embedded Radio Technologies	Integrating 2 ADI Proprietary Protocol: 1.- ADRF8951 chipset 2.- ADRF8951 chipset
Frequency Range / number of channels:	1.- ADRF8951 chipset: Low Power 2.4 GHz wBMS radio Frequency Range: 2405 - 2480 MHz Channels: 0-15 2.- ADRF8951 chipset: Low Power 2.4 GHz wBMS radio Frequency Range: 2405 - 2480 MHz Channels: 0-15
Rated max. EIRP	1.- ADRF8951 chipset: 12 dBm 2.- ADRF8951 chipset: 12 dBm
Tested radio technology	Integrating 2 ADI Proprietary Protocol
Antenna Type / Gain	1. Part No. 1001013 Product: 2.4 GHz FR4 Antenna 2. Part No. 1001013 Product: 2.4 GHz FR4 Antenna
Modes of Operation	1.- ADRF8951 chipset: Proprietary Protocol: 802.15.4 2400 MHz - 2483.5 MHz ISM Band Modulation: GFSK Nominal Channel Bandwidth: 5 MHz Duty Cycle: 27% 2.- ADRF8951 chipset: Proprietary Protocol: 802.15.4 2400 MHz - 2483.5 MHz ISM Band Modulation: GFSK Nominal Channel Bandwidth: 5 MHz Duty Cycle: 27%
Note: All information provided by the client.	

3.3 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	N/A	VPRE1F-12A650-MA	SWE201-28418-000F01	Conducted EUT
2	N/A	VPRE1F-12A650-MA	SWE201-28418-000F01	Radiated EUT

3.4 Accessory Equipment (AE) details

AE #	Type	Model	Manufacturer	Serial Number
1	USB-Dongle	PL2303TA	HiLetgo	NA
2	Harness cables	Power ON cables	NA	NA

Note: all AEs are only used for setup the test mode. They are disconnected before the test.

3.5 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1	The radio of the EUT is configured according to requirement of each test case for the conducted test
2	EUT#2	The radio of the EUT is configured according to requirement of each test case for the radiated test

3.6 Mode of Operation

Mode #	Mode of Operation	Comments
1	TX	Continuously transmission modulated signal Duty cycle >98%

3.7 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and highest possible duty cycle is higher than 98%. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in chapter 1.

4.1 Test procedures and standards applied

- FCC part 15, Subpart C §15.247
- KDB 558074 D01 15.247 Meas Guidance v05r02
- RSS-247 issue 3
- RSS-Gen issue 5 April 2018
- ANSI C63.10:2013

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
FCC §15.247(a)(2) RSS-247 5.2(a) RSS-Gen 6.7	Emission Bandwidth	Nominal	TX	☒	☐	☐	Complies
FCC §15.247(e) RSS-247 5.2(b)	Power Spectral Density	Nominal	TX	☒	☐	☐	Complies
FCC §15.247(b)(3) RSS-247 5.4(d)	Maximum Conducted Output Power and EIRP	Nominal	TX	☒	☐	☐	Complies
FCC §15.247(d) RSS-247 5.5	Band Edge Compliance Unrestricted Band Edges	Nominal	TX	☒	☐	☐	Complies
FCC §15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band Edge Compliance Restricted Band Edges	Nominal	TX	☒	☐	☐	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions-Radiated	Nominal	TX	☒	☐	☐	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	TX	☐	☒	☐	-

Note: NA= Not Applicable; NP= Not Performed.

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor $k=2$.

Radiated measurement

Measurement System		EMC 1	EMC 2
Conducted emissions (mains port)	150 kHz – 30 MHz	1.12 dB	N/A
Radiated emissions	(< 30 MHz)	3.28 dB	2.98 dB
	(30 MHz – 1 GHz)	3.16 dB	2.81 dB
	(1 – 3 GHz)	4.71 dB	4.51 dB
	(3 – 18 GHz)	4.23 dB	4.16 dB
	(18 – 40 GHz)	2.42 dB	2.42 dB

RF conducted measurement ± 0.5 dB

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3dB to the limit.

6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25°C
- Relative humidity: 40-60%

6.2 Dates of Testing:

2024-04-25 – 2024-05-13

6.3 Decision Rule:

Cetecom advanced follows ILAC G8:2019 chapter 4.2.1 (Simple Acceptance Rule).

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3. The measurement uncertainty is mentioned in this test report, See chapter 9, but is not taken into account – neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.


7 Measurement Procedures

7.1 Radiated Measurement


The radiated measurement is performed according to ANSI C63.10 (2013)

- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 360° continuous measurement of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The highest six emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.


Radiated Emissions Test Setup below 30MHz Measurements



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:


Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

8 Test Result Data

8.1 Emission Bandwidth 6dB and 99% Occupied Bandwidth

8.1.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

Spectrum Analyzer settings:

99% Occupied Bandwidth:

- Set frequency = nominal EUT channel center frequency
- Set Span = 1.5 x to 5.0 x OBW
- Set RBW = 1% to 5% of OBW
- Set the video bandwidth (VBW) $\approx 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

6dB (DTS) Bandwidth:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.1.2 Limits:

FCC §15.247(a)(2) and RSS-247 5.2(a)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22 °C	1	TX	nominal

8.1.4 Measurement result:

Test #	Channel	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
1	0	2.0280	-	For info only
2	8	2.0367	-	For info only
3	15	2.0280	-	For info only

Note 1: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.

Note 2: The plots presented below represent the worst-case test results measured.

Test #	Channel	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
4	0	1.3844	> 0.5	Pass
5	8	1.3675	> 0.5	Pass
6	15	1.3675	> 0.5	Pass


Note 1: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.

Note 2: The plots presented below represent the worst-case test results measured.

8.1.5 Measurement Plots: 99% OBW

Occupied Channel Bandwidth 99% (2405 MHz)


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
2405.000000	2.028000	---	---	2403.960000	2405.988000	PASS



8.1.6 Measurement Plots: 6dB BW

Minimum Emission Bandwidth 6 dB (2445 MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2445.000000	1.367533	0.500000	---	2444.307792	2445.675325	8.8	PASS



8.2 Maximum Peak Conducted Output Power

8.2.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

Spectrum Analyzer settings according to mentioned ANSI, sec.11.9.2.2.2 Method AVGSA-1:

8.2.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(3): 1 W (30 dBm)
- IC RSS-247 5.4(d): 1 W (30 dBm)

8.2.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22 °C	1	TX	nominal	2.6 dBi *

Note *: Details regarding the antenna gain are provided by the applicant.

8.2.4 Measurement result:

Test #	Channel	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	0	10.6	13.2 *	30 (PK) / 36 (EIRP)	Pass
2	8	9.6	12.2 *	30 (PK) / 36 (EIRP)	Pass
3	15	10.5	13.1 *	30 (PK) / 36 (EIRP)	Pass

Note *: Results based on calculation utilizing antenna gain information provided by applicant.

Note 2: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.


Note 3: The plots presented below represent the worst-case test results measured.

8.2.5 Measurement Plots:

Peak output power (Sweep) (2405 MHz)

Result

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2405.000000	10.6	30.0	PASS



8.3 Power Spectral Density

8.3.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.3.2 Limits:

FCC§15.247(e) & RSS-247 5.2(b)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22 °C	1	TX	nominal

8.3.4 Measurement result:

Test #	Channel	Maximum Power Spectral Density (dBm/3 kHz)	Limit (dBm / 3 kHz)	Result
1	0	3.630	8	Pass
2	8	2.621	8	Pass
3	15	3.487	8	Pass


Note 1: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.

Note 2: The plots presented below represent the worst-case test results measured.

8.3.5 Measurement Plots:

Peak Power Spectral Density (2405 MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2405.000000	2405.124597	3.630	8.0	PASS



8.4 Duty cycle


8.4.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

8.4.2 Measurement result

Test according to FCC title 47 part 15 §15.247(b), KDB 558074 D01 DTS Meas Guidance v05r02 and ANSI C63.10-2013, section 11.6.

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2405.000000	10.9	30.0	13.5	100.000	PASS



8.5 Non-restricted Band Edge Compliance and Conducted Spurious Emissions

8.5.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.5.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5.5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=100 kHz

8.5.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22 °C	1 (low band edge) 2 (high band edge)	TX	nominal

8.5.4 Measurement result: band edge (conducted)

Test #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Detector	Limit (dBc)	Result
1	TX	Lower, Non-restricted (conducted)	44.2	PK	min. 20	Pass
2	TX	Upper, Non-restricted (conducted)	44.4	PK	min. 20	Pass

Note 1: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.

Note 2: The plots presented below represent the worst-case test results measured.

8.5.5 Measurement result: conducted spurious emission

Test #	EUT operating mode	Frequency range	Measured lowest margin (dBc)	Limit (dBm)	Result
3	TX, channel 0	30 MHz – 18 GHz	23.6	-22.6	Pass
4	TX, channel 8	9 kHz – 27 GHz	21.7	-23.8	Pass
5	TX, channel 15	30 MHz – 18 GHz	25.3	-23.1	Pass

Note 1: The limits are based on the emission levels of the intentional radiator, adjusted with a 30 dB attenuation, as the measurements are performed using an RMS detector averaging over a time interval.

Note 2: The test results and plots are generated by the R&S EMC32 software, which automatically performs the measurements.

Note 3: The plots presented below represent the worst-case test results measured.


8.5.6 Measurement Plots (Non-restricted Band Edge)

Band Edge low (2405 MHz)

DUT Frequency (MHz)	Result
2405.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2404.518824	9.0




8.5.7 Measurement Plots (Conducted Spurious Emissions)

Tx Spurious Emission (2445 MHz)

DUT Frequency (MHz)	Result
2445.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2444.461039	6.2



8.6 Radiated Transmitter Spurious Emissions and Restricted Band Edge

8.6.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02, and ANSI C63.10 Clause 11.

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing frequencies below 30 MHz at distance other than the specified in the standard, the limit conversion is calculated by using the FCC materials for the ANSI 63 committee issued on January, 27 1991.

8.6.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)	Field strength @ 3m (dBμV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBμV/m
88–216	150	3	43.5 dBμV/m
216–960	200	3	46 dBμV/m
Above 960	500	3	54 dBμV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dBμV/m

*AVG. LIMIT= 54 dBμV/m

8.6.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22 °C	2	TX	nominal

8.6.4 Measurement result:

Plot #	Radio / Channel #	Scan Frequency	Emission level with lowest margin to limit	Limit	Result
1-5	Left / Mid	9 kHz – 26 GHz	51.047 dB μ V/m (AV)	See section 8.6.2	Pass
6-8	Right / Low	30 MHz – 18 GHz	50.988 dB μ V/m (AV)	See section 8.6.2	Pass
9-13	Right / Mid	9 kHz – 26 GHz	50.948 dB μ V/m (AV)	See section 8.6.2	Pass
14-17	Right / High	30 MHz – 18 GHz	50.976 dB μ V/m (AV)	See section 8.6.2	Pass


Note 1: Two identical antenna ports on the EUT are tested individually, with only one antenna transmitting at a time.

Note 2: During normal operation of the EUT, the two antennas do not transmit simultaneously.

Note 3: Limited tests on the left antenna port are conducted to verify if the two identical ports exhibit similar performance.

8.6.5 Measurement Plots:

Plot # 1




◆ AVG_MAXH Final_Result QPK ◆ PK+_MAXH Final_Result PK+ — FCC 15.209 QP at 3m

Plot # 2

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
204.516	23.441	---	500.00	476.56	500.0	120.000	209.0	H	86.0	-16.6	-34.5	0.0	17.8	40.1
222.231	24.312	---	500.00	475.69	500.0	120.000	345.0	V	341.0	-16.0	-34.4	0.0	18.4	40.3
239.314	32.225	---	500.00	467.78	500.0	120.000	117.0	H	279.0	-15.0	-34.3	0.0	19.3	47.3
257.706	31.095	---	46.02	14.93	500.0	120.000	100.0	H	245.0	-15.4	-34.3	0.0	18.8	46.5




◆ AVG_MAXH Final_Result QPK
 ◆ PK+ Final_Result PK+
 — FCC 15.247 restricted bands

Plot # 3

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
2920.927	---	30.593	53.98	23.39	500.0	1000.000	257.0	V	352.0	7.4	-22.1	0.0	29.5	23.2
2920.927	42.898	---	73.98	31.08	500.0	1000.000	257.0	V	352.0	7.4	-22.1	0.0	29.5	35.5




— AVG_MAXH
— FCC 15.209 AVG at 3m
 ◆ PK+_MAXH
 Final_Result PK+
 — FCC 15.209 PK at 3m
◆ Final_Result CAV

Plot # 4


Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
14669.943	60.009	---	73.98	13.97	500.0	1000.000	257.0	V	298.0	10.7	14.5	-45.0	41.2	49.3
14669.943	---	50.242	53.98	3.74	500.0	1000.000	257.0	V	298.0	10.7	14.5	-45.0	41.2	39.5
16532.528	---	50.018	53.98	3.96	500.0	1000.000	158.0	V	298.0	13.9	16.2	-43.3	41.1	36.1
16532.528	62.652	---	73.98	11.33	500.0	1000.000	158.0	V	298.0	13.9	16.2	-43.3	41.1	48.7
17593.122	---	50.597	53.98	3.38	500.0	1000.000	307.0	H	171.0	15.1	16.5	-42.8	41.4	35.5
17593.122	63.147	---	73.98	10.83	500.0	1000.000	307.0	H	171.0	15.1	16.5	-42.8	41.4	48.1
17944.199	63.934	---	73.98	10.05	500.0	1000.000	193.0	V	100.0	15.7	16.3	-42.3	41.6	48.3
17944.199	---	51.047	53.98	2.93	500.0	1000.000	193.0	V	100.0	15.7	16.3	-42.3	41.6	35.4



— AVG_MAXH — PK+_MAXH — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 5




— AVG_MAXH	— PK+ _MAXH	* Critical_Freqs AVG
* Critical_Freqs PK+	— FCC 15.209 PK at 1m	— FCC 15.209 AVG at 1m
◆ Final_Result PK+	◆ Final_Result CAV	

Plot # 6

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
30.334	27.108	---	500.00	472.89	500.0	120.000	341.0	V	38.0	-12.3	-35.4	0.0	23.1	39.4
89.150	22.828	---	500.00	477.17	500.0	120.000	349.0	V	50.0	-16.7	-35.0	0.0	18.4	39.5
200.619	23.725	---	500.00	476.27	500.0	120.000	236.0	H	140.0	-16.5	-34.5	0.0	18.1	40.2
220.609	27.872	---	500.00	472.13	500.0	120.000	100.0	V	262.0	-16.0	-34.4	0.0	18.4	43.9
238.820	26.360	---	500.00	473.64	500.0	120.000	107.0	H	244.0	-15.2	-34.3	0.0	19.2	41.5




— AVG_MAXH
◆ Final_Result QPK
 — PK+_MAXH
◆ Final_Result PK+
 — FCC 15.247 restricted bands

Plot # 7

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
2730.191	---	30.208	53.98	23.77	500.0	1000.000	334.0	H	210.0	6.5	-22.2	0.0	28.7	23.7
2730.191	43.267	---	73.98	30.71	500.0	1000.000	334.0	H	210.0	6.5	-22.2	0.0	28.7	36.8




— AVG_MAXH
— FCC 15.209 AVG at 3m
◆ PK+_MAXH
 Final_Result PK+
— FCC 15.209 PK at 3m
◆ Final_Result CAV

Plot # 8


Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
12661.881	56.777	---	73.98	17.20	500.0	1000.000	158.0	H	325.0	8.7	13.4	-43.5	38.8	48.1
12661.881	---	43.842	53.98	10.14	500.0	1000.000	158.0	H	325.0	8.7	13.4	-43.5	38.8	35.1
14604.202	---	46.356	53.98	7.62	500.0	1000.000	325.0	H	182.0	10.8	14.6	-44.9	41.0	35.6
14604.202	59.660	---	73.98	14.32	500.0	1000.000	325.0	H	182.0	10.8	14.6	-44.9	41.0	48.9
16348.612	---	49.188	53.98	4.79	500.0	1000.000	308.0	H	340.0	13.1	16.2	-44.0	40.9	36.1
16348.612	62.040	---	73.98	11.94	500.0	1000.000	308.0	H	340.0	13.1	16.2	-44.0	40.9	49.0
17873.422	63.746	---	73.98	10.23	500.0	1000.000	354.0	H	256.0	15.4	16.2	-42.4	41.6	48.4
17873.422	---	50.988	53.98	2.99	500.0	1000.000	354.0	H	256.0	15.4	16.2	-42.4	41.6	35.6



— AVG_MAXH
— FCC 15.209 AVG at 3m
 ◆ PK+_MAXH Final_Result PK+
 — FCC 15.209 PK at 3m
 ◆ Final_Result CAV

Plot # 9



AVG_MAXH

PK+_MAXH

Critical_Freqs AVG

Critical_Freqs PK+

FCC 15.209 QP at 3m


Final_Result QPK

Final_Result PK+

Plot # 10

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
202.122	24.386	---	500.00	475.61	500.0	120.000	107.0	H	280.0	-16.5	-34.5	0.0	18.0	40.9
221.082	30.908	---	500.00	469.09	500.0	120.000	100.0	V	264.0	-16.0	-34.4	0.0	18.4	46.9
241.389	25.805	---	46.02	20.22	500.0	120.000	235.0	H	235.0	-14.5	-34.3	0.0	19.8	40.3
258.258	25.017	---	46.02	21.00	500.0	120.000	107.0	H	89.0	-15.5	-34.3	0.0	18.7	40.5




◆ AVG_MAXH Final_Result QPK
 ◆ PK+_MAXH Final_Result PK+
 — FCC 15.247 restricted bands

Plot # 11

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
2040.712	---	27.869	53.98	26.11	500.0	1000.000	227.0	V	-4.0	4.7	-22.7	0.0	27.4	23.1
2040.712	40.615	---	73.98	33.36	500.0	1000.000	227.0	V	-4.0	4.7	-22.7	0.0	27.4	35.9
2601.253	---	29.934	53.98	24.05	500.0	1000.000	280.0	V	73.0	6.3	-22.4	0.0	28.7	23.6
2601.253	42.767	---	73.98	31.21	500.0	1000.000	280.0	V	73.0	6.3	-22.4	0.0	28.7	36.5




— AVG_MAXH — PK+_MAXH — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 12


Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
14669.982	---	47.821	53.98	6.16	500.0	1000.000	158.0	V	90.0	10.7	14.5	-45.0	41.2	37.1
14669.982	59.538	---	73.98	14.44	500.0	1000.000	158.0	V	90.0	10.7	14.5	-45.0	41.2	48.8
16137.024	62.424	---	73.98	11.56	500.0	1000.000	325.0	V	46.0	13.7	16.0	-43.1	40.9	48.7
16137.024	---	49.577	53.98	4.40	500.0	1000.000	325.0	V	46.0	13.7	16.0	-43.1	40.9	35.9
16685.154	---	50.488	53.98	3.49	500.0	1000.000	325.0	H	10.0	14.8	15.7	-42.2	41.3	35.7
16685.154	63.343	---	73.98	10.64	500.0	1000.000	325.0	H	10.0	14.8	15.7	-42.2	41.3	48.6
17861.792	64.027	---	73.98	9.95	500.0	1000.000	400.0	H	169.0	15.3	16.1	-42.4	41.6	48.7
17861.792	---	50.948	53.98	3.03	500.0	1000.000	400.0	H	169.0	15.3	16.1	-42.4	41.6	35.6



— AVG_MAXH
— FCC 15.209 AVG at 3m
 ◆ PK+_MAXH
◆ Final_Result PK+
 — FCC 15.209 PK at 3m
◆ Final_Result CAV

Plot # 13




—	AVG_MAXH	—	PK+ _MAXH	*	Critical_Freqs AVG
*	Critical_Freqs PK+	—	FCC 15.209 PK at 1m	*	FCC 15.209 AVG at 1m
◆	Final_Result PK+	◆	Final_Result CAV		

Plot # 14

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
200.823	23.762	---	500.00	476.24	500.0	120.000	117.0	H	94.0	-16.5	-34.5	0.0	18.1	40.2
222.705	24.301	---	500.00	475.70	500.0	120.000	378.0	V	119.0	-16.0	-34.4	0.0	18.4	40.3
242.250	26.128	---	46.02	19.89	500.0	120.000	150.0	H	79.0	-14.3	-34.4	0.0	20.1	40.4
256.484	25.118	---	46.02	20.90	500.0	120.000	125.0	H	75.0	-15.2	-34.3	0.0	19.0	40.4
384.429	28.309	---	500.00	471.69	500.0	120.000	360.0	H	27.0	-11.7	-33.8	0.0	22.1	40.0




◆ AVG_MAXH Final_Result QPK
 ◆ PK+_MAXH Final_Result PK+
 — FCC 15.247 restricted bands

Plot # 15

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
2238.188	---	27.905	53.98	26.07	500.0	1000.000	264.0	V	-10.0	5.0	-22.6	0.0	27.6	22.9
2238.188	40.191	---	73.98	33.79	500.0	1000.000	264.0	V	-10.0	5.0	-22.6	0.0	27.6	35.2




— AVG_MAXH — PK+_MAXH — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 16

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
2483.729	---	40.830	54.00	13.17	500.0	1000.000	285.0	H	14.0	33.5	5.2	0.0	28.4	7.3
2483.729	56.525	---	74.00	17.48	500.0	1000.000	285.0	H	14.0	33.5	5.2	0.0	28.4	23.0




— AVG_MAXH
— FCC 15.247 2400MHz Avg
— PK+_MAXH
◆ Final_Result PK+
— FCC 15.247 2400MHz Pk
◆ Final_Result CAV

Plot # 17

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)
14496.182	59.977	---	73.98	14.00	500.0	1000.000	125.0	H	274.0	10.4	14.6	-44.9	40.6	49.6
14496.182	---	46.209	53.98	7.77	500.0	1000.000	125.0	H	274.0	10.4	14.6	-44.9	40.6	35.8
14879.881	59.545	---	73.98	14.43	500.0	1000.000	100.0	V	67.0	9.2	14.5	-46.3	41.1	50.3
14879.881	---	50.437	53.98	3.54	500.0	1000.000	100.0	V	67.0	9.2	14.5	-46.3	41.1	41.2
16708.121	---	50.566	53.98	3.41	500.0	1000.000	283.0	V	246.0	14.9	15.7	-42.0	41.3	35.6
16708.121	63.823	---	73.98	10.16	500.0	1000.000	283.0	V	246.0	14.9	15.7	-42.0	41.3	48.9
17254.805	61.807	---	73.98	12.17	500.0	1000.000	266.0	H	266.0	13.6	15.6	-43.3	41.3	48.3
17254.805	---	49.107	53.98	4.87	500.0	1000.000	266.0	H	266.0	13.6	15.6	-43.3	41.3	35.6
17947.867	63.362	---	73.98	10.62	500.0	1000.000	232.0	V	90.0	15.7	16.3	-42.3	41.6	47.7
17947.867	---	50.976	53.98	3.00	500.0	1000.000	232.0	V	90.0	15.7	16.3	-42.3	41.6	35.3



— AVG_MAXH — PK+ _MAXH — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

9 Test setup photos

Setup photos are included in supporting file name:
“EMC_VISTE_002_23001_FCC15247_DTS_BPCMF_X_Photos.pdf”

10 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Biconlog Antenna	ETS Lindgren	BiLA2G	00063983	3 YEARS	8/14/2023
HORN ANTENNA	EMCO	3115	00035114	3 YEARS	09/13/2023
HORN ANTENNA	ETS LINDGREN	3117-PA	166067	3 YEARS	09/25/2023
HORN ANTENNA	ETS LINDGREN	3116C-PA	00169535	3 YEARS	10/26/2023
DIGITAL THERMOMETER	CONTROL COMPANY	4410,90080-03	230713059	3 YEARS	10/18/2023
Spectrum Analyzer	Rohde & Schwarz	FSU. Spectrum Analyzer	100189	3 YEARS	5/27/2022
PASSIVE LOOP ANTENNA	ETS-LINDGREN	6512	00164698	3 YEARS	6/9/2023
EMI RECEIVER	R&S	ESW44	101715	2 YEARS	10/24/2023
Thermometer	Control Company	4410,90080-03	23071341	2 YEARS	10/18/2023
EMC32 Test Software	R&S	Version 10.50.40	-	-	-

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated “NA” for cal status either do not specifically require calibration or is internally characterized before use.

11 Revision History

Date	Report name	Changes to report	Prepared by
2024-06-03	EMC_VISTE_002_23001_FCC15247_DTS_BPCM_Fix	Initial version	Guangcheng Huang
2024-06-12	EMC_VISTE_002_23001_FCC15247_DTS_BPCMFX_Rev1	Update dates of testing, Update EUT antenna gain, Modified wording in sec.8, Corrected typo in sec.8.1	Guangcheng Huang
2024-06-13	EMC_VISTE_002_23001_FCC15247_DTS_BPCMFX_Rev2	Corrected typo in sec.8.1	Guangcheng Huang

<<< The End >>>