



Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106




**Plot 7-233. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)**



**Plot 7-234. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)**

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5775MHz  
 Channel: 155



**Plot 7-235. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)**

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          |                                                                                       | Page 158 of 170                 |

## 7.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-61 per Section 15.209 and RSS-Gen (8.9).***

| Frequency         | Field Strength<br>[ $\mu$ V/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                   | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                  | 30                            |
| 1.705 – 30.00 MHz | 30                             | 30                            |
| 30.00 – 88.00 MHz | 100                            | 3                             |
| 88.00 – 216.0 MHz | 150                            | 3                             |
| 216.0 – 960.0 MHz | 200                            | 3                             |
| Above 960.0 MHz   | 500                            | 3                             |

**Table 7-61. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013

### Test Settings


#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          |                                                                                       | Page 159 of 170                 |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-6. Radiated Test Setup < 30MHz**



**Figure 7-7. Radiated Test Setup < 1GHz**

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 160 of 170                 |


## Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-61.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          | Page 161 of 170                                                                       |                                 |

## SISO ANT1 Radiated Spurious Emissions Measurements (Below 1GHz)


§15.209; RSS-Gen [8.9]



Plot 7-236. Radiated Spurious Plot below 1GHz SISO ANT1 (802.11a – U3 Ch. 157)

## SISO ANT2 Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]




Plot 7-237. Radiated Spurious Plot below 1GHz SISO ANT2 (802.11a – U3 Ch. 157)

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          |                                                                                       | Page 162 of 170                 |

## MIMO Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



**Plot 7-238. Radiated Spurious Plot below 1GHz MIMO (802.11a – U3 Ch. 157)**

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          |                                                                                       | Page 163 of 170                 |

## 7.8 Line-Conducted Test Data

§15.407; RSS-Gen [8.8]

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).**

| Frequency of emission (MHz) | Conducted Limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15 – 0.5                  | 66 to 56*              | 56 to 46* |
| 0.5 – 5                     | 56                     | 46        |
| 5 – 30                      | 60                     | 50        |

Table 7-62. Conducted Limits

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.10-2013, Section 6.2

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          | Page 164 of 170                                                                       |                                 |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-8. Test Instrument & Measurement Setup**


## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 165 of 170                 |




Plot 7-239. Line Conducted Plot with 802.11a UNII Band 1 (L1)




Plot 7-240. Line Conducted Plot with 802.11a UNII Band 1 (N)

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 166 of 170                 |




Plot 7-241. Line Conducted Plot with 802.11a UNII Band 2A (L1)




Plot 7-242. Line Conducted Plot with 802.11a UNII Band 2A (N)

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 167 of 170                 |




Plot 7-243. Line Conducted Plot with 802.11a UNII Band 2C (L1)




Plot 7-244. Line Conducted Plot with 802.11a UNII Band 2C (N)

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 168 of 170                 |



Plot 7-245. Line Conducted Plot with 802.11a UNII Band 3 (L1)



Plot 7-246. Line Conducted Plot with 802.11a UNII Band 3 (N)

|                                         |                                 |                                       |           |                                 |
|-----------------------------------------|---------------------------------|---------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFT600TS                       | <b>PCTEST</b>                   | MEASUREMENT REPORT<br>(CERTIFICATION) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020 | EUT Type:<br>Portable Tablet          |           | Page 169 of 170                 |

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **LG Portable Tablet FCC ID: ZNFT600TS** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.

|                                         |                                                                                     |                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFT600TS                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M2001100004-06.ZNF | Test Dates:<br>1/13 - 2/14/2020                                                     | EUT Type:<br>Portable Tablet          |                                                                                       | Page 170 of 170                 |