

FCC RF Exposure Evaluation

1. Product Information

FCC ID:	2AVTH-HTLF1314
Product name	HyFlip
Model number	HTLF14INC4Z1SSG
Additional Model No.	HTLF14INC4Z1SS, HTLF14INC4Z1ES, HTLF14INC4Z1ESG, HTLF13INC4Z1ES, HTLF13INC4Z1ESG
Model Declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power supply	DC 7.6V by Rechargeable Li-ion Battery(5000mAh) Recharged by 12V  2000mA Adapter
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Bluetooth Version	V4.0
Bluetooth Channel Number	79 channels for Bluetooth V4.0 (BDR/EDR) 40 channels for Bluetooth V4.0 (BT LE)
Bluetooth Channel Spacing	1MHz for Bluetooth V4.0 (BDR/EDR) 2MHz for Bluetooth V4.0 (BT LE)
Bluetooth Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.0 (BDR/EDR) GFSK for Bluetooth V4.0 (BT LE)
2.4G WLAN	
Frequency Range	2412MHz ~ 2462MHz
Channel Number	11 Channels for 20MHz bandwidth (2412MHz ~ 2462MHz) 7 Channels for 40MHz bandwidth (2422MHz ~ 2452MHz)
Channel Spacing	5MHz
Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	PIFA Antenna(ANT 0), used for Bluetooth & WIFI 2.05dBi(Max.) for 2.4G band PIFA Antenna(ANT 1), used for WIFI 2.05dBi(Max.) for 2.4G band
Hardware version	A116U1-2 REV02
Software version	WINDOWS10
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Portable Device

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based

time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ “

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f (\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

3. Refer evaluation method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

4. Conducted Power Results

[2.4GWLAN Max Conducted Power]

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	4.549
	39	2441	4.910
	78	2480	4.347
$\pi/4$ DQPSK	0	2402	1.014
	39	2441	1.472
	78	2480	0.931
8DPSK	0	2402	1.263
	39	2441	1.748
	78	2480	1.190
BT LE	0	2402	3.054
	19	2440	3.486
	39	2480	2.954

[2.4GWLAN Max Conducted Power]

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)		
			Ant 0	Ant 1	Sum
IEEE 802.11b	1	2412	7.11	8.05	/
	6	2437	8.06	8.2	/
	11	2462	7.81	7.98	/
IEEE 802.11g	1	2412	7.57	7.41	/
	6	2437	7.64	8.06	/
	11	2462	7.81	8.47	/
IEEE 802.11n HT20	1	2412	6	6.83	9.45
	6	2437	6.34	6.52	9.44
	11	2462	6.07	6.84	9.48
IEEE 802.11n HT40	3	2422	6.49	6.35	9.43
	6	2437	6.21	6.07	9.15
	9	2452	6.1	6.66	9.40

5. Manufacturing tolerance

BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	3.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWIFI

IEEE 802.11b (Peak)						
Channel	Channel 1		Channel 6		Channel 11	
	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
Target (dBm)	7.0	8.0	8.0	8.0	7.0	7.0
Tolerance ±(dB)	1.0		1.0		1.0	
IEEE 802.11g (Peak)						
Channel	Channel 1		Channel 6		Channel 11	
	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
Target (dBm)	7.0	7.0	7.0	8.0	7.0	8.0
Tolerance ±(dB)	1.0		1.0		1.0	
IEEE 802.11n HT20 (Peak)						
Channel	Channel 1		Channel 6		Channel 11	
	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
Target (dBm)	6.0	6.0	6.0	6.0	6.0	6.0
Tolerance ±(dB)	1.0		1.0		1.0	
IEEE 802.11n HT40 (Peak)						
Channel	Channel 3		Channel 6		Channel 9	
	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
Target (dBm)	6.0	6.0	6.0	6.0	6.0	6.0
Tolerance ±(dB)	1.0		1.0		1.0	

6. Evaluation Results

ANT 0

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
GFSK	2.450	5	5.0	3.1623	0.9899< 3.0	Yes
π /4DQPSK	2.450	5	2.0	1.5849	0.4962< 3.0	Yes
8DPSK	2.450	5	2.0	1.5849	0.4962< 3.0	Yes
BT LE	2.450	5	4.0	2.5119	0.7863< 3.0	Yes
IEEE 802.11b	2.412	5	9.0	7.9433	2.4673< 3.0	Yes
IEEE 802.11g	2.412	5	8.0	6.3096	1.9598< 3.0	Yes
IEEE 802.11n HT20	2.412	5	7.0	5.0119	1.5567< 3.0	Yes
IEEE 802.11n HT40	2.412	5	7.0	5.0119	1.5567< 3.0	Yes

ANT 1

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11b	2.412	5	9.0	7.9433	2.4673< 3.0	Yes
IEEE 802.11g	2.412	5	9.0	7.9433	2.4673< 3.0	Yes
IEEE 802.11n HT20	2.412	5	7.0	5.0119	1.5567< 3.0	Yes
IEEE 802.11n HT40	2.412	5	7.0	5.0119	1.5567< 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 25 mm, a distance of 25 mm according to f) in section 4.1 is applied to determine SAR test exclusion.
3. WLAN and BT share same modular and same antenna, no need consider simultaneous transmit.

Simultaneous Transmission for SAR Exclusion

The sample support one modular and supports two antennas, need consider simultaneous transmission;

Σ of (the highest measured or estimated SARANT0+SARANT1)/1.6 = (0.2076+0.2076)/1.6 = 0.3 < 1.0;

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....