



REPORT No. : SZ19050138S01

# RF EXPOSURE EVALUATION REPORT

**APPLICANT** : Shenzhen Jimi IOT Co.,Ltd  
**PRODUCT NAME** : ASSET GPS TRACKER  
**MODEL NAME** : AT6  
**BRAND NAME** : Jimi  
**FCC ID** : 2AMLFAT6  
**STANDARD(S)** : 47CFR 2.1091  
: KDB 447498  
**RECEIPT DATE** : 2019-05-14  
**TEST DATE** : 2019-05-15  
**ISSUE DATE** : 2019-05-21

Edited by:

*Liang Yumei*  
Liang Yumei (Rapporteur)

Approved by:

*Peng Huarui*  
Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.cn

Fax: 86-755-36698525  
E-mail: service@morlab.cn





# DIRECTORY

|   |           |
|---|-----------|
| <b>1. Technical Information .....</b>                   | <b>4</b>  |
| <b>1.1 Applicant and Manufacturer Information .....</b> | <b>4</b>  |
| <b>1.2 Equipment under Test (EUT) Description .....</b> | <b>4</b>  |
| <b>1.3 Identification of all used EUT .....</b>         | <b>5</b>  |
| <b>1.4 Applied Reference Documents .....</b>            | <b>5</b>  |
| <b>2. Device Category and RF Exposure Limit .....</b>   | <b>6</b>  |
| <b>3. RF Output Power .....</b>                         | <b>7</b>  |
| <b>4. RF Exposure Evaluation .....</b>                  | <b>9</b>  |
| <b>Annex A General Information .....</b>                | <b>10</b> |



REPORT No. : SZ19050138S01

| Change history |            |                   |
|----------------|------------|-------------------|
| Version        | Date       | Reason of changed |
| 1.0            | 2019-05-21 | First edition     |
|                |            |                   |
|                |            |                   |
|                |            |                   |
|                |            |                   |



# 1. Technical Information

**Note:** Provide by manufacturer.

## 1.1 Applicant and Manufacturer Information

|                              |   |
|------------------------------|---|
| <b>Applicant:</b>            | Shenzhen Jimi IOT Co.,Ltd   |
| <b>Applicant Address:</b>    | 4/F, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67<br>Xin'an Street, Bao'an District, Shenzhen, China |
| <b>Manufacturer:</b>         | Shenzhen Jimi IOT Co.,Ltd   |
| <b>Manufacturer Address:</b> | 4/F, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67<br>Xin'an Street, Bao'an District, Shenzhen, China |

## 1.2 Equipment under Test (EUT) Description

|                          |   |
|--------------------------|---|
| <b>EUT Name:</b>         | ASSET GPS TRACKER   |
| <b>Hardware Version:</b> | NFC112_V4.0   |
| <b>Software Version:</b> | GT370W_30_S1G15U8_D23_R0_V01_WM_20181115_1136   |
| <b>Frequency Bands:</b>  | GSM850: 824.2MHz ~ 848.8MHz<br>GSM1900: 1850.2MHz ~ 19010.8MHz<br>WCDMA Band II: 1852.4MHz ~ 1907.6MHz<br>WCDMA Band V: 826.4MHz ~ 846.6MHz |
| <b>Modulation Mode:</b>  | GPRS: GMSK, EDGE: 8PSK<br>WCDMA: QPSK   |
| <b>Antenna Type:</b>     | FPC Antenna   |
| <b>Antenna Gain:</b>     | -1.5dBi   |

**Note:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.3 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

| EUT Identity | Hardware Version | Software Version                              |
|--------------|------------------|---|
| 1#           | NFC112_V4.0      | GT370W_30_S1G15U8_D23_R0_V01_WM_20181115_1136 |

### 1.4 Applied Reference Documents

Leading reference documents for testing:

| No. | Identity          | Document Title  |
|-----|-------------------|---|
| 1   | 47 CFR§2.1091     | Radio Frequency Radiation Exposure Evaluation: mobile devices |
| 2   | KDB 447498 D01v06 | General RF Exposure Guidance                                  |

## 2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

| Frequency range (MHz)  | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34   | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30  | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300   | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500   | -                             | -                             | f/1500                              | 30                       |
| 1500-100,000   | -                             | -                             | 1.0                                 | 30                       |

f = frequency in MHz\* = Plane-wave equivalent power density

### 3. RF Output Power

#### <GSM>

| GSM850          | Burst Average Power (dBm) |       |       | Tune-up Limit (dBm) | Frame-Average Power (dBm) |       |       | Tune-up Limit (dBm) |
|-----------------|---------------------------|-------|-------|---------------------|---------------------------|-------|-------|---------------------|
| TX Channel      | 128                       | 189   | 251   |                     | 128                       | 189   | 251   |                     |
| Frequency (MHz) | 824.2                     | 836.4 | 848.8 |                     | 824.2                     | 836.4 | 848.8 |                     |
| GPRS 1 Tx slot  | 32.24                     | 31.96 | 32.07 | 32.50               | 23.24                     | 22.96 | 23.07 | 23.50               |
| GPRS 2 Tx slots | 29.84                     | 30.01 | 30.18 | 30.50               | 23.84                     | 24.01 | 24.18 | 24.50               |
| GPRS 3 Tx slots | 28.72                     | 28.83 | 28.97 | 29.00               | 24.46                     | 24.57 | 24.71 | 24.74               |
| GPRS 4 Tx slots | 26.62                     | 26.67 | 26.88 | 27.00               | 23.62                     | 23.67 | 23.88 | 24.00               |
| EDGE 1 Tx slot  | 26.14                     | 26.13 | 26.24 | 26.50               | 17.14                     | 17.13 | 17.24 | 17.50               |
| EDGE 2 Tx slots | 25.84                     | 25.85 | 25.94 | 26.00               | 19.84                     | 19.85 | 19.94 | 20.00               |
| EDGE 3 Tx slots | 24.70                     | 24.58 | 24.71 | 25.00               | 20.44                     | 20.32 | 20.45 | 20.74               |
| EDGE 4 Tx slots | 21.94                     | 21.99 | 22.13 | 22.50               | 18.94                     | 18.99 | 19.13 | 19.50               |

| GSM1900         | Burst Average Power (dBm) |       |        | Tune-up Limit (dBm) | Frame-Average Power (dBm) |       |        | Tune-up Limit (dBm) |
|-----------------|---------------------------|-------|--------|---------------------|---------------------------|-------|--------|---------------------|
| TX Channel      | 512                       | 661   | 810    |                     | 512                       | 661   | 810    |                     |
| Frequency (MHz) | 1850.2                    | 1880  | 1909.8 |                     | 1850.2                    | 1880  | 1909.8 |                     |
| GPRS 1 Tx slot  | 29.66                     | 29.45 | 29.59  | 30.00               | 20.66                     | 20.45 | 20.59  | 21.00               |
| GPRS 2 Tx slots | 28.45                     | 28.24 | 27.91  | 28.50               | 22.45                     | 22.24 | 21.91  | 22.50               |
| GPRS 3 Tx slots | 26.84                     | 26.59 | 26.25  | 27.00               | 22.58                     | 22.33 | 21.99  | 22.74               |
| GPRS 4 Tx slots | 24.70                     | 24.47 | 24.16  | 25.00               | 21.70                     | 21.47 | 21.16  | 22.00               |
| EDGE 1 Tx slot  | 25.96                     | 25.93 | 25.68  | 26.00               | 16.96                     | 16.93 | 16.68  | 17.00               |
| EDGE 2 Tx slots | 25.62                     | 25.53 | 25.39  | 26.00               | 19.62                     | 19.53 | 19.39  | 20.00               |
| EDGE 3 Tx slots | 23.97                     | 23.95 | 23.65  | 25.00               | 19.71                     | 19.69 | 19.39  | 20.74               |
| EDGE 4 Tx slots | 21.23                     | 21.14 | 21.14  | 21.50               | 18.23                     | 18.14 | 18.14  | 18.50               |

**Note:** According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.



REPORT No. : SZ19050138S01

## &lt;WCDMA&gt;

| Band            | WCDMA II |       |        | Tune-up<br>Limit<br>(dBm) | WCDMA V |       |       | Tune-up<br>Limit<br>(dBm) |
|-----------------|----------|-------|--------|---------------------------|---------|-------|-------|---------------------------|
| TX Channel      | 9262     | 9400  | 9538   |                           | 4132    | 4182  | 4233  |                           |
| Rx Channel      | 9662     | 9800  | 9938   |                           | 4357    | 4407  | 4458  |                           |
| Frequency (MHz) | 1852.4   | 1880  | 1907.6 |                           | 826.4   | 836.4 | 846.6 |                           |
| RMC 12.2Kbps    | 22.07    | 21.95 | 21.96  | 22.50                     | 22.32   | 22.46 | 22.24 | 22.50                     |
| HSDPA Subtest-1 | 21.76    | 21.79 | 21.91  | 22.00                     | 21.78   | 21.54 | 21.57 | 22.00                     |
| HSDPA Subtest-2 | 21.76    | 21.68 | 21.87  | 22.00                     | 21.62   | 21.46 | 21.41 | 22.00                     |
| HSDPA Subtest-3 | 21.81    | 21.84 | 21.73  | 22.00                     | 21.57   | 21.44 | 21.41 | 22.00                     |
| HSDPA Subtest-4 | 21.75    | 21.80 | 21.66  | 22.00                     | 21.48   | 21.36 | 21.32 | 21.50                     |



## 4. RF Exposure Evaluation

### Standalone transmission evaluation:

| Bands         | Frequency (MHz) | Antenna Gain (dBi) | Maximum Tune-up Limit (dBm) | EIRP (mW) | Power density (mW/cm <sup>2</sup> ) | Limit for MPE (mW/cm <sup>2</sup> ) |
|---------------|-----------------|--------------------|-----------------------------|-----------|-------------------------------------|-------------------------------------|
| GSM 850       | 848.8           | -1.5               | 24.74                       | 210.863   | 0.042                               | 0.566                               |
| GSM 1900      | 1850.2          | -1.5               | 22.74                       | 133.045   | 0.026                               | 1.0                                 |
| WCDMA Band II | 1852.4          | -1.5               | 22.50                       | 125.893   | 0.025                               | 1.0                                 |
| WCDMA Band V  | 836.4           | -1.5               | 22.50                       | 125.893   | 0.025                               | 0.558                               |

### Note:

1. According to KDB 447498, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

### 2. MPE calculation method

$$\text{Power Density} = \text{EIRP} / 4\pi R^2$$

Where: EIRP = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)



## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

|                            |  |
|----------------------------|--|
| <b>Laboratory Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.<br>Morlab Laboratory   |
| <b>Laboratory Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road,<br>Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R.<br>China |
| <b>Telephone:</b>          | +86 755 36698555   |
| <b>Facsimile:</b>          | +86 755 36698525   |

### 2. Identification of the Responsible Testing Location

|                 |  |
|-----------------|--|
| <b>Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.<br>Morlab Laboratory   |
| <b>Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road,<br>Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R.<br>China |